

Utilização do postman para geração de token de autenticação para execução dos serviços

POST localhost/api/source/oauth2/token

Params Authorization Headers (8) **Body** Pre-request Script Tests Settings

none form-data x-www-form-urlencoded **raw** binary GraphQL **JSON**

```
1 {
2   "grant_type": "client_credentials",
3   "client_id": "201604191641app.deliver.com.br",
4   "client_secret": "QXTVP0W1WCRDPEBZ620W"
5 }
```

Body Cookies Headers (9) Test Results

Status: 200 OK Time: 188 ms Size: 413 B Save Response

Pretty Raw Preview Visualize JSON

```
1 {
2   "access_token": "7961778c13d90a72ca116e0c4117843891615320",
3   "expires_in": 3600,
4   "token_type": "Bearer",
5   "scope": null
6 }
```

com o access token gerado colocar no campo conforme abaixo:

GET localhost/api/source/deliver/listarClassificacaoGeral

Params **Authorization** Headers (7) Body Pre-request Script Tests Settings

TYPE

OAuth 2.0

The authorization data will be automatically generated when you send the request. [Learn more about authorization](#)

Add authorization data to

Request Headers

Heads up! These parameters hold sensitive data. To keep this data secure while working in a collaborative environment, we recommend using variables. [Learn more about variables](#)

Current Token

This access token is only available to you. Sync the token to let collaborators on this request use it.

Access Token

Available Tokens 7961778c13d90a72ca116e0c4117843891615320

Header Prefix

Bearer

Status: 200 OK Time: 154 ms Size: 1.58 KB Save Response

Pretty Raw Preview Visualize JSON

no arquivo api\source\src\Core\Configure\Config.php há uma função isDeveloper que quando tiver o ip local não é necessário a geração do token de autenticação para executar os serviços

Caminho dos arquivos que foram utilizados para o desenvolvimento do teste

api\source\index.php

api\source\src\deliver_teste\Controller\servicoTesteController.php

api\source\src\deliver_teste\Controller\deliverController.php

api\source\src\deliver_teste\Model\servicoTesteModel.php

api\source\src\deliver_teste\Model\deliverModel.php

Arquivos de configuração de ambiente

api\source\src\Core\Auth\AuthServerController.php

api\source\src\Core\Configure\Config.php

api\.htaccess

api\source\.htaccess

Json para execução dos serviços de inclusão

Gerar Token

```
{
  "grant_type": "client_credentials",
  "client_id": "201604191641app.deliver.com.br",
  "client_secret": "QXTVPOW1WCRDPEBZ620W"
}
```

Inserir Corredor

```
{
  "nome": "Barry Allen",
  "cpf": "025.456.589-99",
  "data_nascimento": "1985-04-02"
}
```

Inserir Prova

```
{
```

```
"tipo_prova":"5 km",  
"data_prova":"24/01/2021 12:00:00"  
}
```

Inserir Prova_Corredor

```
{  
  "id_prova":"1",  
  "id_corredor":"1"  
}
```

Inserir Resultados

```
{  
  "id_prova_corredor":"1",  
  "hora_inicio_prova":"09:00:00",  
  "hora_conclusao_prova":"11:00:00"  
}
```