

Para la actividad 1 lo voy a añadir algunos testes en una API de una aplicación similar con eh Twitter que está desarrollado en NodeJs para probar la búsqueda del Posts.

1. Creación del proyecto para los tests:

a. Jest install

```
PS C:\dev\git\fullstack-engineering\Master_web_development\mod-05-Arq-Server\week-04\act-final> jest --init

The following questions will help Jest to create a suitable configuration for your project

✓ Would you like to use Jest when running "test" script in "package.json"? ... yes
✓ Choose the test environment that will be used for testing » node
✓ Do you want Jest to add coverage reports? ... yes
✓ Automatically clear mock calls and instances between every test? ... yes

Configuration file created at C:\dev\git\fullstack-engineering\Master_web_development\mod-05-Arq-Server\week-04\act-final\jest.config.js
PS C:\dev\git\fullstack-engineering\Master_web_development\mod-05-Arq-Server\week-04\act-final> npm run test
```

```
6   "scripts": {
7     "start": "node app.js",
8     "dev": "nodemon app.js",
9     "test": "jest --ci"
10  },
11
12  "devDependencies": {
13    "jest": "^23.0.0-alpha.0",
14    "nodemon": "^2.0.14"
15  }
16 }
```

b. Test Structure

```
▼ act-final
  > config
  > controllers
  > coverage
  > middlewares
  > models
  > node_modules
  > postman_json
  ▼ tests\unit\controllers
    JS home.controller.test.js
    JS posts.controller.test.js
  .env
  .env.template
  .gitignore
  JS app.js
  JS jest.config.js
  {} package-lock.json
  {} package.json
```

```

PS C:\dev\git\fullstack-engineering\Master_web_development\mod-05-Arq-Server\week-04\act-final> npm run test

> act-02@1.0.0 test
> jest

FAIL tests/unit/controllers/posts.controller.test.js
  ● Test suite failed to run

    Your test suite must contain at least one test.

    at node_modules/jest-cli/build/TestScheduler.js:256:22

Test Suites: 1 failed, 1 total
Snapshots: 0 total
Time: 2.299s
Ran all test suites.

```

2. Implementación de los tests:

```

JS home.controller.test.js X
fullstack-engineering > Master_web_development > mod-05-Arq-Server > week-04 > act-final > tests > unit > controllers > JS home.controller.test.js > ...
1  const handlers = require('../../../../controllers/home.controller');
2
3  test('testing home page', () => {
4    const req = {}, res = { json: jest.fn() }
5    handlers.home(req, res)
6    expect(res.json.mock.calls[0][0]).toEqual({ 'app': 'alive' })
7  })
8

JS posts.controller.test.js U X
fullstack-engineering > Master_web_development > mod-05-Arq-Server > week-04 > act-final > tests > unit > controllers > JS posts.controller.test.js > te
1  const handlers = require('../../../../controllers/posts.controller');
2  const model = require('../../../../models/post.model');
3
4  test('Find posts by ID', () => {
5    /*model.findById = jest.fn().mockReturnValueOnce(() => { ...
21  const spy = jest
22    .spyOn(model, "findById")
23    .mockResolvedValueOnce({ id: '6bb0794d-3f43-4be8-a267-4dc09315a79e' });
24  const req = { params: jest.fn() }, res = { json: jest.fn() }
25
26  handlers.getById(req, res)
27  expect(spy).toHaveBeenCalledTimes(1);
28  spy.mockRestore();
29  });

```

3. Ejecución y Resultados:

```
PS C:\dev\git\fullstack-engineering\Master_web_development\mod-05-Arq-Server\week-04\act-final> npm run test

> act-final@1.0.0 test
> jest --ci

PASS tests/unit/controllers/home.controller.test.js
PASS tests/unit/controllers/posts.controller.test.js

-----|-----|-----|-----|-----|-----|
File      | % Stmts | % Branch | % Funcs | % Lines | Uncovered Line #s |
-----|-----|-----|-----|-----|-----|
All files | 18.18   | 7.14     | 13.04    | 18.18   |                   |
home.controller.js | 100     | 100     | 100     | 100     |                   |
posts.controller.js | 40      | 16.67    | 20       | 40      | ... 42,43,45,53,55 |
users.controller.js | 0       | 0        | 0        | 0       | ... 67,68,70,71,73 |
-----|-----|-----|-----|-----|-----|

Handlebars: Access has been denied to resolve the property "statements" because it is not an "own property" of its parent.
You can add a runtime option to disable the check or this warning:
See https://handlebarsjs.com/api-reference/runtime-options.html#options-to-control-prototype-access for details
Handlebars: Access has been denied to resolve the property "branches" because it is not an "own property" of its parent.
You can add a runtime option to disable the check or this warning:
See https://handlebarsjs.com/api-reference/runtime-options.html#options-to-control-prototype-access for details
Handlebars: Access has been denied to resolve the property "functions" because it is not an "own property" of its parent.
You can add a runtime option to disable the check or this warning:
See https://handlebarsjs.com/api-reference/runtime-options.html#options-to-control-prototype-access for details
Handlebars: Access has been denied to resolve the property "lines" because it is not an "own property" of its parent.
You can add a runtime option to disable the check or this warning:
See https://handlebarsjs.com/api-reference/runtime-options.html#options-to-control-prototype-access for details

Test Suites: 2 passed, 2 total
Tests:       2 passed, 2 total
Snapshots:   0 total
Time:        13.107s
Ran all test suites.
```

4. Configuración

```
JS posts.controller.test.js U JS jest.config.js ●
fullstack-engineering > Master_web_development > mod-05-Arq-Server > week-04 > act-final > JS jest.config.js > ...

4  module.exports = {
5    // Automatically clear mock calls and instances between every test
6    clearMocks: true,
7
8    // Indicates whether the coverage information should be collected while executing the test
9    collectCoverage: true,
10
11    // An array of glob patterns indicating a set of files for which coverage information should be collected
12    collectCoverageFrom: ["controllers/**/*.js"],
13
14    // The directory where Jest should output its coverage files
15    coverageDirectory: "coverage",
16
17    // The test environment that will be used for testing
18    testEnvironment: "node",
19
20  };
```