



Dynamic Bayesian Networks & Hidden Markov Models

– An Introduction



Overview

- In this lecture and lab
 - Introduction to Dynamic Bayesian Networks
 - Markov Chains
 - Hidden Markov Models (HMMs)
 - Models of sequence data / Time-Series
 - Scoring likelihoods of sequences


Reading

- Russell & Norvig:
 - Chapter 15, Section 1
- Rabiner's Paper
- Stamp's paper

Bayesian Networks Recap

- Method to store joint distribution
- Defined as a directed acyclic graph with local conditional dependencies

Bayesian Network Example



Retrieving Probabilities from the Conditional Distributions

$$P(x_1, \dots, x_n) = \prod_{i=1}^n P(x_i \mid \text{Parents}(x_i))$$

e.g. Probability of John and Mary Calling, Alarm sounding, no Burglary and no Earthquake:

$$\begin{aligned} & P(J \ \& \ M \ \& \ A \ \& \ \neg B \ \& \ \neg E) \\ = & P(J|A)P(M|A)P(A|\neg B, \neg E)P(\neg B)P(\neg E) \\ = & 0.9 \times 0.7 \times 0.001 \times 0.999 \times 0.998 \\ = & 0.00062 \end{aligned}$$

Bayesian Networks Recap

- Method to store joint distribution
- Defined as a directed acyclic graph with local conditional dependencies
- Evidence can be entered in to the model using any of the nodes
- Inference can be used to determine the probability distribution over remaining nodes given the observed evidence


Classification / Clustering

Classification:

- Naïve Bayes Classifier assumes independence between variables given the class: $p(X|C)$
- Can calculate $p(C|X)$ using Bayes Rule or inference

Clustering


- “Hidden” variables to model unmeasured features
- Make C a hidden variable



Dynamic Bayesian Networks

- Nodes represent variables at distinct time slices
- Directed links between nodes
 - Within the same “time slice”
 - Between “time slices”
- Often assume 1st Order Markov Assumption:
 - “Links only need to span *adjacent* time slices in order to make predictions over time”

Dynamic Bayesian Networks




Markov Chains

- Essentially links a number of possible state transitions over a sequence, H , or time window
- Requires:
 - An initial probability distribution over the states
 - A transition probability distribution determining state changes
- Assumes 1st order Markov Assumption:
 - only info at time t is needed to calculate the info at time: $P(H^t | H^{t-1})$


Markov Chains

- Initial distribution: $\pi = [0.5 \quad 0.5]$



Markov Chains

- Initial distribution: $\pi = [0.5 \quad 0.5]$




- Transition Distribution Matrix:

$$A = \begin{matrix} & \begin{matrix} \text{To} \end{matrix} \\ \begin{matrix} \text{From} \end{matrix} & \begin{bmatrix} 0.9 & 0.1 \\ 0.3 & 0.7 \end{bmatrix} \end{matrix}$$

Markov Chains

- Initial distribution: $\pi = [0.5 \quad 0.5]$



- Transition Distribution Matrix:

$$A = \begin{matrix} & \begin{matrix} \text{To} \end{matrix} \\ \begin{matrix} \text{From} \end{matrix} & \begin{bmatrix} 0.9 & 0.1 \\ 0.3 & 0.7 \end{bmatrix} \end{matrix}$$

Markov Chains

- Initial distribution: $\pi = [0.5 \quad 0.5]$

$P(\text{State 1 at } t=1)$

$P(\text{State 2 at } t=1)$

- Transition Distribution Matrix:

$P(\text{State 2 at } t \mid \text{State 1 at } t-1)$

$$A = \begin{matrix} & \begin{matrix} \text{To} \end{matrix} \\ \begin{matrix} \text{From} \end{matrix} & \begin{bmatrix} 0.9 & 0.1 \\ 0.3 & 0.7 \end{bmatrix} \end{matrix}$$

$P(\text{State 2 at } t \mid \text{State 2 at } t-1)$

Markov Chains

- To calculate the probability of the sequence:


$$H = 1,2,1,2$$

Given the Markov Chain, M: $P(H|M) = \pi_1 a_{12} a_{21} a_{12}$

- Start with the initial probability $\pi_1 = 0.5$
- And multiply through with each transition based upon the transition matrix: $\pi_1 a_{12} a_{21} a_{12}$
 $= 0.5 \times 0.1 \times 0.3 \times 0.1$
 $= 0.0015$ (often these are very small numbers)

State Transition Diagram


- Visualising the state transition probabilities (here for a Markov chain with three states)



Demo

<http://setosa.io/blog/2014/07/26/markov-chains/>

Hidden States



- Imagine there is an urn of coloured balls with 5 red balls and 3 green balls: $P(G) = 3/8$
- Now imagine there is another urn with 2 red balls and 6 green, $P(G) = 6/8$
- Someone hands you an urn *from behind a curtain* and asks you the $P(G)$
- After selecting a ball and returning the bag, the process is repeated


Hidden Markov Models

- We can model this using a HMM:
 - Consists of a Markov Chain, H , representing *hidden* states
 - Linked by possible transitions between time points
 - The current state determines the probability distribution of the next state
 - Markov assumption assumed: $P(H_t | H_{t-1})$


Hidden Markov Models – Emission Probabilities

- As well as hidden nodes, there are observed nodes, X
- These are linked directly to the hidden node in their own “time-slice”
- The probability distribution of these observed nodes is conditioned upon the hidden state
- $P(X_t | H_t)$

Hidden Markov Models



Hidden Markov Models



Example:

- Given the following HMM, M :
 - Initial State Distribution - $P(H^1 = i)$: $\pi = [1 \quad 0]$
 - Transition Probability Distribution – $P(H^t = j \mid H^{t-1} = i)$:

$$A = \begin{matrix} & t \\ & \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \\ t-1 \end{matrix}$$

- Probability of hidden state seq: $\{1, 2, 2\}$:

$$P(H \mid M) = \pi_1 a_{12} a_{22}$$

$$= 1 \times 0.2 \times 0.6 = 0.12$$

Example:

- Given the following HMM, M :
 - Initial State Distribution - $P(H^1 = i)$: $\pi = [1 \quad 0]$
 - Transition Probability Distribution – $P(H^t = j \mid H^{t-1} = i)$:

$$A = \begin{matrix} & \begin{matrix} t \\ \end{matrix} \\ \begin{matrix} t-1 \\ \end{matrix} & \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \end{matrix}$$


- We also need an Emission (or Sensor) Distribution:

$$B = \begin{matrix} & \begin{matrix} x \\ \end{matrix} \\ \begin{matrix} \mathcal{H} \\ \end{matrix} & \begin{bmatrix} 0.5 & 0.5 \\ 0.1 & 0.9 \end{bmatrix} \end{matrix}$$

Example:

$$\pi = [1 \quad 0] \quad A = \begin{matrix} & & t \\ & & \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \\ & t-1 & \end{matrix} \quad B = \begin{matrix} & & x \\ & & \begin{bmatrix} 0.5 & 0.5 \\ 0.1 & 0.9 \end{bmatrix} \\ & H & \end{matrix}$$

- Use this to generate a sequence




Example:

$$\pi = \begin{bmatrix} 1 & 0 \end{bmatrix} \quad A = \begin{matrix} & \begin{matrix} t & X \end{matrix} \\ \begin{matrix} t-1 \end{matrix} & \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \end{matrix} \quad B = \begin{matrix} & X \\ \begin{matrix} H \end{matrix} & \begin{bmatrix} 0.5 & 0.5 \\ 0.1 & 0.9 \end{bmatrix} \end{matrix}$$

- Use this to generate a sequence

H

X



Example:


$$\pi = \boxed{1} \ 0 \quad A = \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \quad B = \begin{bmatrix} 0.5 & 0.5 \\ 0.1 & 0.9 \end{bmatrix}$$

t $t-1$ X H

- Use this to generate a sequence

H 1

X



Example:


$$\pi = \begin{bmatrix} 1 & 0 \end{bmatrix} \quad A = \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \quad B = \begin{bmatrix} 0.5 & 0.5 \\ 0.1 & 0.9 \end{bmatrix}$$

t $t-1$ X H

- Use this to generate a sequence

H 1

X 1




Example:

$$\pi = \begin{bmatrix} 1 & 0 \end{bmatrix} \quad A = \begin{bmatrix} \overset{t}{\boxed{0.8}} & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \quad \overset{X}{B} = \begin{bmatrix} 0.5 & 0.5 \\ 0.1 & 0.9 \end{bmatrix} \quad \overset{H}{\text{H}}$$

- Use this to generate a sequence

H 1 1

X 1



Example:


$$\pi = \begin{bmatrix} 1 & 0 \end{bmatrix} \quad A = \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \quad B = \begin{bmatrix} 0.5 & \boxed{0.5} \\ 0.1 & 0.9 \end{bmatrix}$$

t $t-1$ X H

- Use this to generate a sequence

H 1 1

X 1 2




Example:

$$\pi = \begin{bmatrix} 1 & 0 \end{bmatrix} \quad A = \begin{matrix} & \begin{matrix} \text{H} & \text{X} \end{matrix} \\ \begin{matrix} \text{H} \\ \text{X} \end{matrix} & \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \end{matrix}^{t-1} \quad B = \begin{matrix} & \begin{matrix} \text{H} & \text{X} \end{matrix} \\ \begin{matrix} \text{H} \\ \text{X} \end{matrix} & \begin{bmatrix} 0.5 & 0.5 \\ 0.1 & 0.9 \end{bmatrix} \end{matrix}$$

- Use this to generate a sequence

H 1 1 1

X 1 2 2




Example:

$$\pi = \begin{bmatrix} 1 & 0 \end{bmatrix} \quad A = \begin{bmatrix} \boxed{0.8} & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \quad B = \begin{bmatrix} \boxed{0.5} & 0.5 \\ 0.1 & 0.9 \end{bmatrix}$$

- Use this to generate a sequence

H 1 1 1 1
X 1 2 2 1




Example:

$$\pi = \begin{bmatrix} 1 & 0 \end{bmatrix} \quad A = \begin{bmatrix} 0.8 & \boxed{0.2} \\ 0.4 & 0.6 \end{bmatrix} \quad B = \begin{bmatrix} 0.5 & 0.5 \\ 0.1 & \boxed{0.9} \end{bmatrix}$$

- Use this to generate a sequence

H 1 1 1 1 2
X 1 2 2 1 2




Example:

$$\pi = \begin{bmatrix} 1 & 0 \end{bmatrix} \quad A = \begin{matrix} & \begin{matrix} t & X \end{matrix} \\ \begin{matrix} t-1 \\ \end{matrix} & \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & \boxed{0.6} \end{bmatrix} \end{matrix} \quad B = \begin{matrix} & \begin{matrix} t & X \end{matrix} \\ \begin{matrix} H \\ \end{matrix} & \begin{bmatrix} 0.5 & 0.5 \\ 0.1 & \boxed{0.9} \end{bmatrix} \end{matrix}$$

- Use this to generate a sequence

H 1 1 1 1 2 2
X 1 2 2 1 2 2




Example:

$$\pi = [1 \quad 0] \quad A = \begin{matrix} & & t \\ & \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & \boxed{0.6} \end{bmatrix} & \\ & & t-1 \end{matrix} \quad B = \begin{matrix} & & X \\ & \begin{bmatrix} 0.5 & 0.5 \\ 0.1 & \boxed{0.9} \end{bmatrix} & \\ & & H \end{matrix}$$

- Use this to generate a sequence

H 1 1 1 1 2 2 2
X 1 2 2 1 2 2 2




Example:

$$\pi = \begin{bmatrix} 1 & 0 \end{bmatrix} \quad A = \begin{matrix} & & t \\ & \begin{bmatrix} 0.8 & 0.2 \\ 0.4 & 0.6 \end{bmatrix} & \\ & & t-1 \end{matrix} \quad B = \begin{matrix} & & x \\ & \begin{bmatrix} 0.5 & 0.5 \\ 0.1 & 0.9 \end{bmatrix} & \\ & & H \end{matrix}$$

- Use this to generate a sequence

H 1 1 1 1 2 2 2 1
X 1 2 2 1 2 2 2 1




Example:

$$\pi = \begin{bmatrix} 1 & 0 \end{bmatrix} \quad A = \begin{bmatrix} \boxed{0.8} & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \quad B = \begin{bmatrix} 0.5 & \boxed{0.5} \\ 0.1 & 0.9 \end{bmatrix}$$

t $t-1$ X H

- Use this to generate a sequence

H 1 1 1 1 2 2 2 1 1
X 1 2 2 1 2 2 2 1 2




Example:

$$\pi = \begin{bmatrix} 1 & 0 \end{bmatrix} \quad A = \begin{bmatrix} \boxed{0.8} & 0.2 \\ 0.4 & 0.6 \end{bmatrix} \quad B = \begin{bmatrix} \boxed{0.5} & 0.5 \\ 0.1 & 0.9 \end{bmatrix}$$

t $t-1$ x H

- Use this to generate a sequence

H 1 1 1 1 2 2 2 1 1 1
X 1 2 2 1 2 2 2 1 2 1



Examples

- Given the following HMM, M to model tossing a coin using 3 hidden states:

$$\pi = [0.2 \quad 0.3 \quad 0.5]$$

$$B = \begin{array}{c} \text{Heads} \quad \text{Tails} \\ \begin{bmatrix} 0.5 & 0.5 \\ 0.75 & 0.25 \\ 0.25 & 0.75 \end{bmatrix} \end{array}$$

$$A = \begin{bmatrix} 0.3 & 0.3 & 0.3 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.5 & 0.2 \end{bmatrix}$$

- You observe the sequence: $X = H H H H T H T T T T$

1) What state sequence is most likely?

Different ways to interpret “most likely”!

Examples

- Given the following HMM, M to model tossing a coin using 3 hidden states:

$$\pi = [0.2 \quad 0.3 \quad 0.5]$$

$$B = \begin{array}{c} \text{Heads} \quad \text{Tails} \\ \begin{bmatrix} 0.5 & 0.5 \\ 0.75 & 0.25 \\ 0.25 & 0.75 \end{bmatrix} \end{array}$$

$$A = \begin{bmatrix} 0.3 & 0.3 & 0.3 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.5 & 0.2 \end{bmatrix}$$

- You observe the sequence: $X = H H H H T$
- 2) What is the probability of the observation sequence and the “most likely” state sequence?

1) What state sequence is “most likely”?

$$\pi = [0.2 \quad 0.3 \quad 0.5]$$

	Heads	Tails
$B =$	$\begin{bmatrix} 0.5 & 0.5 \\ 0.75 & 0.25 \\ 0.25 & 0.75 \end{bmatrix}$	

$$A = \begin{bmatrix} 0.3 & 0.3 & 0.3 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.5 & 0.2 \end{bmatrix}$$
$$X = \text{HHHHT}$$

For now let's assume “most likely” state sequence is the one for which the probability of each individual observation is maximum: for each Heads, the most likely state is S2 and for each Tails, the most likely state is S3:

$$H = 2, 2, 2, 2, 3$$

2) Observing Seq & Most Likely Hidden Seq?

$$\pi = [0.2 \quad 0.3 \quad 0.5]$$

$$B = \begin{array}{c} \text{Heads} \quad \text{Tails} \\ \begin{bmatrix} 0.5 & 0.5 \\ 0.75 & 0.25 \\ 0.2 & 0.8 \end{bmatrix} \end{array}$$

$$A = \begin{bmatrix} 0.3 & 0.3 & 0.3 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.5 & 0.2 \end{bmatrix}$$

X	H	H	H	H	T
H	2	2	2	2	3



$$P(X, H \mid M) = P(X^1 \mid H^1) \times P(H^1) \times P(X^2 \mid H^2) \times P(H^2 \mid H^1) \dots$$

$$= (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.5 \times 0.8)$$

2) Prob of the Observation Seq & Most Likely Hidden Seq?

$$\pi = [0.2 \quad 0.3 \quad 0.5]$$

$$B = \begin{array}{c} \text{Heads} \quad \text{Tails} \\ \begin{bmatrix} 0.5 & 0.5 \\ 0.75 & 0.25 \\ 0.2 & 0.8 \end{bmatrix} \end{array}$$

$$A = \begin{bmatrix} 0.3 & 0.3 & 0.3 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.5 & 0.2 \end{bmatrix}$$

X	H	H	H	H	T
H	2	2	2	2	3



$$P(X, H \mid M) = P(X^1 \mid H^1) \times P(H^1) \times P(X^2 \mid H^2) \times P(H^2 \mid H^1) \dots$$

$$= (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.5 \times 0.8)$$

2) Prob of the Observation Seq & Most Likely Hidden Seq?

$$\pi = [0.2 \quad 0.3 \quad 0.5]$$

$$B = \begin{matrix} & \text{Heads} & \text{Tails} \\ \begin{matrix} \text{H} \\ \text{T} \end{matrix} & \begin{bmatrix} 0.5 & 0.5 \\ 0.75 & 0.25 \\ 0.2 & 0.8 \end{bmatrix} \end{matrix}$$

$$A = \begin{bmatrix} 0.3 & 0.3 & 0.3 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.5 & 0.2 \end{bmatrix}$$

X	H	H	H	H	T
H	2	2	2	2	3



$$P(X, H \mid M) = P(X^1 \mid H^1) \times P(H^1) \times P(X^2 \mid H^2) \times P(H^2 \mid H^1) \dots$$

$$= (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.5 \times 0.8)$$

2) Prob of the Observation Seq & Most Likely Hidden Seq?

$$\pi = [0.2 \quad 0.3 \quad 0.5]$$

$$B = \begin{array}{c} \text{Heads} \quad \text{Tails} \\ \begin{bmatrix} 0.5 & 0.5 \\ 0.75 & 0.25 \\ 0.2 & 0.8 \end{bmatrix} \end{array}$$

$$A = \begin{bmatrix} 0.3 & 0.3 & 0.3 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.5 & 0.2 \end{bmatrix}$$

X	H	H	H	H	T
H	2	2	2	2	3



$$P(X, H \mid M) = P(X^1 \mid H^1) \times P(H^1) \times P(X^2 \mid H^2) \times P(H^2 \mid H^1) \dots$$

$$= (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.5 \times 0.8)$$

2) Prob of the Observation Seq & Most Likely Hidden Seq?

$$\pi = [0.2 \quad 0.3 \quad 0.5]$$

$$B = \begin{array}{c} \text{Heads} \quad \text{Tails} \\ \begin{bmatrix} 0.5 & 0.5 \\ 0.75 & 0.25 \\ 0.2 & 0.8 \end{bmatrix} \end{array}$$

$$A = \begin{bmatrix} 0.3 & 0.3 & 0.3 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.5 & 0.2 \end{bmatrix}$$

X	H	H	H	H	T
H	2	2	2	2	3



$$P(X, H \mid M) = P(X^1 \mid H^1) \times P(H^1) \times P(X^2 \mid H^2) \times P(H^2 \mid H^1) \dots$$

$$= (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.5 \times 0.8)$$

2) Prob of the Observation Seq & Most Likely Hidden Seq?

$$\pi = [0.2 \quad 0.3 \quad 0.5]$$

$$B = \begin{array}{c} \text{Heads} \quad \text{Tails} \\ \begin{bmatrix} 0.5 & 0.5 \\ 0.75 & 0.25 \\ 0.2 & 0.8 \end{bmatrix} \end{array}$$

$$A = \begin{bmatrix} 0.3 & 0.3 & 0.3 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.5 & 0.2 \end{bmatrix}$$

X	H	H	H	H	T
H	2	2	2	2	3



$$P(X, H \mid M) = P(X^1 \mid H^1) \times P(H^1) \times P(X^2 \mid H^2) \times P(H^2 \mid H^1) \dots$$

$$= (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.5 \times 0.8)$$

2) Prob of the Observation Seq & Most Likely Hidden Seq?

$$\pi = [0.2 \quad 0.3 \quad 0.5]$$

$$B = \begin{array}{c} \text{Heads} \quad \text{Tails} \\ \begin{bmatrix} 0.5 & 0.5 \\ 0.75 & 0.25 \\ 0.2 & 0.8 \end{bmatrix} \end{array}$$

$$A = \begin{bmatrix} 0.3 & 0.3 & 0.3 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.5 & 0.2 \end{bmatrix}$$

X	H	H	H	H	T
H	2	2	2	2	3



$$P(X, H \mid M) = P(X^1 \mid H^1) \times P(H^1) \times P(X^2 \mid H^2) \times P(H^2 \mid H^1) \dots$$

$$= (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.3 \times 0.75) \times (0.5 \times 0.8)$$

Typical Algorithms for HMMs

1. Given an observed sequence, X and a HMM, M , how do we compute its probability given the model?: $p(X | M)$ - *Forward Algorithm*
2. Given the observed sequence and the model, how do we choose an *optimal* hidden state sequence?: *Most Probable Explanation using the Viterbi algorithm*


Typical Algorithms for HMMs

3. How do we adjust the model parameters to maximise the probability of the observed sequence given the model?: *Learning using the Expectation Maximisation algorithm*

Sequences for Characters

Exercise: character recognition with HMM(1)

- The structure of hidden states:



- Observation = number of islands in the vertical slice.

- HMM for character 'A' :

$$\text{Transition probabilities: } \{a_{ij}\} = \begin{pmatrix} .8 & .2 & 0 \\ 0 & .8 & .2 \\ 0 & 0 & 1 \end{pmatrix}$$

$$\text{Observation probabilities: } \{b_{jk}\} = \begin{pmatrix} .9 & .1 & 0 \\ .1 & .8 & .1 \\ .9 & .1 & 0 \end{pmatrix}$$



1 1 2 2 2 2 2 1 1

- HMM for character 'B' :


$$\text{Transition probabilities: } \{a_{ij}\} = \begin{pmatrix} .8 & .2 & 0 \\ 0 & .8 & .2 \\ 0 & 0 & 1 \end{pmatrix}$$

$$\text{Observation probabilities: } \{b_{jk}\} = \begin{pmatrix} .9 & .1 & 0 \\ 0 & .2 & .8 \\ .6 & .4 & 0 \end{pmatrix}$$



1 1 3 3 3 3 3 3 3

Aligning Sequences of Nucleotides



- From the UBC Bioinformatics Centre (UBiC)

Applications

- Dynamic mouse gesture recognition

<http://www.youtube.com/watch?v=0CNJ2fCj4xQ>

- Text Modelling – sequences of words

<https://projects.haykranen.nl/markov/demo/>

- Speech Recognition (Rabiner's paper)

- Tracking Speech to create avatar:

<https://www.youtube.com/watch?v=J95TiRLoci8>

Applications

- Dynamic Bayesian Network for monitoring / tracking behaviour:

<https://www.youtube.com/watch?v=nEsS9dukgvM>

- Dynamic Bayesian Network Automatic Driving

<https://www.youtube.com/watch?v=aWtd8ZCcuZg>

Summary

- Sequences and how to model them
- How to build HMMs
 - How to generate sequences
 - Calculate useful probabilities
- Three key useful algorithms:
 - Viterbi, Forward, EM
- Examples

Next Week: Philosophy & Ethics of Artificial Intelligence

- AI in the news
- Impacts on Society

Support The Guardian
Available for everyone, funded by readers
[Contribute →](#) [Subscribe →](#)

Search jobs Sign in Search UK edition

The Guardian

News Opinion Sport Culture Lifestyle More

UK World Business Coronavirus Football Environment UK politics Education Society Science Tech Global development Obituaries

Uber

Uber ditches effort to develop own self-driving car

Ride-hailing company sells division to startup Aurora but says they will collaborate



BBC Sign in News Sport Weather

NEWS TECHNOLOGY

Home World UK England N. Ireland Scotland Wales Business Politics

2 December 2014 Last updated at 13:02

Stephen Hawking warns artificial intelligence could end mankind

COMMENTS (1027)



By Rory Cellan-Jones
Technology correspondent



Stephen Hawking: "Humans, who are limited by slow biological evolution, couldn't compete and would be superseded"

Prof Stephen Hawking, one of Britain's pre-eminent scientists, has said that efforts to create thinking machines pose a threat to our very existence.

Vivas Today and Tomorrow

- Deadline was TODAY
- If you attempt today (having submitted already) but do not get vivad in time we will hold an emergency session next week
- ONLY VIVAS FOR PEOPLE WHO HAVE COMPLETED ALL 3 LABS
- Preference: LAB3 > LAB2&3 > LAB1&2&3