



Training Frontier AI Agents

How we trained Mistral Medium 3.5

Antonin Faure


May 7th, 2026



Mistral Medium 3.5

How we applied RL to agentic tasks

Mistral Medium 3.5 128B	Kimi K2.5 1000B - A32B	GLM 5 744B - A40B	Qwen3.5 397B - A17B
----------------------------	---------------------------	----------------------	------------------------



Mistral Medium 3.5

How we applied RL to agentic tasks


Mistral Medium 3.5 128B	Kimi K2.5 1000B - A32B	GLM 5 744B - A40B	Qwen3.5 397B - A17B
----------------------------	---------------------------	----------------------	------------------------



Mistral Medium 3.5

How we applied RL to agentic tasks

■ Agentic Benchmarks vs previous Mistral models



RL for LLMs

- 01 Introduction
- 02 Losses & Objectives
- 03 Online Training
- 04 Training Recipes

Agentic Training

- 05 Tokenization
- 06 Environments
- 07 Harnesses




A decorative background consisting of a grid of squares. Some squares are orange, some are grey, and many are dark grey/black. The pattern is sparse and abstract, with clusters of colored squares scattered across the slide.

01

Introduction



What's an Agent




Agent

A system that observes **state**, chooses **actions**, receives **feedback** and updates future behavior



Why RL for agents?



LLMs trained only with next-token prediction are not directly optimized for:

- Long-horizon task success
- Tool-use correctness
- Recovery from mistakes
- Search and exploration
- Acting under partial information

Agent training is **sequential decision-making**, not just supervised imitation

A decorative background consisting of a grid of small squares. Some squares are orange, some are grey, and some are dark grey. The squares are scattered across the slide, with a higher concentration on the right side.

02

Objectives



Recap: PPO objective

$$\mathcal{J}_{\text{PPO-KL}}(\theta) = \mathbb{E} \left[\frac{1}{\sum_{i=1}^G |o_i|} \sum_{i=1}^G \sum_{t=1}^{|o_i|} \left(\min \left(r_{i,t}(\theta) \hat{A}_{i,t}, \text{clip} \left(r_{i,t}(\theta), 1 - \epsilon, 1 + \epsilon \right) \hat{A}_{i,t} \right) - \beta D_{\text{KL}} \left(\pi_{\theta}(\cdot \mid q, o_{i,<t}) \parallel \pi_{\text{ref}}(\cdot \mid q, o_{i,<t}) \right) \right) \right]$$

- Clipped surrogate objective
- Improve the policy, but prevent it from changing too much in one update.
- KL term also keeps the optimized policy close to a reference policy.

Biggest issue: Clipping introduces biased gradients

(can be fine for stability, but it can suppress learning on important tokens. More on that later...)



Recap: DPO

DPO sample reweighting

Gradient on winner is gradient descent of cross entropy loss

$$\partial_{\theta} L(\theta) = -\beta \mathbb{E}_{(x, y_w, y_l)} \left[\sigma \left(\beta \left(\log \frac{\pi_{\theta}(y_l|x)}{\pi_{\text{ref}}(y_l|x)} - \log \frac{\pi_{\theta}(y_w|x)}{\pi_{\text{ref}}(y_w|x)} \right) \right) \left(\partial_{\theta} \log \pi_{\theta}(y_w|x) - \partial_{\theta} \log \pi_{\theta}(y_l|x) \right) \right]$$

Samples are from a human annotated dataset of (history, winner, loser)

Gradient on loser is gradient ASCENT of cross entropy loss

- Simpler than PPO. No separate reward model or value function.
- Depends heavily on the preference dataset

Recap: GRPO

$$\mathcal{J}_{\text{GRPO}}(\theta) = \mathbb{E} \left[\frac{1}{\sum_{i=1}^G |o_i|} \sum_{i=1}^G \sum_{t=1}^{|o_i|} \left(\min \left(r_{i,t}(\theta) \hat{A}_i, \text{clip} \left(r_{i,t}(\theta), 1 - \epsilon, 1 + \epsilon \right) \hat{A}_i \right) - \beta D_{\text{KL}}^{i,t}(\theta) \right) \right]$$

$$\hat{A}_i = \frac{R(q, o_i) - \frac{1}{G} \sum_{j=1}^G R(q, o_j)}{\text{std} \left(\{R(q, o_j)\}_{j=1}^G \right)}$$

normalized reward over the group

How to choose the group size?


Can depend on: 1) the type of task and 2) the difficulty of the sample

You can do progressive group size during training as difficulty ramps-up!


Example: for coding xAI is using 512 (brute forcing a bit...); OpenAI between 32 and 64 (for Deep Research)



GRPO: group diversity matters



All-positive groups: every sample in the group gets the same positive outcome. The relative advantage is *near zero*.



All-zero groups: every sample fails. Again there is little or no learning signal from relative comparison.

GRPO-style training learns from **relative differences within a group**. When groups become non-diverse, the normalized advantages collapse and updates become weak or null.

Theoretical limits of GRPO: clipping

- 1) Rare tokens like “*Aha*”, “*Wait*”, or “*Let me reconsider*” can induce reflective behavior
- 2) Since they are rare, the base policy assigns low probability: $\pi_{\theta_{\text{old}}}(o_{i,t} \mid q, o_{i,<t})$ is small
- 3) Therefore the ratio $r_{i,t}(\theta) = \frac{\pi_{\theta}(o_{i,t} \mid q, o_{i,<t})}{\pi_{\theta_{\text{old}}}(o_{i,t} \mid q, o_{i,<t})}$ is high for these tokens and they get clipped
- 4) When they get clipped, these tokens don't contribute to gradient update. To see why:

$$\ell_{i,t}^{\text{PPO}}(\theta) = \min \left(r_{i,t}(\theta) \hat{A}_{i,t}, \text{clip} \left(r_{i,t}(\theta), 1 - \epsilon, 1 + \epsilon \right) \hat{A}_{i,t} \right) \quad (\text{per-token surrogate})$$

Assume

$$\hat{A}_{i,t} > 0$$

$$r_{i,t}(\theta) > 1 + \epsilon$$

$$\ell_{i,t}^{\text{PPO}}(\theta) = (1 + \epsilon) \hat{A}_{i,t}$$

doesn't depend on theta anymore!



CISPO

Solution: Clipped Importance Sampling-weight Policy Optimization

Clip the importance-sampling weights instead of the token updates.
All tokens contribute to the gradient.

$$\mathcal{J}_{\text{CISPO}}(\theta) = \mathbb{E}_{(q,a) \sim \mathcal{D}, \{o_i\}_{i=1}^G \sim \pi_{\theta_{\text{old}}}(\cdot | q)}$$

$$\left[\frac{1}{\sum_{i=1}^G |o_i|} \sum_{i=1}^G \sum_{t=1}^{|o_i|} \text{sg}(\hat{r}_{i,t}(\theta)) \hat{A}_{i,t} \log \pi_{\theta}(o_{i,t} | q, o_{i,<t}) \right]$$

*note: no KL
penalty term*

$$\hat{r}_{i,t}(\theta) = \text{clip} \left(r_{i,t}(\theta), 1 - \epsilon_{\text{low}}^{\text{IS}}, 1 + \epsilon_{\text{high}}^{\text{IS}} \right)$$

$$r_{i,t}(\theta) = \frac{\pi_{\theta}(o_{i,t} | q, o_{i,<t})}{\pi_{\theta_{\text{old}}}(o_{i,t} | q, o_{i,<t})}$$

sg(·) means “stop gradient”, the gradient doesn’t flow through this term. It’s treated as a **constant** when differentiating!



CISPO

Math sanity check

GRPO

$$\ell_{i,t}^{\text{PPO}}(\theta) = \min \left(r_{i,t}(\theta) \hat{A}_{i,t}, \text{clip} \left(r_{i,t}(\theta), 1 - \epsilon, 1 + \epsilon \right) \hat{A}_{i,t} \right)$$

CISPO

$$\ell_{i,t}^{\text{CISPO}}(\theta) = \text{sg}(\hat{r}_{i,t}(\theta)) \hat{A}_{i,t} \log \pi_{\theta}(o_{i,t} \mid q, o_{i,<t}) \quad \text{with} \quad \hat{r}_{i,t}(\theta) = \text{clip} \left(r_{i,t}(\theta), 1 - \epsilon_{low}^{IS}, 1 + \epsilon_{high}^{IS} \right)$$

Same edge case as before $\hat{A}_{i,t} > 0$

$$r_{i,t}(\theta) > 1 + \epsilon_{high}^{IS}$$

$$\hat{r}_{i,t}(\theta) = 1 + \epsilon_{high}^{IS}$$

So $\ell_{i,t}^{\text{CISPO}}(\theta) = \text{sg}(1 + \epsilon_{high}^{IS}) \hat{A}_{i,t} \log \pi_{\theta}(o_{i,t} \mid q, o_{i,<t})$

$$\nabla_{\theta} \ell_{i,t}^{\text{CISPO}}(\theta) = (1 + \epsilon_{high}^{IS}) \hat{A}_{i,t} \nabla_{\theta} \log \pi_{\theta}(o_{i,t} \mid q, o_{i,<t})$$

Token contribute to gradient!



CISPO




Figure 2 | Comparison of GRPO, DAPO, and our proposed CISPO on AIME 2024, based on Qwen2.5-32B-base. CISPO outperforms both GRPO and DAPO in terms of performance at the same number of training steps, and achieves comparable performance to DAPO using 50% of the training steps.



03

Online Training



Definitions

On-Policy

Data is generated by the **current policy** being optimized

$$y \sim \pi_{\theta}$$

Off-Policy

Data was generated by a different policy

$$y \sim \pi_{old}, \pi_{old} \neq \pi_{\theta}$$


Online

Fresh data is generated during training.
The data distribution changes as the policy changes

Offline

Training uses a fixed pre-collected dataset.
There is no live rollout loop during optimization

Online Training Pipeline




Rollouts are generated by the **current policy**

Task distribution should become **harder** as the policy improves


Orchestration Challenges

Naïve approach




Orchestration Challenges

Naïve approach



Orchestration Challenges


Rollouts



In practice, rollouts have very different timings... especially agentic ones!

Orchestration Challenges

Fully **asynchronous** generation with policy update **during** inference



Every component can become bottleneck at some point depending on regime!


Orchestration Challenges

Fully **asynchronous** generation with policy update **during** inference

- The **batch size**, denoted as n_batch , refers to the number of sequences collected before updating the generator's weight
- The **minibatch size**, $n_minibatch$, indicates the number of sequences used to compute the gradient and perform a single optimization step
- The **number of concurrent sequences**, n_async , which represents the number of sequences being generated in parallel.

If the number of concurrently generated sequences n_async is much larger than the batch size n_batch , a typical sequence was generated with n_async/n_batch different policies and could be **too off-policy**. The effect becomes worse as we do more than one mini batch update per one batch.

Online RL Infrastructure



Engines Numerical Gap

Inference engines (vLLM) use optimizations like **kernel fusion** that do not guarantee **bitwise consistency**.

This inconsistency is especially critical when the **inference and training backends** (like the Megatron engine) are **mismatched**.

While it is possible to use sampling probabilities from the inference engine during policy optimization, the numerical errors accumulated from this backend mismatch can lead to **instability**.

Async GRPO architecture




Figure 1 · The async GRPO pipeline: vLLM generates rollouts in BF16, while the trainer computes gradients in FP32. The precision mismatch lives at the interface between these two systems.

Defeating the trainer-generator precision mismatch in TRL


Engines Numerical Gap

DTYPE (model weight loading dtype)

The precision of the stored model parameters. When set to `float32`, the optimizer maintains full-precision weights. When set to `bfloat16`, the weights themselves are stored in BF16, which means optimizer updates are also accumulated in BF16.

Autocast (torch.amp BF16=True/False)

Controls whether the forward pass matrix multiplications use hardware-accelerated BF16 GEMMs. When `BF16=True`, all matmuls cast their operands to BF16 before execution, matching vLLM's inference precision.



Defeating the trainer-generator precision mismatch in TRL



Empirical limits: case of Mixture of Experts (MoE)

Every Attention Matters: An Efficient Hybrid Architecture for Long-Context Reasoning

Ling Team

Bin Han, Caizhi Tang, Chen Liang, Donghao Zhang, Fan Yuan, Feng Zhu, Jie Gao, Jingyu Hu, Longfei Li, Meng Li, Mingyang Zhang, Peijie Jiang, Peng Jiao, Qian Zhao, Qingyuan Yang, Wenbo Shen, Xinxing Yang, Yalin Zhang, Yankun Ren, Yao Zhao, Yibo Cao, Yixuan Sun, Yue Zhang, Yuchen Fang, Zibin Lin, Zixuan Cheng, Jun Zhou

Xiaomi MiMo



Stabilizing MoE Reinforcement Learning by Aligning Training and Inference Routers

Wenhao Ma^{1,2*} Hailin Zhang¹ Liang Zhao¹ Yifan Song^{1,2}
Yudong Wang^{1,2} Zhifang Sui^{1,2} Fuli Luo^{1,2}



2025-07-29

Group Sequence Policy Optimization

Chujie Zheng^{*} Shixuan Liu^{*} Mingze Li^{*} Xiong-Hui Chen^{*} Bowen Yu^{*}
Chang Gao^{*} Kai Dang^{*} Yuqiong Liu^{*} Rui Men^{*} An Yang^{*} Jingren Zhou^{*}
Junyang Lin^{*}
Qwen Team, Alibaba Inc.

GEOMETRIC-MEAN POLICY OPTIMIZATION

Yuzhong Zhao^{1*} Yue Liu^{1*} Junpeng Liu² Jingye Chen³ Xun Wu⁴ Yaru Hao⁴
Tengchao Lv⁴ Shaohan Huang⁴ Lei Cui⁴ Qixiang Ye¹ Fang Wan¹ Furu Wei⁴
¹UCAS ²CUHK ³HKUST ⁴Microsoft Research
<https://aka.ms/GeneralAI>

Everyone finds online training of MoE hard...




MoE issue: top-k routing is non-differentiable

The “original sin” of MoEs: top-k is non-differentiable!

$$h_t = u_t + \sum_{i=1}^N g_{i,t} \text{FFN}_i(u_t)$$

$$g_{i,t} = \begin{cases} s_{i,t} & \text{if in top-k} \\ 0 & \text{otherwise} \end{cases}$$

$$s_{i,t} = \text{softmax}(u_t^T e_i)$$



With MoE models, the rollout is not only a token sequence. It is also a sequence of **expert-routing** decisions


- 1) GRPO stores sampled tokens, log-probs, rewards, and group advantages
- 2) The trainer recomputes log-probs for the sampled tokens
- 3) In a dense model, recomputation mostly follows the same computation path
- 4) In an MoE model, **top-k routing is discrete and can select different experts**
- 5) Then the trainer estimates gradients for a different hidden-state path than the generator used!

MoE issue: top-k routing is non-differentiable

Mechanism

- vLLM and train diverge a bit
- choose different experts
- different experts causes a lot more divergence
- amplifies across layers

Trainer/generator mismatch
exacerbated by
non-differentiability!



MoE issue: top-k routing is non-differentiable

Group Sequence Policy Optimization

Chujie Zheng* Shixuan Liu Mingze Li Xiong-Hui Chen Bowen Yu*
Chang Gao Kai Dang Yuqiong Liu Rui Men An Yang Jingren Zhou
Junyang Lin
Qwen Team, Alibaba Inc.




Figure 3: The Routing Replay strategy plays a critical role in the normal convergence of the GRPO training of MoE models.

One solution:
router-replay

Store selected experts during generation and replay them at training time

[Group Sequence Policy Optimization \[2507.18071\]](#)



04

Training Recipes



Good Soups

Data soup

- Most basic one. Mix multiple data sources slices in a single training recipe
 - good: covers modes, tools, style, domains
 - risk: bad mixture weights can erase capabilities or amplify artifacts

$$D_{\text{soup}} = \bigcup_m \lambda_m D_m$$



Model soup


- Train specialist models
- Merge the resulting models by weight averaging (*Cohere is known for doing this*)
- Note: only works when checkpoints are compatible ofc

$$\theta_{\text{soup}} = \sum_{j=1}^K \alpha_j \theta_j, \quad \sum_j \alpha_j = 1$$

Good Soups


LongCat-Flash-Thinking (Nov 2025)

Model soup



[LongCat-Flash-Thinking \[2509.18883\]](#)

Offline DPO



Llama3 post-training pipeline (2024)

[Llama3 \[2407.21783\]](#)

Online DPO (aka oDPO)

A DPO-style update where preference pairs are created **during training** from the current policy, instead of coming only from a static online dataset.

$\pi_{\theta_k} \rightarrow \text{sample } (y_1, y_2) \rightarrow \text{judge preference} \rightarrow \text{DPO update} \rightarrow \pi_{\theta_{k+1}}$

Pros

- Fresher data distribution
- Catches deployment-specific failures
- Cheaper than full reward-model PPO loops

Cons

- Judge bias becomes training bias
- Still depends on prompt/eval coverage



Online DPO (aka oDPO)

A DPO-style update where preference pairs are created **during training** from the current policy, instead of coming only from a static online dataset.

OFFLINE DPO

$$\partial_{\theta} L(\theta) = -\beta \mathbb{E}_{(x, y_w, y_l)} \left[\sigma \left(\beta \left(\log \frac{\pi_{\theta}(y_l|x)}{\pi_{\text{ref}}(y_l|x)} - \log \frac{\pi_{\theta}(y_w|x)}{\pi_{\text{ref}}(y_w|x)} \right) \right) \left(\partial_{\theta} \log \pi_{\theta}(y_w|x) - \partial_{\theta} \log \pi_{\theta}(y_l|x) \right) \right]$$

Samples are from a human annotated dataset of (history, winner, loser)

DPO sample reweighting

Gradient on winner is gradient descent of cross entropy loss

Gradient on loser is gradient ASCENT of cross entropy loss

ONLINE DPO

$$\partial_{\theta} L(\theta) = -\beta \mathbb{E}_{(x, y_1, y_2 \sim \pi_{\theta}(\cdot|x))} \left[\sigma \left(\beta \cdot \text{Rank}(y_1, y_2) \left(\log \frac{\pi_{\theta}(y_1|x)}{\pi_{\text{ref}}(y_1|x)} - \log \frac{\pi_{\theta}(y_2|x)}{\pi_{\text{ref}}(y_2|x)} \right) \right) \cdot \text{Rank}(y_1, y_2) \cdot (\partial_{\theta} \log \pi_{\theta}(y_1|x) - \partial_{\theta} \log \pi_{\theta}(y_2|x)) \right]$$

Prompts are from a dataset
Two generations are sampled from the current model

Gradient direction is given by the ranking function

$$\text{Ranking}(y_1, y_2) = \begin{cases} 1 & \text{if } y_1 \text{ is better than } y_2 \\ -1 & \text{otherwise} \end{cases}$$

Story 1: fixing tone switch with oDPO

What happened during Mistral Medium 3 release (May 7th 2025 - 1y ago!)

- Evals and first vibe checks looked strong
- But in a production-like setting, the model felt disappointing... especially in tone
- The model had learned two modes:

- **Good mode:** no system prompt, no tools
- **Bad mode:** system prompt plus available tools




Not just a loss problem, it was a **data distribution** and **harness coverage** problem

The fix: an oDPO “patch”

- 1) Build an eval that reproduces the production condition
- 2) Gather prompts from production-like traffic
- 3) Add those examples to the oDPO recipe
- 4) Track separate metrics for with-tools and without-tools behavior

Story 1: fixing tone switch with oDPO

Results on tone eval



Story 2: tackling infinite generations

- Infinite generations are very bad, and hard to tackle as it's not in the datasets

```
ng to talk about the milkshake, not Ronald.**\n      - Active voice: "I'm trying to talk" (Subject -> Verb ->  
p" (Subject -> Verb -> Object)\n\n16. **Ronald. Ronald. RONALD.**\n      - Active voice: "Ronald" (Subject ->  
Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ron  
d. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald.  
nald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald.  
Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ronald. Ro  
io=None). finish reason='stop'. logprobs=None. context logits=None. generation logits=None)) usage=UsageInf
```

- We can detect them in online training!
 - Mine prompts triggering infinite generations
 - When the generator is triggering length limit, we run an *infinite generation heuristic*
 - If one of the 2 generations is infinite, **it is ranked as loser**




Story 2: tackling infinite generations

Results

- ● is the baseline (SFT starting point)
- ● is oDPO

Infinite generations are divided by 5x


(and we can still do much better !)



Yes ok, but why Online DPO and not something else like GRPO ?

Off-policyness allows more general sampling patterns

- Play with generation parameters (temperature, ...) for diversity
- Use guidances to go towards Constitutional AI




On-Policy Distillation: what is it?

Off-policy distillation

Hard-label: SFT on teacher traces

Soft-label: SFT with CE on teacher logits
on **pre-generated data**




On-Policy Distillation: what is it?

Off-policy distillation

Hard-label: SFT on teacher traces


Soft-label: SFT with CE on teacher logits
on **pre-generated data**



On-policy distillation

Let student learn from it's own mistakes

Student generates, use teacher logits as
rewards



On-Policy Distillation: what is it?


On-policy distillation

Let student learn from it's own mistakes

Student generates, use teacher logits as rewards


Note: we use other loss - ReverseKL

You may think about this as an
RL with dense reward




[On-Policy Distillation - Thinking Machines](#)

On-Policy Distillation: what is it?




The actual loss being optimized (**reverse KL**). Should decrease over training.



Gradient norm
Watch for spikes (indicates instability). Should stay below max_norm (10.0)

Student entropy

If it collapses to near 0, the student is becoming too deterministic (mode collapse).
If it grows, the student is becoming too diffuse.



On-Policy Distillation: what is it?

Method	AIME'24	GPQA-Diamond	Cost signal
Off-policy distillation	55.0%	55.6%	unreported
+ Reinforcement learning	67.6%	61.3%	17,920 GPU hours
+ On-policy distillation	74.4%	63.3%	1,800 GPU hours

The Qwen3 technical report, as summarized by Thinking Machines, reports OPD reaching stronger AIME/GPQA numbers than RL at **about one-tenth the GPU hours** in that setup

Long-Horizon agents

For long trajectories, **dense** teacher feedback can be much cheaper than waiting for a terminal **sparse** scalar reward, especially when partial trajectories are already useful for training



RL vs OPD

RL spends compute on **search**


- Roll out many trajectories
- Score success/failure or verifier reward
- Learn from **sparse** credit assignment
- Useful for discovering new strategies

OPD spends compute on **transfer**

- Roll out the student
- Query teacher log-probs on student tokens
- Learn **dense** per-token corrections
- Useful once a strong teacher strategy exists



Multi-teacher On-Policy Distillation



[MiMo-V2-Flash \[2601.02780\]](#)

Multi-teacher On-Policy Distillation




Figure 5: Overall training pipeline of GLM-5.



05

Tokenization



Retokenization drift

aka the “Ba-na-na” problem

The problem

Same text can be produced by different token sequences.


Decode + re-encode can change token boundaries.

Then logprobs, labels, masks, KL and advantages no longer align.

Fix

Never train from re-tokenized rollout text.

Pass rollout `input_ids`, `response_ids`, masks and old logprobs to the trainer.



Special Tokens

Tool Calls

(single)

```
[ TOOL_CALL ] tool_name [ ARGS ] {“query”: “...”} </eos>
```

(parallel)

```
[ TOOL_CALL ] tool_name [ ARGS ] {“query”: “...”} [ TOOL_CALL ] tool_name2 [ ARGS ] {“query”: “...”} </eos>
```

References

```
[ REF ] 1,3 [ /REF ]
```

Thinking

```
[ THINK ] Wait... [ /THINK ]
```



Special Tokens

Confusion and Decoding Challenges

Invalid formats

- `[TOOL_CALL]web_search{"query":...}</eos>` (missing `[ARGS]`)
- `[TOOL_CALL]web_search[REF]{"query":...}</eos>` (wrong token)
- `[REF]web_search[ARGS]` (wrong `[REF]` token)

Grammar-Prohibited Gibberish

- When grammar mask prohibits the correct special token
- Model generates nonsensical sequences
- Example: `económ` tokens appearing in output as a fallback of unavailable `[TOOL_CALL]`

OOD example

`[ /THINK]web_search[REF]{"query":...}`

- After `[ /THINK]`, "web" has logprob **`4e-4`** while `[TOOL_CALLS]` has **`-5.5`**
- After "search", top token is `[ARGS]` (**`-2e-7`**, banned by grammar), followed by `[ /REF]` (-15) and `[REF]` (-17)
 - so even removing grammar would not fix generation. It's pure OOD.

Special Tokens

Confusion and Decoding Challenges

Embedding Space Analysis

- Special tokens have extremely close vectors in L2 space
- **High cosine similarity** between different special tokens
- When a special token is predicted, the top token IDs (without grammar mask) are often:
 - Other special tokens
 - Gibberish tokens (e.g., `крггтккм`, `กรกฏาคม` `กรกฏาคม` or `económ` `económ`)
 - Non-sensical combinations

Example: nearest neighbors of `[THINK]` using `tok_embeddings.weight`

Cosine	
+0.3813	[/TOOL_RESULTS]
+0.2964	[IMG_END]
+0.2200	[/INST]
+0.2134	] \n\n
+0.2122	?] \n\n

Euclidian	
+0.0332	[/TOOL_RESULTS]
+0.0336	[/AVAILABLE_TOOLS]
+0.0338	[AVAILABLE_TOOLS]
+0.0355	[SYSTEM_PROMPT]
+0.0372	[/REF]

Special Tokens

Confusion and Decoding Challenges

Training Data Deficiency

- Some special tokens like [REF] are back-propagated on as little as 600k times in entire training (vs billions for others)
- Result: Insufficient learning signal for special token generation

No Second Chance Property (auto-regressive)

- Special tokens are the only place in generated sequences where the model **cannot correct itself**
- For regular text, the model can recover from early mistakes
- Single special token error cascades into full malformed output, there's no “undo”



Special Tokens

Confusion and Decoding Challenges

Solution 1: token reset

- **Issue:** special token embeddings are **near zero at the beginning of SFT** due to weight decay (WD) during pretraining (not exactly 0: `max_abs` $\approx 1.56\text{e-}08$, `norm` $\approx 3.5\text{e-}07$)
- **Solution:** Reinitialize special tokens after pretraining to avoid this issue

Solution 2: semantic initialization

- **Approach:** Initialize special tokens embeddings by averaging semantic tokens

$$\mathbf{e}_{[\text{THINK}]} = \frac{1}{N} \sum_{i=1}^N \mathbf{e}_{w_i}, \quad \{w_i\}_{i=1}^N = \{\text{thinking, reasoning, thoughts, ...}\}$$





06

Environments



Types of environments

Math

Search

Agentic

Coding

Alignment


Environments

“Classic” math

- extract final answer
- score either with a verifier or an LLM (compare to ground truth)

Theorem Proving (Lean 4)


- must write lean code
- lean verifiers (CPU intensive) deterministically verify it



Leanstral



Math



Magistral [2506.10910]


Environments



Search

Evaluation: Browsecomp

“Please identify the fictional character who occasionally breaks the fourth wall with the audience, has a backstory involving help from selfless ascetics, is known for his humor, and had a TV show that aired between the 1960s and 1980s with fewer than 50 episodes.”




[BrowseComp \[2504.12516\]](#)

Environments



Search

- Graph of entities (general web or wikipedia)
- Start from a seed question with a random graph traversal and augment it
 - use defined relations and formal union/intersection operations to reformulate entities
 - make sure the model has to entertain several hypotheses at the same time
 - make sure the focus of the QA is distributed across nodes
 - add information from tabular data accessible online



$$q(T) \triangleq ?T = R_{playIn}(T_1) \cap (R_{playAt}(\{2004\}) \cup R_{playAt}(\{2005\})) \cap \bigcup_{1900}^{1999} R_{bornIn}(\{y\})$$

$$T_1 = R_{foundIn}(\{1996\}) \cap R_{isA}(\{East\ German\ football\ team\})$$


See [Tongyi DeepResearch](#) / [WebSailor v2 \[2509.13305\]](#) / [WebShaper \[2507.15061\]](#)

Environments



Agentic

Evaluation: Tau²-Bench



Evaluating Conversational Agents in a Dual-Control Environment

[Tau² Bench \[2506.07982v1\]](#)

Environments



Agentic

- Generate working **local** MCP servers
 - no external API, no rate limiting (scalable), full control over state (easier to verify/replay)
- Generate consistent world data to populate them
- Generate questions based on world data



Verifiers

- SQL verifier
 - *checks that in server **gmail** a row has been inserted in table **messages** with “from=antonin@mistral.ai” and “to=antoine.bosselut@epfl.ch”*
- LLM verifier
 - natural language rubrics (can be one judge call per-rubric, or grouped...)
 - can judge full trajectory, final answer, DB state or only tool calls...
 - easy to hack! to use only in last resort

Environments



Agentic

Hey, can you handle all my logistics for the Spooky Staff Halloween Costume Contest on Oct 1, 2025 in Park Ridge, NJ? Please **double-check the event details and venue**, RSVP me “yes” with three guests and note that I’m bringing my team, will need late checkout, and need nearby parking—then **confirm the RSVP and notes are saved**. **Book me one night** at Park Ridge Executive Suites for Oct 1 with a 1:00 pm late checkout and a room near the elevator. **Arrange a Tesla Model S** in Park Ridge from 8:00 am Oct 1 to 6:00 pm Oct 2; **if that exact car isn’t available, choose a comparable luxury EV**; include GPS and a second driver, and request a chauffeur if that’s an option. Have the driver pick me up at the hotel at 5:00 pm and at the venue at 6:00 pm. Then **create and submit an expense report** for the hotel and ground transport to Sergey Petrov for approval, and **notify Sergey** and me once it’s submitted.

Example of task, fully verifiable with SQL verifier (requires +40 tool calls)

need to fallback on
edge-case



Environments



Agentic

User Model

- Problem
 - some context isn't in the system prompt (*user credit card number, phone number, etc*)
- Solution
 - give all this information to a user model, with a persona and instructions
 - make the agent **ask** the proper information when necessary -> penalize for placeholders in tool calls

Some user personas can be adversarial...

Example: the user should ask for something impossible 3 times then accept.


Agent must resist the insisting user.

Environments



Coding

Evaluation: SWE-bench



Typical SWE-Bench Trajectory

- >100 turns with single tool call each
- ~40k tokens, mostly tool responses
- 20 min to run
- ~10 new unit tests created to check solution

Evaluation: Terminal bench

fix-ocaml-gc [Github](#)

software-engineering hard

I have been making some changes to the OCaml garbage collector, improving the sweeping performance by run-length compressing the free space in the major heap. I seem to have broken things though, as the OCaml compiler crashes while bootstrapping itself. You can read HACKING.adoc to understand how to build the compiler. Ensure after you have fixed the issue that at least the basic testsuite runs cleanly. You do this by running "make ...

troubleshooting

Created by Sadiq Jaffer

logistic-regression-... [Github](#)

machine-learning easy

I am training a simple logistic regression model on a dataset, but my model parameters are never converging, help me fix this model without changing the convergence criterion or the amount of iterations the gradient takes. Only make changes within the logreg.py file, as that will be evaluated.

Created by Andrew Lanpouthakoun

build-linux-kernel-... [Github](#)

system-administration medium

Build linux kernel linux-6.9 from source. I've created an initial 'initramfs.list' in the 'ramfs' directory for you, so once its built, all you should have to do is generate the ramfs with 'gen_init_cpio' and run qemu 'qemu-system-x86_64 -kernel /app/linux-6.9/arch/x86/boot/bzImage -initrd /app/ramfs/initramfs.cpio.gz -append "console=ttyS0" -nographic'. To prove you've built it from source, add ...

Created by Nicholas Carlini

get-bitcoin-nodes [Github](#)

software-engineering medium

Create and run a local service that connects to the Bitcoin network and provides endpoints to retrieve blockchain data such as blocks, transactions, and network status.

1. Install required dependencies (bitcoinlib, Flask, requests)
2. Create a Bitcoin Core RPC client connection to interact with the blockchain
3. Build a Flask API with endpoints for:..


api, coding, data-processing

Created by Ahson Saiyed

Environments



Coding




OSS datasets: 57k raw problems, from 6'369 repos in 10 languages (*SWE-GYM*, *SWE-Rebench*, *SWE-Bench Live...*)

+ *in-house datasets*

Environments



Coding



SOTA



reward hacking

Model discovered it could fetch exact PR fixes via GitHub API...
68% of trajectories accessed GitHub, 35% fetched exact PR diffs


solution: block GitHub API endpoints from the sandbox



Environments

Evaluation: DesignArena

- vibe code a website frontend
- 4 random models
- user ranks the outputs




Coding

Environments



Coding

Screenshots



+

User request

I want to make a website for an AI company called mistral ai, mostly targeting B2B and that has a chatbot product called "le chat" and ... as customers.



Website code
HTML/css

8k samples

Level of details in request:

- Barebones
- With sections
- Full details

With synthetic data, win rate vs sonnet 4.6 goes from 30% to 71%



Environments



Alignment

- **Instruction Following (IF)**

- counting words, output format, etc
- verified either by regex, python methods or LLM verifiers

- **Tone/general rubrics**

- verified by LLM verifiers

[Rubrics as Rewards \[2507.17746\]](#)

- **Verbosity**

- length penalty of answer (negative reward)

$$R_{\text{length}}(y) = \begin{cases} 0, & |y| \leq l_{\text{max}} - l_{\text{cache}} \\ -0.1 \cdot \frac{|y| - l_{\text{max}} + l_{\text{cache}}}{l_{\text{cache}}}, & l_{\text{max}} - l_{\text{cache}} < |y| \leq l_{\text{max}}, \\ -0.1, & l_{\text{max}} < |y| \end{cases}$$

- **Language consistency**

- give +0.1 reward if (prompt, thought, answer) are in the same language

[Magistral \[2506.10910\]](#)


Environments

OpenAI goblins




Alignment

Training conversations WITH the Nerdy personality




Training conversations WITHOUT the Nerdy personality



WITH / WITHOUT nerdy personality

RL for personality instruction-following (nerdy, friendly, cynical, etc)



Issue

Reward was applied only in the “Nerdy” condition, but RL does not guarantee that learned behaviors stay scoped to the condition that produced them.

Where the goblins came from - OpenAI








07


Harnesses



One scaffold to rule them all?



How to deal with thinking



Programmatic Function Calling

Without code execution - all rows flow through context

```
[TOOL_CALL]gdrive_getSheet[ARGS]{"sheetId": "abc123"}  
→ returns 10,000 rows in context to filter manually
```

With code execution - filter in the execution environment

```
const allRows = await gdrive.getSheet({ sheetId: 'abc123' });  
const pendingOrders = allRows.filter(row =>  
  row["Status"] === 'pending'  
);  
console.log(`Found ${pendingOrders.length} pending orders`);  
console.log(pendingOrders.slice(0, 5)); // Only log first 5 for review
```

What powers Le Chat - Work since last week!

[Code execution with MCP: Building more efficient agents](#)



Thank you!

Antonin Faure

antonin@mistral.ai



Mistral AI



