



PDDs and modeling patterns

Session 5

19 February 2019

Prof.dr. Sjaak Brinkkemper


Dr. Sietse Overbeek



Universiteit Utrecht

Agenda

- PDD creation
- Documenting PDDs
- Meta-modeling Patterns




Process-deliverable diagram


- The meta-data model and meta-process model are connected in the so-called **Process-Deliverable Diagram**, abbreviated PDD.
- Arrows **link** the deliverable to the activity it has been produced by
----->
- **Input arrows**, e.g. which concepts are required by an activity are **NOT shown**, as all produced deliverables are assumed to be generally available
- Levels of complex activities and complex deliverables are aligned.
- See also: http://en.wikipedia.org/wiki/Process-data_diagram



Generic process-deliverable diagram





PDD example




Risk workflow in UML-Based Web Engineering

GX web engineering method

Use of color to show origin of the method fragments




PDD Game Production Method




From: Stefan de Weerd: A Reference Method for Game Production
PDD of the method in the book: Introduction to Game Development


PDD Product Management



New to PDD: Tools overlay




Tool overlap



Tool support for UML-Based Web Engineering

Agenda

- PDD creation
- Documenting PDDs
- Meta-modeling Patterns



Documenting PDDs


- For a PDD an **activity table** has to be present providing descriptions of (sub-)activities and a **concept table** with definitions of the concepts.
- In case for one study multiple PDDs are produced, then all are documented in **one** activity table and **one** concept table.
- Sometimes additional rules or unclarities are documented in an additional statement.



Activity and concept tables

- Example:
Goal-Oriented And Ontology Driven Requirements Elicitation

process-side



Activity table


Activity	Sub-Activity	Description
Acquire domain ontology		A DOMAIN ONTOLOGY is needed in order to automatically deduce new CANDIDATE GOALS from an existing GOAL GRAPH. It is acquired by a requirements analyst by either developing one himself or using an already existing DOMAIN ONTOLOGY.
Set up goal graph	Find initial goals and relations	Requirements are depicted as GOALS. GOALS may consist of one or more (sub-)GOALS. This relation can either be with an and or an or decomposition, depending on the need of one or all of the (sub) GOALS to be completed to fulfil the (main) GOAL. In this step, the requirements analyst determines some obvious GOALS and the relations between these goals.
	Draw initial goal graph	The GOALS together with their (sub-)GOALS and the relation (and/or) between them form the GOAL GRAPH, constructed as an and/or graph. At this step, the requirements analyst draws this GOAL GRAPH by connecting the GOALS he found in the previous step in the way he determined the relations in that same step. Figure 2 shows an example of an initial GOAL GRAPH.
Find new goals	Map graph to domain ontology	The GOALS from the current GOAL GRAPH need to be changed from natural language to the corresponding concepts in the DOMAIN ONTOLOGY. This is automatically done by a morphological analyzer and involves a couple of steps that speak for themselves. These steps are separately shown in figure 3 .
	Deduce candidate goals	Using the DOMAIN ONTOLOGY, ontological concepts that should be added to the GOAL GRAPH are deduced and detected. This is done by an inference mechanism that finds concepts that are in the ontology (indirectly related to existing GOALS, but do not yet occur in the GOAL GRAPH. These concepts are presented as CANDIDATE GOALS, together forming a CANDIDATE LIST.
	Prioritize candidates	When they are deduced, CANDIDATE GOALS are given a priority, the expected importance of adding them to the GOAL GRAPH. This priority can be calculated from a number of elements, like a numerical degree attached to ontological elements or records of the analysts selection activities (Shibaoka et al., 2007).
	Suggest new goals	The CANDIDATE GOALS with the highest priorities are selectively chosen by the program to be advised as SUGGESTED GOALS.
Adopt new goals	Select new (sub-)goals	From the SUGGESTED GOALS, those that are considered important enough by the requirements analyst are chosen to adopt. If no SUGGESTED GOAL is chosen (or produced), the current GOAL GRAPH is the result of the requirements elicitation.
	Find relation with existing goals	The relation between the SUGGESTED GOALS and the current GOALS in the GOAL GRAPH are being determined by the requirements analyst.

Concept table

Concept	Description
DOMAIN ONTOLOGY	A domain ontology defines the domain and application specific concepts and their relationships (Razmerita et al., 2001). A meta model of an ontology is described in Shibaoka et al. (2007).
GOAL GRAPH	A goal graph is a pair (G,R) where G is a set of goals and R is a set of goal relations over G (Giorgini, Mylopoulos, Nicchiarrelli, & Sebastiani, 2003). In this case, only binary OR and AND goal relations are considered. A template of a goal graph is shown in figure 5 .
GOAL	A goal captures, at different levels of abstraction, the various objectives the system under consideration should achieve (Lamsweerde, 2001). A goal can consist of one or more sub-goals, either with an and or an or decomposition. It has, beside a label (summary) and a description, also a unique ID, useful for e.g. representations in databases.
INITIAL GOAL	An initial goal is a type of goal that is found by the requirements analyst without help of the automated part of the GOORE process and added by him at the initial construction of the goal graph (Shibaoka et al., 2007).
CANDIDATE GOAL	A candidate goal is a type of goal brought up by the automated part of the GOORE method and is deduced or detected from the domain ontology (Shibaoka et al., 2007). Above the attributes of a normal goal, it also comes with a priority, which represents the expected importance of adding this candidate goal to the goal graph. A goal cannot be both an initial goal and a candidate goal, since one is thought up by the requirements analyst and the other is automatically deduced from what was thought up. However, there are possible goals that are not initial goals but have not made it a candidate goal (yet) either.
SUGGESTED GOAL	A suggested goal is a candidate goal with a priority high enough to be suggested by the program to the requirements analyst as a new goal. (Shibaoka et al., 2007)
CANDIDATE LIST	A candidate list is the enumeration of all current candidates.

deliverable-side

PDD



Activity table

Provide short but comprehensive descriptions

Activity	Sub-Activity	Description
Acquire domain ontology		A DOMAIN ONTOLOGY is needed in order to automatically deduce new CANDIDATE GOALS from an existing GOAL GRAPH. It is acquired by a requirements analyst by either developing one himself or using an already existing DOMAIN ONTOLOGY.
Set up goal graph	Find initial goals and relations	Requirements are depicted as GOALS. GOALS may consist of one or more (sub-)GOALS. This relation can either be with an and or an or decomposition, depending on the need of one or all of the (sub) GOALS to be completed to fulfill the (main) GOAL. In this step, the requirements analyst determines some obvious GOALS and the relations between these goals.
	Draw initial goal graph	The GOALS together with their (sub-)GOALS and the relation (and/or) between them form the GOAL GRAPH, constructed as an and/or graph. At this step, the requirements analyst draws this GOAL GRAPH by connecting the GOALS he found in the previous step in the way he determined the relations in that same step. Figure 2 shows an example of an initial GOAL GRAPH.
Find new goals	Map graph to domain ontology	The GOALS from the current GOAL GRAPH need to be changed from natural language to the corresponding concepts in the DOMAIN ONTOLOGY. This is automatically done by a morphological analyzer and involves a couple of steps that speak for themselves. These steps are separately shown in figure 4 .
	Deduce candidate	Using the DOMAIN ONTOLOGY, ontological concepts that should be added to the GOAL GRAPH are deduced and detected. This is done by an inference mechanism that finds concepts that are in the ontology (in)directly related to existing GOALS, but that have not yet occur in the GOAL GRAPH. These concepts are presented as CANDIDATE GOALS, together forming a CANDIDATE LIST.
	Rank candidates	When they are deduced, CANDIDATE GOALS are given a priority: the expected importance of adding them to the GOAL GRAPH. This priority can be calculated from a number of elements, like a numerical degree attached to ontological elements or records of the analysts selection activities (Shibaoka et al., 2007)
	Suggest new goals	The CANDIDATE GOALS with the highest priorities are selectively chosen by the program to be advised as SUGGESTED GOALS.
Adopt new goals	Select new (sub-)goals	From the SUGGESTED GOALS, those that are considered important enough by the requirements analyst are chosen to adopt. If no SUGGESTED GOAL is chosen (or produced), the current GOAL GRAPH is the result of the requirements elicitation.
	Find relation with existing goals	The relation between the SUGGESTED GOALS and the current GOALS in the GOAL GRAPH are being determined by the requirements analyst.

Include both main activities and sub activities

Concept table

Make cross-references to examples

Concept	Description
DOMAIN ONTOLOGY	A domain ontology defines the domain and application specific concepts and their relationships (Razmer, et al., 2001). A meta model of an ontology is described in Shibaoka et al. (2007).
GOAL GRAPH	A goal graph is a pair (G, R) where G is a set of goals and R is a set of goal relations over G (Giorgini, Mylopoulos, Nicchiarelli, & Sebastiani, 2003). In this case, only binary OR and AND goal relations are considered. A template of a goal graph is shown in figure 6 .
GOAL	A goal captures, at different levels of abstraction, the various objectives the system under consideration should achieve (Lamsweerde, 2001). A goal can consist of one or more sub-goals, either with an and or an or decomposition. It has, beside a label (summary) and a description, also a unique ID, useful for e.g. representations in databases.
INITIAL GOAL	An initial goal is a type of goal that is found by the requirements analyst without help of the automated part of the GOORE process and added by him at the initial construction of the goal graph (Shibaoka et al., 2007).
CANDIDATE GOAL	A candidate goal is a type of goal brought up by the automated part of the GOORE method and is deduced or detected from the domain ontology (Shibaoka et al., 2007). Above the attributes of a normal goal, it also comes with a priority, which represents the expected importance of adding this candidate goal to the goal graph. A goal cannot be both an initial goal and a candidate goal, since one is thought up by the requirements analyst and the other is automatically deduced from what was thought up. However, there are possible goals that are not initial goals but have not made it a candidate goal (yet) either.
SUGGESTED GOAL	A suggested goal is a candidate goal with a priority high enough to be suggested by the program to the requirements analyst as a new goal. (Shibaoka et al., 2007)
CANDIDATE LIST	A candidate list is the enumeration of all current candidates.

Include references

Explain the concept's properties



Including additional rules

- **Additional rules** that cannot be depicted graphically are described next to the meta-data model
- **Unclarities and open issues** are also described annex to the meta-data model.

Rule:

1. No splitting and joining of FLOWS
2. Naming of FLOWS is optional

Issues:

- a. Different types of FLOWS: information, financial, goods
- b. Relationship of Goods FLOWS on Supply Chain Diagram to Enterprise Function Level is unclear



Listing of tools

Tools are to be listed in a separate paragraph


Nr.	Tool	Concept
1	MS-Word	Test plan
2	Jira	Issue
3	Github	Software code
...		

- Comments on the quality of support tools can be placed in this paragraph
 - Lack of tools; non-commercial prototypes
 - Overlap in tool support



Another example

Nr	Tool	Concept
1	Google-sheet	RISK LIST RISK
2	MindTool	RISK LIST RISK PRIORITY IMPACT EVALUATION
3	Google-doc	ACTION LIST FOR RISK STRATEGY
...		



Agenda

- PDD creation
- Documenting PDDs
- **Meta-modeling Patterns**



Two concept matrix


Entity \ Use Case	Order	Chemical	Requester	Vendor Catalog
Place Order	✓	✓	✓	✓
Change Order	✓	-	✓	✓
Manage Chemical Inventory	-	✓	-	-
Report on Orders	✓	✓	✓	-
Edit Requesters	-	-	✓	-



Break


Imagine a country where all the parents want to have a boy. Every family keeps having children until they have a boy; then they stop.

What is the proportion of boys to girls in this country?





Two concept matrix



Use Case \ Entity	Order	Chemical	Requester	Vendor Catalog
Place Order	C	R	R	R,L
Change Order	U, D		R	R,L
Manage Chemical Inventory		C,U,D		
Report on Orders	R	R,L	R,L	
Edit Requesters			C,U,L	




One concept diagram




Two concept diagram



Multi-concept diagram



Two possible meta-models:



Choice depends on relations with other concepts in the domain



Tables

Test Coverage sheet

Test Case Name in QC	Test Scenario Name	Script Name	Scripted Business Components Used							
			Driver_Component	AddingCustomer	CreateBusinessDetails	CreateAccount	MapAccountDetails	CheckAccount	MonthlyBilling	PickAccountsforRenewal
0001_CreateAccountsExistingPhno	AUT_Create_Accounts	AUT_001	✓	✓	✓	✓	✓	✓	✓	✗
0002_CalculateTaxforCaliforniaState	AUT_Create_Accounts_Diff_State	AUT_002	✓	✓	✓	✓	✓	✓	✓	✗
0003_CalculateTaxforIllinoisState	AUT_Create_Accounts_Diff_State	AUT_003	✓	✓	✓	✓	✓	✓	✓	✗
0004_CalculateTaxforNewYorkState	AUT_Create_Accounts_Diff_State	AUT_004	✓	✓	✓	✓	✓	✓	✓	✗
0005_CalculateTaxforChicagoCity	AUT_Create_Accounts_Diff_Citie	AUT_005	✓	✓	✓	✓	✓	✓	✓	✗
0006_CalculateTaxforSanJoseCity	AUT_Create_Accounts_Diff_Citie	AUT_006	✓	✓	✓	✓	✓	✓	✓	✗
0007_CalculateTaxforHustonCity	AUT_Create_Accounts_Diff_Citie	AUT_007	✓	✓	✓	✓	✓	✓	✓	✗
0008_NegativeTest	AUT_NegativeTests	AUT_008	✓	✓	✗	✗	✗	✓	✗	✗
0009_CancelCreationofAccount	AUT_InvalidAccountCreation	AUT_009	✓	✗	✗	✗	✗	✓	✗	✗
0010_RenewAccountwithInvalidName	AUT_InvalidRenewalofAccount	AUT_010	✓	✗	✗	✗	✗	✓	✗	✓
0011_RenewAccountwithInvalidCityName	AUT_InvalidRenewalofAccount	AUT_011	✓	✗	✗	✗	✗	✓	✗	✓
0012_RenewAccountNotReadyforRenewal	AUT_InvalidRenewalofAccount	AUT_012	✓	✗	✗	✗	✗	✓	✗	✓

TEST CASE

Case name
Scenario name
Script name

0..*

used
▼

1..*

COMPONENT



Complex tables

FMEA worksheet

Project: ① Product: System:				Date: Prepared by: ②		
System / Component / Function	Potential failure mode	Potential effect(s) of failure	Severity	Critical?	Potential cause(s) of failure	Occurrence
④	⑤	⑥	⑦	⑧	⑨	⑩

Make sure whether the entry is a **property** or another **concept**.

1. Level of analysis

The analysis can be carried out at a project, product, system, subsystem, component or function level.

2. Date & prepared by

To record who was involved and when the analysis took place.

3. FMEA number & reference information

Clear numbering is important, to enable the team to trace an analysis.

4. System / component / function

The specific name / number of the element or issues under study.

5. Potential Failure Modes

The manner in which a component, subsystem or system could possibly fail.

6. Potential Effects of Failure

For each mode of failure, what will the likely effect be? How would the customer be affected?

7. Severity rating

Each failure effect can be judged for its potential seriousness. Typical rating criteria:

Rating Criteria

5 (9-10) With potential safety risk or legal problems - potential loss of life

4 (7-8) High potential customer dissatisfaction - serious injury or significant property damage

3 (5-6) Medium potential customer dissatisfaction - potential small injury or property damage

2 (3-4) The customer may notice the potential failure and may be a little annoyed

1 (1-2) The customer will probably not detect the failure - undetectable

8. Critical?

A column is provided to enable the rapid identification of potentially critical failure modes.

9. Potential Cause / Mechanisms of Failure

Each failure mode will have an underlying root cause. Thus, it is important to identify the causes of failure, such as defective components, maintenance required, environment etc.

10. Occurrence Ranking

It is also necessary to consider the likelihood of the potential failure occurring.

Rating Criteria

5 (9-10) Very high probability of occurrence

4 (7-8) High probability of occurrence

3 (5-6) Moderate probability of occurrence

2 (3-4) Low probability of occurrence

1 (1-2) Remote probability of occurrence

This section is critical in the FMEA procedure and each of the responsible persons should contribute to its completion.

11. Current design controls

Are there any design controls which aim to reduce or eliminate the potential failure modes?

Version-dependent data (1)

- Products have different **versions** that **vary over time**, so the meta-data model should accommodate that in case it is **essential**.
- **Examples:**
 - Different versions of a Release Definition, Functional Design
 - Tracing and tracking of requirements in the release history



Version dependent data (2)

How to keep track of the history of the data of a deliverable?

Example: DESIGN has multiple versions
Properties

- in black: do not change across versions
- in red: change across versions

DESIGN
<u>Code</u>
Status
Author
Effective date
Version
Location
Application




Version stamping

- All time/version related properties are copied into a new Concept, called XX HISTORY and a history relationship is added in between

Example: DESIGN has DESIGN HISTORY

- The key is copied and the effective date is added.



Concluding

- Meta-data modeling and meta-process modeling provide simple means for the **documentation** and **communication** of methodical processes and deliverables.
- Various applications of meta-modeling:
 - Situational methods and Method assembly (week 11)
 - Formalization of methods (week 11)
 - Method rationale (week 12)
 - Incremental method engineering (week 12)
 - Method association for product implementations (week 13)



QUESTIONS?

