



The 14th International Conference
on Pattern Recognition and
Information Processing
(PRIP'2019)
Minsk, Belarus, May 21-23, 2019

High-resolution Aerial Image Segmentation for Automated Building Detection



Vladimir Khryashchev
Anatoly Sedov




RUDN
university

Leonid Ivanovsky
Anna Ostrovskaya



Purpose

Development of effective algorithm for building detection on satellite images based on deep learning methods




A decorative graphic at the top of the slide, consisting of a complex network of thin, grey lines and dots that resemble a circuit board or a neural network diagram, extending across the top edge.

Algorithm requirements



- Take into account the small size of objects
- Be invariant to rotation
- Have enough training examples
- Have an ability to handle huge pictures
- Cope with noise

U-Net



Trainable parameters: 7.8 mil


LinkNet



Trainable parameters: 17.2 mil


Planet database

- 14 samples in JPG format
- Manual image markup (<https://supervise.ly>)
- Resolution: 8192x8192 px, 0.5 m/pixel
- 3 Russian cities: Moscow, Yaroslavl, Rybinsk



Dataset preparation

- Cropped image resolution: 512x512 px
- Training set: 2611 images
- Test set: 653 photos



Training and testing



Loss function: binary cross-entropy

Optimizer: Adam

Batch size: 18 cropped samples

Epochs (E): 96

Time: 2 hours


demid.ai

Numerical results


$$DSC = \frac{2I}{S}, \quad I = \sum_{\substack{x \in X \\ y \in Y}} xy, \quad S = \sum_{\substack{x \in X \\ y \in Y}} (x + y)$$

Model	Sorensen-Dice coefficient (DSC)
U-Net	0.77
LinkNet	0.72


Numerical results



Examples of detection



Examples of detection





Conclusions



- CNNs can be effectively used for building detection on aerial photos
- U-Net and LinkNet were developed to cope with satellite images segmentation
- The training of CNNs was carried out on supercomputer NVIDIA DGX-1
- The best performance was given by using U-Net



Future plans



- Try more complicated loss functions
- Detect building corners
- Try mask search algorithms (Mask R-CNN, Faster-CNN)

Acknowledgment

The work was prepared with the financial support of the Ministry of Education of the Russian Federation as part of the research project No. 14.575.21.0167 connected with the implementation of applied scientific research id. RFMEFI57517X0167



MINISTRY OF EDUCATION AND SCIENCE
OF THE RUSSIAN FEDERATION



RUDN
university



The 14th International Conference
on Pattern Recognition and
Information Processing
(PRIP'2019)
Minsk, Belarus, May 21-23, 2019

High-resolution Aerial Image Segmentation for Automated Building Detection



Vladimir Khryashchev
Anatoly Sedov



RUDN
university

Leonid Ivanovsky
Anna Ostrovskaya

