```
marie@Maria_Leonova UCRT64 ~
$ mkdir my-first-repo
cd my-first-repo
mkdir: cannot create directory ‘my-first-repo’: File exists

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git init
Reinitialized existing Git repository in C:/Users/marie/my-first-repo/.git/

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ echo "Привет, мир!" > readme.txt

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git status
On branch master

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        readme.txt

nothing added to commit but untracked files present (use "git add" to track)

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git config --global user.name "Maria"

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
```

```
marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git config --global user.email "mariel3onova@yandex.ru"

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git add.
git: 'add.' is not a git command. See 'git --help'.

The most similar command is
        add

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git log
fatal: your current branch 'master' does not have any commits yet

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ ssh-keygen -t ed25519 -C "mariel3onova@yandex.ru"
Generating public/private ed25519 key pair.
Enter file in which to save the key (/c/Users/marie/.ssh/id_ed25519):
Created directory '/c/Users/marie/.ssh'.
Enter passphrase for "/c/Users/marie/.ssh/id_ed25519" (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in /c/Users/marie/.ssh/id_ed25519
Your public key has been saved in /c/Users/marie/.ssh/id_ed25519.pub
The key fingerprint is:
SHA256:tkOdxJV1AIIu9I8wIK1S2QLk5HAyCeXs2NFTvNoaIG8 mariel3onova@yandex.ru
The key's randomart image is:
+--[ED25519 256]--+
|O*o+ ..   ...ooo+o|
```

```
O*o+ ..   ...ooo+o|
|**=.+.o .   o. . .|
|  +++oo +     .    |
|o+o. .= o   . .    |
|.+o. o +So. .      |
|   E o ...+.       |
|  .    o  . .      |
|     .             |
|                   |
+----[SHA256]-----+

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ cat ~/.ssh/id_ed25519.pub
ssh-ed25519 AAAAC3NzaC1lZDI1NTE5AAAAIJkVZUbmA62OpbiO8aCh8czt84cF6rs+C25CKdzlTk2P mariel3onova@yandex
.ru

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ ^C

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ ^C

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git add.
git: 'add.' is not a git command. See 'git --help'.

The most similar command is
        add
```

```
marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git add .
warning: in the working copy of 'readme.txt', LF will be replaced by CRLF the next time Git touches
it

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git commit -m "Мой первый коммит"
[master (root-commit) 2bd5b4d] Мой первый коммит
 1 file changed, 1 insertion(+)
 create mode 100644 readme.txt

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git remote add origin https://github.com/leonovaaa1/my-first-repo
error: remote origin already exists.

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git push -u origin master
remote: Repository not found.
fatal: repository 'https://github.com/leonovaaa1/my-first-repo~/' not found

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git remote set-url origin https://github.com/leonovaaa1/my-first-repo.git

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$ git push -u origin master
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Writing objects: 100% (3/3), 267 bytes | 267.00 KiB/s, done.
```

```
Writing objects: 100% (3/3), 267 bytes | 267.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/leonovaaa1/my-first-repo.git
 * [new branch]      master -> master
branch 'master' set up to track 'origin/master'.

marie@Maria_Leonova UCRT64 ~/my-first-repo (master)
$
```

