# Post-relational: Object-based Modeling

**Physical Data Modeling** 

UNIVERSITY OF ILLINOIS AT URBANA-CHAMPAIGN

Kevin C.C. Chang, Professor Computer Science @ Illinois

## Learning Objectives

By the end of this video, you will be able to:

- Describe the object-based models after the relational model.
- Identify the motivations behind these models.
- Give examples of such models.


## Post-Relational Models: Two Driving Forces

#### Meeting programming paradigms

- Driven by the "impedance mismatch" with object-oriented programming.
- (1980s) Object-Oriented.
- (1980s) Object-Relational Model.

#### Dealing with data in various new settings

- Driven by applications beyond enterprise data management.
- (1990s) Document Model.
- (1990s) Key-Value Model.
- (2000s) Graph Model.




Example enterprise data management scenario from Codd's 1970 relational model paper (Codd 1972)

## Impedance Mismatch: Database vs. Application Programming

Object-relational impedance mismatch --

**Object** (of class) vs **Tuple** (of relation):

- **Object identifiers**: Object referenced by identifiers (pointers) while tuples by values.
- **Nesting**: Object can be nested to contain objects while tuple contains only simple values as attributes.
- Methods: Object has methods while tuple contains only attributes.
- Inheritance: Classes can form subclass hierarchy while relations cannot.
- **Encapsulation:** Object can hide internal representation.



Database vs. application programming

#### Meeting Programming Paradigms → Object-based

- Object-Oriented Data Model
  - Extending OO programming languages with database functions.
  - Current systems:.








Example OO database systems

- Object-Relational Data Model
  - Extending RDBMS with object features.
  - Current systems: PostgreSQL
    - Most RDBMS supports object features to various extents.



## And, this is ANOTHER Turing Award




1991



1996





From Postgres to PostgreSQL

A.M. Turing Award 2014 citation. Retrieved from <a href="http://amturing.acm.org/award winners/stonebraker">http://amturing.acm.org/award winners/stonebraker</a> 1172121.cfm

### "Object-Relational" Example: Table Inheritance


Table inheritance in PostgreSQL Beers-Ales scenario, in Object-Relational way:

Superclass

```
create table Beers (
name text,
brewer text,
alcohol float)
```


Subclass

```
CREATE TABLE Ales (
color char(10) ) INHERITS (Beers);
```



## Table Inheritance: Interesting Complications

- When querying about "Beers", what tables should match?
  - Default is to match not only Beers but also Ales.
- When inserting into "Beers", what tables should match?
  - Seems natural to only insert into Beers.
- How do I limit matching to only tuples in Beers?
  - You say "ONLY Beers". E.g.
     SELECT name, alcohol FROM ONLY Beers
- How to expand matching to not only Beers but also Ales?
  - You say "Beers\*".
- See <u>Inheritance in PostgreSQL Manual</u>.



## On StackOverflow, some suggested against using inheritance in PostgreSQL (and recommended the Null-Value approach). Can you imagine why?

To someone who has experience using inheritance in PostgreSQL: Is it worth using it, or better not to? In which situation you would use it?

To be honest, I do not fully understand the difference between the relational and OO models...

postgresgl inheritance

share improve this question

edited Jun 22 '11 at 2:59



Question on table inheritance in PostgreSQL, 2011. Retrieved from https://stackoverflow.com.