

Introduction to Python programming

Léo Picard

Fall semester, 2025

Course material available on:

https://github.com/leops95/intro_to_python

leo.picard@unibas.ch

What's Python?

- General-purpose programming language
- Free and open source
- Elegant and user-friendly syntax
- Many useful libraries (Pandas, NumPy, Matplotlib, OpenCV, NLTK, statsmodels, Scikit-learn, PyTorch...)

Interest over time ?

The chart displays the relative search interest for five programming languages over time. The Y-axis represents interest on a scale of 0 to 100. The X-axis shows time from January 1, 2004, to the present. Vertical lines mark the years 2011, 2016, and 2018. A bar chart on the left shows the average interest for each language: Java (blue, ~45), Python (red, ~15), JavaScript (yellow, ~15), C++ (green, ~10), and R (purple, ~5).

Language	Color	Category
Java	Blue	Programming language...
Python	Red	Programming language...
JavaScript	Yellow	Programming language...
C++	Green	High-level programm...
R	Purple	Programming language...

Switzerland ▼ 2004 - present ▼ All categories ▼ Web Search ▼

Interest over time ?

100
75
50
25
0

Jan 1, 2004 Jan 1, 2011 Jan 1, 2018

Average

Learning curve

- The learning curve is hard at first
- It gets easier with experience:
 - Errors and syntax issues become easier to spot
 - You can use your past projects to help you
- No one knows everything by heart
- My goal is to show you the basics and help you to **become independent**

Objectives

1. **Set-up:** Install and use Python
2. **Python essentials:** The syntax, data types and basic operators
3. **Scientific computing:** Load datasets and work with them, plot data
4. **Asking for help:** Becoming independent online

Before we start

- This course is for **you**, I'm adapting to your needs
- Tell us a bit about yourself!
 - Have you ever used Python?
 - Why would you like to learn Python?
 - Do you have any other programming experience?

1 Set-up

Setting up your environment

2 Python essentials

Variables and data types

Operators and conditions

Loops

Functions

Exercises

3 Scientific computing

Accessing files

Packages

Loading a dataset

Summary statistics

Data manipulation

Plotting data

Exercise

4 Asking for help

Where you can find help

What are you looking for?

Using Stack Overflow

Set-up

Installation

- To install the "core Python package" you can go to `https://www.python.org/`
 - As we want to use Python for scientific programming, you only have to install "Anaconda": `https://www.anaconda.com/`
- Anaconda is a free distribution for Python which provides the core Python package, plus a convenient software and the most popular scientific libraries
- We write and compile code in files ("scripts") with the extension ".py"
For example, `filename.py`

Setting up your environment

Definition

The **IDE (Integrated Development Environment)** is the software we're using to run Python scripts

Different IDEs for different needs:

- Very light: Jupyter Notebook, Google Colab... (for small projects, like problem sets or step-by-step tutorials)
- Intermediate: Spyder (includes a data viewer and advanced debugging tools)
- Heavy but efficient: VS Code, PyCharm... (for big projects and software engineering)

Setting up your environment

- We will use the Spyder IDE which comes with Anaconda
- Load it either from the Anaconda navigator or using the terminal
- Spyder is split into different sections ("panes") providing us with information or access to certain features. The most important are:
 - The editor
 - The console
 - The variable explorer and plots
- You can add, move or remove panes (see "View" → "Panes")

Python essentials

Basics

- Using hashtags (`#`), we take notes ("comments") directly into the code
- Enclosing lines within quotation marks (`"""`) makes multi-line comments
- To display something on the console, we use the `print()` function
- I use the symbol `>` to show what the result looks like on the console

```
# the command below is likely going to be the first thing
# you try to write in any programming language
print("Hello world!")
```

```
> "Hello world!"
```

Note: Most IDEs have a color scheme to distinguish different elements of code

Variables

- **Variables** store data in our program's memory
- Using the assignment operator "=", we give them names and values
- Variables can take different data types: numbers, text, they could be binary, complex numbers, contain a tuple, a list, even a dictionary!
- The variable explorer shows you the type of all variables you have stored in memory

```
# assign values to variables
number_1 = 15
my_name = "Leo"
num_list = [2, 5]
```

Multiple assignment

You can assign multiple values to different variables in one line

```
# assign values to variables
```

```
number_1 = 15
```

```
my_name = "Leo"
```

```
num_list = [2, 5]
```

```
# delete them
```

```
del number_1, my_name, num_list
```

```
# assign them again all at once
```

```
number_1, my_name, num_list = 15, "Leo", [2,5]
```

Numbers

- There are two different types of data representing numbers
 - **Integers** (**int**): whole numbers (0, 1, 2, 5001, -9999)
 - **Floats** (**float**): numbers with decimals (1.1, 2.64, 6.666666...)
- Python may dynamically change variable types if values are affected

```
number_1, number_2 = 1.99, 15
```

```
type(number_2)
```

```
> <class 'int'>
```

```
number_2 = number_1 + number_2
```

```
type(number_2)
```

```
> <class 'float'>
```

Strings

- A **string** (**str**) is a series of characters
- Anything inside single or double quotes are strings
For example: "My name is..." or 'Python is fun!'
- We can also nest single and double quotes
For example: 'He said, "I love my dog."'
- Using **F-strings**, we can enter ("forward") any variable value within a string

```
name, birth = "Léo", 1995  
sent = f"Hi! My name is {name} and I'm {2025-birth} years old."
```

```
print(sent)
```

```
> "Hi! My name is Léo and I'm 30 years old."
```

Booleans

- A **boolean** (**bool**) is a data type that has two possible values (**True** or **False**)
- They are often used to keep track of conditions
- We also get them from doing logical comparisons (e.g., $2 == 3 \rightarrow \text{False}$)

```
boolname = False  
print(boolname)
```

```
> False
```

```
boolname = (5**2 == 25)  
print(boolname)
```

```
> True
```

Lists

- A **list** (**list**) is a sequence of items ("elements") in a particular order
- You can modify any element by accessing its position in the list ("index")

Important

The index numbering in Python starts at 0, not 1

(sorry Matlab users!)

```
listname = [1,4,5,8]; print(listname[2])
```

```
> 5
```

```
listname[2] = 7; print(listname)
```

```
> [1,4,7,8]
```

Lists

- Lists are **mutable** (i.e., we can change the index of elements)
- The following table shows the most important list methods

Method	Description
<code>listname.append(i)</code>	Add the item <code>i</code> at the end of the list
<code>listname.insert(x,i)</code>	Insert the item <code>i</code> at the index <code>x</code>
<code>listname.pop(x)</code>	Remove the item at position <code>x</code> and return it
<code>listname.copy(x)</code>	Return a copy of the list
<code>listname.sort()</code>	Sort all the items in the list (increasing by default)

List operations

Example	Outcome
<code>a = [1,2]; a.append(3)</code>	<code>> a = [1,2,3]</code>
<code>a = [1,2]; a.insert(1,3)</code>	<code>> a = [1,3,2]</code>
<code>a = [1,2,3]; popped = a.pop(1)</code>	<code>> a = [1,3]; popped = 2</code>
<code>a = [1,2]; b = a.copy()</code>	<code>> a = [1,2]; b = [1,2]</code>
<code>a = [4,1,5,3]; b = a.copy(); a.sort(); b.sort(reverse = True)</code>	<code>> a = [1, 3, 4, 5]; b = [5, 4, 3, 1]</code>

Slicing lists

We can select only some elements within a list ("slice") with: `listname[a:b]`

Important

Element **a** is always included, but **b** is always excluded

```
colors = ["red", "green", "blue", "yellow"], print(colors[1:3])
```

```
> ['green', 'blue']
```

```
print(colors[1:], colors[-1:]) # last 3 elements, last element
```

```
> ['green', 'blue', 'yellow'] ['yellow']
```

Dictionaries

- **Dictionaries** (**dict**) are used to store data in pairs (key + value)
- Values can be retrieved by their key (unique)
- Assigning values to a new key creates a new element

```
dictname = {"BS": "Basel Stadt", "GE": "Geneva", "TI": "Ticino"}  
print(dictname["BS"])
```

```
> "Basel Stadt"
```

```
dictname["ZG"] = "Zug"  
print(dictname)
```

```
> {'BS': 'Basel Stadt', 'GE': 'Geneva', 'TI': 'Ticino', 'ZG': 'Zug'}
```

Dictionaries

- Dictionaries (and lists) can be nested
- Nests can contain another data type

```
dictname = {"owners": ("Antonia", "Elda"),  
            "pets": {"dogs": ("Charlie", "Razmotte", "Nemo"),  
                     "cats": ("Zazie", "Peps", "Zélie")}}
```

```
print(dictname["pets"]["dogs"])
```

```
> ('Charlie', 'Razmotte', 'Nemo')
```

Arithmetic Operators

Operator	Description	Example	Result
+	Addition	10 + 5	15
-	Substraction	30 - 20	10
*	Multiplication	2 * 5	10
/	Division	6 / 2	3.0
%	Modulus	10 % 4	2
**	Exponent	2 ** 3	8
//	Floor division	9 // 4	2

Comparison Operators

Operator	Description	Example	Result
<code>==</code>	equal	<code>4 == 3</code>	False
<code>!=</code>	not equal	<code>4 != 3</code>	True
<code>></code>	greater than	<code>6 > 10</code>	False
<code><</code>	less than	<code>2 < 5</code>	True
<code>>=</code>	greater or equal	<code>8 >= 3</code>	False
<code><=</code>	less than or equal	<code>5 <= 5</code>	True

Logical Operations

Let's assume two Boolean variables, $x = \text{True}$ and $y = \text{False}$

Operation	Description	Example	Result
or	Returns True if at least one Boolean is true	$x \text{ or } y$	True
and	Returns True if both Booleans are true	$x \text{ and } y$	False
not	Returns the opposite of the Boolean	not x	False

Conditions

If statements (**if**) execute a piece of code only if a **condition** is satisfied (**True**)

```
x, y = 5, 10
```

```
if y < x:
    print("y smaller than x")
else:
    print("y greater than x")
```

```
> "y greater than x"
```

- the **else** block runs only if the condition is not satisfied (**False**)
- For more than two conditions, you can insert **elif** ("else if") before **else**
- Careful! you need to use consistent spacing ("indentation") to structure blocks

For loops

- Often, we want to perform the same task repeatedly
- **For statements** (**for**) iterate over items, in the index order
- Iterating does not make a copy of the sequence

```
numbers = [4,34,2]
```

```
for number in numbers:  
    print(number + 1)
```

```
> 5  
> 35  
> 3
```

List comprehension

Using brackets usually is more efficient to iterate over elements in a list

```
listname = [1, 2, 3, 4, 5, 6]
```

```
listname = [x*x for x in listname] # this iterates over all elements  
print(listname)
```

```
> [1, 4, 9, 16, 25, 36]
```

```
# we can add conditions to subset elements
```

```
listname = [x for x in listname if x%2 == 0]  
print(listname)
```

```
> [4, 16, 36]
```

How many loops?

- The `range(a, b)` function generates arithmetic progressions
- As with lists, the last element (b) is excluded
- It is commonly used with `for` loops, to iterate over specific values
- You need to name the current item (below, `i`) if you want to use its value inside the loop

```
for i in range(1, 4):  
    print("Loop number", i)
```

```
> Loop number 1  
> Loop number 2  
> Loop number 3
```

How many loops?

The `len()` function gives you the number of elements ("length") of a list

```
floats = [1.2, 2.343, 0.44]
```

```
for i in range(len(floats)):
    print(i, floats[i])
```

```
> 0 1.2
> 1 2.343
> 2 0.44
```

```
# another example with list comprehension
list_loop = [2*i for i in range(5)]
print(list_loop)
```

```
> [0, 2, 4, 6, 8]
```

While loops

- **While statements** (**while**) execute a task repeatedly *while* a condition is true
- You can also stop the loop using **break**

```
i = 1
while i < 10:
    print(i)
    if i == 4:
        break
    i += 1 # equivalent to i = i + 1
```

```
> 1
> 2
> 3
> 4
```

Functions

Definition

A **function** saves a specific task, to be executed upon calling its name

- It saves us time as we don't have to write the same code again
- We first need to **define** (**def**) a function, by giving it:
 - A name
 - A set of parameters in parentheses (optional)
 - A description (optional but recommended)
 - A set of instructions
- After the function is defined, we can call it with the required parameters (if any)

Functions

An example using the Fibonacci series:

```
def fib(n):  
    """  
    Print a Fibonacci series up to n  
    """  
    a, b = 0, 1  
    while a < n:  
        print(a, end = ' ')  
        a, b = b, a + b
```

```
fib(10)
```

```
> 0 1 1 2 3 5 8
```

Now it's your turn!

Some exercises to practice:

- 1) Create two variables, then swap their values
- 2) Create a list containing the numbers 0 to 9, then invert it (9 to 0)
- 3) Write a function that returns the square of all odds or even numbers between 0 and 20

The file `solutions.py` contains the answers

Scientific computing

Paths

Definition

Your computer stores files in folders ("directories"), which can be accessed using **paths**. The latter comes in different formats depending on your operating system.

Let's take the Desktop:

Windows	<code>C:\Users\username\Desktop</code>
MacOS	<code>/Users/username/Desktop</code>
Linux (Ubuntu)	<code>/home/username/Desktop</code>

Simply replace "username" by your own session user name

Note: `~\Desktop` is also valid

Paths

- The Python console is always looking at one directory
- Not sure which one is it? Just type `pwd` ("print working directory") in the console
- Paths can be **absolute** or **relative**
 - Absolute paths refer to the entire path to your destination
 - Relative paths refer to paths *relative* to the current directory
- Changing directory is easy: either enter a new (absolute) path or go up/down the path tree (relative to the working directory)

Note: `".."` refers to the parent directory (i.e., for going down the tree)

Packages

Definition

Packages are a collection of modules (list of Python files) that we can **import** into our script. They contain functions that serve a purpose, and are ready to be used.

- First, search a package name on the internet, find the command to install it
 - `https://pypi.org/`
 - `https://anaconda.org/conda-forge/`
- Then, paste the command on the terminal with a package manager:
 - **Pip**: the default one (`pip install pandas`)
 - **Conda**: the Anaconda version (`conda install -c conda-forge pandas`)

Packages

Installing new packages can be tedious:

- You need to use the terminal (with Bash commands) to install them
- They come in different versions, which can conflict with each other
- They need to be stored in a folder listed in the "\$PATH" variable where Python will look for them

→ Anaconda manages all of this for you.

Otherwise, here are tutorials on using Bash commands **[CLICK HERE FOR LINK]** and managing the \$PATH variable **[CLICK HERE FOR LINK]**

Packages

Finally, we import a package into our script using the keyword **import**

```
import numpy
```

```
# draw two random values (normally distributed)
```

```
print(numpy.random.randn(2))
```

```
> array([-1.0856306 ,  0.99734545])
```

- Subpackages (e.g. "numpy.random") only contain some functions
- Calling **import** numpy.random instead of **import** numpy saves memory!

Packages

- The keyword **as** gives a nickname to the package
- The keyword **from** calls only specific subpackages or functions

```
import numpy as np # "np" is a widely adopted alias
from numpy import cos, pi
```

```
print(np.sin(np.pi))
```

```
> 1.2246467991473532e-16
```

```
print(cos(pi)) # using "from" allows us to omit "np."
```

```
> -1.0
```

Some examples

- **NumPy**: Basic package for scientific computing. Very fast with mathematical and matrix operations. You can create "ndarrays" which are flexible, efficient and also faster than lists.
- **SciPy**: More advanced than Numpy (e.g. find the determinant or the inverse of a matrix, solve linear equations).
- **Matplotlib**: Plotting data, with complete control over the outline of graphs.
- **Pandas**: Loading datasets and data manipulation.
- **Scikit-learn**: Classification, clustering, basic machine learning

Some examples

- **Requests + BeautifulSoup**: Scraping data from websites
- **NLTK, Regex, Fuzzywuzzy**: Text and natural language processing (NLP)
- **OpenCV**: Images and computer vision (CV)
- **Statsmodels**: Statistical analysis and regressions
- **Tensorflow, Keras, PyTorch**: Advanced machine learning

Loading a dataset

- We will use the **Pandas package** to work with datasets
- Pandas can load most types of **structured data** (e.g., spreadsheets)
- First, find the appropriate command to your dataset type, for example:
 - `pd.import_excel(path_data)` for Excel files (.xlsx, .xls)
 - `pd.import_csv(path_data)` for comma-separated values (.csv)
 - `pd.import_stata(path_data)` for Stata datasets (.dta)
 - `pd.import_r(path_data)` for R datasets (.RData)
 - Tons of other options (e.g., .json, .pkl etc...)
- Then, simply replace `path_data` with the path leading to your dataset

Loading a dataset

- Pandas comes with a special data type to handle datasets: **DataFrames**
- They are very popular for handling structured data
- It can do all the data cleaning operations, like:
 - Rename variables, replace or filter values
 - Concatenate, merge, group rows and columns
- Fast and efficient up to a few gigabytes of data (if you have 16Gb of RAM)
- If memory becomes scarce: look for alternatives like Dask, Modin, or Vaex (many other packages exist)

Loading a dataset

A short example, using my own research on metaphors:

```
import os # to navigate between paths
import pandas as pd
```

```
os.chdir("/home/username/Desktop/intro_to_python-master")
```

```
df = pd.read_csv("data_raw/Idaho_2022.csv")
```

- Here, we use `os.chdir()` to set the working directory
- We capture paths in string format, do not forget " or ' around them

Summary statistics

Before going any further:

- A DataFrame contains observations ("rows") and variables ("columns")
- The **dimensions** of the DataFrame can be seen in the data viewer
- Each column has its own data type, use `df.dtypes` in the console to see them all at once
- Columns usually contain special data types called objects (**object**)

Mea Culpa

When I speak, I tend to use both Stata and Python terminologies

Summary statistics

→ Let's have a look at the DataFrame we have opened...

- We access columns using brackets: `df["filename"]`
- We access rows using their index: `df.iloc[1]`
- Subsetting rows in a dataset works just like lists: `df.iloc[1:3]`

Summary statistics

Basic summary statistics functions:

Function	Description
<code>df.dtypes</code>	Show all data types
<code>df["metaphor_score"].mean()</code>	Display the mean of the variable
<code>df["metaphor_score"].std()</code>	Display the standard error
<code>df["metaphor_score"].max()</code>	Display the maximum value
<code>df["metaphor_score"].describe()</code>	Display N, mean, std, p10, median...
<code>df["arg1"].value_counts()</code>	Tabulate all values and frequencies
<code>df["speaker"].unique()</code>	Look for duplicates

See website to translate Stata commands into Python **[CLICK HERE FOR LINK]**
and R commands into Python **[CLICK HERE FOR LINK]**

Data manipulation

Let's apply some basic data manipulation techniques...

```
# Drop the filename column
```

```
df = df.drop(columns = ["filename"])
```

```
# Rename the state column
```

```
df = df.rename(columns = {"st_name": "state"})
```

```
# Filter out bad metaphor scores
```

```
df = df[df["metaphor_score"] >= 0.7]
```

```
# Create a new metaphor column
```

```
df["metaphor"] = df["arg0"] + " " + df["arg1"]
```

Apply and map

You can add or change rows using `apply()` (with a function) or `map()`

```
# Recode the gender variable from int to str
```

```
def recode_gender(x):  
    gender_str = ""  
    if x == 1:  
        gender_str = "Woman"  
    else:  
        gender_str = "Man"  
    return gender_str
```

```
df["gender_str"] = df.apply(lambda x: recode_gender(x["gender"]),  
                           axis = 1)
```

```
# Alternatively ,
```

```
gender_map = {0: "Man", 1: "Woman"}  
df["gender_str2"] = df["gender"].map(gender_map)
```

Append

You can join datasets based on columns ("append") with the function `pd.concat()`

```
import os
import glob # to store many file names
import pandas as pd

os.chdir("/home/username/Desktop/into_to_python-master")

files = glob.glob("data_raw/*_2022.csv") # star = "any"

df = pd.DataFrame() # creates an empty DataFrame

for file in files:
    data = pd.read_csv(file)
    df = pd.concat([df, data])
```

Note: `df.append(data)` is **deprecated** (i.e, it is not updated anymore!)

Merge

You can also join other information based on rows ("merge")

```
df_party = pd.read_csv("data_raw/political_party.csv")

df_merged = df.merge(df_party, on = "st_name", indicator = True,
                     how = "outer") # or "left", "right", "inner"

# print the output of the merge
print(df_merged['_merge'].value_counts())
```

```
> both          13186
> right_only      1
> left_only       0
> Name: _merge, dtype: int64
```

Merge

- Here, we are in a situation where one speaker belongs to one party
- But we have multiple rows for each speaker!
- We can enforce the type of merge using the "validate" parameter:
 - 1:1 = one-to-one
 - m:1 = many-to-one / 1:m = one-to-many
 - m:m = many-to-many

```
df_merged = df.merge(df_party, on = "st_name", indicator = True,  
                      validate = "m:1") # or "many_to_one"
```

Note: The default value for the parameter "how" is "inner"

Collapse

Now, which political party employs the most metaphors?

We can answer this question by grouping the data (by party)

```
df_merged = df_merged[df_merged["metaphor_score"] >= 0.7]
df_merged["nb_metaphors"] = 1 # each row is counted as one metaphor

df_collapsed = df_merged.groupby(
    "party", as_index = False)["nb_metaphors"].sum()

print(df_collapsed)
```

```
>      party  nb_metaphors
> 0  Democrat           220
> 1  Republican          305
```

Pivot

Finally, we can rearrange rows and columns ("reshape", or "pivot") of the dataset with the following:

```
df_collapsed["statistic"] = "metaphor frequency"

df_wide = df_collapsed.pivot(index = "statistic",
                              columns = "party",
                              values = "nb_metaphors")

print(df_wide)
```

```
> party           Democrat  Republican
> statistic
> metaphor frequency      220         305
```

Note: stack and unstack are elegant substitutes

Plotting data


The easiest way to visualize ("plot") data is using the **Matplotlib** package

```
import matplotlib.pyplot as plt
import numpy as np

x_vals = np.linspace(0,10,10) # Generate 10 values within [0, 10]
y_vals = np.linspace(0,6,10)

plt.plot(x_vals, y_vals)
plt.ylabel("y-axis")
plt.xlabel("x-axis")
plt.savefig("plot_example.png") # save as png
plt.savefig("plot_example.pdf") # save as pdf
plt.show()
```

Plotting data



Plotting data

Useful Pyplot functions:

Function	Description
<code>plt.plot()</code>	Plot y versus x as lines and/or markers
<code>plt.ylabel()</code>	Set the label for the y-axis
<code>plt.xlabel()</code>	Set the label for the x-axis
<code>plt.axis()</code>	Method to get or set some axis properties
<code>plt.title()</code>	Set a title for the axes
<code>plt.scatter()</code>	A scatter plot of y vs x
<code>plt.bar()</code>	Make a bar plot
<code>plt.figure()</code>	Create a new figure
<code>plt.subtitle()</code>	Add a centered title to the figure
<code>plt.subplot()</code>	Add a subplot to the current figure
<code>plt.show()</code>	Display the figure

Plotting data


Histograms, pie charts, violin plots... everything is possible!

```
df_bar = df_merged.groupby(["party", "gender"],
                           as_index = False)["nb_metaphors"].sum()

df_bar = df_bar.pivot(index = "party",
                      columns = "gender", values = "nb_metaphors")

ax = df_bar.plot.bar(stacked = True, rot = 0)
ax.set_ylabel("Metaphor frequency"); ax.set_xlabel("Party")
ax.legend(["Men", "Women"])
plt.tight_layout()
plt.savefig("plot_example2.pdf")
plt.show()
```

Plotting data



Note: Check out **Seaborn** for more customization options!

Asking for help

Where you can find help

Search engines: Another way to find answers (tutorials, videos, short courses)

- Lot of content, but very few is applicable to your own *special* question
- Answers can be outdated, or simply not most efficient

Large language models: great tools, but be careful of copy-pasting!

Friends and university staff: sharing your questions with someone also helps:

- Your peers may learn from your questions too
- ...but their time is limited!

What are you looking for?

- *"I don't know how to code something"*
 - Structure your question with a few keywords
 - Look for answers online
 - If no answer apply to your question, you may ask on Stack Overflow, or an LLM
- *"I tried something but my code doesn't give me the expected result"*
 - Ask yourself if you copy/pasted something online?
 - Try to run a simpler version of your script, then add complexity one step at a time
 - Or, review your code line by line until you identify the culprit
 - If the culprit is a function/package, refer to the documentation

What are you looking for?

- *"I don't know how to code something"*
 - Structure your question with a few keywords
 - Look for answers online
 - If no answer apply to your question, you may ask on Stack Overflow, or an LLM
- *"I tried something but my code doesn't give me the expected result"*
 - Ask yourself if you copy/pasted something online?
 - Try to run a simpler version of your script, then add complexity one step at a time
 - Or, review your code line by line until you identify the culprit
 - If the culprit is a function/package, refer to the documentation

What are you looking for?

- *"I don't know how to code something"*
 - Structure your question with a few keywords
 - Look for answers online
 - If no answer apply to your question, you may ask on Stack Overflow, or an LLM
- *"I tried something but my code doesn't give me the expected result"*
 - Ask yourself if you copy/pasted something online?
 - Try to run a simpler version of your script, then add complexity one step at a time
 - Or, review your code line by line until you identify the culprit
 - If the culprit is a function/package, refer to the documentation

Stack Overflow: How it works

- This website prioritizes quality over quantity of questions (or "posts")
- Do not ask a question before checking if it has already been answered before
- Only after, ask your question in the clearest and shortest way
 - Focus on what you don't know, skip all the details that you know how to do
 - Explain what you have tried before
 - Add a reproducible example (some code with fake data)
 - End your post by writing what the outcome should look like

→ Link to all the rules: <https://stackoverflow.com/help/how-to-ask>

Stack Overflow: Badly written question

Python Script for column creation [closed]

Asked 3 days ago · Modified 3 days ago · Viewed 70 times



Closed. This question needs [details or clarity](#). It is not currently accepting answers.

 **Want to improve this question?** As written, this question is lacking some of the information it needs to be answered. If the author adds details in comments, consider [editing them into the question](#). Once there's sufficient detail to answer, vote to reopen the question.

Closed 3 days ago.

[Improve this question](#)

I have an excel file with no column names. Just the default A, B, C etc. that aren't technically a header. I have a total of 57 columns of data in the file. I am looking for a quick python Script that will take my XLSX file and create a column name for all the default columns with data in them.

So if like default a to become says column 1, or column A etc. I'm using python pandas. I am working on creating scripts to speed up some work.

I've already made a script that will take my .csv file with strip all columns except for the defined columns, however I am trying to take my original XLSX file and add column names/headers. I am brand new to any type of scripting and used this forum to manage one to extract specific columns.

I can open my original file, select every column and the data and create a table which then creates a column and header, but I'm trying to automate the process of opening the file, selecting all the data and creating a column name for each so that the next script I made will delete all the unneeded columns.

I hope this makes sense.

Nothing that's worked lol

python

Stack Overflow: Nicely written question

how to skip 2 data index array on numpy

Asked 2 years, 7 months ago Modified 2 years, 7 months ago Viewed 92 times



1



so I have an 8x6 array, then I want to make the array 4x6.the data such as below:

```
array([[76, 34, 56, 32, 55, 66],
       [99, 23, 11, 34, 45, 32],
       [87, 98, 87, 23, 12, 77],
       [78, 98, 89, 28, 91, 72],
       [76, 42, 45, 23, 56, 87],
       [81, 22, 34, 42, 81, 23],
       [91, 23, 45, 67, 45, 34],
       [87, 98, 23, 45, 23, 55]])
```

the data I want such below:

```
array([[87, 98, 87, 23, 12, 77],
       [78, 98, 89, 28, 91, 72],
       [91, 23, 45, 67, 45, 34],
       [87, 98, 23, 45, 23, 55]])
```

I've try use the slices but it doesn't work for my case. the code is here:

```
import numpy as np

data = [
    [76,34,56,32,55,66],
    [99,23,11,34,45,32],
    [87,98,87,23,12,77],
    [78,98,89,28,91,72],
    [76,42,45,23,56,87],
    [81,22,34,42,81,23],
    [91,23,45,67,45,34],
    [87,98,23,45,23,55]
]

data = np.array(data)
data[:,2:]
```


Wrapping-up

Wrapping-up

With this course, you should now be able to:

- Install Python, set-up your first environment
- Understand most data types and work with them
- Load packages and datasets, perform basic data manipulation
- Efficiently look for help in the future...

Questions, remarks?

leo.picard@unibas.ch

Other fun stuff on: leopiscard.net