

## TECHNICAL SPECIFICATIONS

Bore & Stroke 74 x 71mm

Carburetion PGM-FI electronic fuel injection with automatic choke

Compression Ratio 9.8:1

Engine Displacement 1,832cm3

Engine Type Liquid-cooled 4-stroke 12-valve SOHC flat-6

Ignition System Computer-controlled digital transistorised with electronic advance

Max. Power Output 87kW / 5,500rpm (95/1/EC)

Max. Torque 167Nm / 4,000rpm (95/1/EC)

Starter Electric

Brakes Front 296 x 4.5mm dual hydraulic disc with combined 3-piston calipers,

ABS, floating rotors and sintered metal pads

Brakes Rear 316 x 11mm ventilated disc with 3-piston calipers, Combined ABS and

sintered metal pads

Suspension Front 45mm telescopic fork with anti-dive, 140mm stroke

Suspension Rear Pro-Link, Pro-Arm with electronically-controlled spring preload

adjustment, 105mm axle travel

Tyre Size Front 130/70 R18 (63H)
Tyre Size Rear 180/60 R16 (74H)

Wheels Front Hollow-section 5-spoke cast aluminum

Wheels Rear Hollow-section 5-spoke cast aluminum

Final Drive Enclosed Shaft

Transmission Type 5-speed (including overdrive,

plus electric reverse)

Caster Angle 29° 15'

**Dimensions (L x W x H)** 2,630 x 945 x 1,455mm

Frame Type Diamond; triple-box-section

aluminum twin-spar

Fuel Capacity 25 litres

Ground Clearance 125mm

Clutch Hydraulically actuated clutch

Kerb Weight 413kg Seat Height 740mm

Wheelbase 1,690mm

All specifications are provisional and subject to change without notice. The mentioned technical data is general



Candy Prominence Red Pearl Glare White



