CS061 – Programming Assignment 06

Objective	You may not know it, but in C++, you can use manipulators to alter the base of a number when displaying it on the console. The purpose of this assignment is to bring you to a deep understanding of how this kind of process works and to implement it yourself in LC3.

High Level Description	Build a decimal-to-hex converter as a subroutine, and build an appropriate test harness for it. The range of possible input numbers is [0, 65535].

Examples	Fun Fact:
	In C++, the following will print the value of x in hexadecimal format:
	int x = 12092;
	cout<< hex << x; // outputs "2f3c"
	
	For this assignment:
	User enters "#64222" , the program outputs "xFADE"
	User enters "#10" , the program outputs "xA" or "x000A"
	User enters "#2468" , the program outputs "x9A4" or "x09A4"

Your Tasks	This programming assignment can be broken into four steps: 1. The testbed asks the user to enter a decimal number between [0, 65535]. 2. The testbed then calls the DEC_TO_HEX subroutine. 3. The DEC_TO_HEX subroutine translates the decimal number into a hexadecimal representation and stores it as a null-terminated string in an array. 4. The testbed prints out the array – i.e. the hexadecimal number. • Zero-padded input is inappropriate at this point (you can do better!). The user should NOT be asked to input numbers in the form "#00025". • No error checking required – you may assume always valid input (yay!!☺)

Uh…help?	There are a number of things to consider for this assignment: • The input can be anything up to #65535. Nut the LC3 can only handle 16-bit 2's complement numbers, so any number that goes beyond 32767 will overflow to the negative range of numbers (for example: in LC3, 32767 + 1 == -32768 – *make sure you understand this!*). • If the number entered is in the range [0,32767] then you can convert it the way you would do it on paper • If the number entered is in the range of [32768, 65535], your algorithm will have to act in a slightly different way until, as you are translating, the number returns to the [0,32767] range.

- In order to perform the translation algorithm, it helps to reinvent the natural number line:



Now the "biggest" possible number is #-1 and the "smallest" possible number is #0. The standard paper-based algorithm for translating decimal numbers to 4-digit hexadecimal representation (which you already know) is:
Normal Decimal To Hex Translation Algorithm:
(1) How many 16^3 are there in this number? (that's the first hex digit)
(2) How many 16^2 are there in the remaining number? (that's the second hex digit)
(3) How many 16^1 are there in the remaining number? (that's the third hex digit)
(4) How many 16^0 are there in the remaining number? (that's the fourth hex digit)

This is nearly identical to Exercise 01 from Lab 06, where you took a number in a register and printed it out in base-10 (decimal).

The only difference between the "normal" algorithm and the algorithm you will write is that your algorithm will proceed in two steps:

(1) Modified part
(2) Normal part

For the modified part, instead of seeing how many 16^x you can *subtract* from the number until the remaining number becomes ***negative***, you check how many times you can *add* 16^x before the remaining number becomes ***positive***.

For the normal part, follow the normal paper-based algorithm for converting numbers to hex.

Rubric

- Code does not assemble: -10 points *(no reshow)*
- No header: -10 points *(no reshow)*
- Zero-padded input: (-2 points)
- Not following specifications: -??? points (depending on severity)

- Well commented code: +2 points
- Proper input of decimal number from user: +2 points
- Proper hex translation for numbers in the range [0, 32767]: +3 points
- Proper hex translation for numbers in the range [32768, 65535]: +3 points

Comics?!Sweet!!



Source: http://xkcd.com/413/