



OpsGate

DailyOps.Tech

User Guide

[Console admins](#) · [pilots](#) · [support](#)

Product version 1.2

[Extension](#) · [MMC console](#) · [Policies](#) · [Licenses](#) · [Logs](#) · [Recovery](#)

[DailyOps.Tech](#) · [OpsGate](#) · [EN](#)



OpsGate

Administrator guide · MMC console

Day-to-day OpsGate use: extension, console, enrollment, policies, licenses, logs and recovery. Local install: GUIDE-STACK-LOCALE.md.

Audience: console administrators, pilots, support

Product version: 1.2 / V2 batch (July 2026)

Language: English

This guide covers day-to-day OpsGate use: extension, console, enrollment, policies, licenses, logs, messages, MFA, and recovery.

For local technical setup (Docker, ports), see also GUIDE-STACK-LOCALE.md.

Richer V2 guide: GUIDE-UTILISATEUR-V2-EN.md.

1. Overview

Component	Role
Extension	Detects sensitive data on AI sites, applies policy, logs decisions
API (control plane)	Enrollment, policy/pack sync, events, console authentication
Console	Administration: dashboard, policy, agents, packs, events, audit
Postgres	Durable storage (recommended for pilot / production)

Without Postgres, the API uses an in-memory store: all data is lost on restart.

2. First console sign-in

1. Start the API (and Postgres if used).
2. Open the console (e.g. `http://127.0.0.1:5173`).
3. Sign in with the principal email and install password.
4. Change the password on first login if prompted.

Advanced (login): the API URL field is hidden by default; enable it only to point at another instance.

Concurrent session: if another browser is already signed in, the open session gets a prompt (accept / refuse). With no response within 10 s, the session is released. Alternative: read-only (view only, no changes).

Passkey / Windows Hello: button on the login screen (after registration under Settings -> General).

Wrong password: the message shows how many attempts remain. After too many failures, the account is locked - a principal admin unlocks it under Admins & groups.



Multi-organization (MSP): same email on several orgs -> org picker at login; switch requires MFA code; MSP portfolio for a consolidated view.

3. Enrollment (extension)

Organization

1. OpsGate extension options.
2. Enter the API URL and organization code (e.g. DEMO-OPSGATE).
3. Name the device (label).
4. Enroll.

After a successful sync:

- policies are managed by the org (not editable locally);
- protection stays active offline with the last policy received.

Personal

Personal license key -> personal mode (no org telemetry to the console).

Unenroll

If policy requires it: admin identifier + password.
Vendor recovery: principal / support only (see §8).

4. Dashboard

Fleet overview: licenses, connected agents, decisions, top threats, user requests.

- Movable / resizable widgets (local preference).
- Click an indicator for detail (agent list or logs).
- Expand: full-screen dashboard (Esc to exit).
- Force sync: pushes config to online agents (effect within ~2 min).
- Deep links: `#/policy`, `#/agents`, `#/settings/mail`, etc.

5. Policy

Default org policy

Applies to licensed agents without a specific profile / group.

- AI sites: catalog by groups + custom sites
- Default action: warn | mask_recommend | mask_force | block
- Event collection: on/off
- User messages: banner texts (optional)

Save then Sync (or wait for poll $\leq$ 2 min).



Department policies (profiles)

1. Create a profile (e.g. Finance).
2. Assign via groups (or agent).
3. Agents in the group inherit the profile.
4. You can disable a profile without deleting it.

6. Licenses

- One seat = one protected agent.
- Without a seat: grace period (24 h), then inactive protection (unlicensed).
- Assigning to a group (or manually) usually activates the seat.
- Trial: 30 days from organization creation.
- Full license: key like OPS-XXXX-XXXX-XXXX-XXXX (Settings -> Licenses).
- Dashboard: Licensed / Grace / UNLICENSED lists.

7. Rule packs

A pack is the detection signature set pushed to agents without rebuilding the extension.

- Publish: new version (optionally without noisy rules).
- Activate: version received on next sync.

8. Admins, recovery & settings

Admins & groups

- Multiple administrators; one or more principals (full access).
- Edit account · New password · Unlock · delete (by role).
- Groups link agents and policy profiles.

Vendor recovery

Phase	Practice
Current	Strong secret OPSGATE_VENDOR_RECOVERY; offline delay >= 2 h
Recommended V1.x	One-time code pool (bottom of Admins & groups, principal only)

Messages (Kaspersky-style inbox)

End users can contact admin from the extension.

Console -> Messages: read, reply, close; the client gets a banner / ack popup.

Useful settings

- Language FR / EN and date/time (Settings -> General).



- TOTP MFA + passkeys (Windows Hello / fingerprint).
- Configuration backup: JSON export / import (principal).
- Event log retention and legal audit retention (min. 90 days, WORM).
- Notifications: email + Telegram / Slack / webhook channels.
- Email / SMTP: required for OTP, alerts, and scheduled exports.
- Reports: scheduled log export (day/time/recipients) + Send test now.
- Monitoring: online / long offline thresholds; work schedule; SIEM.

9. Events (logs) & export

Typical decisions: mask_send, send_anyway, cancel, enroll / unenroll.

Retention & scanned files

- Event retention set by the organization (Settings -> Logs).
- Beyond retention: automatic purge - export first.
- Manual export CSV/JSON; scheduled export by email (Settings -> Reports).
- Extension: scan PDF, DOCX, PPTX, XLSX; image OCR when policy scanImages is on.

Admin audit (WORM)

Append-only journal with SHA-256 seal (integrity chain).

Principal only. Verify integrity button + CSV export.

10. Monitoring & schedule

- Online / not connected long time thresholds
- Schedule (timezone, days, breaks) to avoid off-hours alerts
- Log retention + weekly archive

Timezones: Europe, Cameroon (Africa/Douala), Madagascar (Africa/Antananarivo), etc.

11. Agents & assignment rules

- Export agents CSV/JSON; CSV import (group / profile / license on already enrolled agents).
- Moving rules: label / hostname -> group; AND or OR conditions; permanent option (even if already grouped).
- Applied at enroll and via "Re-evaluate".

12. Data & database - why everything can "disappear"

Cause	Effect	Prevention
API without Postgres	Memory store -> empty on restart	Always start Postgres
docker compose down -v	Postgres volume destroyed	Do not use -v in pilot
New volume / other machine	"Empty" DB + DEMO re-seed	Check Docker volume
Short log retention	Old events purged	Adjust retention; export first



API restart in memory mode	Loss of agents, events, custom admins	Move to Postgres
No backups	Irrecoverable loss	scripts/backup-db.ps1 + console config export

Backup: Settings -> General -> Export backup; full DB: scripts/backup-db.ps1 (see architecture/BACKUP.md).

The DEMO-OPSGATE seed runs only if the org does not exist yet: it does not overwrite an existing org.

Durable startup checklist

```
docker compose up -d
$env:DATABASE_URL = "postgres://opsgate:opsgate@127.0.0.1:5432/opsgate"
pnpm api:dev
pnpm console:dev
```

Check the API log: store=postgres (not memory).

13. Console shortcuts (V1)

Action	Detail
/	Focus events search / filter (Events tab)
Theme	Light / dark on the status strip

14. Support & related docs

Document	Content
GUIDE-STACK-LOCALE.md	Docker, ports, extension build
RECOVERY-CONCEPTEUR.md	One-time pool, offline
RULE-PACKS.md	Rule packs
RUNBOOK-OPS.md	Operations
PRIVACY.md	Modes & privacy

Support contact: contact@dailyops.tech (include organization code and version).

OpsGate V1.2 / V2 batch · User guide · product reference · July 2026



OPSGATE · DAILYOPS.TECH

Protect your company data in every interaction with AI.