

OpsGate — User Guide (V1)

Audience : console administrators, pilots, support

Product version : 1.2

Language : English

This guide covers day-to-day OpsGate use: extension, console, enrollment, policies, licenses, logs, and recovery. For local technical setup (Docker, ports), see also GUIDE-STACK-LOCALE.

1. Overview

Component	Role
Extension	Detects sensitive data on AI sites, applies policy, logs decisions
API (control plane)	Enrollment, policy/pack sync, events, console authentication
Console	Administration: dashboard, policy, agents, packs, events, audit
Postgres	Durable storage (recommended for pilot / production)

Without Postgres, the API uses an in-memory store: all data is lost on restart.

2. First console sign-in

- Start the API (and Postgres if used).
- Open the console (e.g. `http://127.0.0.1:5173`).
- Sign in with the principal email and install password.
- Change the password on first login if prompted.

Advanced (login): the API URL field is hidden by default; enable it only to point at another instance.

Single session: a second sign-in offers “Force sign-out”.

Wrong password: the message shows how many attempts remain (e.g. “Invalid. You have 3 attempt(s) remaining.”). After too many failures, the account is locked — a principal admin unlocks it under Admins & groups.

3. Enrollment (extension)

Organization

- OpsGate extension options.
- Enter the API URL and organization code (e.g. DEMO-OPSGATE).
- Name the device (label).
- Enroll.

After a successful sync:

- policies are managed by the org (not editable locally);
- protection stays active offline with the last policy received.

Personal

Personal license key → personal mode (no org telemetry to the console).

Unenroll

If policy requires it: admin identifier + password. Vendor recovery: principal / support only (see §8).

4. Dashboard

Fleet overview: licenses, connected agents, decisions, top threats.

- Click an indicator for detail (agent list or logs).
- Expand: charts fill the content area (top bar and left menu stay visible).
- Collapse: back to the normal view.

- Force sync: pushes config to online agents (effect within ~2 min).

5. Policy

Default org policy

Applies to licensed agents without a specific profile / group.

- AI sites: catalog by groups + custom sites
- Default action: warn | mask_recommend | mask_force | block
- Event collection: on/off
- User messages: banner texts (optional)

Save then Sync (or wait for poll ≤ 2 min).

Department policies (profiles)

- Create a profile (e.g. Finance).
- Assign via groups (or agent).
- Agents in the group inherit the profile.
- You can disable a profile without deleting it.

6. Licenses

- One seat = one protected agent.
- Without a seat: grace period (24 h), then inactive protection (unlicensed).
- Assigning to a group (or manually) usually activates the seat.
- Trial: 30 days from organization creation.
- Full license: key like OPS-XXXX-XXXX-XXXX-XXXX (Settings → Licenses).
- Dashboard: Licensed / Grace / UNLICENSED lists.

7. Rule packs

A pack is the detection signature set pushed to agents without rebuilding the extension.

- Publish: new version (optionally without noisy rules).
- Activate: version received on next sync.

8. Admins, recovery & settings

Admins & groups

- Multiple administrators; one or more principals (full access).
- Edit account · New password · Unlock · delete (by role).
- Groups link agents and policy profiles.

Vendor recovery

Phase	Practice
Current	Strong secret OPSGATE_VENDOR_RECOVERY; offline delay ≥ 2 h
Recommended V1.x	One-time code pool (bottom of Admins & groups, principal only)

Useful settings

- Language FR / EN (Settings → General) — applies to the whole console.
- Log retention (default 90 days) and log types.
- Login failure threshold (account lockout).
- Monitoring: online / long offline thresholds; work-hours schedule.

9. Events (logs) & export

Typical decisions: mask_send, send_anyway, cancel, enroll / unenroll.

Retention

- Set by the organization (Settings → logs).
- Beyond retention: automatic purge.
- Export week, all, or a custom range (CSV / JSON).
- Optional weekly archive before purge.

Admin audit

Journal of console actions (policy, profiles, admins, packs...). Principal only. Export available.

10. Monitoring & schedule

- Online / not connected long time thresholds
- Schedule (timezone, days, breaks) to avoid off-hours alerts
- Log retention + weekly archive

Timezones: Europe, Cameroon (Africa/Douala), Madagascar (Africa/Antananarivo), etc.

11. Assignment rules

Auto rules (label / hostname → group), AND conditions, ordered priority. Applied at enroll and via “Re-evaluate”.

12. Data & database — why everything can "disappear"

Cause	Effect	Prevention
API without Postgres	Memory store → empty on restart	Always start Postgres
docker compose down -v	Postgres volume destroyed	Do not use -v in pilot
New volume / other machine	“Empty” DB + DEMO re-seed	Check Docker volume
Short log retention	Old events purged	Adjust retention; export first
API restart in memory mode	Loss of agents, events, admins	Move to Postgres

The DEMO-OPSGATE seed runs only if the org does not exist yet: it does not overwrite an existing org.

Durable startup checklist

```
docker compose up -d
$env:DATABASE_URL = "postgres://opsgate:opsgate@127.0.0.1:5432/opsgate"
pnpm api:dev
pnpm console:dev
```

Check the API log: store=postgres (not memory).

13. Console shortcuts (V1)

Action	Detail
/	Focus events search / filter (Events tab)
Theme	Light / dark on the status strip

14. Support & related docs

Document	Content
GUIDE-STACK-LOCALE	Docker, ports, extension build
RECOVERY-CONCEPTEUR	One-time pool, offline
RULE-PACKS	Rule packs
RUNBOOK-OPS	Operations
PRIVACY	Modes & privacy

Support contact: contact@dailyops.tech (include organization code and version).

