

```

+----- Add Channel Path -----+
|
| Specify or revise the following values.
|
| Processor ID . . . . : MUSCA      Musca
| Configuration mode . : LPAR
| Channel Subsystem ID : 2
|
| Channel path ID . . . . 14      +          Channel ID 114      +
| Number of CHPIDs . . . . 1
| Channel path type . . . FC      +
| Operation mode . . . . SHR      +
| Managed . . . . . No (Yes or No)  I/O Cluster _____ +
| Description . . . . . FC#0428 16Gb FICON Exp16S+ SX
|
| Specify the following values only if connected to a switch:
| Dynamic entry switch ID 41 + (00 - FF)
| Entry switch ID . . . . 41 +
| Entry port . . . . . 10 +
| F1=Help    F2=Split    F3=Exit    F4=Prompt    F5=Reset    F9=Swap
| F12=Cancel
|
+-----+

```

Figure 12-3 Processors: Add Channel Path

HCD now prompts you to select to which partition the CHPID can access.

6. Enter a forward slash '/' next to the partition that you want (see Figure 12-4), and press Enter.

```

+----- Define Access List -----+
|                                     Row 1 of 1
| Command ==> _____ Scroll ==> CSR
|
| Select one or more partitions for inclusion in the access list.
|
| Channel subsystem ID : 2
| Channel path ID . . . : 14      Channel path type . . : FC
| Operation mode . . . : SHR      Number of CHPIDs . . : 1
|
| / CSS ID Partition Name  Number Usage Description
| / 2      MUSCA21         1      OS    MUSCA21 test OS partition
| ***** Bottom of data *****
|
| F1=Help    F2=Split    F3=Exit    F5=Reset    F6=Previous
| F7=Backward F8=Forward  F9=Swap    F12=Cancel
|
+-----+

```

Figure 12-4 Processors: Define Access List

Because only one partition is defined in this CSS, we do not see the Define Candidate List panel, even though we defined the CHPID as SHR.