```
itso-sles12-powerha-n-1:~ # ifconfig -a
         Link encap:Ethernet HWaddr C2:FE:D7:D7:EF:07
eth0
         BROADCAST MULTICAST MTU:1500 Metric:1
          RX packets:0 errors:0 dropped:0 overruns:0 frame:0
         TX packets:0 errors:0 dropped:0 overruns:0 carrier:0
         collisions:0 txqueuelen:1000
          RX bytes:0 (0.0 b) TX bytes:0 (0.0 b)
          Interrupt:24
         Link encap: Ethernet HWaddr FA:01:E9:97:87:20
eth1
          inet addr:192.168.16.156 Bcast:192.168.16.255 Mask:255.255.255.0
          inet6 addr: fe80::f801:e9ff:fe97:8720/64 Scope:Link
         UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
         RX packets:344542 errors:0 dropped:0 overruns:0 frame:0
         TX packets:152218 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
         RX bytes:30032364 (28.6 Mb) TX bytes:17675278 (16.8 Mb)
          Interrupt:32
eth1:0
         Link encap: Ethernet HWaddr FA:01:E9:97:87:20
          inet addr:20.20.20.1 Bcast:20.20.20.255 Mask:255.255.255.0
          UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
          Interrupt:32
10
         Link encap:Local Loopback
          inet addr:127.0.0.1 Mask:255.0.0.0
         inet6 addr: ::1/128 Scope:Host
         UP LOOPBACK RUNNING MTU:65536 Metric:1
         RX packets:24474 errors:0 dropped:0 overruns:0 frame:0
         TX packets:24474 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1
         RX bytes:1983556 (1.8 Mb) TX bytes:1983556 (1.8 Mb)
```

15. To add a custom application and make it highly available, review the help for the **clmgr** command to know the correct syntax of the command, as shown in Example 11-28.

Example 11-28 Adding a custom application for PowerHA