

```
@foo = (
    1,
    2,
    3,
);
```

To use a here-document to assign an array, one line per element, you might use an approach like this:

```
@sauces = <<End_Lines =~ m/(\S.*\S)/g;
    normal tomato
    spicy tomato
    green chile
    pesto
    white wine
End_Lines
```

LISTs do automatic interpolation of sublists. That is, when a LIST is evaluated, each element of the list is evaluated in list context, and the resulting list value is interpolated into LIST just as if each individual element were a member of LIST. Thus arrays and hashes lose their identity in a LIST—the list

```
(@foo,@bar,&SomeSub,%glarch)
```

contains all the elements of @foo followed by all the elements of @bar, followed by all the elements returned by the subroutine named SomeSub called in list context, followed by the key/value pairs of %glarch. To make a list reference that does *NOT* interpolate, see *perlref*.

The null list is represented by (). Interpolating it in a list has no effect. Thus ((),(),()) is equivalent to (). Similarly, interpolating an array with no elements is the same as if no array had been interpolated at that point.

This interpolation combines with the facts that the opening and closing parentheses are optional (except when necessary for precedence) and lists may end with an optional comma to mean that multiple commas within lists are legal syntax.

The list 1,,3 is a concatenation of two lists, 1, and 3, the first of which ends with that optional comma. 1,,3 is (1,),(3) is 1,3 (And similarly for 1,,3 is (1,),(,),3 is 1,3 and so on.) Not that we'd advise you to use this obfuscation.

A list value may also be subscripted like a normal array. You must put the list in parentheses to avoid ambiguity. For example:

```
# Stat returns list value.
$time = (stat($file))[8];

# SYNTAX ERROR HERE.
$time = stat($file)[8]; # OOPS, FORGOT PARENTHESES

# Find a hex digit.
$hexdigit = ('a','b','c','d','e','f')[$digit-10];

# A "reverse comma operator".
return (pop(@foo),pop(@foo))[0];
```

Lists may be assigned to only when each element of the list is itself legal to assign to:

```
($a, $b, $c) = (1, 2, 3);

($map{'red'}, $map{'blue'}, $map{'green'}) = (0x00f, 0x0f0, 0xf00);
```

An exception to this is that you may assign to `undef` in a list. This is useful for throwing away some of the return values of a function: