

- Press on the adapter and remove it.

S18-0270

Technical data

The holder is for fixing a tablet with a height of min. 11.5 cm and max. 19.5 cm.

The maximum load for the holder is 0.75 kg.

12-Volt power socket

Operating conditions

ⓘ NOTICE

Risk of damage to the electrical system of the vehicle!

- Use the sockets only for the connection of approved electrical accessories with a total power consumption of up to 120 watts.

ⓘ NOTICE

Danger of damage to the connected consumers!

- Switch off the consumers before switching the ignition on or off and before starting the engine.

Roof rack and hitch

Roof rack

Technical data

The maximum weight of the load incl. roof rack is 75 kg.



S19-0476

Depending on the equipment, the roof bars can be attached at the attachment points **A** and **B** or to the roof rail.

Removable tow coupling

What you should be mindful of

⚠ WARNING

Risk of accident and danger of vehicle damage!

- Before each time you make a journey when using the ball rod, check that it is seated correctly and is secured in the mounting recess.
- Do not use the tow bar if it is damaged or incomplete.
- Do not carry out any modifications to the hitch.

⚠ WARNING


Risk of an accident!

Dirt in the mounting recess prevents the ball rod from being attached securely!

- Keep the hitch mounting recess clean at all times.

Overview

Hitch carrier



S19-0410

A Mounting recess

B Cover for the mounting recess