

## Step 4: Configuring ArchPro environment

To configure ArchPro environment:

1. Create an AIX user ID to run ArchPro.
  - a. Create the group as shown in Table 8-25.

Table 8-25 AIX group

Configuration field	Sample input value	Description
Group Name	cmstore	This group enables the two CommonStore user IDs to transfer files.

- b. Create the user as shown in Table 8-26.

Table 8-26 AIX user to run Archpro

Configuration field	Sample input value	Description
User Name	ARCHPRO	User ID that will run the ArchPro program.
Primary Group	cmstore	Both the user ID that runs ArchPro and the user ID that runs the Tasks and Crawlers need to have this group as the primary group. This is because they read and write temporary files when archiving and retrieving content.
Group Set	cmstore, staff, ibmcmgrp	

- c. Set the user's password.

**Note:** All new AIX user accounts require the password to be changed the first time they are used after being created. To do this, Telnet to localhost and log on as the new user. After you enter the password, you are required to change the password. Enter the same password as before and again to confirm it. If this is not done, if applications require this ID for authentication, the authentication will fail.

2. Set the DB2 environment.

The ARCHPRO user ID has to run the DB2 profile to enable it to communicate with the Content Manager database.

3. Set the CommonStore environment.

The ARCHPRO user ID has to set environment settings to enable it to access the CommonStore files.