Example Actions:

1. Type 1 on the command line.
2. Press the Enter key.

The Work with Source Overlays display appears.

```
                        Work with Source Overlays

File . . . . . . . . . .    OVLFILE       Name, F4 for list
  Library . . . . . . . .      OVLLIB     Name, *LIBL, *CURLIB
Source overlay . . . . .    *ALL          Name, generic*, *ALL
Position to . . . . . . .                 Starting characters

Type options, press Enter.
  1=Create   2=Change   3=Copy   4=Delete   6=Print   7=Rename
  9=Create overlay

      Source
Opt   Overlay    Text                                          Changed

 2    STATIONERY  Sample Form number 3                         12/12/90



                                                                Bottom
Parameters or command
===>
F3=Exit   F4=Prompt   F5=Refresh   F9=Retrieve   F11=Display names only
F12=Cancel
```

Example Actions:

1. Type 2 in the *Opt* column next to the source overlay name STATIONERY.
2. Press the Enter key.

The Change Source Overlay display appears.

```
                        Change Source Overlay

File . . . . . . . . . . . . :    OVLFILE
  Library  . . . . . . . . . :      OVLLIB
Source overlay . . . . . . . :    STATIONERY

Type options, press Enter.
  1=Select

Opt     Action
        Define overlay specifications
        Work with source overlay fonts
 1




F3=Exit    F5=Refresh   F9=Select all   F12=Cancel
```