Example 10-3   DISPLAY IPLINFO,PAGESCM

```
DISPLAY IPLINFO,PAGESCM
IEE255I SYSTEM PARAMETER 'PAGESCM': NOT_SPECIFIED
```

Because no PAGESCM parameter is specified, the default value of ALL is used. If a VFM
allocation is defined for the LPAR and PAGESCM=ALL is specified (or kept at the default), then at
IPL time, the initial amount of VFM specified is used automatically by z/OS for paging.
Likewise, if a specific amount is specified, this amount is made available for paging.

From SC76, run the enhanced **DISPLAY ASM** and **DISPLAY M** commands to display Virtual Flash
Memory SCM-related information and status. The result for each command is shown in
Example 10-4.

Example 10-4   Display commands

```
DISPPLAY ASM
IEE200I 12.04.41 DISPLAY ASM 799
TYPE     FULL STAT   DEV   DATASET NAME
PLPA     28%   OK   9A0B  PAGE.SC76.PLPA
COMMON    0%   OK   9A0B  PAGE.SC76.COMMON
LOCAL     0%   OK   9A36  PAGE.SC76.LOCAL01
LOCAL     0%   OK   9AB6  PAGE.SC76.LOCAL02
LOCAL     0%   OK   9B36  PAGE.SC76.LOCAL03
SCM       0%   OK   N/A   N/A
PAGEDEL COMMAND IS NOT ACTIVE


DISPLAY ASM,SCM
IEE207I 12.05.26 DISPLAY ASM 801
STATUS      FULL              SIZE           USED          IN-ERROR
IN-USE       0%          4,194,304        20,247                 0


DISPLAY M=SCM
IEE174I 12.06.04 DISPLAY M 803
STORAGE-CLASS MEMORY STATUS
32G DEFINED
ONLINE
 0G-16G
16G OFFLINE-AVAILABLE
1% IN USE
SCM INCREMENT SIZE IS 16G
DISPLAY M=SCM(DETAIL)
IEE174I 12.06.53 DISPLAY M 805
STORAGE-CLASS MEMORY STATUS - INCREMENT DETAIL
32G DEFINED
ADDRESS  IN USE  STATUS
    0G      1%   ONLINE
ONLINE: 16G  OFFLINE-AVAILABLE: 16G  PENDING OFFLINE: 0G
1% IN USE
SCM INCREMENT SIZE IS 16G
```

From these commands, you see that 32 GB of VFM is defined, but only 16GB are online,
while the other 16 GB are offline-available.

To vary an additional 16 GB VFM online to the example LPAR, issue the **CONFIG
SCM(xxG),ONLINE** command, as shown in Example 10-5 on page 257. The amount of VFM