

Table 6.1 – continued from previous page

atype	param	result
revokePrivilegesFromRole	<pre>{ role: <role name>, db: <database name>, privileges: [{ resource: <resource document>, actions: [<action>, ...] }, ...] }</pre> <p>For details on the resource document, see Resource Document (page 417). For a list of actions, see Privilege Actions (page 419).</p>	0 - Success
replSetReconfig	<pre>{ old: <configuration>, new: <configuration> }</pre> <p>Indicates membership change in the replica set. The <code>old</code> field is optional.</p>	0 - Success
enableSharding (page 421)	<pre>{ ns: <database> }</pre>	0 - Success
shardCollection	<pre>{ ns: <database>.<collection>, key: <shard key pattern>, options: { unique: <boolean> } }</pre>	0 - Success
addShard (page 421)	<pre>{ shard: <shard name>, connectionString: <hostname>:<port>, maxSize: <maxSize> }</pre> <p>When a shard is a replica set, the <code>connectionString</code> includes the replica set name and can include other members of the replica set.</p>	0 - Success
removeShard (page 422)	<pre>{ shard: <shard name> }</pre>	0 - Success
shutdown (page 423)	<pre>{ }</pre> <p>Indicates commencement of database shutdown.</p>	0 - Success

Continued on next page