

Format	Description	Added, Deprecated, or Removed
<code>--ndb-mgmd-host=connection-string,</code> <code>-c</code> <code>--ndb-nodeid=#</code>  <code>--ndb-optimized-node-selection</code>  <code>--no-defaults</code>  <code>--parsable,</code> <code>-p</code> <code>--print-defaults</code>  <code>--show-temp-status</code>  <code>--type=#,</code> <code>-t</code> <code>--unqualified,</code> <code>-u</code> <code>--usage,</code> <code>-?</code> <code>--version,</code> <code>-V</code>	Same as <code>--ndb-connectstring</code>  Set node ID for this node, overriding any ID set by <code>--ndb-connectstring</code>  Enable optimizations for selection of nodes for transactions. Enabled by default; use <code>--skip-ndb-optimized-node-selection</code> to disable  Do not read default options from any option file other than login file  Return output suitable for MySQL LOAD DATA statement  Print program argument list and exit  Show table temporary flag  Limit output to objects of this type  Do not qualify table names  Display help text and exit; same as <code>--help</code>  Display version information and exit	(Supported in all NDB releases based on MySQL 8.0)  (Supported in all NDB releases based on MySQL 8.0)  (Supported in all NDB releases based on MySQL 8.0)  (Supported in all NDB releases based on MySQL 8.0)  (Supported in all NDB releases based on MySQL 8.0)  (Supported in all NDB releases based on MySQL 8.0)  (Supported in all NDB releases based on MySQL 8.0)  (Supported in all NDB releases based on MySQL 8.0)  (Supported in all NDB releases based on MySQL 8.0)  (Supported in all NDB releases based on MySQL 8.0)

## Usage

```
ndb_show_tables [-c connection_string]
```

- `--character-sets-dir`

Command-Line Format	<code>--character-sets-dir=path</code>
---------------------	--

Directory containing character sets.

- `--connect-retries`

Command-Line Format	<code>--connect-retries=#</code>
Type	Integer
Default Value	12