

```

+----- Add/Modify Physical Network IDs -----+
|
| If the Channel ID (CHID) is associated to one or more physical networks,
| specify each physical network ID corresponding to each applicable
| physical port.
|
| Physical network ID 1 . . _____
| Physical network ID 2 . . _____
| Physical network ID 3 . . _____
| Physical network ID 4 . . _____
|
+-----+

```

Figure 13-20 Processors: Add/Modify Physical Network IDs, OSD

10. HCD will now prompt you to select which partition the CHPID should have Access to. Enter forward slash '/' next to the partition that you want (Figure 13-21), and press **Enter**.

```

+----- Define Access List -----+
|                                     Row 1 of 6 |
| Command ==> _____ Scroll ==> CSR |
|
| Select one or more partitions for inclusion in the access list.
|
| Channel subsystem ID : 2
| Channel path ID . . : E1      Channel path type . : OSD
| Operation mode . . . : SHR    Number of CHPIDs . . : 1
|
| / CSS ID Partition Name  Number Usage Description
| / 2    ARIES21           1      OS   ARIES21 test OS partition
| / 2    ARIES22           2      CF/OS
| / 2    ARIES23           3      CF/OS
| / 2    ARIES24           4      CF/OS
| / 2    ARIES25           5      CF/OS
| / 2    ARIES26           6      CF/OS
| ***** Bottom of data *****
|
+-----+

```

Figure 13-21 Processors: Define Access List, OSD

Because we select all partitions to the Access List, we do not see the Define Candidate List panel, even though we have defined the CHPID as SHR.