

---

## **--descending**

Section 23.4.24, “[ndb\\_select\\_all — Print Rows from an NDB Table](#)”

## **--description**

Section 4.6.4.4, “[Other myisamchk Options](#)”

## **--destination-keyring**

Section 6.4.4.13, “[Migrating Keys Between Keyring Keystores](#)”

Section 4.6.8, “[mysql\\_migrate\\_keyring — Keyring Key Migration Utility](#)”

## **--destination-keyring-configuration-dir**

Section 4.6.8, “[mysql\\_migrate\\_keyring — Keyring Key Migration Utility](#)”

## **--detach**

Section 4.5.8, “[mysqlslap — A Load Emulation Client](#)”

## **--diff-default**

Section 23.4.7, “[ndb\\_config — Extract NDB Cluster Configuration Information](#)”

## **--disable**

Section 4.2.2.4, “[Program Option Modifiers](#)”

## **--disable-admin-ssl**

Section 5.1.7, “[Server Command Options](#)”

## **--disable-auto-rehash**

Section 15.8.10.2, “[Configuring Non-Persistent Optimizer Statistics Parameters](#)”

Section 4.5.1.1, “[mysql Client Options](#)”

## **--disable-indexes**

Section 23.4.23, “[ndb\\_restore — Restore an NDB Cluster Backup](#)”

[Restoring to More Nodes Than the Original](#)

## **--disable-keys**

Section 4.5.4, “[mysqldump — A Database Backup Program](#)”

## **--disable-log-bin**

Section 17.1.6.4, “[Binary Logging Options and Variables](#)”

Section 17.1.3.1, “[GTID Format and Storage](#)”

Section 4.6.9, “[mysqlbinlog — Utility for Processing Binary Log Files](#)”

Section 17.3.3.1, “[Privileges For The Replication PRIVILEGE\\_CHECKS\\_USER Account](#)”

Section 5.4.4.2, “[Setting The Binary Log Format](#)”

Section 25.7, “[Stored Program Binary Logging](#)”

Section 5.4.4, “[The Binary Log](#)”

## **--disable-named-commands**

Section 4.5.1.1, “[mysql Client Options](#)”

## **--disable-plugin\_name**

Section 5.6.1, “[Installing and Uninstalling Plugins](#)”