The protocol in protocol mode 3 (AT+DEBUG=3\n) can be displayed on the host computer

field		Number of bytes	explain
HEAD		8	The frame header is fixed to \x01 \x02 \x03 \x04 \x05 \x06 \x07 \x08
LENGTH		4	Whole frame data length (uint32)
FRAME		4	Frame number (uint32)
TLVs		4	TLVs=1 followed by point cloud information (uint32)
POINTLENTH		4	The length of the point cloud data (number of points =POINTLENTH/25) (uint32)
Point cloud 1	X	4	Coordinate (meter) X/Y/Z/V/SNR/ID/Energy (v is int8, others are float) True velocity = V*0.11m/s
	Y	4	
	Z	4	
	v	1	
	SNR	4	
	ID	4	
	POW	4	
.....			
Point cloud n	X	4	Coordinate x/y/z and energy SNR information (v is int8, others are float)
	Y	4	
	Z	4	
	v	1	
	SNR	4	
	ID	4	
	POW	4	
TLVs		4	TLVs=2 followed by person information (uint32)
TRACKLENTH		4	0

If the data volume is large, it is recommended to set the baud rate to 921600 (AT+BAUD=921600\n)

The upper opportunity will save the point cloud data as a.bin file

```
571,0
572,29
-0.80939,0.929938,0,-1,13.6807,2,4.84454
-0.80939,0.826611,0,0,30.728,2,4.90233
-0.80939,0.774948,0,1,16.0667,2,4.47679
-0.872534,0.872534,0,-1,9.45658,2,4.73949
-0.872534,0.781645,0,0,19.5529,2,4.75696
-0.854356,0.727112,0,1,9.68006,2,4.64043
-1.0524,1.17869,0,-1,4.97967,2,4.19209
-1.0524,1.15764,0,0,8.71262,2,4.3381
-0.946202,-0.320068,0.800848,-1,5.41009,2,4.16711
-0.946202,-0.300064,0.808556,0,8.98258,2,4.85477
-0.946202,-0.28006,0.815701,1,4.36684,2,4.86756
-0.941419,-0.354858,0.87894,-1,3.77801,2,4.95293
-0.941419,-0.31311,0.894663,0,6.33449,2,5.12708
-0.987341,-0.354858,0.82702,1,3.00839,2,4.34666
1.27627,-0.504456,0.849989,-1,3.29871,4,4.2027
0.545334,1.70871,1.12122,-1,2.92942,2,4.9672
0.58169,1.49058,1.38348,0,5.77544,2,5.81654
0.634309,1.60443,1.31767,-1,4.21178,2,5.08393
0.671622,1.67905,1.20104,0,7.47801,2,4.8825
0.631439,1.22078,2.02723,0,2.42734,2,4.65756
0.731896,1.42074,1.9288,0,3.00144,2,4.06114
-2.3325,2.02443,0,1,3.20993,255,4.09446
-0.26023,0.650574,3.71974,0,4.60656,2,4.10599
-0.330071,0.396085,3.80606,0,4.32466,255,4.18198
1.67618,2.58412,2.65039,0,3.06432,2,6.26817
-0.727112,2.10862,3.5947,1,2.78676,3,4.12267
1.3662,3.05387,3.26654,-1,3.55667,2,4.04725
-2.58029,-1.58904,3.7775,0,13.6005,2,4.26587
-2.74676,-1.51337,3.69019,1,6.49832,2,4.32885
572,0
```

Frame number, point cloud number

X/Y/Z/V/SNR/ID/POW

Frame number, number of tracks (constantly 0)