



# Advanced Classification Models



DR. ZVI BEN AMI




# Agenda

---

- Ensemble Learning
- Tree Bagging
  - Random Forest
- Tree boosting
  - AdaBoost
  - XgBoost
  - CatBoost
- Distances based models
  - KNN
- Introduction to Image classifications

# Decision Tree will Overfit!



Fully developed decision tree classifier:

- Training set error is always zero!
- Lots of variance (similar inputs may lead to very different outputs)

User must introduce some bias towards simpler trees

# Where Can I Find The Shirt?



Source*	Past success
Shop in Ashkelon	50%
Shop in Jerusalem	70%
Online Shop	90%

\* Assume independent probabilities

- What is my chance to find the shirt?

# Where Can I Find The Shirt?



Source*	Past Success
Shop in Ashkelon	50%
Shop in Jerusalem	70%
Online Shop	90%

\* Assume independent probabilities

- What is my chance to find the shirt?

$$p(t - shirt|Ashkelon\&Jerusalm) = 0.5 + (1 - 0.5) * 0.7 = 0.85$$

$$p(t - shirt|Ashkelon\&Jerusalm\&Online) = 0.85 + (1 - 0.85) * 0.9 = 0.985$$

# Ensemble Learning

- Best learning results are produced by meta-models: models that combine several machine learning models.

## Bagging (Bootstrap Aggregating):


- Reduce **overfitting** by creating a bunch of models. Each model overfits, but their average reduces overfitting.

## Boosting aggregate weak learners to produce strong learners

- Reduce **underfitting** by creating a sequence of models, each trained to reduce errors of the previous one.

## Stacking (improvement over boosting):

- Trains a model that optimally combines predictions from numerous models.



# Ensemble Learning - Bagging

---

## **Bagging** (Bootstrap Aggregating):

When to use: when basic method tends to **Overfit**


- Each of the artificial training sets:
  - Has the same size as the original training set
  - Generated by pooling data with repetitions (**with replacement**) from the original dataset
- All models have comparable performance (if compared to the one trained on the entire dataset)
- Models run in parallel (independently)
- The models are combined by majority vote (classification) or averaging (regression)
- Objective: reduce variance of the prediction
  - In general, overfitted model is very sensitive to the change in the input -> large variance in results.
  - Alternative view: different training sets result in very different models.

# Random Forest: Bagging with Forests

The objective is to reduce variance of prediction by combining many independent classifiers


Random forests fight data overfitting

1. **Create Multiple Datasets** (each of the same size as the original)
2. **Build Multiple Classifiers**
3. **Combine Classifiers**






# Decision Tree




# Random Forest: Bagging

$$X_1 = \begin{bmatrix} f_{A7} & f_{B7} & f_{C7} & f_{D7} \\ f_{A12} & f_{B12} & f_{C12} & f_{D12} \\ \vdots & \vdots & \vdots & \vdots \\ f_{AN_1} & f_{BN_1} & f_{CN_1} & f_{DN_1} \end{bmatrix} \quad Y_1 = \begin{bmatrix} C_7 \\ C_{12} \\ \vdots \\ C_{N_1} \end{bmatrix}$$




$$X_2 = \begin{bmatrix} f_{A4} & f_{B4} & f_{C4} & f_{D4} \\ f_{A8} & f_{B8} & f_{C8} & f_{D8} \\ \vdots & \vdots & \vdots & \vdots \\ f_{AN_2} & f_{BN_2} & f_{CN_2} & f_{DN_2} \end{bmatrix} \quad Y_2 = \begin{bmatrix} C_4 \\ C_8 \\ \vdots \\ C_{N_2} \end{bmatrix}$$




$$X = \begin{bmatrix} f_{A1} & f_{B1} & f_{C1} & f_{D1} \\ f_{A2} & f_{B2} & f_{C2} & f_{D2} \\ \vdots & \vdots & \vdots & \vdots \\ f_{AN} & f_{BN} & f_{CN} & f_{DN} \end{bmatrix} \quad Y = \begin{bmatrix} C_1 \\ C_2 \\ \vdots \\ C_N \end{bmatrix}$$

$$X_3 = \begin{bmatrix} f_{A5} & f_{B5} & f_{C5} & f_{D5} \\ f_{A6} & f_{B6} & f_{C6} & f_{D6} \\ \vdots & \vdots & \vdots & \vdots \\ f_{AN_3} & f_{BN_3} & f_{CN_3} & f_{DN_3} \end{bmatrix} \quad Y_3 = \begin{bmatrix} C_5 \\ C_6 \\ \vdots \\ C_{N_4} \end{bmatrix}$$



# Classifying With Random Forest

Given an observation (a set of features)



Application of these trees yields: 2x  and 1x   result 


# Random Forest

## Advantages

- Can work on classification and regression problems
- Scalable – can handle datasets with thousands of features.
- Can be used to identify the most significant variables
- Parallelizable

## Disadvantages

- Regression random forests do not yield continuous results.
- Black box – too complex to interpret.
- (Relatively) Slow to make predictions



## Getting insights from the tree

```
Instance 0: (13)
Bias (trainset mean) 22.8353963415
Feature contributions:
  RM -1.59
  PTRATIO 0.56
  RAD 0.38
  CRIM -0.35
  LSTAT -0.30
  NOX -0.26
  AGE 0.17
  B -0.12
  ZN 0.09
  INDUS 0.07
  TAX -0.05
  CHAS 0.04
  DIS -0.04
```

Classification\_Models\_Part\_B.ipynb

# How Good Is Random Forest?

---

Fernández-Delgado, M., Cernadas, E., Barro, S., & Amorim, D. (2014). Do we need hundreds of classifiers to solve real world classification problems. *Journal of Machine Learning Research*, 15(1), 3133-3181.

- Evaluate 179 classifiers arising from 17 families
- 121 data sets - the whole UCI data base
- Find that Random Forest is the overall best classifier

# Ensemble Learning - Boosting

---

**Boosting:** aggregate weak learners to produce strong learners

- The original dataset is ***split*** into smaller datasets
- Each model has weaker performance (if compared to the one trained on the entire dataset)
- Models run sequentially. New training sets are constructed while giving misclassified samples higher preference
- Combination of models (e.g. majority vote) produces better predictions
- Objective: improve prediction, reduce bias
- When to use: when basic method tends to **Underfit** (not flexible enough, can't describe the real relationship in the data)
- Works because every model focuses on fixing misclassification of previous models.

# Tree Boosting

---

- Random Forest – bagging of trees. Each tree has low bias, but high variance (overfit).
- Boosted trees: sequential decision using a bunch of shallow trees (high bias, low variance).
- Adaboost (Adaptive Boosting - [sklearn.ensemble.AdaBoostClassifier](#))
  - Repeatedly retrains *any model*. Misclassifications of the previous step are assigned higher weight in the following step.
- Initialize:
  - Each sample is assigned a weight – how important is it to classify it correctly?
- Train a classifier.
  - Assign new weights to each sample, based on their classification error.
  - Assign weight to the classifier, based on its overall accuracy.
- Repeat until:
  - Either all samples are classified correctly
  - Or maximum allowed number of classifiers trained.

[Classification\\_Models\\_Part\\_B.ipynb](#)

# Tree Boosting

---

- Random Forest – bagging of trees. Each tree has low bias, but high variance (overfit).
- Boosted trees: sequential decision using a bunch of shallow trees (high bias, low variance).
- Adaboost (Adaptive Boosting - `sklearn.ensemble.AdaBoostClassifier`)
  - Repeatedly retrains *any model*. Misclassifications of the previous step are assigned higher weight in the following step.

## Gradient Tree Boosting

- Consequent model is trained to predict errors of the earlier model.
- XGBoost (eXtreme Gradient Boosting)– specific implementation of boosting: fast way of finding a sequence of shallow trees and weighting their decisions together.
- Many alternative implementations for tree boosting exist: GBM (R), LightGBM (Microsoft), CatBoost (Yandex)
- Difference from Random forest:
- Random Forest – overfit; XGBoost underfit.
- Boosting is sequential (RF – parallel)
- [pip install xgboost](#)

[Classification\\_Models\\_Part\\_B.ipynb](#)



# CatBoost

---

- CatBoost (Yandex): gradient-boosted decision trees with first-class categorical feature support.
- Core ideas:
  - Ordered boosting to reduce target leakage.
  - Target statistics for categorical encoding done on the fly with permutations.
  - Symmetric (oblivious) trees → fast inference, regularization by design.
  - Works well out-of-the-box (strong defaults, fewer knobs than XGBoost/LightGBM).
  - Handles missing values and text/categorical features natively.
  - Optional GPU training Requires a CUDA-enabled environment and a GPU build of CatBoost.
- When to Prefer CatBoost
  - Many high-cardinality categoricals (IDs, product codes, clinics, teams).
  - Mixed tabular data where manual one-hot would explode feature space.
  - Need strong default performance with minimal tuning.
  - Want fast, compact models for production inference.

[Classification\\_Models\\_Part\\_B.ipynb](#)

# Ensemble Learning Stacking

---

**Stacking** (improvement over boosting - Improve Predictions) – in python: *StackingClassifier*

- Perform boosting
- Train another predictive model (e.g. logit) using input and prediction of the boosted models to assess performance of each of the models. Use *out of sample data*.
- Combine predictions by appropriately weighting the models in the ensemble.
- Objective: reduce variance and improve prediction

# Stacking Ensemble

---

- Step 1 – Base Models (Level 0):
  - Train diverse models on the same dataset (e.g., Decision Tree, Logistic Regression, KNN, Random Forest).
- Step 2 – Meta-Model (Level 1):
  - Collect predictions from base models. Use them as input features for a new model (often Logistic Regression or XGBoost).
- Step 3 – Out-of-Sample Predictions:
  - Train the meta-model only on predictions from a validation set (to avoid overfitting).
- Step 4 – Final Prediction:
  - Meta-model learns which base models perform best under different conditions and combines them optimally.
- Key Idea: Stacking *learns how to combine models*, rather than just averaging or voting.

# Distance-based Classification


---

- Classification (General):
  - Given a collection of records, where each record is a set of attributes and a class (category), the objective is to find a model for the class as a function of the values of other attributes.
  - The model is inferred from a training set
  - Trained model can make accurate predictions for the (previously unseen) test set
- Distance-based classification:
  - Place items in class to which they are “closest”
  - Must determine distance between an item and a class
  - Classes can be represented by the central value (Centroid), representative point (Medoid) or a set of points.

# Similarity Measures

Given two vectors,  $\bar{X}$  and  $\bar{Y}$ , find how “similar” they are

- Euclidean Distance:  $Euclidean(\bar{X}, \bar{Y}) = \sqrt{\sum (x_i - y_i)^2}$
- Manhattan Distance:  $Manhattan(\bar{X}, \bar{Y}) = \sum |x_i - y_i|$
- Minkowski Distance:  $Minkowski(\bar{X}, \bar{Y}) = \sqrt[\gamma]{\sum |x_i - y_i|^\gamma}$
- Cosine Similarity:  $CosineSim(\bar{X}, \bar{Y}) = \frac{\sum x_i y_i}{\sqrt{\sum x_i^2} \sqrt{\sum y_i^2}}$



$\gamma$	$Minkowski(\bar{X}, \bar{Y})$ equivalent	Common name	Main Properties
1	$Manhattan(\bar{X}, \bar{Y})$	$L1$	Robust to outliers
2	$Euclidean(\bar{X}, \bar{Y})$	$L2$	Invariant to rotation
$\infty$	$Chebyshev(\bar{X}, \bar{Y})$	Lmax-norm	$\sim \max( x_i - y_i )$

# Similarity/Distance Between Data Items

Each data item is represented with a set of attributes (consider them to be numeric for the time being)



Michael:  
Age=30  
Income=105K  
No. of children=4



Andrea:  
Age=35  
Income=200K  
No. of children =1

The Euclidean distance between Michael and Andrea is:

$$Distance(John, Rachel) = \sqrt{(30 - 35)^2 + (105K - 200K)^2 + (4 - 1)^2}$$

$$Euclidean(\bar{X}, \bar{Y}) = \sqrt{\sum (x_i - y_i)^2}$$

# Distances in Python

## Classification\_Models\_Part\_B.ipynb

```
from IPython.display import HTML, display
import tabulate
table = [ ['LIBRARY', 'METHOD', 'X', 'Y', 'VALUE']]

from sklearn.metrics.pairwise import euclidean_distances
table.append(test_metric('sklearn.metrics.pairwise.euclidean_distances', 'euclidean_distances', euclidean_distances, X, Y))
table.append(test_metric('sklearn.metrics.pairwise.euclidean_distances', 'euclidean_distances', euclidean_distances, X, Z))

from sklearn.metrics.pairwise import manhattan_distances
table.append(test_metric('sklearn.metrics.pairwise.manhattan_distances', 'manhattan_distances', manhattan_distances, X, Y))
table.append(test_metric('sklearn.metrics.pairwise.manhattan_distances', 'manhattan_distances', manhattan_distances, X, Z))

from sklearn.metrics.pairwise import cosine_similarity
table.append(test_metric('sklearn.metrics.pairwise.cosine_similarity', 'cosine_similarity', cosine_similarity, X, Y))
table.append(test_metric('sklearn.metrics.pairwise.cosine_similarity', 'cosine_similarity', cosine_similarity, X, Z))

from sklearn.metrics.pairwise import cosine_distances
table.append(test_metric('sklearn.metrics.pairwise.cosine_distances', 'cosine_distances', cosine_distances, X, Y))
table.append(test_metric('sklearn.metrics.pairwise.cosine_distances', 'cosine_distances', cosine_distances, X, Z))

display(HTML(tabulate.tabulate(table, tablefmt='html')))
```

	LIBRARY	METHOD	X	Y	VALUE
	sklearn.metrics.pairwise.euclidean_distances	euclidean_distances	[[1 2 3 4]]	[[4 3 2 1]]	[[4.47213595]]
	sklearn.metrics.pairwise.euclidean_distances	euclidean_distances	[[1 2 3 4]]	[[1 2 2 1]]	[[3.16227766]]
	sklearn.metrics.pairwise.manhattan_distances	manhattan_distances	[[1 2 3 4]]	[[4 3 2 1]]	[[8.]]
	sklearn.metrics.pairwise.manhattan_distances	manhattan_distances	[[1 2 3 4]]	[[1 2 2 1]]	[[4.]]
	sklearn.metrics.pairwise.cosine_similarity	cosine_similarity	[[1 2 3 4]]	[[4 3 2 1]]	[[0.66666667]]
	sklearn.metrics.pairwise.cosine_similarity	cosine_similarity	[[1 2 3 4]]	[[1 2 2 1]]	[[0.8660254]]
	sklearn.metrics.pairwise.cosine_distances	cosine_distances	[[1 2 3 4]]	[[4 3 2 1]]	[[0.33333333]]
	sklearn.metrics.pairwise.cosine_distances	cosine_distances	[[1 2 3 4]]	[[1 2 2 1]]	[[0.1339746]]

# KNN - K Nearest neighbors

---

A group of algorithms capable to find neighboring points in multi-dimensional space.

Can be used to

- segment (group) data
- Recommender systems
- Search engines

KNN can be **unsupervised** (for clustering) or **supervised** (for classification)

KNN can use different distance metrics (e.g. Euclidian - `sklearn.neighbors.DistanceMetric`)

KNN can retrieve

- k nearest neighbors
- All neighbors within specified distance
- Neighbors until drop off
- Predefined number of groups

KNN finds nearest neighbors. For clustering/classification one has to vote for labels.


- Classification provides sample labels




# KNN for Prediction

To make a prediction for a new example E:

- Calculate the distance between E and all examples in the training set
- Select k examples closest to E in the training set
- Combine the k values for the target variable using some combining function (for example: mode, mean, median)









# KNN Prediction



# KNN Classifier – Example (K=3)

Customer	Age	Income (K)	No Children	Response
Michael	30	105	4	Yes
Andrea	35	200	1	No
Ester	65	150	3	No
David	66	120	3	No
Amit	23	50	0	Yes
John	31	100	2	?

# KNN Classifier – Example (K=3)

Customer	Age	Income (K)	No Children	Response	Distance to John
Michael 	30	105	4	Yes	$distance_{toJohn} = \sqrt{(30 - 31)^2 + (105 - 100)^2 + (4 - 2)^2}$ <b>5.477</b>
Andrea 	35	200	1	No	$distance_{toJohn} = \sqrt{(35 - 31)^2 + (200 - 100)^2 + (1 - 2)^2}$ <b>100.084</b>
Ester 	65	450	3	No	$distance_{toJohn} = \sqrt{(65 - 31)^2 + (450 - 100)^2 + (3 - 2)^2}$ <b>351.648</b>
David 	66	120	3	No	$distance_{toJohn} = \sqrt{(66 - 31)^2 + (120 - 100)^2 + (3 - 2)^2}$ <b>40.323</b>
Amit 	23	50	0	Yes	$distance_{toJohn} = \sqrt{(23 - 31)^2 + (50 - 100)^2 + (0 - 2)^2}$ <b>50.675</b>
John 	31	100	2	Yes	

# KNN Classifier Strengths and Weaknesses

---

## Strengths:

- Simple to implement and use
- Comprehensible – easy to explain prediction
- Robust to noisy data by averaging k-nearest neighbors
- Some appealing applications
  - consider collaborative filtering for personalized recommendations
- Distance function can be tailored using domain knowledge

## Weaknesses:

- Need a lot of space to store all examples
- Takes (much) more time to classify a new example than with a parsimonious model (need to calculate and compare distance from new example to all training examples)
- Distance function must be designed carefully, using domain knowledge

# KNN Classifier – Normalize Data




Michael:

Age=30

Income=105K

No. of children=4



Andrea:

Age=35

Income=200K

No. of children=1



Distance (Michael, Andrea)= $\text{sqrt} [(30-31)^2 + (105,000-100,000)^2 + (1-2)^2]$

Distance between neighbors can be dominated by an attribute with relatively large values (e.g., income in our example).

Important to *normalize* (e.g., map numbers to numbers between 0-1)







Example: Income

Highest income = 500K

John's income is normalized to 95/500, Rachel's income is normalized to 215/500, etc.)

(there are more sophisticated ways to normalize)

# KNN Classifier – Example (K=3)

Customer	Age	Income (K)	No Children	Response	Distance to John
<b>Michael</b> 	$30/66 = 0.455$	$105/450 = 0.233$	$4/4 = 1$	Yes	$distance_{toJohn} = \sqrt{(0.455 - 0.47)^2 + (0.233 - 0.222)^2 + (1 - 0.5)^2}$ <b>0.506</b>
<b>Andrea</b> 	$35/66 = 0.530$	$200/450 = 0.444$	$1/4 = 0.25$	No	$distance_{toJohn} = \sqrt{(0.53 - 0.47)^2 + (200 - 0.222)^2 + (0.25 - 0.5)^2}$ <b>0.340</b>
<b>Ester</b> 	$65/66 = 0.985$	$450/450 = 1$	$3/4 = 0.75$	No	$distance_{toJohn} = \sqrt{(0.985 - 0.47)^2 + (450 - 0.222)^2 + (0.75 - 0.5)^2}$ <b>0.966</b>
<b>David</b> 	$66/66 = 1$	$120/450 = 0.267$	$3/4 = 0.75$	No	$distance_{toJohn} = \sqrt{(1 - 0.47)^2 + (120 - 0.222)^2 + (0.75 - 0.5)^2}$ <b>0.588</b>
<b>Amit</b> 	$23/66 = 0.348$	$50/450 = 0.111$	$0/4 = 0$	Yes	$distance_{toJohn} = \sqrt{(0.348 - 0.47)^2 + (0.111 - 0.222)^2 + (0 - 0.5)^2}$ <b>0.527</b>
<b>John</b> 	$31/66 = 0.470$	$100/450 = 0.222$	$2/4 = 0.5$	Yes	

# Categorical Features in KNN

---

- Challenge:
  - KNN relies on distance metrics, naturally numeric.
  - Categorical features (e.g., color) lack natural distances.
- Approaches:
  - One-Hot Encoding → binary vectors (good for low-cardinality).
  - Ordinal Encoding → maps categories to integers, but may impose false order.
  - Specialized distances:
    - Hamming
    - Gower



# Hamming and Gower Distances

---

- Hamming Distance:

- Counts mismatches between categorical features.
- Example:
  - [Red, Large] vs [Blue, Large] → 1 mismatch.

$$d_{ij} = \begin{cases} 0 & \text{if category is the same} \\ 1 & \text{if category is different} \end{cases}$$

- Gower Distance:

- Handles mixed numeric + categorical features.
- Numeric: normalized difference.
- Categorical: 0 if same, 1 if different.
- Example:
  - Age=30,Red vs Age=40,Blue
  - Age difference = 0.2
  - Color difference = 1
  - Average =  $(0.2+1)/2 = 0.6$

# KNN: K Nearest neighbors Classifier



KNN uses  $k$  closest points to perform classification

To train requires:

- The set of labeled records: attributes ( $X$ ) and labels ( $y$ )
- Distance metric to compute distance between records
- $k$  – the number of nearest neighbors to check

To classify unknown point

- Compute distance to training records
- Identify  $k$  nearest neighbors
- In classification: The item is placed in the class with the most number of close items (majority vote)
- In regression: The output is the average across values of  $k$ -nearest neighbors




# KNN – choosing $k$

If  $k$  is too small, sensitive to noise points

If  $k$  is too large, neighborhood may include points from other classes

## KNN – CONSTRUCTION

- KNN does not create a model of the data
- KNN stored the training data for effective retrieval
  - Uses a number of approaches (e.g.: ball tree, kd-tree, brute force)
- <https://www.analyticsvidhya.com/blog/2017/11/information-retrieval-using-kdtree/>






Classification\_Models\_Part\_B.ipynb


# Example

## Classification\_Models\_Part\_B.ipynb


Classifying people by income ( $< \$50k$  vs  $\geq \$50k$ )






# Image Classification



Source: [https://cdn-images-1.medium.com/max/1200/1\\*zY1qFB9aFfZz66Yxxol2aw.gif](https://cdn-images-1.medium.com/max/1200/1*zY1qFB9aFfZz66Yxxol2aw.gif)



Source: <https://www.kdnuggets.com/2017/08/convolutional-neural-networks-image-recognition.html>




Source: <https://becominghuman.ai/building-an-image-classifier-using-deep-learning-in-python-totally-from-a-beginners-perspective-be8dbaf22dd8>

# Image Classification

Classification\_Models\_Part\_B.ipynb


Can we use classification to recognize handwritten digits?



# Image Classification

## Train Data Set:

- Millions of images from the web.
- Manually labeled categories.



# THANK YOU FOR LISTENING

ZVI.BENAMI@MAIL.HUJI.AC.IL

---

