



EUROPEAN
SPALLATION
SOURCE

Document Type

EDMS ID Number	Add reference
Date	2014-01-07

Naming Convention Tool - Development Environment Setup Instructions

Author	Affiliation	Editor	Approver
Andraž Požar	Cosylab	Miroslav Pavleski	

European Spallation Source ESS AB
Visiting address: ESS, Tunavägen 24
P.O. Box 176
SE-221 00 Lund
SWEDEN

www.ess.se



EUROPEAN
SPALLATION
SOURCE

Document Type

EDMS ID Number	Add reference
Date	2014-01-07

DOCUMENT REVISION HISTORY

Version	Reason for revision	Date
1.0	Initial version	2014-01-07

TABLE OF CONTENTS

1.	JAVA ENVIRONMENT.....	4
1.1	JRE.....	4
2.	CHECKOUT THE APPLICATION.....	4
3.	MySQL Database Preparation	4
3.1	Software requirements	4
3.2	Create database user and schema for the application.....	5
4.	GLASSFISH CONFIGURATION.....	6
4.1	Install GlassFish.....	6
4.2	Install MySQL JDBC driver	6
4.3	Start GlassFish.....	6
4.4	Setup security realm	7
4.5	Deploy application.....	8

LIST OF TABLES

No table of figures entries found.

LIST OF FIGURES

Figure 1: MySQL user creation.....	5
Figure 2: Navigate to security realm configuration.....	7
Figure 3: Create new security realm.....	7
Figure 4: Manage users	8

1. **JAVA ENVIRONMENT**

1.1 **JRE**

Java 7 should be selected as default java. Check this with the following command in terminal:

```
sudo alternatives --config java
```

Java 7 should be selected as default. If it is not, please select it.

2. **CHECKOUT THE APPLICATION**

To checkout the application using Git, please do the following in terminal:

```
git clone https://your_user_name@git.esss.dk/ad/NamingConventionTool
```

Please substitute "your_user_name" with your user account at DMSC put it in suitable directory (hereinafter referred as project_home).

3. **MYSQL DATABASE PREPARATION**

3.1 **Software requirements**

MySQL server and MySQL Workbench should be installed on the machine. If they are not, please install them.


3.2 Create database user and schema for the application

Start the MySQL Workbench.

Select "Database/Connect to Database..." menu and connect to localhost, with the root username.

When connected, navigate to "Users and Privileges" on the left-hand panel, and create "discs_names" user with password set to "discs_names":

Make sure to put **localhost** in the field "**Limit Connectivity to Hosts**", as shown in the picture. Please, click the "Apply" button.



Details for account discs_names@localhost

Login Administrative Roles Account Limits

Login Name: discs_names You may create multiple accounts with the same name to connect from different hosts.

Authentication Type: Standard For the standard password and/or host based authentication, select 'Standard'.

Limit Connectivity to Hosts Matching: localhost % and _ wildcards may be used

Password: Type a password to reset it.

Consider using a password with 8 or more characters with mixed case letters, numbers and punctuation marks.

Confirm Password: Enter password again to confirm.

Figure 1: MySQL user creation

Create new schema and name it "discs_names".

Assign permissions to user "discs_names" for the database schema "discs_names", please navigate again to "User and Privileges" on the left-hand side navigation bar and select the "discs_names" user from the list. Click the "Schema Privileges" tab, and click "Add Entry...", select "Selected schema" radio button in the new dialog and select the "discs_names" schema. Please click "OK" button to close the dialog. Please, click the "Select "ALL"" button to enable full access of the user to the schema and click the "Apply" button.

4. GLASSFISH CONFIGURATION

4.1 Install GlassFish

If glassfish is not yet installed, please download it from

<http://download.java.net/glassfish/3.1.2/release/glassfish-3.1.2.zip>

and extract it to suitable directory (hereinafter referred as glassfish_home).

4.2 Install MySQL JDBC driver

To be able to use Glassfish with MySQL, JDBC driver must be installed in the server's **lib** directory. To do that please, download driver from

<http://cdn.mysql.com/Downloads/Connector-J/mysql-connector-java-5.1.27.tar.gz>

extract it and copy it to `${glassfish_home}/glassfish/lib`.

4.3 Start GlassFish

To start GlassFish server, navigate to `${glassfish_home}/glassfish/bin` and run

```
./asadmin start-domain
```

To test the server, visit the <http://localhost:4848/> URL in the browser after server is started. The Server Administration console is hosted on the 4848 port.

If this is a first run, administrator password should be set. To set it, please go to <http://localhost:4848/> and select the Domain from the left-hand menu. There is a tab named "Administrator Password", please click it and enter the new password. Click the "Save" button.

4.4 Setup security realm

Security and permissions of the application are managed via security realm of Glassfish. To login to the application you have to create new realm and add new user to it.

Go to <http://localhost:4848> and navigate to security realm as shown below:




Figure 2: Navigate to security realm configuration

Click "New" and fill in as show below:

Name: *

Class Name: ☒

☐

Choose a realm class name from the drop-down list or specify a custom class

Properties specific to this Class

JAAS Context: *
Identifier for the login module to use for this realm

Key File: *
Full path and name of the file where the server will store all user, group, and password information for this realm

Assign Groups:
Comma-separated list of group names

Figure 3: Create new security realm

Click "OK".

Click on newly created realm and then click "Manage users". Fill out as show below (password is "root"):

New File Realm User

Create new user accounts for the currently selected security realm.

Configuration Name: server-config

Realm Name:	org.openepics.names.realm
User ID: *	<input type="text" value="root"/> <small>Name can be up to 255 characters, must contain only alphanumeric, underscore, dash, or dot characters</small>
Group List:	<input type="text" value="Authenticated"/> <small>Separate multiple groups with colon</small>
New Password:	<input type="password" value="...."/>
Confirm New Password:	<input type="password" value="...."/>

Figure 4: Manage users

Click "OK".

Now root user is added. This step should be repeated for every new user.

4.5 Deploy application

First the application has to be build and packaged to web archive (maven2 is required). To do this navigate to `${project_root}` of previously downloaded project and execute

```
mvn clean package
```

Web archive should be created in `${project_root}/target` with name "names-x.x.x.war".

To deploy this web archive first make sure that GlassFish server is running. Then navigate to `${glassfish_home}/glassfish/bin` and execute

```
./asadmin deploy ${project_root}/target/names-x.x.x.war
```

To test the application UI, please visit:

<http://localhost:8080/names>

Login with username and password set in Setup security realm section (user:root, password:root).