

\CONDITIONAL STATEMENTS

Making decisions



Conditional Statements

Used to determine if a block of code should or should not be executed depending on a specific evaluation (condition)

/COMPARISON OPERATORS

==

IS EQUAL TO

Compares two values

"3" == 3 returns true

===

STRICT EQUAL TO

Compares values **and**

data types

"3" === 3 returns false

/COMPARISON OPERATORS

!=

IS NOT EQUAL TO

Compares two values

"3" != 3 returns false

!==

STRICT EQUAL TO

Compares values **and**

data types

"3" !== 3 returns true

/COMPARISON OPERATORS

>

GREATER THAN

Checks if the number on
the left is greater than
the number on the right

1 > 4 returns false

>=

GREATER THAN OR EQUAL TO

Checks if the number on the
left is greater than or equal
to the number on the right

5 >= 5 returns true

/COMPARISON OPERATORS



LESS THAN

Checks if the number on the left is less than the number on the right

`1 < 4` returns true



LESS THAN OR EQUAL TO

Checks if the number on the left is less than or equal to the number on the right

`5 <= 5` returns true



/LET'S PRACTICE

BLACKBOARD: COMPARISON OPERATORS

/IF-STATEMENTS

IF KEYWORD CONDITION

```
if (score > 50){  
    // code to exec when true  
}
```


/IF-ELSE STATEMENTS

```
IF KEYWORD      CONDITION
...             ...
if (score > 50){
    // code to exec when true
} else {
    // code to exec when false
}
ELSE KEYWORD
```

/IF-ELSE STATEMENTS

```
if (score >= 90){  
    // code to exec when score > 90 is true  
} else if (score >= 80){  
    // code to exec when score > 80 is true  
} else if (score >= 70){  
    // code to exec when score > 70 is true  
} else {  
    // code to exec when false  
}
```

/CHECKING EXISTENCE

```
var x = document.getElementById("x")

if (x){
    // the element exists in the page.
    x.innerHTML = "Best time of my life!"
}
```



/LET'S PRACTICE

BLACKBOARD: IF STATEMENTS

/LOGICAL OPERATORS

&&

AND

This operator tests more than one condition. All must be true.

```
((age>18) && (isValid))
```

||

OR

This operator tests at least one condition.

```
((age>18) || (isValid))
```

!

NOT

This operator inverts a boolean value.

```
!(isValid)
```

/TESTING MULTIPLE CONDITIONS

CONDITION 1	LOGICAL OP	CONDITION 2
.....		
if ((midterm > 60)		(absence < 3))
{		
// code to exec when true		
} else {		
// code to exec when false		
}		



/LET'S PRACTICE

BLACKBOARD: LOGICAL OPERATOR

/PRACTICE

Based on the time of day, create a script to greet the user. If the hour is between 6 AM and just before 12 PM, say “**Good morning!**” If the hour is between 12 PM and just before 6 PM, say “**Good afternoon!**” For any other time, say “**Good evening!**”.

Complete the code in the **greetings.js** file