

# 1 PyUncertainNumber for uncertainty propagation with 2 black-box models: beyond probabilistic arithmetic

3 **Yu Chen**  <sup>1</sup>, **Scott Ferson**<sup>1</sup>, and **Edoardo Patelli**<sup>2</sup>

4 <sup>1</sup> Institute for Risk and Uncertainty, University of Liverpool, UK  <sup>2</sup> Centre for Intelligent  
5 Infrastructure, University of Strathclyde  Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

## License

Authors of papers retain copyright  
and release the work under a  
Creative Commons Attribution 4.0  
International License ([CC BY 4.0](#))  


## 6 Summary

7 Scientific computations or simulations play a central role in quantifying the performance,  
8 reliability, and safety of complex engineered systems. However, these analyses are complicated  
9 by the various sources of uncertainties inherent in the computational pipeline. To ensure that  
10 complex engineered systems can be operated reliably and robustly even during rare and extreme  
11 environment conditions, a comprehensive uncertainty analysis is required. The analysis should  
12 be comprehensive in two senses: (i) all possible sources of uncertainty should be identified  
13 and represented using appropriate mathematical constructs; (ii) The mixture of various types  
14 of uncertainties should be rigorously propagated through. `pyuncertainnumber` enables such  
15 comprehensive analysis, by computing guaranteed bounds on functions of uncertain variables,  
16 intrusively and non-intrusively, given only partial empirical knowledge.

## Statement of need

A comprehensive uncertainty framework for scientific computation involves a mathematical  
model, through which various input uncertainties are propagated to estimate the uncertainty  
of an unknown quantity of interest (QoI). Real world complex systems (physical or engineered)  
of industrial significance typically involves input parameters subject to uncertainties of various  
nature (Oberkampf et al., 2004). These input uncertainties are commonly manifested as  
mixed uncertainties, e.g. probability boxes (p-boxes) which effectively represents a set of  
distributions, combining both the aleatory and epistemic uncertainty in one structure, or a  
mixture of uncertainties encompassing, for instance, a vector of inputs parameters of aleatory  
(e.g. probability distributions), epistemic (e.g. intervals), and mixed nature (e.g. probability  
boxes).

Probability bounds analysis (Ferson, 2001) is one of the expressive frameworks proposed to  
manage uncertainties in an imprecise setting (Beer et al., 2013). Software packages have been  
developed to facilitate the calculations of uncertain quantities, such as interval arithmetic  
(Angelis, 2022) and probability arithmetic (A. Gray et al., 2021; N. Gray et al., 2022).  
Collectively, they can be referred to as *uncertainty arithmetic* (Chen & Ferson, 2025) which  
straightforwardly computes the response provided the performance function.

While it has the potential to automatically compile non-deterministic subroutines via uncertain  
primitives, its usages face several challenges, one significant challenge is that code accessibility  
of the simulation model (e.g. finite element or computational fluid dynamics models) of the  
system is often not guaranteed and hence unable to proceed. This would largely restrict  
the adoption of mixed uncertainty calculations in real-world applications of computational  
engineering and physics.

`pyuncertainnumber` addresses this challenge by providing the non-intrusive capability designed  
to allow generic black-box models to be rigorously propagated with polymorphic uncertainty.

<sup>42</sup> This capability significantly boosts versatility for scientific computations through interfacing  
<sup>43</sup> with many engineering softwares.

#### <sup>44</sup> Interval propagation in a non-intrusive manner

<sup>45</sup> Interval analysis ([Moore et al., 2009](#)) features the advantages of providing rigorous enclosures of  
<sup>46</sup> the solutions to problems, especially for engineering problems subject to epistemic uncertainty,  
<sup>47</sup> such as modelling system parameters due to lack-of-knowledge or characterising measurement  
<sup>48</sup> incertitude. Naive interval arithmetic typically faces difficulties such as the infamous [interval](#)  
<sup>49</sup> [dependency](#) issue. Though it may be mitigated through arithmetic rearrangements in some  
<sup>50</sup> simple cases, it still can challenge for models of most complex systems. The critical issue  
<sup>51</sup> remains the accessibility of code.

<sup>52</sup> Generally, the interval propagation problem can be cast as an optimisation problem where the  
<sup>53</sup> minimum and maximum are sought via a function mapping. The function, for example  $f$  in  
<sup>54</sup> [Equation 1](#), is not necessarily monotonic or linear and may well be a black-box deterministic  
<sup>55</sup> model for a generic system.

$$Y = f(I_{x1}, I_{x2}, \dots, I_{xn}) \quad (1)$$

<sup>56</sup> where  $\mathbf{I} = [\underline{\mathbf{I}}, \bar{\mathbf{I}}] = [I_{x1}, I_{x2}, \dots, I_{xn}]^T$  represents the vector of interval-valued inputs. For black  
<sup>57</sup> box models the optimisation can generally be solved via gradient-free optimisation techniques.


$$\underline{Y} = \min_{\mathbf{I} \leq \mathbf{I} \leq \bar{\mathbf{I}}} [f(\mathbf{I})]; \bar{Y} = \max_{\mathbf{I} \leq \mathbf{I} \leq \bar{\mathbf{I}}} [f(\mathbf{I})]$$

<sup>58</sup> [pyuncertainnumber](#) provides a series of non-intrusive methodologies of varying applicability.  
<sup>59</sup> It should be noted that there is generally a trade-off between applicability and computational  
<sup>60</sup> efficiency. With more knowledge pertaining the characteristics of the underlying function, one  
<sup>61</sup> can accordingly dispatch an efficient method. For example, when monotonicity is known one  
<sup>62</sup> can use the vertex method which requires  $2^n$  model evaluations. Furthermore, the accuracy  
<sup>63</sup> of these methods varies, and a common rule of thumb indicates that increasing the number  
<sup>64</sup> of model evaluations generally leads to improved accuracy. A summary of applicability is  
<sup>65</sup> tabulated in [Table 1](#), readers can refer to ([Chen & Ferson, 2025](#)) for additional details.

**Table 1:** Supported methods for non-intrusive interval propagation.

Method	End-points	Subinterval reconstitution	Cauchy-Deviate method	Bayesian optimisation	Genetic algorithm
As- sum- ption	mono- tonicity	monotonicity in subintervals	linearity and gradient required	No	No
Exam- ple result	[13.0,148.0][13.0,148.0]		[-11.7,100.67]	[13.0,148.0]	[13.0,147.8]

<sup>66</sup> To better demonstrate the non-intrusive capability, two numerical examples, as displayed below  
<sup>67</sup> in [Figure 1](#), are provided where they are treated as black-box models. [Table 1](#) lists the response  
<sup>68</sup> interval of  $f_b([1, 5], [7, 13], [5, 10])$  for respective methods.



**Figure 1:** Exampler functions as black-box models. (a)  $f_a(x, y) = 100(x - y^2)^2 + (1 - x)^2$ ; (b)  $f_b(x, y, z) = x^3 + y + z$


## 69 Mixed uncertainty propagation for black-box models

70 Real world complex systems (physical or engineered) of industrial significance typically in-  
 71 volves parameters subject to uncertainties of various nature (Oberkampf et al., 2004). It  
 72 requires faithful characterisation of these uncertainties given the empirical information, and  
 73 the approach to rigorously propagate them. Due to the fact that empirical information is  
 74 often sparse or scarce or conflicting, even the uncertainty characterisation for one parameter  
 75 could be of mixed nature, for example one may be confident about the distributional family  
 76 but uncertain about its shape parameters, or when there exists multiple expert opinion of  
 77 different credibility regarding its elicitation. Commonly, real systems expect a high-dimensional  
 78 input which effectively represents a mixture of aleatory, epistemic, and mixed uncertainties, as  
 79 symbolified below:

$$Y = f(\mathbf{u}; C) \quad (2)$$


80 where  $\mathbf{u} \in \mathbb{R}^n$  denotes the collection of  $n$  uncertain inputs and  $C$  denotes intervariable  
 81 dependency structure.

82 When both aleatory and epistemic uncertainties are present in  $\mathbf{u}$ , a *nested (double) Monte*  
 83 *Carlo* approach can be used for determininsitc models without confounding the two distinct  
 84 types of uncertainty. As illustrated in Figure 2, Latin-hypercube samples are first drawn from  
 85 the epistemic interval, conditioned on which aleatory samples are drawn from the aleatoric  
 86 probability distributions. Propagate these samples, which are visually denoted as rug ticks  
 87 alongside the abscissa, through the computational model results in an ensemble of CDF  
 88 (cumulative distribution function) of the QoI whereby a final p-box is obtained as the envelope.  
 89 Each CDF (orange color) corresponds to an epistemic sample.



**Figure 2:** Workflow of the Double Monte Carlo method.

To scale to a more realistic setting, Figure 3 illustrates the workflow of *interval Monte Carlo* method where a mixture of aleatory, epistemic, and mixed uncertainty parameters are present, and a certain copula is specified denoting the dependency structure. Correlated samples in the uniform space from the copula, visually denoted as rug ticks alongside the probability axis, are converted to physical space through alpha-cuts. Interval propagation (see the last section) then does the heavy lifting in which scalar values can be considered as degenerate intervals. As a result, the response QoI in Figure 3 is then obtained as a p-box shown in gray. In contrast, a pinched response, obtained from propagating pinched input variables (e.g. a p-box is pinched into a distribution and an interval is pinched into a scalar), is also shown as a comparison. Importantly, the pinched result being enclosed in the p-box manifests a critical feature of probability bounds analysis which yields results that are guaranteed to enclose all possible distributions of the output so long as the input p-boxes were all sure to enclose their respective distributions.



**Figure 3:** Workflow of the Interval Monte Carlo method. The first row shows the marginal of the inputs and the second row shows the bivariate copula density.

103

## Conclusion

104

It is evident that many computational tasks in engineering and physics rely on complex numerical methods in which the model functions are black boxes. This makes uncertainty arithmetic difficult to cope due to the code accessibility of models. By providing methods supporting generic black box models, pyuncertainnumber enables rigorous uncertainty analysis for real-world scenarios of mixed uncertainties and partial knowledge. This non-intrusive capability allows pyuncertainnumber to interface with multiple software environments to provide extensive compatibility with engineering applications, thereby its applicability across diverse computational workflows.

112

## Acknowledgements

113

The work leading to these results received funding through the UK project Development of Advanced Wing Solutions 2 (DAWS2). The DAWS2 project is supported by the Aerospace Technology Institute (ATI) Programme, a joint government and industry investment to maintain and grow the UK's competitive position in civil aerospace design and manufacture. The programme, delivered through a partnership between ATI, Department for Business and

<sup>118</sup> Trade (DBT) and Innovate UK, addresses technology, capability and supply chain challenges.

## <sup>119</sup> References

- <sup>120</sup> Angelis, M. de. (2022). *Intervals* (Version v0.1). Zenodo. <https://doi.org/10.5281/zenodo.6205624>
- <sup>121</sup> Beer, M., Ferson, S., & Kreinovich, V. (2013). Imprecise probabilities in engineering analyses. *Mechanical Systems and Signal Processing*, 37(1-2), 4–29.
- <sup>122</sup> Chen, Y., & Ferson, S. (2025). Imprecise uncertainty management with uncertain numbers to facilitate trustworthy computations. *SciPy Proceedings*. <https://doi.org/10.25080/ahrt5264>
- <sup>123</sup> Ferson, S. (2001). Probability bounds analysis solves the problem of incomplete specification in probabilistic risk and safety assessments. In *Risk-based decisionmaking in water resources IX* (pp. 173–188).
- <sup>124</sup> Gray, A., Ferson, S., & Patelli, E. (2021). ProbabilityBoundsAnalysis. Jl: Arithmetic with sets of distributions. *Proceedings of JuliaCon*, 1, 1.
- <sup>125</sup> Gray, N., Ferson, S., De Angelis, M., Gray, A., & Oliveira, F. B. de. (2022). Probability bounds analysis for python. *Software Impacts*, 12, 100246. <https://doi.org/https://doi.org/10.1016/j.simpa.2022.100246>
- <sup>126</sup> Moore, R. E., Kearfott, R. B., & Cloud, M. J. (2009). *Introduction to interval analysis*. SIAM.
- <sup>127</sup> Oberkampf, W. L., Trucano, T. G., & Hirsch, C. (2004). Verification, validation, and predictive capability in computational engineering and physics. *Appl. Mech. Rev.*, 57(5), 345–384.