SI2302

N-Channel MOSFET

FEATURES

- High dense cell design for extremely low $R_{DS(ON)}$
- Rugged and reliable
- Case Material: Molded Plastic.

1.Gate
2.Source
3.Drain

SOT-23



Absolute Maximum Ratings (TA=25°C, unless otherwise noted)

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DS}	20	V
Gate-source Voltage	V_{GS}	±8	V
Drain Current (Continuous)	I_D	3	A
Drain Current (Pulsed) [a]	I_{DM}	10	A
Total Power Dissipation @TA=25oC	P_D	1.25	W
Operating Junction and Storage Temperature Range	T_j, T_{stg}	-55 to +150	°C
Thermal Resistance Junction to Ambient (PCB mounted)[b]	$R_{\theta JA}$	100	°C/W

Electrical Characteristics (TA=25°C, unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS} = 0V, I_D = 10μA	20			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 20V, V_{GS} = 0V			1	μA
Gate Body Leakage Current, Forward	I_{GSSF}	V_{GS} = 8V, V_{DS} = 0V			100	nA
Gate Body Leakage Current, Reverse	I_{GSSR}	V_{GS} = -8V, V_{DS} = 0V			-100	nA
On Characteristics [c]						
Gate Threshold Voltage	$V_{GS(th)}$	V_{GS} = V_{DS}, I_D = 50μA	0.65		1.2	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	V_{GS} = 4.5V, I_D = 3.6A		55	72	mΩ
		V_{GS} = 2.5V, I_D = 3.1A		82	110	mΩ
Forwand Transconductance	g_{FS}	V_{DS} = 5V, I_D = 3.6A		8.5		S
Dynamic Characteristics [d]						
Input Capacitance	C_{iss}	V_{DS} = 10V, V_{GS} = 0V, f = 1.0 MHz		237		pF
Output Capacitance	C_{oss}			120		pF
Reverse Transfer Capacitance	C_{rss}			45		pF
Switching Characteristics [d]						
Turn-On Delay Time	$t_{d(on)}$	V_{DD} = 10V, I_D = 3.6A, V_{GS} = 4.5V, R_{GEN} = 6Ω		23	45	ns
Turn-On Rise Time	t_r			11	30	ns
Turn-Off Delay Time	$t_{d(off)}$			34	70	ns
Turn-On Fall Time	t_f			36	70	ns

Total Gate Charge	Q_g	V_{DS} = 10V, I_D = 3.6A, V_{GS} = 4.5V		6	10	nC
Gate-Source Charge	Q_{gs}			1.4		nC
Gate-Drain Charge	Q_{gd}			1.8		nC
Drain-Source Diode Characteristics and Maximun Ratings						
Drain-Source Diode Forward Current [c]	I_S				0.94	A
Drain-Source Diode Forward Voltage [d]	V_{SD}	V_{GS} = 0V, I_S = 0.94A			1.2	V

a.Repetitive Rating : Pulse width limited by maximum junction temperature. b.Surface Mounted on FR4 Board,t<10 sec.
c.Pulse Test : Pulse Width < 300μs, Duty Cycle < 2%. d.Guaranteed by design, not subject to production testing.

ME2302 Typical Characteristics



Figure 1. Output Characteristics



Figure 2. Transfer Characteristics



Figure 3. Capacitance



Figure 4. On-Resistance Variation with Temperature

ME2302 Typical Characteristics



Figure 5. Gate Threshold Variation with Temperature



Figure 6. Body Diode Forward Voltage Variation with Source Current



Figure 7. Gate Charge



Figure 8. Maximum Safe Operating Area