Holodeck: A VR-First System for Prompt-Driven Walkable World Generation

Leslie Osei-Anane

April 1, 2026

1 Introduction

Science fiction has always been reliable at predicting what we want before we know how to build it. The communicator from Star Trek became the first commercial flip phone. The tablet computer from 2001: A Space Odyssey became the iPad. These weren't coincidences. They were the same human desire, expressed first in story, then in silicon.

Of all the technologies science fiction imagined, the Holodeck stuck around the longest without a real answer. A user walked in, described a world, and the system built one around them. No menus, no asset browsers, no friction between imagination and experience. It felt further away than flying cars because the problem it was solving was harder to name. The hardware was the easier problem to solve. Understanding what a person meant, building something coherent from it, and delivering it before the moment of anticipation turned into waiting was the actual problem. That sequence of steps is deceptively demanding. A user speaks a sentence. The system interprets intent, selects a layout, furnishes it with appropriate objects, themes it correctly, and verifies that every surface is safe to walk on. In VR specifically, all of that has to work before the user takes a single step. The system earns the experience before it offers it.

Recent work has made real progress on pieces of this. ProcTHOR demonstrates that large-scale valid indoor environments can be generated procedurally with measurable generalization benefits for embodied AI [2]. Text2Room shows that a text prompt can seed a spatially consistent 3D mesh by lifting 2D generative outputs into a 3D representation [5]. Work directly named Holodeck has explored language-guided 3D environment generation by selecting and placing assets to satisfy language-specified constraints [7]. Each of these advances a different part of the problem. None of them put a user inside a headset and asked the system to perform in real time.

This paper describes a VR-first system in which a user enters a stable origin room, submits a natural language prompt by voice or text, and steps through a portal into a compiled, walkable destination world. The client application is implemented in Unity using C# and targets the Meta Quest platform via the OpenXR runtime. Prompts are converted into a validated intermediate representation called WorldSpec, which a deterministic compiler transforms into a runtime-executable world bundle. To reduce perceived latency and prevent disorienting world-formation effects, the destination world appears first as a walkable greybox

and upgrades visually in streaming phases as assets load. The system is evaluated on time to first walkable world, compilation success rate, constraint satisfaction, and runtime performance under Quest-native conditions.

2 Background

2.1 Large Language Models and Structured Output

Large language models (LLMs) are neural networks trained on large corpora of text to model and generate natural language. When prompted with appropriate constraints, these models produce outputs that conform to structured formats, including JSON schemas, enabling their integration as planning components in software pipelines. Prior work has demonstrated this planning pattern by mapping natural language into structured layout representations suitable for downstream scene construction [3]. Schema-locking, which constrains model output to a predefined JSON schema, reduces the likelihood of hallucinated or invalid field values and allows downstream components to parse and validate model responses deterministically. This property is central to the system described in this paper, which uses an LLM to convert natural language prompts into a validated WorldSpec representation rather than generating 3D content directly. A deterministic fallback planner handles cases where the LLM produces invalid or out-of-registry outputs, ensuring the pipeline succeeds even under model failure.

2.2 Virtual Reality and OpenXR

Virtual reality systems present stereoscopic rendered environments through a head-mounted display, tracking head and controller motion to update the view in real time. The OpenXR standard defines a cross-platform API for extended reality applications, allowing a single codebase to target multiple headset platforms [6]. The Meta Quest line of headsets runs OpenXR natively and imposes strict performance constraints: frame time budgets, draw call limits, and texture memory ceilings must be respected to maintain visual stability and user comfort. Teleport locomotion, a standard interaction pattern in VR, allows a user to select a destination on a valid floor surface and reposition instantly, sidestepping continuous motion that can cause discomfort. These constraints shaped the design of this system at every level, from asset budget enforcement to the decision to prioritize greybox compilation before visual quality.

2.3 Asset-Based Scene Composition

Asset-based scene composition constructs environments by selecting and placing pre-authored 3D objects from a controlled library, rather than generating geometry procedurally from noise functions or lifting it from 2D outputs. This approach trades generative range for reliability: the resulting environments contain assets with known geometry, collision data, and performance characteristics that a runtime can depend on. Large-scale procedural environment generation systems such as ProcTHOR illustrate this trade-off by composing valid scenes from constrained asset sets and layout rules [2]. Procedural placement systems

arrange these assets according to spatial constraints and layout rules while preserving physical validity. This system adopts asset-based composition as its primary generation strategy, supplemented by procedurally generated greybox geometry for structural layout. Assets enter the planner-safe inventory only after passing a manual review pipeline that validates semantic quality and assigns exclusion flags where appropriate.

2.4 Compiler Pipelines

Compiler pipelines transform high-level input into validated intermediate representations before producing executable outputs. Classic compiler design formalizes this staged structure as lexical and syntactic analysis, semantic checks, intermediate representation generation, optimization, and target code emission [1]. The same architectural pattern is useful for prompt-to-world systems: natural language is parsed into a constrained WorldSpec, validated for schema and safety constraints, and then compiled into runtime-ready artifacts. Treating world generation as a compiler pipeline makes failures diagnosable at stage boundaries, supports deterministic fallback behavior, and reduces runtime surprises in VR.

3 Related Work

Research in prompt-driven 3D environment generation has split along one foundational question: should a system generate novel geometry from a prompt, or assemble environments from a curated library of pre-authored assets? That choice has consequences for reliability, performance, and what guarantees a downstream runtime can actually make. Text2Room takes the generative geometry approach. Hollein et al. showed that a text prompt can produce a spatially consistent, textured 3D mesh by lifting outputs from 2D image generation models into a 3D representation [5]. The strength of this approach is coverage. Because geometry is synthesized rather than retrieved, the system can respond to arbitrary prompts without being limited by an asset catalog. In a live VR context, however, synthesized geometry requires post-generation analysis to determine walkability, draw call cost, and memory footprint before a runtime can safely load it. That additional step adds latency and introduces failure modes at the validation stage that are difficult to recover from within an interactive session. 3D-SceneDreamer addresses one dimension of this problem by representing global scene structure in a stable tri-plane NeRF and refining content in stages [9]. The staged approach improves cross-view consistency and reduces cumulative geometric error, and that architectural pattern, stabilizing global structure first then refining locally, maps onto the greybox-first compilation strategy this system uses. The difference is that geometry synthesis still produces outputs without known collision or performance properties, whereas asset-based compilation carries those properties from the start.

The asset-based approaches accept a narrower generative range in exchange for stronger guarantees. Deitke et al. and Yang et al. both work within pre-authored asset libraries, using structured representations and constraint satisfaction to produce environments whose physical properties are known before the world loads [2, 7]. Deitke et al. focus on procedural layout generation at scale, producing large collections of varied indoor environments for embodied AI training [2]. Yang et al. connect natural language to asset selection and

spatial placement directly, using a language model to convert prompts into structured scene descriptions that get compiled into interactive environments [7]. Both systems treat generation as a pipeline with explicit validation stages, and both produce environments reliable enough to train agents in. Both systems assume the asset library contains what the prompt requests. Asset coverage is an implicit prerequisite, not a problem the pipeline resolves. Feng et al. extend this direction by showing that large language models can serve as visual planners, converting natural language prompts into stylesheet-like structured layouts through in-context demonstrations [3]. Their results support a clear separation of concerns: planning in structured symbolic space first, then compilation afterward. That separation directly motivates the WorldSpec stage in this system, where the language model produces a schema-locked intermediate representation rather than geometry, and a deterministic compiler handles the rest.

A related body of work approaches structured scene representation through scene graphs, where objects are nodes and spatial relationships are edges. GraphDreamer uses scene graph conditioning to generate compositional 3D scenes, introducing object-wise disentanglement and relationship-aware constraints to reduce interpenetration and improve spatial coherence [4]. CommonScenes takes a similar position, combining a layout branch and a shape generation branch conditioned on scene-object and object-object relationships, and reports improved semantic consistency compared with retrieval-heavy alternatives [8]. Both works provide evidence that explicit relational structure, represented before rendering rather than inferred from it, produces more controllable and reproducible outputs. For the purposes of this system, the scene graph functions as an analogue to WorldSpec: a machine-checkable intermediate representation that the compiler can validate against spatial and budget constraints before any geometry is loaded.

All three systems treat generation as an offline or training-time problem, where compilation time and frame stability fall outside the design requirements. A user standing in a headset waiting for a portal to open operates under a different set of conditions. The system described in this paper sits within the asset-based tradition of Deitke et al. and Yang et al., adopting structured intermediate representations and constraint-driven compilation for the same reliability reasons, but applies them to a live interactive setting where those guarantees have to hold in real time [2, 7]. A deterministic fallback planner handles cases where the language model produces invalid output. A greybox-first compilation phase ensures a walkable world exists before visual assets begin streaming. A substitution system replaces missing assets with the closest tagged alternatives, keeping the pipeline moving regardless of asset coverage gaps. The contribution is a composition of these properties into a pipeline that maintains reliability guarantees under the constraints of a standalone VR headset.

4 Methodology

4.1 Client (VR application)

The client consists of the Unity-based VR runtime, the Creation Room, the in-world assistant panel, the portal transition system, and the destination-world executor. Together, these components handle prompt entry, user feedback, comfort-preserving movement, and the final

handoff into the compiled world. The client also enforces the runtime interaction contract by reading backend-produced manifest and phase artifacts, preparing the portal only after a valid destination is available, and relocating the XR origin to a validated safe spawn point on entry. At runtime, the client applies comfort and presentation logic such as teleport-surface enforcement, destination-world polish, and return-home transitions while keeping headset-side behavior deterministic.

4.2 Backend (planning, compilation, and validation)

The backend consists of the planner, WorldSpec validator, pack and stylekit registries, substitution layer, safe-spawn search, and the phase0 compiler that writes the runtime contract. These components convert a prompt into a validated manifest and phase artifact that the Unity client can execute deterministically.

4.2.1 Backend Pipeline

Planning occurs in two stages. First, the language model converts the prompt into a structured intent and selection proposal over a safe, indexed asset shortlist, producing a schema-constrained WorldSpec rather than geometry directly. If the semantic path fails or returns invalid identifiers, the request either fails explicitly or enters a deterministic fallback path only when that policy is enabled.

Compilation transforms the validated WorldSpec into a runtime-executable bundle. The compiler resolves missing assets through constrained substitution, builds a greybox destination shell, solves legal placements under deterministic constraints, computes a safe spawn, and writes the manifest and phase0 artifact that Unity consumes at runtime. Validation occurs throughout this pipeline: schema checks reject malformed WorldSpecs, placement solving enforces walkability and non-overlap constraints, and budget checks preserve Quest-compatible runtime performance before the portal is allowed to open.

4.3 Implementation

The most important design choices are to use an LLM for semantic planning while keeping compilation, validation, and runtime safety deterministic, and to rely on a reviewed asset pool instead of unconstrained generation for the MVP. A greybox-first compile stage, non-stacking floor placement, and explicit safe-spawn checks were chosen to preserve reliability and comfort on standalone VR hardware.

4.4 Research Questions and Goals

My research question is whether a prompt-driven system can convert natural language into a walkable VR world quickly enough to remain interactive while still enforcing safety, validity, and runtime constraints. The main goals are to generate a validated WorldSpec from a prompt, compile it into a room the user can safely enter, and measure whether this pipeline remains reliable on standalone VR hardware.



Figure 1: Simplified system architecture for the prompt-to-world pipeline, showing the client, backend compiler pipeline, and runtime handoff.

4.5 Data, Tools, and Systems

The system uses manually reviewed asset packs, stylekit manifests, WorldSpec and manifest JSON contracts, and compiled phase0 artifacts as its primary data sources. The implementation uses Unity with C# and OpenXR on the client side, and Python modules for planning, validation, substitution, safe-spawn search, and compilation on the backend, with Gemini providing the semantic planning path.

4.6 Replication Requirements

To replicate the system, a developer would need the Unity project, the Python backend, the reviewed asset and stylekit manifests, a configured '.env' file for the LLM provider, and the dependencies listed in 'requirements.txt'. They would also need a Quest-compatible OpenXR setup for runtime testing, although the backend contract generation can be reproduced from the terminal without the headset.

5 Conclusion

This system currently targets indoor room-scale environments compiled from a fixed, manually reviewed asset library. Several directions remain open for future work. Asset coverage is the

most immediate constraint: expanding the indexed inventory through additional reviewed packs would allow the planner to satisfy a broader range of prompts without falling back to substitution. Supporting multi-room and outdoor environments would require extending the WorldSpec schema and the greybox compiler to handle more complex spatial graphs. Geometry synthesis, as demonstrated by approaches such as Text2Room [5], represents a longer-term direction for handling prompts that fall entirely outside the indexed inventory, provided that synthesized geometry can be validated against the same walkability and performance constraints the current compiler enforces. Finally, the progressive streaming architecture opens the door to interactive world editing, where a user could modify a StyleKit or adjust prop density on an already-compiled world without triggering a full recompilation.

References

[1] Aho, A. V., Lam, M. S., Sethi, R., and Ullman, J. D. *Compilers: Principles, Techniques, and Tools*, 2 ed. Addison-Wesley, 2006.

[2] Deitke, M., VanderBilt, E., Herrasti, A., Weihs, L., Ehsani, K., Salvador, J., Han, W., Kolve, E., Kembhavi, A., and Mottaghi, R. ProcTHOR: Large-Scale Embodied AI Using Procedural Generation. In *Advances in Neural Information Processing Systems* (2022), vol. 35, Curran Associates, Inc.

[3] Feng, W., Zhu, W., Fu, T.-J., Jampani, V., Akula, A., He, X., Basu, S., Wang, X. E., and Wang, W. Y. LayoutGPT: Compositional visual planning and generation with large language models. In *Advances in Neural Information Processing Systems* (2023), vol. 36, Curran Associates, Inc.

[4] Gao, G., Liu, W., Chen, A., Geiger, A., and Schölkopf, B. GraphDreamer: Compositional 3D scene synthesis from scene graphs. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)* (June 2024), IEEE/CVF, pp. 21295–21304.

[5] Höllein, L., Cao, A., Owens, A., Johnson, J., and Niessner, M. Text2Room: Extracting Textured 3D Meshes from 2D Text to Image Models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)* (October 2023), IEEE/CVF, pp. 7909–7920.

[6] Khronos Group. OpenXR 1.1 specification. URL: https://registry.khronos.org/OpenXR/specs/1.1/html/xrspec.html, 2024. Accessed: March 5, 2026.

[7] Yang, Y., Sun, F.-Y., Weihs, L., VanderBilt, E., Herrasti, A., Han, W., Wu, J., Haber, N., Krishna, R., Liu, L., Callison-Burch, C., Yatskar, M., Kembhavi, A., and Clark, C. Holodeck: Language Guided Generation of 3D Embodied AI Environments. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)* (June 2024), IEEE/CVF, pp. 16227–16237.

[8] Zhai, G., Örnek, E. P., Wu, S.-C., Di, Y., Tombari, F., Navab, N., and Busam, B. CommonScenes: Generating commonsense 3D indoor scenes with scene graph diffusion. In *Advances in Neural Information Processing Systems* (2023), vol. 36, Curran Associates, Inc.

[9] Zhang, S., Zhang, Y., Zheng, Q., Ma, R., Hua, W., Bao, H., Xu, W., and Zou, C. 3D-SceneDreamer: Text-driven 3D-consistent scene generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)* (June 2024), IEEE/CVF, pp. 10170–10180.