OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

Shaders

EDAF80: Computer Graphics

Rikard Olajos

Lund University Graphics Group
LUND UNIVERSITY
LTH FACULTY OF ENGINEERING

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

AGENDA

1. OpenGL Shader Language
2. Textures
3. Shading theory
4. Assignment 3

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

OpenGL Shader Language (GLSL)

- C like language for programming GPUs
- Vertex & fragment shaders
- Labs: GLSL 4.10 (OpenGL 4.1)
  - Have geometry & tessellation shaders as well
- Compute shaders since OpenGL 4.3
- Newest OpenGL 4.6

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

GLSL TYPES

- Types

```
float, int, bool, vec2, vec3, vec4, mat3 ...
sampler2D, samplerCube ...
```

- Type qualifiers

```
const        // compile-time constant
uniform      // constant per primitive
in, out      // attributes passed to/from, and between,
             // the vertex & pixel shader
```

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

GLSL OPERATORS AND FUNCTIONS

- Structures and arrays with built-in operators

```
vec2, vec3, vec4, mat3, mat4
vec3 v = vec4(1.0f).xyz;            // Swizzle
vec4 u = mat4(1.0f) * vec4(1.0f);   // Operator overloading
```

- User defined functions
- Built-in functions

```
sin(), cos(), pow(), normalize(), min(), max(), clamp(),
reflect(), refract(), sqrt(), noise(), ...
```

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

GLSL FLOW CONTROL AND PREPROCESSOR

- Flow control

```
if, if-else, for, while, do-while
discard      // Fragment shader only
```

- Preprocessor directives

```
#define, #undef, #if, #else, #endif, ...
```

- Comments

```
// Like this
/* Or, like this */
```

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

DEVELOPMENT TOOLS

- Shadertoy: `https://www.shadertoy.com/`
- NVIDIA Nsight Visual Studio Edition
- GLSL-Debugger
- This course: by hand ☺
  - Text-editor in Visual Studio
  - Compiler messages (from the GPU) written to ImGUI log window
- Check out `https://docs.gl/` and GLSL 4.10 Specification

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

DIFFUSE VERTEX SHADER

```
layout (location = 0) in vec3 vertex;
layout (location = 1) in vec3 normal;

uniform mat4 vertex_model_to_world;
uniform mat4 normal_model_to_world;
uniform mat4 vertex_world_to_clip;

out VS_OUT {
    vec3 vertex;
    vec3 normal;
} vs_out;

void main()
{
    vs_out.vertex = vec3(vertex_model_to_world * vec4(vertex, 1.0));
    vs_out.normal = vec3(normal_model_to_world * vec4(normal, 0.0));

    gl_Position = vertex_world_to_clip * vertex_model_to_world * vec4(vertex, 1.0);
}
```

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

VERTEX SHADER INPUTS

```
layout (location = 0) in vec3 vertex;
layout (location = 1) in vec3 normal;

uniform mat4 vertex_model_to_world;
uniform mat4 normal_model_to_world;
uniform mat4 vertex_world_to_clip;
```

- `layout` specifies the location of the input data in the vertex buffer
  - Sent from `node.cpp: Node::render()`
  - Other `mat4` also comes from there
- Matrix data is loaded with `glUniformMatrix4fv(...)`

```
glUseProgram(program);
GLint i = glGetUniformLocation(program, "vertex_model_to_world");
glUniformMatrix4fv(i, 1, GL_FALSE, glm::value_ptr(world));
```

- More in reference pages

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

VERTEX SHADER OUTPUTS

```
out VS_OUT {
    vec3 vertex;
    vec3 normal;
} vs_out;

void main()
{
    vs_out.vertex = vec3(vertex_model_to_world * vec4(vertex, 1.0));
    vs_out.normal = vec3(normal_model_to_world * vec4(normal, 0.0));

    gl_Position = vertex_world_to_clip * vertex_model_to_world * vec4(vertex, 1.0);
}
```

- `VS_OUT` is a struct with the output values
- This must match the input to the fragment shader

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

DIFFUSE FRAGMENT SHADER

```
uniform vec3 light_position;

in VS_OUT {
    vec3 vertex;
    vec3 normal;
} fs_in;

out vec4 frag_color;

void main()
{
    vec3 L = normalize(light_position - fs_in.vertex);
    frag_color = vec4(1.0) * clamp(dot(normalize(fs_in.normal), L), 0.0, 1.0);
}
```

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

DIFFUSE FRAGMENT SHADER

```
uniform vec3 light_position;

in VS_OUT {
    vec3 vertex;
    vec3 normal;
} fs_in;

out vec4 frag_color;

void main()
{
    vec3 L = normalize(light_position - fs_in.vertex);
    frag_color = vec4(1.0) * clamp(dot(normalize(fs_in.normal), L), 0.0, 1.0);
}
```

- `VS_OUT` struct matches the vertex shader output and contains interpolated values
- `vertex` is the world position of the current pixel
- `L` is the normalized to the light
- `light_position` set with

```
glUseProgram(program);
GLint i = glGetUniformLocation(program, "light_position");
glUniform3fv(i, 1, glm::value_ptr(light_position));
```

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

INTERPOLATION OVER TRIANGLE

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

TEXTURES

Recognise the texture?

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

WRAPPING

- Wrapping defines behaviour of texture, outside $(\boldsymbol{s}, \boldsymbol{t}) \in [0, 1]$
- `GL_REPEAT`: Coordinates wrap around the texture $(-0.2 \rightarrow 0.8)$
- `GL_MIRRORED_REPEAT`: Coordinates wraps with mirrored value $(-0.2 \rightarrow 0.2)$
- `GL_CLAMP_TO_EDGE`: Clamp coordinates to $[0, 1]$, edge value get copied
- `GL_CLAMP_TO_BORDER`: Clamp coordinates to $[0, 1]$, border colour is used
  - `GL_TEXTURE_BORDER_COLOR` needs to be set

```
glBindTexture(GL_TEXTURE_2D, texture);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_S, GL_MIRRORED_REPEAT);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_T, GL_MIRRORED_REPEAT);
```

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

WRAPPING

`GL_REPEAT` (default)

`GL_MIRRORED_REPEAT`

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

WRAPPING

GL_CLAMP_TO_EDGE

GL_CLAMP_TO_BORDER

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

MAGNIFICATION

- Magnification filter defines behaviour of texture when a texel covers more than one pixel
- `GL_NEAREST`: Use the nearest texel only
- `GL_LINEAR`: Use linear interpolation of four closest texels

```
glBindTexture(GL_TEXTURE_2D, texture);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MAG_FILTER, GL_NEAREST);
```

- (Minification is discussed in EDAN35 ☺)

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

MAGNIFICATION

`GL_LINEAR` (default)

`GL_NEAREST`

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

PHONG SHADING

- Phong shading per pixel
- Assuming normalized vectors

$$\texttt{color} = \texttt{ambientColor} + \texttt{diffuseColor} * \max(\mathbf{n} \cdot \mathbf{L}, 0) + \texttt{specularColor} * \max((\text{reflect}(-\mathbf{L}, \mathbf{n}) \cdot \mathbf{V})^{\texttt{shininess}}, 0)$$

ambient

ambient + diffuse

ambient + diffuse + specular

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

CUBE MAPPING

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

SKYBOX

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

SKYBOX

- Attach cube map to large sphere (large enough to contain all scene content)
- Write a “skybox”-shader that looks up colours from the cube map
  - in the normal direction,
  - or with world position coordinates(?)
- Create illusion of sphere placed at infinity
- Make sure back-face culling is disabled
- Inside of sphere will appear as surrounding sky/landscape

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

ADDING A CUBE MAP

- Complete `loadTextureCubeMap()` and use it

```
GLuint cubemap = bonobo::loadTextureCubeMap(
    config::resources_path("cubemaps/NissiBeach2/posx.jpg"),
    config::resources_path("cubemaps/NissiBeach2/negx.jpg"),
    config::resources_path("cubemaps/NissiBeach2/posy.jpg"),
    config::resources_path("cubemaps/NissiBeach2/negy.jpg"),
    config::resources_path("cubemaps/NissiBeach2/posz.jpg"),
    config::resources_path("cubemaps/NissiBeach2/negz.jpg"));
```

- Add a cube map to your sphere node

```
sphere.add_texture("cubemap", cubemap, GL_TEXTURE_CUBE_MAP);
```

- `node.cpp` will bind the cube map and set the uniform (check code)

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

ADDING A CUBE MAP

- In your fragment shader add

```
uniform samplerCube cubemap;
```

- Then use it in your fragment shader

```
frag_color = texture(cubemap, coordinates);
```

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

NORMAL MAPPING

- Obtain normal from normal map instead of interpolation from vertices
- Requires a defined ***tangent space***

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

TANGENT SPACE

- Basis vectors: tangent **t**, binormal **b**, normal **n**
- Basis matrix: **TBN**
- Derived from the surface equation, $\mathbf{p}(u, v)$
  - Assignment 2!

$$\mathbf{TBN} = \begin{pmatrix} t_x & b_x & n_x \\ t_y & b_y & n_y \\ t_z & b_z & n_z \end{pmatrix}$$

tangent space $\mapsto$ model space

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

SPACES OVERVIEW

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

NORMAL MAP LOOK-UP

- Normals stored as (r, g, b) where each component lies in $[0, 1]$
- Map to $[-1, 1]$: $\mathbf{n} = (r, g, b) \times 2 - 1$
- Blue-ish colour since "unmodified" normal, $\mathbf{n} = (0, 0, 1)$, maps to $RGB = (0.5, 0.5, 1.0)$

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

NORMAL TRANSFORMATIONS

- Normal not ready to use yet; light vector is in world space, so normal must be as well
- Transform normal from tangent to world space:

$$\mathbf{WORLD}^{-T} \cdot \mathbf{TBN} \cdot \mathbf{n}$$

- Available as `normal_model_to_world` in Bonobo shaders (check `node.cpp`)
- Now we can proceed with light calculations

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

SUMMARY

1. Look up $(\boldsymbol{r}, \boldsymbol{g}, \boldsymbol{b})$ from texture
2. Create $\mathbf{n}$ by mapping from $[0, 1]$ to $[-1, 1]$
3. Transform to world space: $\mathbf{WORLD}^{-T} \cdot \mathbf{TBN} \cdot \mathbf{n}$
4. Use this normal when performing light calculations

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

ROUGHNESS MAPPING

- Similar to normal mapping
  - Store material properties in a texture
  - During lighting calculations, do texture look-ups and apply value
- Replace specular component of Phong model
- Many other material properties are also common to store in textures

Diffuse texture

Roughness texture

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

ASSIGNMENT 3

- Implement the following shader techniques:
  - Phong shading
  - Cube mapping using a skybox
  - Normal mapping
- Finish implementation of cube map loading
- Files you have to modify
  - `src/EDAF80/assignment3.cpp`
  - `src/EDAF80/parametric_shapes.cpp`
  - `src/core/helpers.cpp`
  - Any shader files that you created

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

HINTS

- Create new shader programs as needed
  - `skybox.vert`, `skybox.frag`...
- Use `R` key to do hot reload of shaders
  - Performs read from disk and compilation
  - Check log for error messages
- In `shaders/EDAF80/`, look at `diffuse.vert` and `diffuse.frag` for guidance

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

NORMAL MAPPING IN SHADER

- All tangent space basis vectors are needed (normal, tangent, binormal)
- Complete vertex definition:

```
struct Vertex {
    float   x, y, z,        /* vertex position */
            s, t,           /* texture coords */
            nx, ny, nz,     /* normal */
            tx, ty, tz,     /* tangent */
            bx, by, bz;     /* binormal */
};
```

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

NORMAL MAPPING IN SHADER

- Hint:
  - Set **t**, **b**, **n** as `in`-attributes to the vertex shader and make them vary per fragment using `out`
  - Construct **TBN**-matrix in fragment shader using `mat4`
- Check out `res/textures/` for more textures

OpenGL Shader Language
Types, operators and flow
Development tools
Example: Diffuse shader
Interpolation
Textures
Wrapping
Magnification
Shading theory
Phong shading
Cube mapping
Normal mapping
Roughness mapping
Assignment 3
Hints
Demo

DEMO