TasteRoute: Preference-Based Place Recommendation and Route Planning

Final Report · Machine Learning Term Project, Gachon University · November 2026

Team: 이태현 (leten02), 효빈 (Hyobin0515), 건희 (Bae-kunhee), 가경 (GaKingOh) · Code: https://github.com/leten02/TasteRoute

Summary

TasteRoute recommends restaurants a user is likely to enjoy, re-ranks them so they are reachable in a day, and orders the final places into the shortest visiting route. It is trained and evaluated on 490,539 Yelp ratings of 7,693 restaurants within 15 km of Philadelphia City Hall.

Question	Answer	Evidence
Which rating model is best?	Bias, MF, CBF and Hybrid tie at test RMSE 1.051 to 1.052; Item-kNN 1.121, global mean 1.190	Section 9.1
RQ1: what does adding distance cost?	Nothing: with exponential decay (tau = 2 km) the mean list distance falls 6.3 → 2.1 km and Hybrid NDCG@10 rises 0.0009 → 0.0062	Section 9.2
RQ2: does CBF help cold-start users?	No: with 1, 3 or 5 training ratings, CBF and Hybrid stay within 0.002 RMSE of the bias model, also with 42 extra place attributes	Section 9.3
RQ3: heuristic vs exact route?	NN + 2-opt is exactly optimal for 82% of users (mean gap 0.9%); visiting in recommendation order walks 26% more (median); Held-Karp takes 0.9 ms for 8 places	Section 9.4
Do the conclusions survive a time-ordered split?	Yes: all metrics get worse, but model order and the distance effect hold	Section 9.6

The strongest ranking signals in this data are popularity and distance, not predicted ratings. Popularity alone beats every rating model on Precision@10 (0.0094 vs 0.0004 to 0.0005), and the best list blends the Hybrid prediction with log popularity and then re-ranks by distance.

1. Overview

We build a system that recommends Top-N places a user is likely to enjoy, re-ranks them so they are actually reachable, and plans a one-day visiting route through the final N places.

- Domain: place and restaurant recommendation on Yelp business reviews.

- Problem: rating prediction alone pushes far-away places to the top, and place data is far sparser than movie data (median 1 review per user, 99.998% sparsity).
- Approach: machine learning (CF, CBF, Hybrid) produces candidates; deterministic algorithms handle distance re-ranking and route optimization.

Research questions:

1. RQ1: How much ranking accuracy is lost, and how much travel distance is saved, when distance is added to the ranking?
2. RQ2: Does content-based filtering reduce error for users with few ratings (cold start)?
3. RQ3: How close does a fast heuristic route (nearest neighbor + 2-opt) come to the exact optimum, and at what speed?

The end-to-end score for user u and place i is a rating prediction discounted by distance:

$$\text{score}(u, i) = \hat{r}_{ui} \cdot w(d(\ell_u, \ell_i))$$

where the predicted rating comes from one of the recommenders, d is the haversine distance between the user anchor and the place, and w is a decreasing weight in [0, 1].




Figure 1. System architecture: machine learning picks candidates; algorithms make them reachable and ordered.

2. Dataset

We use the Yelp Open Dataset (January 2022 release, yelp.com/dataset): 6,990,280 reviews by 1,987,929 users on 150,346 businesses. The archive is 4.34 GB compressed and 8.65 GB once extracted into five JSON files.

File	Size	Records	Fields we use	Role
business.json	119 MB	150,346	business_id, latitude, longitude, categories, is_open, hours,	Item features, location, opening hours

File	Size	Records	Fields we use	Role
			attributes	
review.json	5.34 GB	6,990,280	user_id, business_id, stars, date	Rating matrix (target)
checkin.json	287 MB	131,930 businesses	not used	-
tip.json	181 MB	908,915	not used	-
user.json	3.36 GB	1,987,897	not used (mostly friend lists)	-

Property of the full data	Value	Consequence
Rating matrix density	0.0023%	CF needs aggressive filtering
Reviews per user, median	1 (57.1% of users have one review)	Cold start is the default case
Reviews per business, median	15	Items are better covered than users
Mean rating	3.75	Global-mean baseline is strong
Duplicate (user, business) pairs	244,520 (3.5%)	Need a dedup rule
Closed businesses	20.4%	Train on them, never recommend them
Distinct categories	1,311 (mean 4.45 per business)	Needs pruning and weighting

$$\rho = \frac{|\mathcal{R}|}{|\mathcal{U}|\,|\mathcal{I}|} = \frac{6{,}990{,}280}{1{,}987{,}929 \times 150{,}346} \approx 2.34 \times 10^{-5}$$

3. Exploratory data analysis

The EDA justified four decisions: which city, which k-core threshold, how far a user is willing to travel, and which categories to keep.




Figure 2 (E1). Two thirds of all reviews give 4 or 5 stars, so a model that predicts high everywhere already looks good on RMSE; ranking metrics carry the comparison.




Figure 3 (E2). Review volume peaked in 2019 and fell 39% in 2020; the time-ordered split in Section 9.6 checks whether this drift changes the conclusions.




Figure 4 (E5). After 5-core filtering Philadelphia keeps twice the restaurant ratings of any other city, which keeps the ranking metrics stable.




Figure 5 (E9). Restaurants and Food tag almost every kept place and are dropped from the content features.

The remaining figures use the Philadelphia scope (15 km around City Hall, Restaurants or Food, deduplicated).




Figure 6 (E3). Only 13% of in-scope users have 5 or more ratings, while every business already has 5 or more; the k-core filter mainly removes users.




Figure 7 (E4). The top 10% of restaurants hold 56% of all ratings (Gini 0.68): strong popularity concentration.




Figure 8 (E6). Restaurants concentrate near City Hall; 57% of kept places lie within 5 km.




Figure 9 (E7). Two random restaurants in scope are typically 9.1 km apart.




Figure 10 (E8). Half of users stay within 2.3 km of their own centre; this sets the starting decay scale tau = 2 km.

The gap between Figure 9 and Figure 10 is the case for distance re-ranking: places are spread about 9 km apart, but users behave locally. The median distance from a user's anchor to the places they rate is 1.4 km, and 90% are within 8.5 km.




Figure 11 (E10). Bars and Nightlife are near duplicates (Jaccard 0.95), which IDF weighting must not count twice.




Figure 12 (E11). Business mean ratings spread wider than user mean ratings (std 0.72 vs 0.65), so both bias terms are needed.




Figure 13 (E12). More-reviewed restaurants rate higher (3.48 → 4.00 stars), so a popularity prior is not only bias.

Statistics behind these figures:

$$\bar{F}(x) = P(n_u \geq x) = \frac{1}{|\mathcal{U}|} \sum_{u \in \mathcal{U}} \mathbb{1}[\, n_u \geq x \,], \qquad G = \frac{\sum_{i=1}^{n} (2i - n - 1)\, x_{(i)}}{n \sum_{i=1}^{n} x_{(i)}}$$

$$\text{radius}(u) = \frac{1}{n_u} \sum_{i \in \mathcal{I}_u} d\,(c_u, \ell_i), \qquad c_u = \frac{1}{n_u} \sum_{i \in \mathcal{I}_u} \ell_i$$

4. Preprocessing

The working set is Philadelphia restaurants within 15 km of City Hall after 5-core filtering: 490,539 ratings, 31,743 users and 7,693 businesses (density 0.20%). It is built by `data_analysis_preprocessing/preprocess.py` in about 90 seconds.




Figure 14 (P1). Preprocessing pipeline, all counts measured.

Stage	Ratings	Users	Businesses
Raw reviews	6,990,280	1,987,929	150,346
Within 15 km of City Hall	1,101,215	-	18,613
Restaurants and Food	836,276	-	8,956
Deduplicated (latest kept)	809,070	242,139	8,956
5-core (working set)	490,539	31,743	7,693

4.1 Scope and deduplication

Businesses are kept by radius around the city center instead of the city string, because suburbs are stored as separate cities. When a user reviewed the same business more than once, the most recent rating is kept.

$$\mathcal{I}_{\text{city}} = \{\, i : d(\ell_i, \ell_{\text{center}}) \le R \,\} \cap \{\, i : \text{Restaurants} \in C_i \ \vee\ \text{Food} \in C_i \,\}, \qquad R = 15 \text{ km}$$

4.2 Iterative k-core filtering

$$\mathcal{R}_k = \text{largest } \mathcal{R}' \subseteq \mathcal{R} \ \text{ s.t. } \ |\mathcal{I}'_u| \ge k \ \ \forall u, \quad |\mathcal{U}'_i| \ge k \ \ \forall i$$




Figure 15 (E13). At k = 5, 61% of ratings but only 13% of users survive; k = 10 would halve the users again, so k = 5 stays.

4.3 Category matrix

Restaurants and Food are dropped, as are categories on fewer than 10 businesses, leaving 188 of 451 in-scope categories. The binary matrix is IDF-weighted and L2-normalized.

$$X_{ic} = \mathbb{1}[\, c \in C_i \,], \qquad \text{idf}(c) = \log \frac{|\mathcal{I}|}{1 + |\{i : X_{ic} = 1\}|}, \qquad \boldsymbol{x}_i = \frac{(X_{ic}\,\text{idf}(c))_c}{\| \,(X_{ic}\,\text{idf}(c))_c \,\|_2}$$

4.4 Split and cold-start group

Each user's ratings are split about 70 / 15 / 15 into train, validation and test, with at least one validation and one test rating per user. Hyperparameters are tuned only on validation; the test set is used once. Because k-core filtering removes exactly the users RQ2 is about, 10% of users with at least 10 ratings (1,306 users) keep only m = 1, 3 or 5 training ratings to simulate new users.




Figure 16 (P4). Split sizes and the cold-start group.




Figure 17 (P2). 5-core filtering removes one-off extremes: the 1-star share falls from 10% to 6%.

5. Models

All rating models share one interface (`fit(train)`, `predict(u, i)`, `score_all(u)`), train on the same split and are tuned on validation RMSE. Final settings are in Section 9.5.

5.1 Baselines

$$\hat{r}_{ui} = \mu, \qquad b_{ui} = \mu + b_u + b_i$$

$$\min_{b_*} \sum_{(u,i)\in\mathcal{R}} (r_{ui} - \mu - b_u - b_i)^2 + \lambda_u \sum_u b_u^2 + \lambda_i \sum_i b_i^2$$

$$b_i = \frac{\sum_{u\in\mathcal{U}_i} (r_{ui} - \mu - b_u)}{\lambda_i + |\mathcal{U}_i|}, \qquad b_u = \frac{\sum_{i\in\mathcal{I}_u} (r_{ui} - \mu - b_i)}{\lambda_u + |\mathcal{I}_u|}$$

5.2 Memory-based CF: item-based kNN

Cosine, adjusted cosine and Pearson similarities were compared, with shrinkage toward zero for items with few co-raters and prediction on top of the bias baseline:

$$\text{sim}_{\cos}(i,j) = \frac{\sum_{u\in\mathcal{U}_{ij}} r_{ui}\, r_{uj}}{\sqrt{\sum_{u\in\mathcal{U}_{ij}} r_{ui}^2}\,\sqrt{\sum_{u\in\mathcal{U}_{ij}} r_{uj}^2}}, \qquad s_{ij} = \frac{|\mathcal{U}_{ij}|}{|\mathcal{U}_{ij}| + \beta}\,\text{sim}(i,j)$$

$$\hat{r}_{ui} = b_{ui} + \frac{\sum_{j\in N_k(i;u)} s_{ij}\,(r_{uj} - b_{uj})}{\sum_{j\in N_k(i;u)} |\,s_{ij}|}$$

5.3 Model-based CF: matrix factorization

$$\hat{r}_{ui} = \mu + b_u + b_i + \boldsymbol{p}_u^{\top}\boldsymbol{q}_i, \qquad \mathcal{L} = \sum_{(u,i)} (r_{ui} - \hat{r}_{ui})^2 + \lambda\big(b_u^2 + b_i^2 + \|\,\boldsymbol{p}_u\,\|^2 + \|\,\boldsymbol{q}_i\,\|^2\big)$$

Stochastic gradient descent with error e_ui and learning rate eta, early stopping after 3 epochs without validation improvement:

$$b_u \leftarrow b_u + \eta\,(e_{ui} - \lambda b_u), \qquad b_i \leftarrow b_i + \eta\,(e_{ui} - \lambda b_i)$$
$$\boldsymbol{p}_u \leftarrow \boldsymbol{p}_u + \eta\,(e_{ui}\,\boldsymbol{q}_i - \lambda \boldsymbol{p}_u), \qquad \boldsymbol{q}_i \leftarrow \boldsymbol{q}_i + \eta\,(e_{ui}\,\boldsymbol{p}_u - \lambda \boldsymbol{q}_i)$$

5.4 Content-based filtering

Each user gets a linear taste vector over the IDF-weighted categories, fitted by ridge regression on what the bias baseline leaves unexplained. A first version centered on the user mean failed for new users (with one rating the user mean is that rating; RMSE 1.50), which is why it is fitted on bias residuals.

$$\boldsymbol{\theta}_u = (X_u^\top X_u + \lambda_c I)^{-1} X_u^\top (\boldsymbol{r}_u - \boldsymbol{b}_u), \qquad \hat{r}_{ui}^{\text{CBF}} = b_{ui} + \boldsymbol{\theta}_u^\top \boldsymbol{x}_i$$

For RQ2 two richer content models were added: CBF with 42 Yelp place attributes (take-out, ambience, meal times and others, IDF-weighted) and a content-based neighbor model that generalizes from a single rating:

$$\hat{r}_{ui} = b_{ui} + \frac{\sum_{j \in \mathcal{I}_u} s_{ij}\ (r_{uj} - b_{uj})}{\sum_{j \in \mathcal{I}_u} |\, s_{ij}| + \text{shrink}}, \qquad s_{ij} = \cos(\boldsymbol{x}_i, \boldsymbol{x}_j)$$

5.5 Hybrid

The weight on CF grows with the number of training ratings; kappa is the count at which CF and CBF get equal weight:

$$\alpha(n_u) = \frac{n_u}{n_u + \kappa}, \qquad \hat{r}_{ui} = \alpha(n_u)\,\hat{r}_{ui}^{\text{CF}} + (1 - \alpha(n_u))\,\hat{r}_{ui}^{\text{CBF}}$$

5.6 Candidate generation and popularity blend

Candidates are open places the user has not rated, with at least 20 training ratings (rating models over-score places few users rated). Because rating models predict how much a user would like a place, not whether they would go, the ranking score blends in popularity:

$$\text{score}_{\text{blend}}(u, i) = \hat{r}_{ui} + \gamma \log(1 + |\mathcal{U}_i|)$$

5.7 Ranking models: BPR and a learned visit model

BPR learns the ranking of visited over unvisited places directly from pairs (i visited, j not), with mini-batch stochastic gradient ascent and early stopping on validation NDCG@10 (Rendle et al., 2009):

$$x_{ui} = b_i + \boldsymbol{p}_u^\top \boldsymbol{q}_i, \qquad \max \sum_{(u,i,j)} \ln \sigma(x_{ui} - x_{uj}) - \frac{\lambda}{2}\left(\| \boldsymbol{p}_u \|^2 + \| \boldsymbol{q}_i \|^2 + \| \boldsymbol{q}_j \|^2 + b_i^2 + b_j^2\right)$$

The learned visit model replaces the fixed decay rule with logistic regression on distance, personal travel radius rho_u, predicted rating and popularity, trained with our own gradient descent, L2 regularization and backtracking line search:

$$P(\text{visit} \mid u, i) = \sigma(\boldsymbol{w}^\top \boldsymbol{x}(u, i) + b), \quad \boldsymbol{x} = \left[\log(1 + d),\ d,\ \log(1 + d/\rho_u),\ \hat{r}_{ui},\ \log(1 + \text{pop}_i)\right]$$

$$L = -\frac{1}{n}\sum [y \log p + (1 - y)\log(1 - p)] + \frac{\lambda}{2} \| \boldsymbol{w} \|^2, \qquad \nabla_{\boldsymbol{w}} L = \frac{1}{n} X^\top (\boldsymbol{p} - \boldsymbol{y}) + \lambda \boldsymbol{w}$$

6. Distance-aware re-ranking

The candidates are re-scored by multiplying the predicted rating (rescaled to [0, 1]) with a distance weight. The user anchor is the median of the coordinates of the user's training places.

$$d(\ell_a, \ell_b) = 2R_E \arcsin\sqrt{\sin^2\left(\frac{\varphi_b - \varphi_a}{2}\right) + \cos\varphi_a \cos\varphi_b \sin^2\left(\frac{\lambda_b - \lambda_a}{2}\right)}, \qquad R_E = 6{,}371 \text{ km}$$

$$w_{\text{exp}}(d) = e^{-d/\tau}, \quad w_{\text{gauss}}(d) = e^{-d^2/(2\sigma^2)}, \quad w_{\text{pow}}(d) = (1 + d/d_0)^{-\gamma}, \quad w_{\text{cut}}(d) = \mathbb{1}[\, d \le D_{\max}\,]$$

$$\text{score}(u, i) = \frac{\hat{r}_{ui} - 1}{4} \cdot w(d(\ell_u, \ell_i))$$




Figure 18 (R1). The decay shape decides how fast a far place loses its score; scales are tuned on validation.

Maximal Marginal Relevance (category diversity) and division by a power of popularity were implemented as optional knobs; on this data both cost accuracy and stay off by default.

7. Route optimization

The final N places (N = 5 to 8) are ordered to minimize total distance from the start point: an open-path traveling salesman problem.

$$\pi^* = \underset{\pi \in S_N}{\text{argmin}} \left[D_{0\,\pi(1)} + \sum_{t=1}^{N-1} D_{\pi(t)\,\pi(t+1)} \right]$$

Held-Karp dynamic programming, with C(S, j) the shortest path from 0 that visits exactly S and ends at j:

$$C(\{j\}, j) = D_{0j}, \qquad C(S, j) = \min_{k \in S \setminus \{j\}} \left[C(S \setminus \{j\}, k) + D_{kj} \right], \qquad T_{\text{HK}}(N) = O(N^2 2^N)$$

The heuristic is nearest neighbor followed by 2-opt, which reverses a segment whenever that shortens the path:

$$\Delta(a,b) = D_{\pi_a\pi_b} + D_{\pi_{a+1}\pi_{b+1}} - D_{\pi_a\pi_{a+1}} - D_{\pi_b\pi_{b+1}} < 0 \;\Rightarrow\; \text{reverse } \pi_{a+1..b}, \qquad \text{gap} = \frac{L_{\text{heur}} - L^*}{L^*}$$

Opening hours extend Held-Karp: each state (S, j) keeps the Pareto set of labels (closed visits, finish time), and the objective is lexicographic: fewest visits that arrive at a closed place, then the earliest finish. Travel is at 4.5 km/h, and arriving before opening means waiting:

$$\text{arrive}_j = \text{end}_k + D_{kj} \cdot \frac{60}{4.5}, \qquad \text{begin}_j = \text{earliest_start}(j, \text{arrive}_j), \qquad \text{end}_j = \text{begin}_j + \text{stay}$$

8. Evaluation protocol

A test rating of 4 or 5 stars counts as relevant. Top-N metrics use 3,000 sampled warm test users; model differences are tested per user with a paired t-test and a 95% bootstrap interval over users (1,000 resamples).

$$\text{RMSE} = \sqrt{\frac{1}{|\mathcal{T}|}\sum_{(u,i)\in\mathcal{T}} (r_{ui} - \hat{r}_{ui})^2}, \qquad \text{MAE} = \frac{1}{|\mathcal{T}|}\sum_{(u,i)\in\mathcal{T}} |r_{ui} - \hat{r}_{ui}|$$

$$\text{Precision@}K = \frac{1}{|\mathcal{U}|}\sum_u \frac{|L_u^K \cap \text{Rel}_u|}{K}, \qquad \text{Recall@}K = \frac{1}{|\mathcal{U}|}\sum_u \frac{|L_u^K \cap \text{Rel}_u|}{|\text{Rel}_u|}$$

$$\text{DCG@}K = \sum_{k=1}^{K} \frac{2^{\text{rel}_k} - 1}{\log_2(k+1)}, \qquad \text{NDCG@}K = \frac{\text{DCG@}K}{\text{IDCG@}K}, \qquad \text{Coverage} = \frac{|\bigcup_u L_u^K|}{|\mathcal{I}|}$$

$$t = \frac{\bar{\delta}}{s_\delta/\sqrt{n}}, \qquad \delta_u = m_A(u) - m_B(u)$$

9. Results

All numbers are on the test set; every choice was made on validation. Sources are the result files in the repository (`results/*.json`).

9.1 Rating prediction

Model	Setting	Test RMSE [95% CI]	MAE	p vs Bias
Global mean	-	1.190 [1.182, 1.198]	0.943	< 0.001
Bias	lambda = 5	1.051 [1.044, 1.059]	0.818	-
Item-kNN	cosine, k = 80, beta = 0	1.121 [1.113, 1.130]	0.839	< 0.001
MF (SGD)	f = 10, lambda = 0.1, 15 epochs	1.052 [1.044, 1.059]	0.819	0.0015
CBF (ridge)	lambda_c = 30	1.051 [1.043, 1.059]	0.818	0.81
Hybrid	kappa = 100	1.051 [1.044, 1.059]	0.818	0.93

The median user has only 6 training ratings, so there is little structure beyond the user and item biases. MF is slightly worse than Bias, and CBF and Hybrid cannot be told apart from it.




Figure 19 (V1). Test RMSE per model with 95% bootstrap intervals over users (69,847 warm test ratings).

9.2 Ranking and distance re-ranking (RQ1)

Method (3,000 test users)	P@10	NDCG@10	Mean list distance	Coverage
Popularity	0.0094	0.0323	3.0 km	0.32%
Bias	0.0005	0.0009	6.2 km	4.25%
MF	0.0004	0.0011	6.3 km	4.74%
CBF	0.0004	0.0008	6.2 km	4.41%
Hybrid	0.0004	0.0009	6.3 km	4.30%
Hybrid + distance (exp, tau = 2 km)	0.0018	0.0062	2.1 km	-
Popularity + distance	0.0100	0.0337	2.7 km	0.47%
Hybrid blend (gamma = 5)	0.0095	0.0323	3.0 km	0.34%
Hybrid blend + distance	0.0102	0.0340	2.6 km	0.55%

RQ1 expected a trade-off: closer lists, lower accuracy. The opposite happened. Exponential decay with tau = 2 km cuts the Hybrid list's mean distance from 6.3 to 2.1 km and raises NDCG@10 from 0.0009 to 0.0062 (6.9 times). Users mostly rate places near where they already go, so distance is itself a strong relevance signal. The hard cutoff is worse than smooth decay at every radius.




Figure 20 (R2). Closer lists are also more accurate: NDCG@10 against mean list distance, one point per decay scale.

Predicted ratings alone do not beat popularity, and a popularity blend plus distance (P@10 0.0102) is practically the same as popularity plus distance (0.0100): the ranking signal in this data comes mostly from popularity and distance.




Figure 21 (D1). Popularity and distance carry the ranking signal.

The learned visit model (Section 5.7) is significantly more accurate than the earlier fixed setting (NDCG@10 0.0340 → 0.0365, p = 0.003). It is not significantly different from a fixed rule with tau re-tuned on 200 candidates (0.0373, p = 0.36), but it covers more of the catalog (1.26% vs 1.01%, point estimate). Removing the personal travel radius makes it significantly worse.




Figure 22 (L1). Learned visit model against fixed decay rules.




Figure 23 (L2). Learned distance response: at 1 km, one more km of distance is offset by 1.56 times the popularity.

BPR, which learns the ranking directly, shows no evidence of beating popularity overall (NDCG@10 0.0326 vs 0.0323, p = 0.61). It was ahead only for users with 21 or more training ratings (0.0419 vs 0.0381, p = 0.03 before correcting for three groups). Changing the objective to ranking does not create a strong personal signal in this data.




Figure 24 (B1). BPR against popularity by user activity.

9.3 Cold start (RQ2)

Model	m = 1	m = 3	m = 5
Global mean	1.131	1.148	1.151
Bias	1.069	1.026	1.039
Item-kNN	1.245	1.213	1.152
MF	1.067	1.024	1.040
CBF	1.069	1.026	1.040
Hybrid	1.069	1.025	1.040

Test RMSE of the 1,306 simulated new users who keep m training ratings. CBF and Hybrid stay within 0.002 of the bias model. Adding 42 place attributes and the content-based neighbor model did not help either: for both attribute models, validation chose the setting that switches content off as far as the range allowed, and no model differs from Bias (all $p \geq 0.19$). The answer to RQ2 is no: in this data, content does not explain a new user's ratings.




Figure 25 (V5). Cold-start RMSE at 1, 3 and 5 training ratings.




Figure 26 (C1). With place attributes, validation shrinks the content term toward zero.

9.4 Route optimization (RQ3)

Method (3,000 test users, N = 6)	Exactly optimal	Mean gap to optimum
Recommendation order	-	median +26%
Nearest neighbor	32.1%	5.8%
NN + 2-opt	81.9%	0.9%
Held-Karp	100%	0%

Ordering matters even for six nearby places: the optimal order saves a median 1.2 km. Held-Karp takes 0.9 ms for 8 places and 31 ms for 12, while brute force needs 314 ms already at 9, so the exact solver is used in the system and the heuristic is a comparison for RQ3.




Figure 27 (T3). Visiting in recommendation order walks 26% more; NN + 2-opt is exactly optimal for 82% of users.




Figure 28 (T2). Measured runtime per instance by number of places.

Opening hours: on 400 random day plans, the hours-aware Held-Karp cut visits that arrive at a closed place from 272 to 82 (70% fewer, Wilcoxon p < 1e-26). It walks 0.9 km more on average, but waiting time falls by 39 minutes and the day ends 27 minutes earlier.

Walking distance on real streets (OpenStreetMap, Dijkstra): real walks are a median 1.30 times the straight line. For 2,230 Center City test users, re-ranking by walking distance gave no significant accuracy difference (p = 0.61), and the straight-line optimal order is also walking-optimal for 65% of users (mean extra 1.2%, worst 14%). Straight-line distance is a sufficient approximation for the experiments; real streets are needed only for the routes shown to users. These walking numbers were measured before the study-area boundary fix of issue #66 and are marked for re-run in the repository.




Figure 29 (W1). Walking detour factor: median 1.30 times the straight line.




Figure 30 (W2). Straight-line routing is almost free on real streets.

9.5 Hyperparameter search

Model	Searched	Best (validation)
Bias	lambda in {1, 5, 10, 25}	lambda = 5
Item-kNN	similarity (cosine, adjusted cosine, Pearson) x k in {10, 20, 40, 80} x beta in {0, 25, 100}	cosine, k = 80, beta = 0 (val 1.1134)
MF (SGD)	f in {10, 20, 50, 100} x lambda in {0.01, 0.02, 0.05, 0.1}	f = 10, lambda = 0.1, eta = 0.01
CBF	lambda_c in {0.3, 1, 3, 10, 30}	lambda_c = 30
Hybrid	fixed alpha in {0, …, 1}; adaptive kappa in {0.5, …, 100}	kappa = 100
Distance decay	4 shapes x tau from 0.5 to 1000 km	exponential, tau = 2 km
Popularity blend	gamma in {0, …, 20}	gamma = 5
BPR	relevance definition x learning rate x f x lambda (24)	ratings >= 4, 0.05, f = 64, lambda = 1e-4

MF prefers few factors and strong regularization, the same message as Section 9.1: the data supports little latent structure.




Figure 31 (M4). MF validation RMSE over factors x regularization.




Figure 32 (M1). Item-kNN validation RMSE by similarity and neighbors.




Figure 33 (M3). MF learning curve with early stopping.




Figure 34 (M5, M6). Hybrid weight: fixed alpha and adaptive kappa curves are nearly flat.

9.6 Robustness: time-ordered split

The default split shuffles each user's ratings, so 88% of warm users train on a rating newer than one of their test ratings. Re-splitting each warm user by date (oldest about 70% train, newest about 15% test) makes most metrics worse: Bias RMSE 1.051 → 1.108, popularity NDCG@10 0.0323 → 0.0218. The conclusions hold. The four rating models remain within 0.001 of each other, and distance re-ranking still raises Hybrid NDCG@10 (0.0012 → 0.0049) while cutting list distance from 5.0 to 2.3 km. The best method is still the Hybrid blend plus distance (0.0245).




Figure 35 (S1). Random vs time-ordered split.

9.7 Worked example: one user through the pipeline

The figures below come from the first end-to-end prototype run documented in the proposal and illustrate the three stages for one test user with 45 training ratings; their numbers are from that run, not from the final experiments above.




Figure 36 (X1). Rating prediction: item bias adds +0.75 to +0.91 stars, the latent term at most 0.02.




Figure 37 (X2). Re-ranking pulls the user's top 10 from a mean 13.9 km to 8.8 km away.




Figure 38 (X3). The optimal order shortens the 6-stop route from 54.3 km to 24.1 km.

10. Discussion

10.1 What worked and what did not

- Distance re-ranking is the clearest win: it shortens lists and improves accuracy at the same time, and it survives the time-ordered split.
- Exact route optimization is cheap at this size, and ordering alone saves a quarter of the walking.
- Rating models could not beat the bias baseline (RQ2 negative, MF and kNN no better). With a median of 6 training ratings, there is little to learn beyond biases.
- Rating-trained models rank worse than popularity; the fix was to blend popularity into the candidate score and to re-rank by distance.

10.2 Difficulties and how we solved them

Difficulty	Solution
Extreme sparsity (99.998%)	Radius scope, 5-core filtering, strong regularization
CBF failed for 1-rating users (RMSE 1.50)	Fit CBF on bias residuals instead of the user mean
Rating models rank below popularity	Minimum-support filter, popularity blend, distance re-ranking
Random split leaks the future	Time-ordered split as a robustness check
Straight-line distance is unrealistic	Walking distance on OpenStreetMap, opening-hours-aware routing

10.3 Limitations and what we would do differently

- Users have no location in Yelp; the anchor is the median of their rated places, which favors users who stay local.
- Open/closed status (`is_open`) is the 2022 snapshot, and the walking evaluation awaits a re-run after the boundary fix.
- The time-ordered split is per user, not a global cut-off date.
- Starting again, we would train for ranking (BPR or the visit model) and evaluate on a time-ordered split from the first day.

11. System and open source

Component	Location	Role
Data analysis and preprocessing	`data_analysis_preprocessing/`	EDA, scope, k-core, split, figures E and P
Package	`src/tasteroute/`	data, models (baseline, item_knn, mf, cbf, hybrid, content_knn, visit, bpr), candidates, rerank, geo, roads, route, pipeline, cluster
Experiments	`experiments/` (`run_all.py`)	every result in `results/` and figure in `figures/`, about 6 minutes
Demo and dashboard	`demo/bakery_tour.py`, `app/dashboard.py`	Philadelphia bakery tour on real streets; Streamlit dashboard
Tests and CI	`tests/`, `.github/workflows/ci.yml`	pytest on synthetic data, ruff, commit-convention check

Work followed issue → branch → pull request into `develop`, with four CI checks and CodeRabbit review required before merge.

Member	Main contributions
이태현 (leten02)	Team lead; model and experiment pipeline, dashboard, repository and CI
효빈 (Hyobin0515)	Data analysis and preprocessing, proposal, time-ordered split evaluation, review follow-ups
건희 (Bae-kunhee)	Dashboard keyboard accessibility, road-network cache and opening-hours boundaries
가경 (GaKingOh)	Walking experiment scope fix and re-run, documentation tables

Run the whole study:

```
pip install -e ".[dev,demo]"
python data_analysis_preprocessing/preprocess.py
python experiments/run_all.py
pytest
python demo/bakery_tour.py --straight
```

References

- Y. Koren, R. Bell, C. Volinsky, “Matrix Factorization Techniques for Recommender Systems”, IEEE Computer, 2009 (bias model, MF and SGD updates)
- A. Yeung, “Matrix Factorization: A Simple Tutorial and Implementation in Python”, https://albertauyeung.github.io/2017/04/23/python-matrix-factorization.html/ (MF SGD implementation reference)
- B. Sarwar et al., “Item-based Collaborative Filtering Recommendation Algorithms”, WWW, 2001 (item-kNN similarity)
- Y. Koren, “Factor in the Neighbors: Scalable and Accurate Collaborative Filtering”, ACM TKDD, 2010 (similarity shrinkage, neighbors on a bias baseline)
- S. Rendle et al., “BPR: Bayesian Personalized Ranking from Implicit Feedback”, UAI, 2009 (BPR)
- K. Järvelin, J. Kekäläinen, “Cumulated Gain-based Evaluation of IR Techniques”, ACM TOIS, 2002 (NDCG)
- M. Held, R. Karp, “A Dynamic Programming Approach to Sequencing Problems”, J. SIAM, 1962 (Held-Karp)
- G. A. Croes, “A Method for Solving Traveling-Salesman Problems”, Operations Research, 1958 (2-opt)
- E. W. Dijkstra, “A Note on Two Problems in Connexion with Graphs”, Numerische Mathematik, 1959 (shortest paths)
- G. Boeing, “OSMnx”, Computers, Environment and Urban Systems, 2017 (road network download)
- Yelp Open Dataset, https://www.yelp.com/dataset (data; redistribution not allowed, not committed)
- OpenStreetMap contributors, https://www.openstreetmap.org (walking network, ODbL)