

Glossary

active reconnaissance The use of active investigation methods for gathering information about a system or an infrastructure directly.

adware A general term for software that uses typical malware intrusion techniques to obtain marketing data or advertise a product or service.

alternate key A field with values that are not chosen as a primary key, but can be used in cases where the primary key is not available.

attribute A characteristic or variable that describes or further identifies an entity.

audit scope The area or system on which the security audit will focus. Defining the scope of the audit is one of the most important steps of the auditing process.

authentication The process of confirming the identity of those individuals or applications that request access to a secure environment.

authorization The process of ensuring that those individuals or applications that request access to an environment or an object within that environment have the permission to do so.

automated audit An audit conducted using tools that are either installed onto a machine or embedded within an application for the purpose of recording the typical behavior of a system.

availability The efforts taken through policy, procedures, and design in order to create and maintain the accessibility of resources within a database environment.

back door A method created during the programming of a worm in which access is gained into a system by avoiding normal security, which gives the creator of the worm undetected access into the system.

backup An intentional copy of data, program files, and system configurations that is used to archive and store information in the event of network failure or malware attacks.

backup management plan A process developed to ensure the safety of the data on a network.

binary code installations Binary files that are packaged and ready to be installed without the need for compiling the code to enable it to be run as an executable file on a particular machine.

binary file A file that contains code that can be read by machines and run as an executable file.

black box testing An assessment that is conducted with no prior knowledge of the system or infrastructure that is being tested.

black hat Someone who breaks into computer networks without authorization and with malicious intent.

bond parameters Placeholders to bind user input.

boot sector An area of the hard disk that contains records necessary to the boot process of a computer.

boot sector virus Malware that infiltrates a system by loading itself onto the boot sector of a hard disk via an infected floppy disk left in a floppy disk drive.

bot (software robot) A form of malware that has the ability to perform a large array of automated tasks for an intruder at a remote location, ranging in severity from spamming a system to initiating DoS attacks on systems.

botmaster An individual who controls a network of bots and who accumulates a number of bots and then rents these botnets to other intruders and cybercriminals for the purpose of spamming, phishing, and other more serious types of cybercrime.

botnet A network of bots.

buffer manager A portion of the SQL Server responsible for accessing data pages and updating the database.

buffer pool (buffer cache) The area where data pages from a database are stored to minimize the need to read and write from the database file located on the hard disk.

caching The process of saving a duplicate of the requested data to another area of a system in

hopes of saving resources and speeding up the future requests for that same data.

candidate key A field with values that meet the requirements for a primary key.

Client Access License (CAL) A unique license that allows users or devices access to gain a licensed Microsoft SQL Server 2008 server.

cold site A facility that provides the basic necessities for rebuilding a network. A contract that involves a cold site would promise the use of a facility that provides water, power, and air conditioning or heat.

column (field) The component of a table that maintains a general category of information with similar data types.

commit To make a change within a DBMS that is permanent and visible to other users.

compile The act of converting source code that is written in one language into a different programming language or machine language.

composite key A group of two or more fields where their values can be combined to be used as a primary key.

computer security A set of established procedures, standards, policies, and tools that is used to protect a computer from theft, misuse, and unwanted intrusions, activities, and attacks.

computer virus A form of malware intended to spread from one computer to another without detection.

concurrency The simultaneous access of resources and data.

confidentiality The efforts taken through policy, procedure, and design to create and maintain the privacy and discretion of information and systems.

control file A file within a database that contains the location and important credentialing information of other files.

cracker An individual who breaks into networks without authorization with hopes to destroy and/or steal information.

credential A piece of information that is used to verify identity, such as a person's username and password, an application's secure ID, or a host's network name and address.

database A collection of data stored on a computer using an application called a database management system.

database connection manager The component of the database architecture that manages connections to the MySQL server.

database link A link made between two databases that when created results in one logical data storage unit. Links are created in Oracle to apply common policies and to create associations between databases.

database management system (DBMS) An application that allows users to search stored data in order to locate specific information.

database model A representation of the way data is stored.

database security A set of established procedures, standards, policies, and tools that is used to protect data from theft, misuse, and unwanted intrusions, activities, and attacks.

datafile A file that contains the actual data for the database and holds the information for all logical structures (tables, records, and so forth) within the database.

data sending Trojan Malware that obtains sensitive data from your computer and transmits it back to a cracker.

deadlock A situation when two transactions cannot proceed because each user has data that the other needs.

denial of service (DoS) attack A concerted effort made by malware to keep system resources, such as Internet sites, from functioning correctly.

destructive Trojan Malware that is installed on a computer with the intent to destroy a system as a whole by randomly deleting files and folders and corrupting the registry.

differential backup An intentional copy of data, program files, and system configurations that only saves the data that has changed since the last backup was complete.

digital certificate A password-protected and encrypted file that holds the identity of a user or object.

digital signature Code that uses cryptography to verify the authenticity of a source of information.

disaster plan A plan developed to ensure the quick reinstatement of a network that has fallen victim to a human or naturally caused disaster.

DNS poisoning An intrusion where a cracker gains control over the DNS server and changes the domain name's respective IP address, redirecting requests to sites that the cracker has built and maintains.

dynamic analysis An attempt to find errors or vulnerabilities in the source code of a program dynamically while it is being executed.

dynamic SQL statement A SQL statement that is generated on the fly by an application (such as a Web application), using a string of characters derived from a user's input parameters into a form within the application itself.

encryption The transformation of data by using sophisticated algorithms in an attempt to make the data unrecognizable.

entity A person, place, or thing stored within the table of a database and for which attributes and relationships exist.

exploitation The act of using system vulnerabilities and carefully crafted SQL queries to gather information and subsequently peel away at the infrastructure's security defense for the purpose of gaining access or control of a system.

external audit An audit conducted using a third-party group or a number of individuals from a source outside the organization itself.

external testing An assessment that is conducted outside the organization's security border; this type of testing will display attacks and liabilities that can be exploited externally from competitors, external users, and hackers. Initial tasks most commonly completed during external testing involve information gathering. An external intruder must gain information from a system or an infrastructure to break into it.

fiber A subcomponent of a thread, which is handled by the server to accomplish a task.

filegroup A collection of one or more physical data files within a SQL Server database.

file-infected virus A form of malware that will attach itself to an executable file that requires a user to run before it can propagate and corrupt the system.

File Transfer Protocol (FTP) Trojan Malware that allows the attacker to use someone else's computer as an FTP server.

flat model A two-dimensional list of data entries, where all data within a field are understood to be similar, and all data within a record are understood to be related to one another.

foreign key A field within a table that contains a label used to build a relationship between two tables.

formal audit An audit most often conducted to satisfy specific industry standards that are required by law for certain types of organizations.

full backup An intentional copy of data, program files, and system configurations that stores all information, regardless of its critical nature, age, and prior backup activity.

grey hat An individual or groups of individuals who waver between the classification of a hacker and a cracker, and who either act in goodwill or in malice.

hacker Someone who has mastered the hardware and software of modern computer systems and enjoys the exploration and analysis of network security with no intent to intrude or cause harm.

hactivist Hackers and crackers who use their extensive experience and skill to use networks to share their ideologies regarding controversial social, political, and economic topics.

Health Insurance Portability and Accountability Act (HIPAA) Strict laws for health institutions throughout the United States that ensure the security and privacy of patient records by dictating the way in which files are accessed, stored, and transmitted on a network.

hierarchical database structure A treelike storage schema that represents records and relationships through the use of tiers and parent-child relationships.

hijacking A process in which Web sites are hacked into and rewritten to react differently to users than how the original Web site designer intended.

honeypot A fake environment that includes false data to mislead intruders who are attempting to gather information about the database.

hot site An exact replica of an organization's network, or a mirror site, that promises the vendor will assume all responsibility for ensuring that the network is readily available in the event of a disaster.

Hypertext Transfer Protocol (HTTP) The portion of an Internet address that informs the browser what protocol is used to send the request for a particular Web site.

incremental backup An intentional copy of data, program files, and system configurations that is conducted on only the data that has changed since the last full or incremental backup.

inference A way that unauthorized users can obtain sensitive information by making assumptions based on the database's reactions or query responses to nonsensitive queries.

informal audit An audit conducted as a way to provide organizations evidence that their security policies and practices are effective and working properly.

information reconnaissance The process of gathering information either directly (e.g., actively) or indirectly (e.g., passively) from a system or the system's environment.

instance A broad term that refers to the background processes and structured memory used during interaction with the database.

integrated services A valuable tool in data warehouses where different types of data need to be joined together for reporting and extrapolation.

integrity Efforts taken through policy, procedure, and design in order to create and maintain reliable, consistent, and complete information and systems.

internal audit An audit conducted using a committee of individuals who are employees of the company itself.

internal security controls The systematic measures and checks put into place to ensure that networks remain sound and secure.

internal testing An assessment that is conducted within the organization's security border that will display vulnerabilities that exist among internal users such as employees and contractors. It also identifies attacks and the damage that can be caused within the network itself. A task conducted during an internal security assessment might include an evaluator logging in to a user's computer in an attempt to raise the user's privileges on a particular system.

Kerberos An authentication protocol that was built by MIT to provide secure means for authentication using symmetric-key cryptology to verify the identity of a client to a server and a server to a client.

key A single field or group of fields used to identify an entry in a table.

key logger Malware constructed to log every keyboard stroke that a user types on the keyboard.

lock A mechanism within a DBMS that controls concurrency by preventing users from taking hold of data until changes being made are completed or committed.

log file A file that stores information about the transactions in the database to be used for recovery and backup.

logic bomb Malware that can lie dormant until a specific predetermined variable is met, whose variables typically depend on the environment in which it resides.

login An object that is mapped to a user account within each database and is associated to users by the security identifier or SID.

macro A small program that enables users to automate a large number of repeated processes within a document.

macro virus Malware that can either be attached to a macro, or can replace a macro within a

document, and that runs automatically when the document containing the infected macro is opened or closed.

malicious software A programming code written and used by unauthorized intruders to perform a certain task on a computer.

malware An abbreviation for the term malicious software.

memory target The reserved space for the buffer cache.

misleading applications Applications that deceive users into believing that their computer's security has been breached, therefore tricking the user into downloading and purchasing rogue antivirus tools to remove the bogus breach.

Mixed Mode Authentication A form of authentication that allows both Windows authentication and SQL Server authentication to be used. The database will accept both Windows and server logins.

multipartite virus A form of malware that combines the characteristics of a boot sector virus with those of a file-infected virus.

network database model A treelike structure that stores information in the form of a hierarchy, using tiers and parent-child-like entities to represent relationships.

network port scanner Automated tools that are designed to traverse the network in an attempt to locate available vulnerable ports and identify the services that they use.

network security A set of established procedures, standards, policies, and tools that are used to protect data from theft, misuse, and unwanted intrusions, activities, and attacks.

network sniffers The utilities that monitor the network looking for a number of combined types of vulnerability. Network sniffers can identify missing software patches, application types, application version numbers, open ports, operating systems, and firewalls, to name a few.

nonresident virus The general term for malware that requires users to initiate it by downloading a program or opening up an e-mail attachment.

online analytical processing (OLAP), (decision support systems [DSS]) Databases that store large volumes of historical data for report generating and analyzing.

online transaction processing (OLTP) database A database that is created for real-time storage and manipulation of data within an organization.

open source A term that refers to software that has been written to be distributed for use and downloaded free of charge.

operational information security A term that refers to the secure operation of an organization through the development and reliability of an environment's policies and procedures that focus on security policies, change management, update management, and disaster recovery plans.

optimization The process of locating the quickest and most efficient way to retrieve the data being requested by a user.

OS upgrade The process of installing a new version of an operating system onto a host or a server.

page A fixed unit of storage that is transferred or swapped from one storage device to another.

pagefile The dedicated swap space for a page.

parallel processing When more than one server processes one query at the same time.

parsing The act of analyzing a construction of a query for correct syntax and semantics.

passive reconnaissance The use of passive investigation methods to gather information about a system or an infrastructure indirectly.

password hash A cryptology-encoded string version of a user or system password.

password scanners Essentially, network sniffers that traverse the network searching for passwords from remote authentication systems. Password scanners capture passwords as they are sent remotely across the network and record them for the attacker to maintain.

patch A small program that is used to fix or update software programs or hardware devices.

payload The component of a worm that holds all of the instructions on how to affect each computer that it encounters.

personal identifiable information (PII) Personal information that identifies a person.

phishing The attempt to obtain PII from people through the use of spoofed e-mail addresses and URLs.

point of sales (POS) system A system that is meant to handle cash register or sales transactions.

polyinstantiation A strategy that allows the database to contain multiple instances of a record, all pointing to the same primary key, but contain and display different values to users of different security classifications.

polymorphism The incidence of changing forms, or self-modification.

primary data file The main data file for a SQL Server database which is the file of origin for the entire database and references all other secondary data files.

primary filegroup The collection of files that contains all of the SQL Server system files, including the primary data files.

primary key A field that contains a unique label by which we can identify a record or row in a table.

principle of least privilege A security standard by which each user added to a system is given the minimum set of privileges that he or she requires to conduct legitimate business within that system.

privilege The ability to access a specific database resource or to perform a specific action within a database.

process A set of instructions that is executed by the operating system intended to complete a task.

Process Global Area (PGA) The central area where information is stored for background and server processes. It allocates space for each individual background process.

programming language A type of synthetic language developed with a specific syntax and semantic rules that allows individuals to create

statements or functions to interface and control the behavior or functionality of a machine.

proxy Trojan Malware that enables a cracker to use someone else's computer to access the Internet in order to keep his or her identity hidden.

query A search initiated by a user in an attempt to retrieve certain information from a database.

query cache A memory component that plays a role in ensuring that query processing is successful.

query engine A component of the architecture that optimizes and manages queries and SQL statements.

query management The steps taken by a database management application to process a user query.

read consistency A term that refers to the accuracy and reliability of data within a database.

redo log A file within a database that contains information regarding all changes made to the data within the database.

relational database A storage model in which common entities are stored within separate tables that use unique key identifiers to build relationships between these entities.

relationship A term that defines the association between two entities and binds them.

remote access and administration Trojan (RAT) Malware that provides remote access capability to the cracker from whom the virus originated, who in turn is provided complete control of and access to someone else's computer from a remote location.

replication The act of sending copies of one database to another database within a network.

report A document that contains a formatted result of a user's query.

resident virus Malware that installs itself or takes residence directly in the main system memory of a computer.

response file A file that holds the specification of a typical Oracle installation for the purpose of creating silent installations.

rogue access point A wireless access point (e.g., wireless router) that is installed within a

company's wireless range without authorization, exposing the entire network and leaving it open for anyone and everyone to navigate.

role A set of related privileges that are combined to provide a centralized unit from which to manage similar users or objects of a database.

row (record, tuple) The component of a table that holds distinct units of data identified using unique strings of numbers or characters.

script kiddie Amateur cracker who uses programs and scripts written by other people to infringe upon a computer network system's integrity.

secondary (alternative) key A field with values that contains nonunique data and that can refer to several records at one time.

secondary data file An optional data file found within a SQL Server database that is not a primary data file.

security audit The procedures by which all of an environment's security controls and systems are thoroughly reviewed to identify and report weaknesses within an organization.

security policy A document that defines the overall goal of security and identifies the scope of what to secure, as well as the roles and responsibilities of the people within the organization.

security scope This defines the perimeter of the overall security assessment, the physical and logical area included within the assessment.

security testing The process of identifying the feasibility and impact of an attack or intrusion of a system by simulating active exploitation and executing potential attacks within that environment.

service ticket A unique key that is used to validate a person's identification (similar to a driver's license), for the purpose of gaining access into a secured environment.

shared site agreement An arrangement between companies with similar, if not identical, data centers.

signature A pattern of characters that is identified for a specific family of viruses.

silent installation An installation of an application that completes without prompting a user for setting specifications.

social engineer An individual who uses human interaction to manipulate people into gaining access to systems, unauthorized areas, and confidential information.

software upgrade A combination of a number of software or hardware packages that creates a new version of software.

sort (control) key A field in which values are used to sequence data.

source code A group of statements or functions written using a specific programming language and that are combined to create a specific type of application or utility.

source code installation Allows a user to download the actual MySQL source code, change it, and compile it into a binary file for installation execution.

spoofing A process that involves hackers building Web sites to look identical to other popular sites in hopes of drawing in a user.

spyware A general term for any software that intentionally monitors and records a user's computer and/or Internet activities.

SQL injections Methods by which intruders use bits of SQL code and SQL queries to gain database access.

startup page The Web site that is displayed when the Web browser is started.

static analysis An effort to find problems while the program is inactive.

static SQL statement A statement that is built by the user; the full text of the statement is known at compilation.

storage engine A component of the MySQL database architecture that reads and writes data to and from the database and offers services to enable customization of an environment.

storage management A term that refers to the process of storing and retrieving data throughout the database.

System Global Area (SGA) The central area where all shared data and processes are stored, including information shared by users and database processes.

table One of the most basic units of storage within a database, typically representing unique and specific data objects.

Tabular Data Stream (TDS) A Microsoft-defined protocol that describes the specifications as to how the SQL Server and a client can communicate.

thread A process that runs independently from another process. It utilizes a portion of the CPU and contains tasks or executions that share the same resources, yet run independently from one another.

time bomb (time-delayed virus) Malware that can lie dormant until a specific variable is met, such as times, days, or specific days that are predetermined and written within its code.

transaction The group of statements or operations processed by a database to execute a user's request to update or change the database.

transaction manager A component of the MySQL database architecture that is responsible for avoiding and resolving deadlocks and corrupted data.

transmission packet Sensitive information about users or businesses compiled by spyware that is sent back to its original creators for use as they see fit.

Trojan (Trojan horse) Malware that disguises itself and its harmful code and often hides within enticing programs such as software updates, games, and movies.

update A change to a system that is added to software or firmware that is already installed on a network.

update management policy A document that includes procedures for patch updates, software upgrades, OS upgrades, and firmware changes.

upgrade Replacements for older versions of software or firmware.

user-defined filegroup A collection of files created by a user.

user profile A set of rules that limits a user's access to database resources, and can be used to set password restrictions as well.

virtual address space The complete virtual memory area allotted to a program.

virtual memory A technique for extending the availability of memory by which units of storage located on different memory devices are used to store data from one entity in such a way that it appears as though the data has been stored in one continuous block of the same memory.

warm site A facility that contains the basic environmental concerns, as well as computers, connection firmware, and software devices necessary to rebuild a network system.

Web applications Programs that are available on a network and provide a way for users to interact with remote systems or databases.

Web browser An application that acts as a user interface of the Internet, allowing users to interact and view Web pages on the World Wide Web.

Web page A document containing a specific programming language (e.g., HTML or JAVA) that is designed to be viewable on the World Wide Web.

white box testing (targeted testing) An assessment that is conducted by an intruder who already has information about the system or the infrastructure. It is also known as targeted testing because prior knowledge exists and known weaknesses within the infrastructure allow for intruders to focus on specific areas of the infrastructure. The goal is to assess the damage that can be done by users who understand the infrastructure that they are attempting to intrude; the results will provide a more comprehensive, thorough picture of specific system weakness than that found in black box testing.

white hat An ethical hacker; hackers who use their extensive experience and knowledge to test systems and provide security consultation to others.

Windows Authentication mode A form of authentication that allows only Windows authentication to be used for accessing the database; those users logging in to the database must have a Windows login to access it.

Wired Equivalent Privacy (WEP) crackers

Software applications that are used to decrypt WEP keys.

wireless scanners Utilities that identify vulnerabilities within a wireless network, including missing encryption keys and poor security measures.

word blocking The act of blocking keywords that are not allowed to be used as input within a Web application or a Web URL.

word filtering A balance of blocking those known keywords that are not allowed to be used as input within a Web application or Web URL, and identifying those keywords that are allowed to be used as input within a Web application or Web URL.

worker process A pool of either threads or fibers that SQL Server keeps for all user connections.

worm Self-replicating malware that is able to harness the power of networks and use this power in its attacks against them.

A

ABCConsulting, 272
 access control, auditing, 252
 access points, rogue, 271
 account administration, auditing, 251–252
 Account Provisioning page, 135
 Active Data Guard application, Oracle, 155
 active reconnaissance, 268–269, 276
 activity, auditing, 253
 Add node to a SQL Server failover cluster link, 127
 Add Port option, 86
 administrator account, 205
 Advanced Cluster Completion link, 128
 Advanced Cluster Preparation link, 128
 Advanced Compression application, Oracle, 154
 advanced page, installing Microsoft SQL Server, 128
 Advanced Replication tool, 153
 Advanced Security Option, 154
 Advanced Security service, 179
 Advanced settings, Windows, 86
 adware, 20, 35
 alert of events, 196
 Allow program through Windows Firewall option, 86
 Allow the connection it is secure option, 87
 alpha phase, 81
 alternate key, 47, 71, 73
 amazon.com, 203
 Analysis Services Configuration window, 135, 136
 Analysis Services (SSAS), 123
 architecture, of Microsoft SQL Server, 65–66
 Archive storage engine, 64
 assessment phase of security architecture, 25
 attachments, e-mail, 15–16
 attributes, 50, 71
 audit scope, 245, 257

auditing, 241–259
 access control, 252
 account administration, 251–252
 activity, 253
 data privileges, 252
 encryption, 253
 overview, 244–245
 passwords, 252
 planning for, 249–251
 process of, 245–249
 reporting on, 253–254
 server maintenance, 251
 types of, 243–244
 vendor-specific information, 254–257
 Microsoft SQL Server, 254
 MySQL, 256–257
 Oracle, 254–255
 authentication, 175–183
 database authentication, 176
 for Microsoft SQL Server, 178
 for MySQL, 178–179
 network authentication, 176–178
 operating system
 authentication, 176
 for Oracle, 179
 password policies, 179–183
 database-enforced, 180
 for Microsoft SQL Server, 182
 for MySQL, 182
 for Oracle, 182–183
 written, 180–182
 third-party authentication, 176–178
 authorization, 183–192
 adding and removing users, 185–186
 default user accounts
 for Microsoft SQL Server, 184
 for MySQL, 185
 for Oracle, 185
 roles, 189–192
 in Microsoft SQL Server, 190–191
 in MySQL, 191
 in Oracle, 192
 user account management, 184

 user privileges, 186–189
 in Microsoft SQL Server, 186–187
 in MySQL, 187–188
 in Oracle, 188–189
 automated audits, 244, 257
 availability, 6–7, 35

B

back door, 22, 35
 backup management plan, 31–32, 35
 beta phase, 80
 binary code installations, 79
 binary file, 79
 Bitmap Indexes feature, 153
 black box testing, 264, 276
 black hat, 8, 35
 Black Hole Engine, 65
 blind injections, 210
 bloggers, 83, 126, 157
 bond parameters, defending against SQL injection, 236
 boot sector, 20, 35
 bot (software robot), 35
 botmaster, 24, 35
 botnet, 24, 35
 browser plug-ins, 207
 brute force attacks, exploiting privileges using, 234
 buffer cache, 68, 69
 buffer management, for Microsoft SQL Server, 69
 buffer manager, 69, 71
 buffer pool, 69, 71
 bug alerts, 84
 BUILT-IN\Administration account, 184
 Business Intelligence Development Studio, 124

C

C Include Files/Lib Files, 89
 caching, 58, 71
 CAL (Client Access License), 124, 143
 CallsRus, 191
 candidate key, 47, 71

case sensitivity, 232
 Case statement, 232
 CD-RW (compact disc-rewritable), 32
 Change Management Pack application, Oracle, 155
 checkpoint (CKPT), 57
 CLDCLL_SALES_ROLE role, 189
 Client Access License (CAL), 124, 143
 Client Tools Connectivity, 124
 clients, 199, 200
 close ports, 167
 CMAN (Oracle Connection Manager), 154
 code, locating vulnerabilities for SQL injection, 212
 cold site, 33, 35
 column field, 71
 Column_Name, 227
 columns, 45, 230–231
 Comma-separated values (CSV), 64
 commit, 56, 71
 common words, breaking down, 232
 Community site, Oracle, 157
 Compact 3.5, 121
 compact disc-rewritable (CD-RW), 32
 compiling, 79
 Complete installation type, 89
 Complete Package, MySQL, 85
 Complete window, 137
 complexity, 169, 180
 components, of databases, 45–48
 keys, 45–47
 queries, 48
 tables, 45
 composite key, 47, 71
 computer security, 5, 35. *See also* security
 computer users, as threats, 9–10
 computer viruses. *See* viruses
 concurrency, 56, 72
 conditions, extracting data with SQL injection using, 228–229
 confidentiality, 6, 36
 Configuration Assistant window, 163

Configuration Management Pack application, Oracle, 155
 configuration security options, 98
 Configure the MySQL Server now check box, Configuration Wizard, 96, 98
 connect to user, 179
 connection context, 69
 connections, encrypting, 108
 control (sort) key, 73
 control file, 58, 72
 control key, 47
 CPU, determining, 150
 crackers, 7–8, 36
 credentials, 175, 197
 CSV (comma-separated values), 64
 current user, 179
 Custom installation screen, 89
 Custom installation type, 89

D

data definition language (DDL), 62
 data flow analysis, locating vulnerabilities for SQL injection, 214
 data manipulation language (DML), 62
 Data Mining application, Oracle, 154
 Data Profiling and Quality application, Oracle, 154
 Data Security Standard (DSS), 40
 data structures, system-level, 68
 data type errors, 227
 database, 72
 database administrator (DBA), 250
 database authentication, 176
 Database Configuration Assistant (DBCA), 149, 255
 database connection manager, 61–62, 72
 Database Engine Configuration window, 135, 136
 Database Engine Services, 122
 database link, 179, 197
 database management system (DBMS), 44, 72, 248
 database model, 48, 72
 database response, 223
 database security, 4–5, 36, 167
 Database Vault application, 154
 database-enforced password policies, 180
 databases, 43–76
 components of, 45–48
 keys, 45–47
 queries, 48
 tables, 45
 defending against SQL injection
 by restricting databases, 236
 using security-conscious design of, 236–237
 defined, 44
 environment policies, 27–35
 backup management plan, 31–32
 disaster plan, 33–35
 security policies, 27–28
 update and upgrade management, 28–31
 management systems for, 54–55
 Microsoft SQL Server, 65–71
 architecture and engines, 65–66
 installing, 113–144
 memory management for, 67–69
 physical structure of, 66
 models for, 48–53
 flat model, 48–49
 hierarchical model, 49–50
 network model, 50
 object-oriented databases, 51–52
 object-relational database, 53
 relational database, 50–51
 MySQL, 60–71
 database connection manager, 61–62
 installing, 77–111
 query engine, 62
 storage engine, 63–65
 storage management, 63
 transaction manager, 62–63
 Oracle, 57–60
 installing, 145–172
 instance and database, 57–58

- memory structure of, 58–60
- physical structure of, 58
- query management in, 55–56
- read consistency in, 55–56
- relationships in, 53–54
- restricting access to, 108
- types of, 54
- datafile, 58, 72
- data-sending Trojan, 23, 36
- DBA (database administrator), 250
- DBCA (Database Configuration Assistant), 149, 255
- DBMS (database management system), 44, 72, 248
- DDL (data definition language), 62
- deadlock, 56, 72
- decision support system (DSS), 54
- Dedicated MySQL Server Machine option, 100
- Dedicated option, 100
- default user accounts
 - for Microsoft SQL Server, 184
 - for MySQL, 185
 - for Oracle, 185
- denial of service (DoS) attacks, 22, 36
- denying privileges, 186
- deployment phase of security architecture, 26–27
- design phase of security architecture, 25–26
- destructive Trojan, 23, 36
- detailed configuration type, Configuration Wizard, 95, 98
- Developer Edition, 121
- Developer option, 99
- Diagnostic Pack application, Oracle, 155
- differential backup, 32, 36
- digital certificate, 177, 197
- digital signatures, 85, 110
- digital versatile discs (DVD), 32
- disaster plan, 33–35, 36
- Disk Space Requirements Window, 133
- disregard for company policy error, 9
- distribution formats, for MySQL, 79–80
- dll (dynamic link library), 67

- DML (data manipulation language), 62
- DNS (Domain Name Server), 14, 36
- DoS (denial of service) attacks, 22, 36
- downloading MySQL, 84–85
- DSS (Data Security Standard), 40
- DSS (decision support system), 54
- DVD (digital versatile disc), 32
- dynamic analysis, 212, 215
- dynamic link library (dll), 67
- dynamic SQL statement, 204, 215

E

- Edition Upgrade link, 127
- editions
 - of Microsoft SQL Server, 121–122
 - of MySQL, 80–82
 - of Oracle, 152–154
- e-mail, 15–17
 - attachments, 15–16
 - embedded HTML in, 17
 - exploiting privileges using, 235
 - phishing with, 16
- embedded HTML, in e-mail, 17
- employees, defining roles of, 28
- Enable TCP/IP Networking check box, 102
- encoding, 232
- encryption, 18, 36, 108, 168, 253
- End User License Agreement, 87
- engines, for Microsoft SQL Server, 65–66
- Enterprise Edition, 121, 153, 154–155, 156
- entities, 50, 72
- Error and Usage Reporting window, 137
- errors, vulnerabilities for SQL injection through, 208–211
- Essentials Package, MySQL, 85
- executable (exe), 67
- expired passwords, 169, 180
- exploitation, 221, 238. *See also* SQL injection
- Express Edition (XE), 152, 155
- external audits, 244, 257
- external testing, 265, 276

- extracting data with SQL injection, 225–232
 - advanced techniques for, 231–232
 - large-scale, 229–231
 - obtaining columns, 230–231
 - obtaining database names, 230
 - obtaining table names, 230
 - statement exploits, 225–232
 - using conditions, 228–229
 - using UNION, 226–227

F

- failed attempts, 169, 180
- Falcon Engine, 65
- Fast Start Fault Recovery feature, 153
- Feature Selection window, 130, 133
- Federated storage engine, 64
- fibers, 69, 72
- fields, 45
- file transfer protocol (FTP) Trojan, 23, 36
- filegroups, 66, 72
- file-infected viruses, 21, 36
- Fine Grained Access Control feature, 153
- firewalls, 167, 272
- fixed database roles, 190–191
- Fixed privileges, 186
- fixed server roles, 190
- flat model, 48–49, 72
- Folder Name field, 89
- foreign key, 46–47, 72
- formal audits, 244, 257
- Forums, Microsoft SQL, 126
- free downloads, of Oracle, 157
- FTP (file transfer protocol) Trojan, 23, 36
- full backup, 32, 36

G

- General Availability (GA), 80
- General Public License (GPL), 79
- glibc2.3 library, 94
- GNU gunzip, 93
- GNU tar, 93
- GnuPG (Gnu Privacy Guard), 85
- goals, for policies, 28

GPL (General Public License), 79
 GRANT command, 188
 grantable privileges, 233
 granting privileges, 186
 graphical user interface (GUI), 124
 grey hat, 8, 36
 Guest user, 184
 GUI (graphical user interface), 124
 .gz format, 94

H

-h option, 95
 hackers, 7–8, 36
 hactivist, 8, 36
 handling noncompliance, 28
 hard disk space, 149
 Hardware and Software Requirements link, 126
 hardware requirements
 for Microsoft SQL Server, 115–119
 for Oracle, 149–150
 Health Information Technology for Economic and Clinical Health (HITECH), 40
 Health Insurance Portability and Accountability Act (HIPAA), 6, 36
 help
 for Microsoft SQL Server, 125–126
 for MySQL, 83–84
 for Oracle, 157–158
 hierarchical model, for databases, 49–50
 hijacking, 11, 36
 HIPAA (Health Insurance Portability and Accountability Act), 6, 36
 HITECH (Health Information Technology for Economic and Clinical Health), 40
 honeypot, 237, 238
 hot site, 33, 37
 How to Get Started with SQL Server 2008 Failover Clustering link, 127
 HTML (HyperText Markup Language), 11, 203

HTTP (hypertext transfer protocol), 13, 37
 HTTP actions, 206–207
 HyperText Markup Language (HTML), 11, 203
 hypertext transfer protocol (HTTP), 13, 37

I

ibdata1 file, 101
 IE (Internet Explorer), 14
 If statement, 232
 inappropriate disclosure, 9
 incremental backup, 32, 37
 inference, 193–197
 examples of, 193–194
 minimizing, 194–197
 informal audits, 243, 257
 information reconnaissance, 268–269, 276
 Information_schema, 233
 Information_Schema.Columns, 227
 Information_Schema.Tables, 227
 initiated delays, 228
 injection attack, SQL, 235
 injection defense, SQL, 235
 injections, SQL, 202, 215
 In-Memory Database Cache application, Oracle, 154
 InnoDB storage engine, 64
 InnoDB tablespace, 101
 Install As Windows Service option, Configuration Wizard, 96, 104
 Install Upgrade Advisor link, 127
 installation page, installing Microsoft SQL Server, 127
 Install-based configuration file link, 128
 Installed SQL Server features discovery report link, 127
 installing
 Microsoft SQL Server, 126–128
 advanced page, 128
 installation page, 127
 maintenance page, 127
 options page, 128
 resources page, 128
 server installation center, 126–127

 step-by-step instructions, 128–139
 tools page, 127
 MySQL
 on UNIX, 93–96
 on Windows, 85–86, 87–92
 Oracle
 on UNIX, 166
 on Windows, 158–165
 instance, 57–58, 72
 Instance Configuration window, 133
 instant messages, as threats, 17
 Integrated Services (SSiS), 123, 143
 integrity, 6, 37
 internal audits, 244, 257
 internal security controls, 244, 257
 internal testing, 264, 276
 Internet, 10–15
 Web browsers, 13–15
 Web pages, 11–12
 Internet Explorer (IE), 14
 Internet Protocol (IP), 14
 Internet relay chat (IRC), 23
 intrusion, process of, 273
 IP (Internet Protocol), 14
 IP addresses, 108, 167
 IRC (Internet relay chat), 23

K

KDC (Key Distribution Center), 177
 Kerberos, 176, 197
 Key Distribution Center (KDC), 177
 key logger, 270, 276
 keys, 45–47, 72
 foreign key, 46–47
 primary key, 46
 Knowledge Center, Oracle, 157

L

Label Security application, 154
 Launch the MySQL Server automatically option, Configuration Wizard, 96, 104
 layers of security
 computer security, 5
 database security, 4–5
 network security, 5

- lexical analysis, locating vulnerabilities for SQL injection, 214–215
- LGWR (log writer), 57
- licensing options
 - for Microsoft SQL Server, 124–125
 - for Oracle, 155–156
- Licensing Terms window, 132
- locks, 56, 72
- log cache, 69
- log file, 66, 72
- log writer (LGWR), 57
- logic bombs, 19, 37
- logic inference, 193–194
- login, 175, 197
- Look In list arrow, 89

M

- m2 suffix, 81
- macro, 20, 37
- mailing lists, MySQL, 83
- main memory, 150
- maintenance page, installing
 - Microsoft SQL Server, 127
- malicious software, 11–12, 37
- malware, 11–12, 18–24, 37
 - Bots, 24
 - computer viruses, 18–21
 - Trojan viruses, 22–24
 - worms, 21–22
- management
 - phase of security architecture, 27
 - policies, updating, 28
 - systems for databases, 54–55
 - tools for Microsoft SQL Server, 123–124
 - of user accounts, 184
- Manual Setting, 102
- many-to-many relationship, 54
- Materialized View feature, 153
- MD5 Checksum, 84
- MDAC (Microsoft Data Access Components), 120
- media type, choosing, 31
- memory pool, for Microsoft SQL Server, 68–69
- Memory storage engine, 64
- memory structure
 - of Microsoft SQL Server, 67–69
 - buffer management, 69

- executable code, 67–68
- memory pool, 68–69
- threads and processes, 69–71
- of Oracle, 58–60
- PGA, 59–60
- processes, 60
- SGA, 59
- memory target, 69, 72
- Metalink account, 160
- Metalink service, 157
- Microsoft Data Access Components (MDAC), 120
- Microsoft Online Books*, 125
- Microsoft SQL Forums, 126
- Microsoft SQL release notes, 126
- Microsoft SQL Server, 55, 65–71, 113–144
 - architecture and engines, 65–66
 - auditing, 254
 - authentication for, overview, 178
 - default user accounts for, 184
 - editions of, 121–122
 - features of
 - licensing options, 124–125
 - management tools, 123–124
 - server tools, 122–123
 - help for, 125–126
 - installing, 126–128
 - advanced page, 128
 - installation page, 127
 - maintenance page, 127
 - options page, 128
 - resources page, 128
 - server installation center, 126–127
 - step-by-step instructions, 128–139
 - tools page, 127
- memory management for, 67–69
 - buffer management, 69
 - executable code, 67–68
 - memory pool, 68–69
 - threads and processes, 69–71
- password policies for, 182
- physical structure of, 66
- preinstallation preparation, 115
- requirements for, 115–119
- roles in, 190–191

- security suggestions for, 140–142
 - after installation, 141–142
 - during installation, 140–141
 - prior to installation, 140
 - software prerequisites, 120
 - supported platforms, 119
 - user privileges in, 186–187
- Microsoft Windows Installer (MSI), 87
- misleading applications, 15, 37
- Mixed Mode Authentication, 135, 178, 197
- models, for databases, 48–53
 - flat model, 48–49
 - hierarchical model, 49–50
 - network model, 50
 - object-oriented databases, 51–52
 - object-relational database, 53
 - relational database, 50–51
- monitoring, defending against SQL injection with, 237–238
- MSI (Microsoft Windows Installer), 87
- Multifunctional option, 100
- multipartite viruses, 21, 37
- multiple layers of security
 - computer security, 5
 - database security, 4–5
 - network security, 5
- my.cnf file, 95, 106
- my.ini file, 95, 98, 104
- MyISAM storage engine, 64
- MySQL, 55, 60–71, 77–111
 - auditing, 256–257
 - authentication for, overview, 178–179
 - database connection manager, 61–62
 - default user accounts for, 185
 - downloading, 84–85
 - editions of, 80–82
 - forums for, 83
 - help for, 83–84
 - manual for, 83
 - password policies for, 182
 - preinstallation preparation, 79–84
 - query engine, 62
 - roles in, 191
 - security suggestions for, 107–109

- account access and user privileges, 108
- network connection
 - administration, 108–109
 - passwords, 108
- storage engine, 63–65
- storage management, 63
- supported platforms, 83
- transaction manager, 62–63
- on UNIX
 - configuring, 106–107
 - installing tar.gz, 93–94
 - installing, 93–96
 - installing binary distributions, 93
 - installing RPM, 94–95
- user privileges in, 187–188
- on Windows
 - adding MySQL port in Windows 7, 86–87
 - adding MySQL port in Windows Vista, 86
 - configuring, 95–107
 - installing, 85–86, 87–92
- mysql_install_db file, 106, 107
- mysql.user table, 234

N

- Name text field, 87
- Native Mode type, 137
- network and database
 - administrators, as threats, 10
- network authentication, 176–178
- network connection
 - administration, for MySQL, 108–109
- network database model, 50, 72
- network errors, 9
- network model, for databases, 50
- network port scanners, 270, 276
- network resource requirements
 - for Microsoft SQL Server, 120
 - for Oracle, 152
- network security, 5, 37
- network sniffers, 268, 270, 276
- New Inbound Rule Wizard
 - dialog box, 87
- New SQL Server failover cluster
 - installation link, 127
- new target, testing, 22
- Noinstall Archive, MySQL, 86

- noncompliance, handling, 28
- non-platform-specific category, RPM package, 94
- nonresident virus, 19, 37
- Non-Transactional option, 100
- Not Configured type, 137
- nothing returned, 225
- null, 227

O

- objectives
 - of security, 5–7
 - availability, 6–7
 - confidentiality, 6
 - integrity, 6
 - of testing, 265
- object-oriented databases, 51–52
- object-relational database, 53
- OFA (Optimal Flexible Architecture), 149
- OLAP (online analytical processing), 54, 72, 123
- OLTP (online transaction processing), 54, 72
- one-to-many relationship, 53
- one-to-one relationship, 53
- online analytical processing (OLAP), 54, 72, 123
- Online Index Rebuild feature, 153
- Online Installation Help link, 127
- online intruders, types of, 8
- Online Release Notes link, 126
- online transaction processing (OLTP), 54, 72
- open source, 55, 72
- opening unknown e-mails error, 9
- OPENROWSET procedure, exploiting privileges using, 235
- operating system (OS), 18, 167
 - authentication, 176
 - requirements
 - for Microsoft SQL Server, 119
 - for Oracle, 150
 - upgrades, 31, 37
- operational information security, 27, 37
- OPQ (Oracle Parallel Query), 153
- Optimal Flexible Architecture (OFA), 149
- optimization, 56, 73
- options page, installing
 - Microsoft SQL Server, 128
- Oracle, 57–60, 145–172
 - auditing, 254–255
 - authentication for, overview, 179
 - default user accounts for, 185
 - editions of, 152–154
 - Enterprise Edition options, 154–155
 - free downloads of, 157
 - help for, 157–158
 - instance and database, 57–58
 - licensing options, 155–156
 - memory structure of, 58–60
 - PGA, 59–60
 - processes, 60
 - SGA, 59
 - OUI for, 158
 - password policies for, 182–183
 - physical structure of, 58
 - preinstallation preparation, 147–149
 - requirements for, 149–152
 - 64-bit and 32-bit, 150–151
 - hardware requirements, 149–150
 - network resource requirements, 152
 - operating system requirements, 150
 - software requirements, 151
 - roles in, 192
 - security suggestions for, 166–170
 - checklist, 167–168
 - password policies and user accounts, 168–170
 - using Oracle security suite, 168
 - on UNIX, installing, 166
 - user privileges in, 188–189
 - on Windows, installing, 158–165
- Oracle Active Data Guard application, 155
- Oracle Advanced Compression application, 154

- Oracle Change Management Pack application, 155
- Oracle Community site, 157
- Oracle Configuration Management Pack application, 155
- Oracle Connection Manager (CMAN), 154
- Oracle Data Guard feature, 153
- Oracle Data Mining application, 154
- Oracle Data Profiling and Quality application, 154
- Oracle Database Standard Edition One (SEO), 152, 156
- Oracle Database Standard Edition (SE), 153, 156
- Oracle Diagnostic Pack application, 155
- Oracle In-Memory Database Cache application, 154
- Oracle Knowledge Center, 157
- Oracle OLAP application, 155
- Oracle Parallel Query (OPQ), 153
- Oracle Partitioning application, 155
- Oracle patches, 167
- Oracle Provisioning and Patch Automation Pack application, 155
- Oracle RAC One Node application, 154
- Oracle Real Application Clusters (RAC), 154
- Oracle Real Application Testing application, 155
- Oracle security suite, 168
- Oracle Spatial application, 155
- Oracle Streams feature, 154
- Oracle Total Recall application, 155
- Oracle Tuning Pack application, 155
- Oracle University Installer (OUI), 158
- Oracle University site, 157
- oraInstRoot.sh file, 166
- OS. *See* operating system
- OUI (Oracle University Installer), 158
- OUI welcome screen, 160

P

- pagefile, 67, 73
- pages, 67, 73
- Parallel Backup and Recovery feature, 154
- Parallel DML feature, 153
- Parallel Index Scans feature, 154
- Parallel Indexing Rebuilding feature, 154
- parallel processing, 56, 73
- parsing, 56, 73
- Partitioning application, Oracle, 155
- passive reconnaissance, 268, 276
- password discretion, 181
- password error, 9
- password hash, 233, 238
- Password Management, 164, 166
- password policies, 179–183
 - database-enforced, 180
 - for Microsoft SQL Server, 182
 - for MySQL, 182
 - for Oracle, 182–183
 - written, 180–182
- password scanners, 270, 277
- passwords
 - auditing, 252
 - exploiting, 233–234
 - reuse of, 180
 - sharing, 181
 - storing, 181
- patch, 30, 37, 167
- payload, 22, 37
- Payment Card Industry (PCI), 40
- Per Processor Licensing, 124
- Per Server Plus Device CAL license, 124
- Per Server Plus User CAL license, 124
- performance monitor (PMON), 57
- personal identifiable information (PII), 14, 37
- PGA (Process Global Area), 57, 58, 59–60, 73
- phases of security architecture
 - assessment, 25
 - deployment, 26–27
 - design, 25–26
 - management, 27
- phishing, 16, 37
- physical structure
 - of Microsoft SQL Server, 66
 - of Oracle, 58
- PII (personal identifiable information), 14, 37
- PKI (public key infrastructure), 177
- planning
 - for auditing, 249–251
 - for testing, 266–267
- platform-specific category, RPM package, 94
- platforms, 83, 119, 223
- PMON (performance monitor), 57
- point of sales (POS) system, 54, 73
- policies, for database environment, 27–35
 - backup management plan, 31–32
 - disaster plan, 33–35
 - security policies, 27–28
 - update and upgrade management, 28–31
- polymorphism, 19, 37
- poor habits, network error, 9
- port addresses, 271
- Port Number text field, 87
- port redirection, 272
- ports, 86–87, 108
- POS (point of sales) system, 54, 73
- primary data file, 66, 73
- primary filegroup, 66, 73
- primary key, 46, 73
- principle of least privilege, 186, 198
- privileges, 186–189
 - auditing, 252
 - exploiting, 232–235
 - automated tools, 234–235
 - brute force attacks, 234
 - using e-mail, 235
 - using OPENROWSET procedure, 235
 - in Microsoft SQL Server, 186–187
 - in MySQL, 187–188
 - in Oracle, 188–189

procedure cache, 69
 process, 60, 73
 Process Global Area (PGA), 58, 59–60, 73
 processes
 identifying, 28
 for Microsoft SQL Server, 69–71
 for Oracle, 60
 processors, 156
 procrastination, 9
 Product Key window, 132
 Program Global Area (PGA), 57
 programming language, 79, 110
 programs, 233
 Provisioning and Patch
 Automation Pack
 application, Oracle, 155
 proxy servers, 207
 proxy Trojan, 23, 37
 public key infrastructure (PKI), 177

Q

queries, components of
 databases, 48
 query cache, 62, 73
 query engine, 62, 73
 query management, 55–56, 73
 query responses, limiting, 196

R

RAC (Oracle Real Application Clusters), 154
 RAC One Node application, Oracle, 154
 random access memory (RAM), 19, 150
 RAT (Remote access and administration Trojan), 23, 38
 RC (Release Candidate), 80
 RDBMSs (Relational Database Management Systems), 51, 54
 read consistency, 55–56, 73
 Real Application Testing
 application, Oracle, 155
 RECO (recovered), 57
 records, 45
 recovered (RECO), 57

redo log, 58, 73
 relational database, 50–51, 73
 Relational Database
 Management Systems
 (RDBMSs), 51, 54
 relational engine, 66
 relationships, 50, 53–54, 73
 Release Candidate (RC), 80
 release notes, Microsoft SQL, 126
 Remote access and
 administration Trojan
 (RAT), 23, 38
 remote access, disabling, 108
 Remove node to a SQL Server
 failover cluster link, 127
 removing user accounts,
 185–186
 Repair link, 127
 replication, 122, 143
 reporting
 on auditing, 253–254
 on testing, 274–276
 Reporting Services Configuration
 window, 137
 Reporting Services (SSRS), 122
 reports, 48, 73
 requirements
 for Microsoft SQL Server,
 115–119
 for Oracle, 149–152
 64-bit and 32-bit, 150–151
 hardware requirements,
 149–150
 network resource
 requirements, 152
 operating system
 requirements, 150
 software requirements, 151
 residence, 19
 resident virus, 19, 38
 resources page, installing
 Microsoft SQL Server, 128
 response file, 171
 restricting access to databases,
 with IP addresses, 108
 results returned, 224
 reused passwords, 169
 reverse Telnet, 272
 revoking privileges, 186
 rogue access point, 277
 roles, 189–192

in Microsoft SQL Server,
 190–191
 in MySQL, 191
 in Oracle, 192
 root commands, 94
 root.sh file, 166
 Row Level Security feature, 153
 rows, 45
 .rpm format, 94
 run time, restricting, 167
 ./runInstaller.sh file, 166

S

SA account, 184
 SALES_DEPTAPP_ROLE role,
 189
 sanitizing data, 236
 Sarbanes-Oxley Act (SOX), 40
 scope boundary, 267
 script kiddie, 8, 38
 scripting language, 222
 SE (Oracle Database Standard
 Edition), 153, 156
 Search for product updates link,
 127
 secondary (alternative) key, 73
 secondary data file, 66, 73
 secondary key, 47
 security
 architecture of, 24–27
 assessment and analysis, 25
 deployment, 26–27
 design, 25–26
 management and support, 27
 objectives of, 5–7
 availability, 6–7
 confidentiality, 6
 integrity, 6
 reasons for, 3–7
 threats against, 7–17
 computer users, 9–10
 e-mails, 15–17
 hackers, 7–8
 instant messages, 17
 Internet, 10–15
 malware, 18–24
 misleading applications, 15
 network and database
 administrators, 10
 social engineers, 9
 tweets, 17

- security audits, 243, 257, 263
 - Security Documentation link, 126
 - security patches, 167
 - security policies, 27, 38
 - security scope, 266, 277
 - security testing, 277
 - SELECT @@VERSION command, 224
 - SELECT statement, 227
 - self-encryption, 18
 - Send Windows and SQL Server Error Reports to Microsoft or your corporate report server option, 137
 - SEO (Oracle Database Standard Edition One), 152, 156
 - Server Books Online, SQL, 125
 - Server Configuration Manager, SQL, 123
 - Server Express Edition, SQL, 121
 - server maintenance, auditing, 251
 - Server Management Studio, SQL, 124
 - Server option, 100
 - Server Profiler, 124
 - server tools, for Microsoft SQL Server, 122–123
 - Service Accounts window, 133
 - service ticket, 177, 198
 - Setup Wizard exit screen, 99
 - setup.exe file, 87
 - SGA (System Global Area), 57, 58, 59, 74
 - shared site agreements, 33, 38
 - SharePoint Integrated Mode type, 137
 - SID (System Identifier), 164
 - signatures, 18, 38
 - silent installation, 158, 171
 - Single statement privileges, 186
 - SMON (system monitor), 57
 - social engineering, 269
 - social engineers, 9, 38
 - software requirements
 - for Microsoft SQL Server, 120
 - for Oracle, 151
 - software robot (bot), 35
 - software upgrades, 30, 38
 - sort (control) key, 73
 - sort key, 47
 - source code, 79, 110
 - source code installations, 79, 110
 - SOX (Sarbanes-Oxley Act), 40
 - Spatial application, Oracle, 155
 - spoofing, 12, 38
 - spyware, 19, 38
 - SQL (Structured Query Language), 48
 - SQL CAL, 124
 - SQL injection, 201–238
 - defending against, 235–238
 - diligent monitoring, 237–238
 - restricting databases, 236
 - sanitizing data, 236
 - security-conscious database design, 236–237
 - using bond parameters, 236
 - exploiting privileges and passwords, 232–235
 - identifying privileges, 232–233
 - obtaining passwords, 233–234
 - obtaining privileges, 234–235
 - extracting data with, 225–232
 - advanced techniques for, 231–232
 - large-scale, 229–231
 - statement exploits, 225–232
 - using conditions, 228–229
 - using UNION, 226–227
 - identifying vulnerabilities for, 205–215
 - data flow analysis, 214
 - direct testing, 212
 - and HTTP actions, 206–207
 - inferential testing for, 205–206
 - lexical analysis, 214–215
 - string-based matching, 213
 - through errors, 208–211
 - using code for locating, 212
 - information gathering for, 221–225
 - about database, 222
 - identifying vendor, 222–224
 - identifying version, 224–225
 - overview, 202–205
 - SQL Server, 65
 - SQL Server Books Online, 125
 - SQL Server Configuration Manager, 123
 - SQL Server Express Edition, 121
 - SQL Server Management Studio, 124
 - sql_logins table, 234
 - SSAS (Analysis Services), 123
 - SSH encryption, 108
 - SSiS (Integrated Services), 123, 143
 - SSL encryption, 108
 - SSRS (Reporting Services), 122
 - Standard Character Set option, 102
 - standard configuration,
 - Configuration Wizard, 95
 - Standard Configuration option,
 - Configuration Wizard, 96
 - Standard Edition, 121
 - startup page, 14, 38
 - statement exploits, 225–232
 - static analysis, 212, 215
 - static SQL statement, 204, 215
 - statistical inference, 194
 - stealth, 18
 - storage engines, 63–65, 66, 74
 - storage management, 63, 74
 - storage units, swapping, 67
 - Streams feature, Oracle, 154
 - Strict Mode, 102
 - string-based matching, 213
 - Structured Query Language (SQL), 48
 - swapping units of storage, 67
 - sys.columns, 231
 - System Configuration Checker link, 126, 127, 130
 - System Global Area (SGA), 57, 58, 59, 74
 - System Identifier (SID), 164
 - system monitor (SMON), 57
 - system-level data structures, 68
 - system.mgmt_credentials2.table, 234
 - sysxlogins table, 234
- ## T
- table identification, 231
 - Table_Name, 227
 - tables
 - components of databases, 45
 - obtaining names for data extraction, with SQL injection, 230

Tabular Data Stream (TDS), 65, 74
 TAF (Transparent Application Failover), 153
 .tar format, 94
 target testing, 265, 277
 TCP Protocol, 86
 TDE (transparent data encryption), 140
 TDS (Tabular Data Stream), 65, 74
 technical support, 157
 testing, 261–279
 escalating privileges, 273–274
 information reconnaissance, 268–269
 objectives of, 265
 obtaining access, 269–273
 exploiting network hardware, 271–272
 exploiting operating system, 272–273
 exploiting Web applications, 273
 using automated tools, 269–271
 planning for, 266–267
 reporting on, 274–276
 types of, 264–265
 TFName, 213
 TGS (Ticket-granting service), 177
 TGT (ticket-granting ticket), 177
 third-party applications, 207
 third-party authentication, 176–178
 threads, for Microsoft SQL Server, 69–71
 threats, 7–17
 computer users, 9–10
 e-mails, 15–17
 attachments, 15–16
 embedded HTML in, 17
 phishing with, 16
 hackers, 7–8
 instant messages, 17
 Internet, 10–15
 Web browsers, 13–15
 Web pages, 11–12
 misleading applications, 15
 network and database administrators, 10
 social engineers, 9
 tweets, 17

Ticket-granting service (TGS), 177
 ticket-granting ticket (TGT), 177
 time bomb (time-delayed virus), 19, 38
 time-based responses, 228
 tools page, installing Microsoft SQL Server, 127
 Total Recall application, Oracle, 155
 transaction commits, 56
 transaction manager, 62–63, 74
 Transactional Database Only option, 100
 Transactional option, 100
 transactions, 56, 74
 transmission packet, 19, 38
 Transparent Application Failover (TAF), 153
 transparent data encryption (TDE), 140
 Transportable Tablespaces feature, 153
 Trojan horse, 38
 Trojan viruses, 22–24
 Tuning Pack application, Oracle, 155
 tuples, 45
 tweets, as threats, 17
 Twitter.com, 17, 83, 126, 158
 Typical installation type, 89

U

undo, transaction commits, 56
 Uniform Resource Locator (URL), 12
 UNION statement, 226–227
 units of storage, swapping, 67
 Universal Serial Bus (USB), 9
 University site, Oracle, 157
 UNIX, MySQL on
 configuring, 106–107
 installing tar.gz, 93–94
 installing, 93–96
 installing binary distributions, 93
 installing RPM, 94–95
 update management policy, 38
 updates, 28–31, 38
 Upgrade Documentation link, 127

Upgrade for SQL Server 2000 or SQL Server 2005 link, 127
 Upgrade Integration Services Package link, 127
 upgrades, 28–31, 38
 URL (Uniform Resource Locator), 12
 USB (Universal Serial Bus), 9
 user accounts
 adding and removing, 185–186
 default
 for Microsoft SQL Server, 184
 for MySQL, 185
 for Oracle, 185
 management of, 184
 user capability, limiting, 196
 user profile, 183, 198
 user-defined filegroup, 66, 74
 UserInput, 213
 users, as threats, 9–10

V

–v option, 95
 /var/lib/mysql directory, 95
 versions, 224–225. *See also* editions
 virtual address space, 67, 74
 virtual memory, 67, 74
 Virtual Private Database (VPD), 153
 viruses, 18–21
 categories of, 19–20
 types of, 20–21
 VPD (Virtual Private Database), 153
 vulnerabilities for SQL injection, 205–215
 data flow analysis, 214
 direct testing, 212
 and HTTP actions, 206–207
 inferential testing for, 205–206
 lexical analysis, 214–215
 string-based matching, 213
 through errors, 208–211
 using code for locating, 212

W

warm site, 33, 38
 WBDS (World Bank Database Society), 177
 Web applications, 203, 215

Web browsers, 13–15, 38
Web Edition, 121
Web pages, 11–12, 38
Web sites, 12, 125
WEP (Wired Equivalent Privacy)
 crackers, 271, 277
white box testing, 265, 277
white hat, 8, 38
Windows, MySQL on
 adding MySQL port in
 Windows 7, 86–87
 adding MySQL port in
 Windows Vista, 86
 configuring, 95–107
 installing, 85–86, 87–92

Windows Authentication mode,
 135, 178, 198
Windows Firewall with
 Advanced Security dialog
 box, 86
Wired Equivalent Privacy (WEP)
 crackers, 271, 277
wireless scanners, 270, 277
word blocking, 236, 238
word filtering, 236, 238
worker process, 70, 74
Workgroup CAL, 124
Workgroup Edition, 121
World Bank Database Society
 (WBDS), 177

worms, 21–22, 38
written password policies,
 180–182

X

XE (Express Edition), 152, 155

Y

yahoo.com, 14

Z

.zip format, 94