```
Inferring fsid cd6a42ce-36f6-11ec-8c67-52540000fa0c
Inferring config /var/lib/ceph/cd6a42ce-36f6-11ec-8c67-52540000fa0c/mon.clienta/
config
Using recent ceph image registry.redhat.io/rhceph/rhceph-5-
rhel8@sha256:6306...47ff
[ceph: root@clienta /]# ceph health
HEALTH_OK
```

- 5. Manually add OSDs to the servere node using devices /dev/vde and /dev/vdf. Set 172.25.250.0/24 for the OSD public network and 172.25.249.0/24 for the OSD cluster network.
  - 5.1. Display the servere node storage device inventory on the Ceph cluster. Verify that the /dev/vde and /dev/vdf devices are available.

```
[ceph: root@clienta /]# ceph orch device ls --hostname=servere.lab.example.com
                                                            Size
Hostname
                        Path
                                 Type Serial
Ident Fault Available
servere.lab.example.com /dev/vde hdd
                                       4d212d34-e5a0-4347-9 10.7G Unknown N/A
   N/A
          Yes
                                       d86b1a78-10b5-46af-9 10.7G
servere.lab.example.com /dev/vdf hdd
                                                                   Unknown N/A
   N/A
                                       1880975e-c78f-4347-8
servere.lab.example.com /dev/vdb
                                 hdd
                                                            10.7G
                                                                   Unknown N/A
   N/A
          No
                                       2df15dd0-8eb6-4425-8 10.7G
servere.lab.example.com /dev/vdc
                                 hdd
                                                                   Unknown N/A
   N/A
servere.lab.example.com /dev/vdd hdd
                                       527656ac-8c51-47b2-9 10.7G Unknown N/A
   N/A
          No
```

5.2. Create the OSDs using the /dev/vde and /dev/vdf devices on the servere node.

```
[ceph: root@clienta /]# ceph orch daemon add osd servere.lab.example.com:/dev/vde
Created osd(s) 9 on host 'servere.lab.example.com'
[ceph: root@clienta /]# ceph orch daemon add osd servere.lab.example.com:/dev/vdf
Created osd(s) 10 on host 'servere.lab.example.com'
```

5.3. For the OSD options, set public\_network to 172.25.250.0/24 and cluster\_network to 172.25.249.0/24.

```
[ceph: root@clienta /]# ceph config set osd public_network 172.25.250.0/24
[ceph: root@clienta /]# ceph config set osd cluster_network 172.25.249.0/24
```

5.4. Return to workstation as the student user.

```
[ceph: root@clienta /]# exit
[admin@clienta ~]$ exit
[student@workstation ~]$
```

## **Evaluation**

As the student user on the workstation machine, use the lab command to grade your work. Correct any reported failures and rerun the command until successful.