5.1. Enable the orchestrator service to create OSD daemons automatically from the available cluster devices.

[ceph: root@clienta /]# ceph orch apply osd --all-available-devices Scheduled osd.all-available-devices update...

5.2. Verify the creation of the all-available-devices OSD service.

[ceph: root@clienta /]# o	ceph orch l	.s		
NAME	RUNNING	REFRESHED	AGE	PLACEMENT
alertmanager	1/1	11s ago	13h	count:1
crash	4/4	5m ago	13h	*
grafana	1/1	11s ago	13h	count:1
mgr	4/4	5m ago	13h	
mon	4/4	5m ago	13h	4.750
node-exporter	1/4	5m ago	13h	*
osd.all-available-devices	0/4		10s	*
osd.default_drive_group	9/12	5m ago	13h	server*
osd.unmanaged	2/2	11s ago	-69	<unmanaged></unmanaged>
prometheus	1/1	11s ago	13h	count:1
rgw.realm.zone	2/2	5m ago	8m	

5.3. Verify the existence of new OSDs.

[ce	ph: roc	t@clienta	/]# ceph osd tree			
ID	CLASS	WEIGHT	TYPE NAME	STATUS	REWEIGHT	PRI-AFF
-1		0.19592	root default	*//		
-9		0.04898	host clienta	A		
12	hdd	0.00980	osd.12	up	1.00000	1.00000
16	hdd	0.00980	osd.16	up	1.00000	1.00000
17	hdd	0.00980	osd.17	ир	1.00000	1.00000
18	hdd	0.00980	osd.18	up	1.00000	1.00000
19	hdd	0.00980	osd.19	up	1.00000	1.00000
-3		0.04898	host serverc			
0	hdd	0.00980	osd.0	up	1.00000	1.00000
1	hdd	0.00980	osd.1	up	1.00000	1.00000
2	hdd	0.00980	osd.2	up	1.00000	1.00000
9	hdd	0.00980	osd.9	up	1.00000	1.00000
10	hdd	0.00980	osd.10	up	1.00000	1.00000
-5		0.04898	host serverd			
3	hdd	0.00980	osd.3	ир	1.00000	1.00000
4	hdd	0.00980	osd.4	up	1.00000	1.00000
5	hdd	0.00980	osd.5	ир	1.00000	1.00000
11	hdd	0.00980	osd.11	ир	1.00000	1.00000
14	hdd	0.00980	osd.14	up	1.00000	1.00000
-7		0.04898	host servere			
6	hdd	0.00980	osd.6	up	1.00000	1.00000
7	hdd	0.00980	osd.7	up	1.00000	1.00000
8	hdd	0.00980	osd.8	up	1.00000	1.00000
13	hdd	0.00980	osd.13	up	1.00000	1.00000
15	hdd	0.00980	osd.15	up	1.00000	1.00000