

```

    "id": "93a7f406-0bbd-43a5-a32a-c217386d534b",
    "zonegroups": [
      {
        "id": "2b1495f8-5ac3-4ec5-897e-ae5e0923d0b9",
        "name": "classroom",
        "api_name": "classroom",
        "is_master": "true",
        "endpoints": [
          "http://serverc:80"
        ]
      }
    ]
  },
  "zones": [
    {
      "id": "b50c6d11-6ab6-4a3e-9fb6-286798ba950d",
      "name": "main",
      "endpoints": [
        "http://serverc:80"
      ]
    }
  ]
}

```

...output omitted...

```

    "master_zonegroup": "2b1495f8-5ac3-4ec5-897e-ae5e0923d0b9",
    "master_zone": "b50c6d11-6ab6-4a3e-9fb6-286798ba950d",
    "realm_id": "8ea5596f-e2bb-4ac5-8fc8-9122de311e26",
    "realm_name": "cl260",
    "realm_epoch": 2
  }
}

```

...output omitted...

3.3. Set the cl260 realm and classroom zone group as default.

```

[ceph: root@serverf /]# radosgw-admin realm default --rgw-realm=cl260
[ceph: root@serverf /]# radosgw-admin zonegroup default --rgw-zonegroup=classroom

```

3.4. Create a zone called fallback. Configure the fallback zone with the endpoint pointing to http://serverf:80.

```

[ceph: root@serverf /]# radosgw-admin zone create --rgw-zonegroup=classroom \
--rgw-zone=fallback --endpoints=http://serverf:80 --access-key=replication \
--secret-key=secret --default
{
  "id": "fe105db9-fd00-4674-9f73-0d8e4e93c98c",
  "name": "fallback",
  "system_key": {
    "access_key": "replication",
    "secret_key": "secret"
  }
}

```

...output omitted...

```

    "realm_id": "8ea5596f-e2bb-4ac5-8fc8-9122de311e26",
    "notif_pool": "fallback.rgw.log:notif"
  }
}

```

...output omitted...

3.5. Commit the site configuration.

```

[ceph: root@serverf /]# radosgw-admin period update --commit --rgw-zone=fallback
{
  "id": "93a7f406-0bbd-43a5-a32a-c217386d534b",

```