

4.2. Pull the period configuration from the serverc node.

```
[ceph: root@serverf /]# radosgw-admin period pull --url=http://serverc:80 \
--access-key=replication --secret-key=secret
{
  "id": "7cdc83cf-69d8-478e-b625-d5250ac4435b",
  "epoch": 1,
  "predecessor_uuid": "031c3bfb-6626-47ef-a523-30b4313499d9",
  "sync_status": [],
  "period_map": {
    "id": "7cdc83cf-69d8-478e-b625-d5250ac4435b",
    "zonegroups": [
      {
        "id": "d3524ffb-8a3c-45f1-ac18-23db1bc99071",
        "name": "classroom",
        "api_name": "classroom",
        "is_master": "true",
        "endpoints": [
          "http://serverc:80"
        ],
        "hostnames": [],
        "hostnames_s3website": [],
        "master_zone": "4f1863ca-1fca-4c2d-a7b0-f693ddd14882",
        "zones": [
          {
            "id": "4f1863ca-1fca-4c2d-a7b0-f693ddd14882",
            "name": "us-east-1",
            "endpoints": [
              "http://serverc:80"
            ]
          }
        ]
      }
    ]
  },
  "master_zonegroup": "d3524ffb-8a3c-45f1-ac18-23db1bc99071",
  "master_zone": "4f1863ca-1fca-4c2d-a7b0-f693ddd14882",
  "realm_id": "9eef2ff2-5fb1-4398-a69b-eeb3d9610638",
  "realm_name": "cl260",
  "realm_epoch": 2
}
```

4.3. View the current period id for us-east-2 zone.

```
[ceph: root@serverf /]# radosgw-admin period get-current
{
  "current_period": "7cdc83cf-69d8-478e-b625-d5250ac4435b"
}
```

- 5. On the serverf node, configure the us-east-2 site. Set the cl260 realm and classroom zone group as the defaults and create the us-east-2 zone. Commit the site configuration and review the period id. Update the zone name in the configuration database.

5.1. Set the cl260 realm and classroom zone group as default.