6.7. Review the file-system usage.

```
[root@clientb ~]# df /mnt/rbd
Filesystem     1K-blocks  Used Available Use% Mounted on
/dev/rbd0         123584 18180    105404  15% /mnt/rbd
```

6.8. Review the content of the cluster.

```
[root@clientb ~]# ceph df
--- RAW STORAGE ---
CLASS     SIZE    AVAIL     USED  RAW USED  %RAW USED
hdd     90 GiB   90 GiB  158 MiB   158 MiB       0.17
TOTAL   90 GiB   90 GiB  158 MiB   158 MiB       0.17

--- POOLS ---
POOL                   ID  PGS   STORED  OBJECTS     USED  %USED  MAX AVAIL
...output omitted...
test_pool               6   32  2.5 MiB       14  7.5 MiB      0     28 GiB
```

6.9. Unmount the file system and unmap the RBD image on the `clientb` node.

```
[root@clientb ~]# umount /mnt/rbd
[root@clientb ~]# rbd unmap /dev/rbd0
[root@clientb ~]# rbd showmapped
```

7. Configure the client system so that it persistently mounts the `test_pool/test` RBD image as `/mnt/rbd`.

7.1. Create a single-line entry for `test_pool/test` in the `/etc/ceph/rbdmap` RBD map file. The RBD mount daemon should authenticate as the `test_pool.clientb` user using the appropriate key-ring file. The resulting file should have the following contents:

```
[root@clientb ~]# cat /etc/ceph/rbdmap
# RbdDevice            Parameters
#poolname/imagename     id=client,keyring=/etc/ceph/ceph.client.keyring
test_pool/test
 id=test_pool.clientb,keyring=/etc/ceph/ceph.client.test_pool.clientb.keyring
```

7.2. Create an entry for `/dev/rbd/test_pool/test` in the `/etc/fstab` file. The resulting file should have the following contents:

```
[root@clientb ~]# cat /etc/fstab
UUID=fe1e8b67-e41b-44b8-bcfe-e0ec966784ac /                       xfs     defaults
        0 0
UUID=F537-0F4F          /boot/efi               vfat
 defaults,uid=0,gid=0,umask=077,shortname=winnt 0 2
/dev/rbd/test_pool/test /mnt/rbd                xfs noauto 0 0
```

7.3. Verify your RBD map configuration. Use the `rbdmap` command to map and unmap configured RBD devices.