

```
[ceph: root@clienta ~]# ceph osd dump | grep ratio
full_ratio 0.9
backfillfull_ratio 0.9
nearfull_ratio 0.86
```

10. Locate the host with the OSD 7 service. List that host's available storage devices.

10.1. Locate the OSD 7 service. The location of the OSD 7 service might be different in your lab environment.

```
[ceph: root@clienta ~]# ceph osd find osd.7
{
  "osd": 7,
  "addrs": {
    "addrvec": [
      {
        "type": "v2",
        "addr": "172.25.250.13:6816",
        "nonce": 1160376750
      },
      {
        "type": "v1",
        "addr": "172.25.250.13:6817",
        "nonce": 1160376750
      }
    ]
  },
  "osd_fsid": "53f9dd65-430a-4e5a-a2f6-536c5453f02a",
  "host": "serverd.lab.example.com",
  "crush_location": {
    "host": "serverd",
    "root": "default"
  }
}
```

10.2. Use the `ceph orch device ls --hostname=serverd.lab.example.com` command to list the available storage devices on the located host. Use the host you located in your environment.

```
[ceph: root@clienta ~]# ceph orch device ls --hostname=serverd.lab.example.com
```

Hostname	Path	Type	Serial	Size	Health	Ident	Fault	Available
serverd.lab.example.com	/dev/vde	hdd	65d5b32d-594c-4dbe-b	10.7G	Unknown	N/A	Yes	
serverd.lab.example.com	/dev/vdf	hdd	63124a05-de2b-434f-8	10.7G	Unknown	N/A	Yes	
serverd.lab.example.com	/dev/vdb	hdd	e20fad81-6237-409e-9	10.7G	Unknown	N/A	No	
serverd.lab.example.com	/dev/vdc	hdd	6dad9f98-2a5a-4aa8-b	10.7G	Unknown	N/A	No	
serverd.lab.example.com	/dev/vdd	hdd	880d431d-15f3-4c20-b	10.7G	Unknown	N/A	No	