

```
[ceph: root@serverf /]# radosgw-admin realm default --rgw-realm=cl260
[ceph: root@serverf /]# radosgw-admin zonegroup default --rgw-zonegroup=classroom
```

- 5.2. Create a zone called us-east-2. Configure the us-east-2 zone with an endpoint pointing to `http://serverf:80`.

```
[ceph: root@serverf /]# radosgw-admin zone create --rgw-zonegroup=classroom \
--rgw-zone=us-east-2 --endpoints=http://serverf:80 --access-key=replication \
--secret-key=secret --default
{
  "id": "3879a186-cc0c-4b42-8db1-7624d74951b0",
  "name": "us-east-2",
  "domain_root": "us-east-2.rgw.meta:root",
  "control_pool": "us-east-2.rgw.control",
  ...output omitted...
  "system_key": {
    "access_key": "replication",
    "secret_key": "secret"
  },
  "placement_pools": [
    {
      "key": "default-placement",
      "val": {
        "index_pool": "us-east-2.rgw.buckets.index",
        "storage_classes": {
          "STANDARD": {
            "data_pool": "us-east-2.rgw.buckets.data"
          }
        },
        "data_extra_pool": "us-east-2.rgw.buckets.non-ec",
        "index_type": 0
      }
    }
  ],
  "realm_id": "9eef2ff2-5fb1-4398-a69b-eeb3d9610638",
  "notif_pool": "us-east-2.rgw.log:notif"
}
```

- 5.3. Commit the site configuration.

```
[ceph: root@serverf /]# radosgw-admin period update --commit --rgw-zone=us-east-2
{
  "id": "7cdc83cf-69d8-478e-b625-d5250ac4435b",
  "epoch": 2,
  "predecessor_uuid": "031c3bfb-6626-47ef-a523-30b4313499d9",
  "sync_status": [],
  "period_map": {
    "id": "7cdc83cf-69d8-478e-b625-d5250ac4435b",
    "zonegroups": [
      {
        "id": "d3524ffb-8a3c-45f1-ac18-23db1bc99071",
        "name": "classroom",

```