Unit Testing Output

Section	Test suite	Sub-area	Total test cases	Passed	Failed	Pass %
A	Flutter behavioral (`lets_go/test/*.dart`)	Behavioral + widget tests	18	18	0	100%
B	Flutter generated contracts (`lets_go/test/generated/**`)	Utils contracts	45	45	0	100%
B	Flutter generated contracts (`lets_go/test/generated/**`)	Controllers contracts	59	59	0	100%
B	Flutter generated contracts (`lets_go/test/generated/**`)	Screens contracts	159	159	0	100%
C	Backend pytest (`backend/lets_go/test/**`)	Views + utils + integration smoke	199	199	0	100%
Overall	All	All	480	480	0	100%

Section A: Flutter behavioral tests (`lets_go/test/*.dart`)

Flutter tests (behavioral) — Documentation Table (Part 1)

> Columns: **Test case** = the `group(...)` + `test(...)` name, **Function/Unit under test**, **Input/Setup**, **Expected output**, **Actual output (asserted)**, **Status**

lets_go/test/actual_path_rules_test.dart

Test case	Function/unit under test	Input / setup	Expected output
ActualPathRules.validateActualPathCoversAllStops → returns true when each stop is within threshold of some actual point	`ActualPathRules.validateActualPathCoversAllStops`	`actual` polyline points near stops; `stops` has 2 points; `thresholdMeters: 200`	Returns `true` when each stop is within distance threshold of at least one actual point
ActualPathRules.validateActualPathCoversAllStops → returns false when any stop is not covered	`ActualPathRules.validateActualPathCoversAllStops`	`actual` has 2 points; one stop far away; `thresholdMeters: 150`	Returns `false` if any stop not covered
ActualPathRules.validateActualPathCoversAllStops → returns false when actual polyline has < 2 points	`ActualPathRules.validateActualPathCoversAllStops`	`actual` length = 1; `stops` length = 2	Returns `false` for invalid actual path (<2 points)
ActualPathRules.validateActualPathCoversAllStops → returns false when stops has < 2 points	`ActualPathRules.validateActualPathCoversAllStops`	`actual` length = 2; `stops` length = 1	Returns `false` for invalid stop list (<2 points)
ActualPathRules.shouldExtendActualPathAppendOnly → returns true when current stops start with initial snapshot and new stops appended	`ActualPathRules.shouldExtendActualPathAppendOnly`	`initialStopsSnapshot` = 2 stops; `currentStops` = same 2 + appended stop	Returns `true` if current is **prefix match** of initial and only appended

Test case	Function/unit under test	Input / setup	Expected output
ActualPathRules.shouldExtendActualPathAppendOnly → returns false when a stop is deleted	`ActualPathRules.shouldExtendActualPathAppendOnly`	`initialStopsSnapshot` = 3; `currentStops` = 2 (deleted)	Returns `false` when any initial stop removed
ActualPathRules.shouldExtendActualPathAppendOnly → returns false when order changes (no longer a prefix match)	`ActualPathRules.shouldExtendActualPathAppendOnly`	`initialStopsSnapshot` = [A,B]; `currentStops` = [B,A,C]	Returns `false` if ordering changes (not a prefix)

lets_go/test/create_route_controller_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (
CreateRouteController.loadExistingRouteData → loads planned points, names, routePoints, and route metadata	`CreateRouteController.loadExistingRouteData`	Map includes `points`, `locationNames`, `routePoints`, `routeId`, `distance`, `duration`	Controller fields populated with provided planned-route + metadata	`c.points==po` `c.locationNa` `c.routePoint` `c.createdRou` `c.routeDista` `c.routeDurat`
CreateRouteController.loadExistingRouteData → loads actualRoutePoints overlay and preferActualPath flag	`CreateRouteController.loadExistingRouteData`	Map includes `actualRoutePoints` + `preferActualPath: true`	Overlay stored and preference flag set	`c.actualRout` `c.preferActu`
CreateRouteController overlay is read-only during planned-route edits → adding/deleting/renaming stops does not mutate actualRoutePoints	`CreateRouteController.addPointToRoute`, `updateStopName`, `deleteStop` (in presence of overlay)	Controller preloaded with `actualRoutePoints`; then planned-stop edits executed	Planned-stop editing must **not change** overlay polyline	`c.actualRout` length remains
CreateRouteController.getRouteData → returns actualRoutePoints and preferActualPath to callers	`CreateRouteController.getRouteData`	Controller preloaded with overlay + flag + `routeId`	Returned map contains overlay + flag	`data['actual` `data['prefer` `data['routeI`

lets_go/test/create_route_screen_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
CreateRouteScreen actual path overlay → shows the overlay switch when actualRoutePoints are present	`CreateRouteScreen` UI logic (overlay switch visibility)	`CreateRouteController` preloaded with `actualRoutePoints` and `preferActualPath: true`; `isLoading=false`; in-memory map tiles	Overlay toggle should be visible	Finds `Text('Show actual path overlay')` and `SwitchListTile`	PASS
CreateRouteScreen actual path overlay → does not show the overlay switch when no actualRoutePoints	`CreateRouteScreen` UI logic	Controller loaded without `actualRoutePoints`; `isLoading=false`; in-memory tiles	Overlay toggle hidden	Finds nothing for `Text('Show actual path overlay')`	PASS

lets_go/test/ride_edit_controller_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual outpu test)

Test case	Function/unit under test	Input / setup	Expected output	Actual outpu test)
RideEditController.initializeWithRideData → parses actual_path into actualRoutePoints for overlay	`RideEditController.initializeWithRideData`	`rideData` contains `route.stops` and `actual_path` (mix of `{lat, lng}` and `{latitude, longitude}`), `notes:''`	Controller parses `actual_path` into `LatLng` list	`length==2`, first=`LatLng` last=`LatLng`
RideEditController.initializeWithRideData → keeps description empty when notes are empty (no stop-name auto-generation)	`RideEditController.initializeWithRideData`	`notes:''`	`description` remains empty	`c.descript`
RideEditController.applyUpdatedRouteData → preserves actualRoutePoints when returned by route editor	`RideEditController.applyUpdatedRouteData`	Existing `actualRoutePoints` set; updated route data includes `actualRoutePoints`	Overlay should update to new overlay provided	`c.actualRo == [LatLng(30 LatLng(30`
RideEditController.applyUpdatedRouteData → does not wipe actualRoutePoints when route editor returns no actualRoutePoints	`RideEditController.applyUpdatedRouteData`	Existing overlay set; updated route data omits `actualRoutePoints`	Overlay should remain unchanged	`c.actualRo` remains origi

lets_go/test/widget_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
Counter increments smoke test	App boot smoke test (`MyApp`)	`pumpWidget(MyApp(initialRoute: '/'))` then `pump()`	App builds successfully showing a `MaterialApp`	`find.byType(MaterialApp)` == one widget	PASS

Section C: Backend pytest tests (`backend/lets_go/test/**`)

Backend pytest tests — Documentation Table (Part 1)

backend/lets_go/test/test_views_authentication.py

Test case	Function/unit under test	Input / setup	Expected output
test_parse_json_body_empty_returns_dict	`_parse_json_body`	Request-like object with `body=b""`	`{}`
test_parse_json_body_invalid_returns_dict	`_parse_json_body`	`body=b"not-json"`	`{}`
test_parse_json_body_valid_dict	`_parse_json_body`	`body=b'{"a": 1}'`	`{"a":1}`
test_parse_json_body_valid_non_dict_returns_empty	`_parse_json_body`	`body=b"[1, 2]"`	`{}`
test_normalize_gender	`_normalize_gender`	Inputs: `"Male"`, `"m"`, `"Female"`, `"f"`, `""`, `None`	Normalized: `"male"`, `"male"` `"female"`, `None`, `None`
test_get_profile_contact_change_cache_key	`_get_profile_contact_change_cache_key`	`(5, "email", "a@b.com")`	`"profile_contact_chang`
test_parse_iso_date	`_parse_iso_date`	`"2026-02-27"`, `""`, `None`, `"27-02-2026"`	date object for ISO, else `None`
test_generate_otp_length_digits	`generate_otp`	length = `8`	8 digits numeric string
test_get_cache_key	`get_cache_key`	`"x@y.com"`	`"pending_signup_x@y.co`
test_get_reset_cache_key	`get_reset_cache_key`	`("email","x@y.com")`	`"reset_pwd_email_x@y.c`
test_login_success	`login` endpoint	Create user then POST with correct creds	HTTP 200 and payload include
test_login_invalid_password	`login` endpoint	Create user then wrong password	HTTP 404, `success=False`
test_check_username_available_true	`check_username` endpoint	POST username `"newuser"`	available true and registry rov

Test case	Function/unit under test	Input / setup	Expected output
test_check_username_already_reserved_false	`check_username` endpoint	Pre-create registry `"taken"`, then POST `"TAKEN"`	available false
test_send_otp_requires_email_or_phone	`send_otp` endpoint	POST `{}`	HTTP 400 and `success=Fal`
test_send_otp_registration_sets_cache	`send_otp` endpoint	POST email otp registration	HTTP 200, cache populated w
test_verify_otp_success_email	`verify_otp` endpoint	Cache preset with otp; POST verify	HTTP 200, cache updated `ema`
test_verify_password_reset_otp_success	`verify_password_reset_otp` endpoint	Cache preset with reset OTP	HTTP 200, cache key updated
test_reset_password_success	`reset_password` endpoint	Create user; cache verified; POST new password	HTTP 200 and `success=Tru`
test_reset_rejected_user_deletes_user	`reset_rejected_user` endpoint	User status REJECTED; POST email	HTTP 200; user deleted
test_reset_rejected_user_non_rejected_forbidden	`reset_rejected_user` endpoint	Verified user; POST email	HTTP 403
test_upload_to_supabase_missing_settings_raises	`upload_to_supabase`	Patch settings empty	Raises `RuntimeError`
test_upload_to_supabase_success	`upload_to_supabase`	Patch settings + mock `requests.post` status 200	Returns public URL

backend/lets_go/test/tests/test_db_integration_smoke.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in t
test_db_smoke_create_and_query	Django model integration smoke (`UsersData`, `Route`, `Trip`, `Booking`)	DB fixtures create driver/passenger/route/stops/vehicle/trip; create `Booking` then query	Objects persisted and queryable; relationships correct	`.exists()` checks true; fet booking has expected `trip_` passenger email
test_booking_clean_rejects_wrong_stop_order	`Booking.full_clean` validation	Create booking with `from_stop` after `to_stop`	Validation error raised	`pytest.raises(Validat`

backend/lets_go/test/tests/test_utils_route_geometry.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asse test)
test_decode_polyline_empty	`_decode_ors_polyline`	`''`	`[]`	equals `[]`
test_decode_polyline_known	`_decode_ors_polyline`	Encoded polyline `_p~iF~ps|U_ulLnnqC_mqNvxq@|` `First decoded point approx`(38.5,-120.2) | dec[0] == approx((38.5,-120.2))`	PASS	
test_fetch_geometry_without_key	`fetch_route_geometry_osm`	Patch `api_key=''`; points list	Returns empty list when key missing	equals `[]`
test_fetch_geometry_geojson	`fetch_route_geometry_osm`	Patch `api_key='abc'` and mock `requests.post` returning GeoJSON	Returns list of dict `{lat,lng}` converted from GeoJSON coordinates	equals `[{lat:2.0,lng:1` `{lat:4.0,lng:3.`

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asse test)
test_update_route_geometry_from_stops	`update_route_geometry_from_stops`	Patch fetch to fixed points; mock RouteGeometryPoint; route has `save` mocked	Saves route + assigns route geometry + bulk creates points	`route.save` called `route.route_geo` `[{'lat':1.2,'ln` bulk_create called

backend/lets_go/test/tests/test_views_rideposting.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	St
test_parse_limit_offset	`_parse_limit_offset`	Request `/x?limit=5&offset=2`	`(5,2)`	equals `(5,2)`	PA
test_is_archived_after_24h	`_is_archived_after_24h`	created at `2026-01-01 08:00`, now `2026-01-02 10:00`	`True` (more than 24h)	`is True`	PA
test_to_int_pkr	`_to_int_pkr`	`'120.4'`; `'bad'` with default 9	`120`; `9`	equals values	PA
test_map_trip_status	`map_trip_status_to_frontend`	`'COMPLETED'`	returns truthy mapped value	asserted truthy	PA
test_create_trip_invalid_method	`create_trip` endpoint	GET request	405	`status_code==405`	PA
test_cancel_booking_invalid_method	`cancel_booking` endpoint	GET request	405	asserted	PA
test_create_route_invalid_method	`create_route` endpoint	GET request	400	asserted	PA
test_get_trip_breakdown_invalid_method	`get_trip_breakdown` endpoint	POST request (invalid)	400	asserted	PA
test_get_user_created_rides_history_invalid_method	`get_user_created_rides_history` endpoint	POST invalid	400	asserted	PA
test_trigger_auto_archive_for_driver_invalid_method	`trigger_auto_archive_for_driver` endpoint	PUT invalid	405	asserted	PA
test_get_user_booked_rides_history_invalid_method	`get_user_booked_rides_history` endpoint	POST invalid	400	asserted	PA
test_get_user_rides_invalid_method	`get_user_rides` endpoint	POST invalid	400	asserted	PA
test_get_trip_details_invalid_method	`get_trip_details` endpoint	POST invalid	400	asserted	PA
test_update_trip_invalid_method	`update_trip` endpoint	POST invalid	400	asserted	PA
test_delete_trip_invalid_method	`delete_trip` endpoint	POST invalid	400	asserted	PA
test_cancel_trip_invalid_method	`cancel_trip` endpoint	GET invalid	400	asserted	PA
test_get_route_details_invalid_method	`get_route_details` endpoint	POST invalid	400	asserted	PA
test_get_route_statistics_invalid_method	`get_route_statistics` endpoint	POST invalid	400	asserted	PA
test_search_routes_invalid_method	`search_routes` endpoint	POST invalid	400	asserted	PA
test_get_available_seats_invalid_method	`get_available_seats` endpoint	POST invalid	400	asserted	PA
test_create_booking_invalid_method	`create_booking` endpoint	GET invalid	400	asserted	PA
test_get_user_bookings_invalid_method	`get_user_bookings` endpoint	POST invalid	400	asserted	PA
test_search_rides_invalid_method	`search_rides` endpoint	POST invalid	400	asserted	PA
test_cancel_ride_invalid_method	`cancel_ride` endpoint	POST invalid	400	asserted	PA
test_calculate_distance_helper	`_calculate_distance`	Same coordinates	distance `0`	`d == 0`	PA
test_calculate_estimated_arrival	`calculate_estimated_arrival`	departure `10:00`, route distance=100	non-null arrival time	`out is not None`	PA

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	St
test_trip_edit_delete_cancel_guards_helpers	`can_edit_trip`, `can_delete_trip`, `can_cancel_trip`	trip with status SCHEDULED; no existing bookings	return booleans	`isinstance(..., bool)` for each	PA
test_update_trip_status_automatically_smoke	`update_trip_status_automatically`	trip scheduled with date/time	returns same trip object	`result is trip`	PA

Backend pytest tests — Tables (Part 2)

> Below are the **additional backend test suites** I just opened and tabulated.
> Same columns: **Test case**, **Function/unit under test**, **Input/Setup**, **Expected output**, **Actual output (asserted)**, **Status**

backend/lets_go/test/tests/test_administration_views.py

Test case	Function/unit under test
TestAdministrationHelpers.test_build_resolved_sos_snapshot_payload_minimal	`administration.views._build_resolved_sos_snapsho`
TestAdministrationHelpers.test_attach_latest_payments	`administration.views._attach_latest_payments`
TestAdministrationHelpers.test_combine_trip_dt	`administration.views._combine_trip_dt`
TestAdministrationHelpers.test_compute_reached_trigger_dt	`administration.views._compute_reached_trigger_dt`
TestAdministrationHelpers.test_vehicle_to_dict	`administration.views._vehicle_to_dict`
TestAdministrationBasicViews.test_guest_list_view	`administration.views.guest_list_view`
TestAdministrationBasicViews.test_api_guests	`administration.views.api_guests`
TestAdministrationBasicViews.test_admin_analytics_settings_views	`admin_view`, `analytics_view`, `settings_view`
TestAdministrationBasicViews.test_api_users	`administration.views.api_users`
TestAdministrationAuthViews.test_login_view_get	`administration.views.login_view` (GET)
TestAdministrationAuthViews.test_login_view_post_invalid	`login_view` (POST invalid creds)
TestAdministrationAuthViews.test_login_view_post_success	`login_view` (POST valid)

Test case	Function/unit under test
TestAdministrationAuthViews.test_logout_view	`logout_view`
TestAdministrationMethodGuardsAndPosts.test_reached_overdue_dashboard_method_not_allowed	`reached_overdue_dashboard_view`
TestAdministrationMethodGuardsAndPosts.test_reached_overdue_dashboard_forbidden_non_staff	`reached_overdue_dashboard_view`
TestAdministrationMethodGuardsAndPosts.test_reached_overdue_dashboard_success	`reached_overdue_dashboard_view`
TestAdministrationMethodGuardsAndPosts.test_vehicle_update_status_invalid_status_redirects	`vehicle_update_status_view`
TestAdministrationMethodGuardsAndPosts.test_vehicle_delete_post	`vehicle_delete_view`
TestAdministrationMethodGuardsAndPosts.test_user_add_view_get	`user_add_view`
TestAdministrationAdditionalCoverage.test_user_related_render_views	multiple render views
TestAdministrationAdditionalCoverage.test_update_user_status_view_post	`update_user_status_view`
TestAdministrationAdditionalCoverage.test_user_vehicles_redirect_view	`user_vehicles_redirect_view`
TestAdministrationAdditionalCoverage.test_sos_views_smoke	`sos_dashboard_view`
TestAdministrationAdditionalCoverage.test_remaining_admin_symbols_callable	symbol existence smoke

backend/lets_go/test/tests/test_utils_auto_archive.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
test_auto_archive_for_driver_invalid_driver	`auto_archive.auto_archive_for_driver`	`driver_id=0`	No-op count `0`	equals `0`	PASS
test_auto_archive_for_driver_limit	`auto_archive.auto_archive_for_driver`	Patch Trip queryset => 3 trips; patch `_archive_trip` side effects `[True, False, True]`; `limit=2`	Stops after archiving up to limit	returns `2`	PASS
test_auto_archive_global	`auto_archive.auto_archive_global`	Patch Trip queryset => 2 trips; patch `_archive_trip` => True; `limit=5`	Archives both trips	returns `2`	PASS
test_archive_trip_skips_when_recent	`auto_archive._archive_trip`	Patch `timezone.now` to fixed `now`; patch Booking/Payment aggregates return `now`; trip completed recently	Should **not** archive if too recent	returns `False`	PASS

backend/lets_go/test/tests/test_utils_email_otp.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
test_send_email_otp_success	`email_otp.send_email_otp`	Patch `smtplib.SMTP`	Returns True on success path	`is True`	PASS
test_send_email_otp_failure	`email_otp.send_email_otp`	Patch `smtplib.SMTP` raising exception	Returns False on exception	`is False`	PASS
test_send_email_otp_for_reset_success	`email_otp.send_email_otp_for_reset`	Patch `smtplib.SMTP`	Returns True	`is True`	PASS

backend/lets_go/test/tests/test_utils_email_phone.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
test_constants_are_strings	`lets_go.utils.email_phone` constants	None	All configured constants are strings	`isinstance(..., str)` for each	PASS

backend/lets_go/test/tests/test_utils_phone_otp_send.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
test_send_phone_otp_success	`phone_otp_send.send_phone_otp`	Patch `requests.post` to return response with `raise_for_status()` ok and `json={'ok':True}`	Returns True when SMS API ok	`is True`	PASS
test_send_phone_otp_failure	`phone_otp_send.send_phone_otp`	Patch `requests.post` raising exception	Returns False	`is False`	PASS
test_send_phone_otp_reset_failure	`phone_otp_send.send_phone_otp_for_reset`	Patch `requests.post` raising exception	Returns False	`is False`	PASS

backend/lets_go/test/tests/test_utils_verification_guard.py

Test case	Function/unit under test	Input / setup	Expec outpu
test_verification_block_user_not_found	`verification_guard.verification_block_response`	Patch `UsersData.objects.only().get` raises DoesNotExist	404 respo
test_verification_block_banned	`verification_guard.verification_block_response`	Patch user status `BANNED`	403 respo
test_verification_block_none_for_active	`verification_guard.verification_block_response`	Patch user status `ACTIVE`	No bl
test_has_any_requested_keys	`_has_any_requested_keys`	Pending change req list includes `{'email':...}`	True f email False f phone key
test_ride_booking_block_response_pending_gender	`ride_booking_block_response`	Patch `verification_block_response` => None; pending requests contain `gender` change	403 bl
test_ride_create_block_response_pending_license	`ride_create_block_response`	Patch block => None; pending requests contain `driving_license_no` change	403 bl

backend/lets_go/test/tests/test_views_blocking.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
test_user_brief	`views_blocking._user_brief`	User namespace `{id:1,...}`	Dict includes user id	`out['id']==1`	PASS
test_list_blocked_users_invalid_method	`list_blocked_users`	POST (invalid)	405	`status_code==405`	PASS
test_search_users_to_block_invalid_method	`search_users_to_block`	POST (invalid)	405	`status_code==405`	PASS
test_block_user_invalid_method	`block_user`	GET (invalid)	405	`status_code==405`	PASS
test_unblock_user_invalid_method	`unblock_user`	GET (invalid)	405	`status_code==405`	PASS

backend/lets_go/test/tests/test_views_chat.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
test_list_chat_messages_invalid_method	`list_chat_messages`	POST invalid	405	asserted	PASS
test_list_chat_messages_updates_invalid_method	`list_chat_messages_updates`	POST invalid	405	asserted	PASS
test_send_chat_message_invalid_method	`send_chat_message`	GET invalid	405	asserted	PASS
test_mark_message_read_invalid_method	`mark_message_read`	GET invalid	405	asserted	PASS
test_send_broadcast_message_invalid_method	`send_broadcast_message`	GET invalid	405	asserted	PASS

backend/lets_go/test/tests/test_views_incidents.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
TestViewsIncidentsHelpers.test_helper_coercion	`_coerce_int`, `_coerce_float`, `_parse_iso_dt`	`'8'`, `'1.2'`, `'bad'`	8, 1.2, None	asserted	PASS
TestViewsIncidentsHelpers.test_send_email_success	`_send_email`	Patch `smtplib.SMTP`	True	asserted	PASS
TestViewsIncidentsHelpers.test_send_sms_success	`_send_sms`	Patch `requests.post` => status 200	True	asserted	PASS
TestViewsIncidentsEndpoints.test_sos_incident_invalid_json	`sos_incident`	POST non-json body with JSON content-type	400	status 400	PASS
TestViewsIncidentsEndpoints.test_sos_incident_missing_fields	`sos_incident`	POST `{}` JSON	400	status 400	PASS
TestViewsIncidentsEndpoints.test_get_share_token_empty	`_get_share_token`	`''`	None	asserted	PASS
TestViewsIncidentsEndpoints.test_get_trip_share_token_empty	`_get_trip_share_token`	`''`	None	asserted	PASS
TestViewsIncidentsShareEndpoints.test_trip_share_token_invalid_method	`trip_share_token`	GET request	400 or 405	status in (400,405)	PASS
TestViewsIncidentsShareEndpoints.test_trip_share_view_missing_token	`trip_share_view`	token `''`	400 or 404	status in (400,404)	PASS
TestViewsIncidentsShareEndpoints.test_trip_share_live_missing_token	`trip_share_live`	token `''`	400 or 404	status in (400,404)	PASS
TestViewsIncidentsShareEndpoints.test_sos_share_view_missing_token	`sos_share_view`	token `''`	400 or 404	status in (400,404)	PASS
TestViewsIncidentsShareEndpoints.test_sos_share_live_missing_token	`sos_share_live`	token `''`	400 or 404	status in (400,404)	PASS
TestViewsIncidentsShareEndpoints.test_sos_share_send_invalid_method	`sos_share_send`	POST invalid	400 or 405	status in (400,405)	PASS

backend/lets_go/test/tests/test_views_notifications.py

Test case	Function/unit under test	Input / setup	Ex ou
test_update_fcm_token_missing_user	`update_fcm_token`	POST JSON missing `user_id`	40
test_update_fcm_token_user_not_found	`update_fcm_token`	Patch `UsersData.objects.filter(...).update()` => 0; POST JSON with user_id 99	40
test_normalize_payload	`_normalize_ride_notification_payload`	`{'user_id':5,'title':'T','body':123,'data':{'a':1}}`	st no va
test_send_ride_notification_async	`send_ride_notification_async`	Patch `threading.Thread` to run inline; patch `requests.post` => 200	Sh in H re
test_register_fcm_token_with_supabase_async	`register_fcm_token_with_supabase_async`	Patch Thread inline; patch `requests.post` => 200	Sh in H re

backend/lets_go/test/tests/test_views_post_booking.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)
test_helper_coercion_and_distance	`_coerce_int`, `_coerce_float`, `_haversine_meters`	`'5'`, `'2.5'`, identical coords	5, 2.5, distance ~0	asserted
test_compute_reached_trigger	`_compute_reached_trigger_dt`	Trip date 2026-01-01; dep 10:00; arr 11:00	delay approx 2.0 minutes (?) + dt not null	`dt is not None`; `delay==approx(2.0)`
test_require_cron_secret	`_require_cron_secret`	Env `CRON_SECRET='ok'`; header ok vs header no	None when ok; 401 when mismatch	asserted
test_send_email_success	`_send_email`	Patch SMTP	True	asserted
test_send_sms_success	`_send_sms`	Patch requests.post => 200	True	asserted
test_cron_requires_secret	`cron_post_booking_reached_reminders`	Env secret ok; request header no	401	asserted
test_get_ride_readiness_invalid_method	`get_ride_readiness`	POST invalid	405	asserted
test_update_booking_readiness_invalid_method	`update_booking_readiness`	GET invalid	405	asserted
test_verify_pickup_code_invalid_method	`verify_pickup_code`	GET invalid	400 or 405	asserted
test_parse_iso_dt	`_parse_iso_dt`	`'bad'`	None	asserted
test_combine_trip_dt	`_combine_trip_dt`	Trip with date + time	non-null datetime	asserted
test_start_trip_ride_invalid_method	`start_trip_ride`	GET invalid	400 or 405	asserted
test_start_booking_ride_invalid_method	`start_booking_ride`	GET invalid	400 or 405	asserted
test_complete_trip_ride_invalid_method	`complete_trip_ride`	GET invalid	400 or 405	asserted
test_mark_booking_dropped_off_invalid_method	`mark_booking_dropped_off`	GET invalid	400 or 405	asserted
test_driver_mark_reached_pickup_invalid_method	`driver_mark_reached_pickup`	GET invalid	400 or 405	asserted
test_driver_mark_reached_dropoff_invalid_method	`driver_mark_reached_dropoff`	GET invalid	400 or 405	asserted

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)
test_get_booking_payment_details_invalid_method	`get_booking_payment_details`	POST invalid	400 or 405	asserted
test_submit_booking_payment_invalid_method	`submit_booking_payment`	GET invalid	400 or 405	asserted
test_confirm_booking_payment_invalid_method	`confirm_booking_payment`	GET invalid	400 or 405	asserted
test_get_trip_payments_invalid_method	`get_trip_payments`	POST invalid	400 or 405	asserted
test_update_live_location_invalid_method	`update_live_location`	GET invalid	400 or 405	asserted
test_get_live_location_invalid_method	`get_live_location`	POST invalid	400 or 405	asserted
test_generate_pickup_code_invalid_method	`generate_pickup_code`	GET invalid	400 or 405	asserted
test_compute_reminder_helpers	`compute_driver_reminder_time`	Trip with id/date/dep time	non-null reminder time	asserted
test_remaining_helper_symbols_callable	symbol existence smoke	None	helpers callable	`callable(...)` true

backend/lets_go/test/tests/test_views_profile.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Statu
test_user_change_requests_invalid_method	`user_change_requests`	POST invalid	400	status 400	PASS
test_send_profile_contact_change_otp_invalid_method	`send_profile_contact_change_otp`	GET invalid	400	status 400	PASS
test_send_profile_contact_change_otp_success_email	`send_profile_contact_change_otp`	Patch UsersData.get => user; patch otp => '1111'; patch cache empty; patch send_email_otp True; POST JSON which=email	200	status 200	PASS
test_send_profile_contact_change_otp_not_found	`send_profile_contact_change_otp`	Patch UsersData.get raises DoesNotExist	404	status 404	PASS
test_upload_user_driving_license_invalid_method	`upload_user_driving_license`	GET invalid	400	status 400	PASS
test_upload_user_photos_invalid_method	`upload_user_photos`	GET invalid	400	status 400	PASS
test_upload_user_cnic_invalid_method	`upload_user_cnic`	GET invalid	400	status 400	PASS
test_upload_vehicle_images_invalid_method	`upload_vehicle_images`	GET invalid	400	status 400	PASS
test_verify_profile_contact_change_otp_invalid_method	`verify_profile_contact_change_otp`	GET invalid	400	status 400	PASS
test_upload_user_accountqr_invalid_method	`upload_user_accountqr`	GET invalid	400	status 400	PASS
test_user_image_invalid_method	`user_image`	Patch UsersData.values_list.get => '' ; call with POST and field `profile_photo`	Raises `Http404`	exception caught -> assert True	PASS
test_vehicle_image_invalid_method	`vehicle_image`	POST invalid	400 or 405	status in (400,405)	PASS

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Statu
test_user_profile_invalid_method	`user_profile`	DELETE invalid	400 or 405	status in (400,405)	PASS
test_user_emergency_contact_invalid_method	`user_emergency_contact`	Patch UsersData.get => user; DELETE invalid	400	status 400	PASS
test_user_vehicles_invalid_method	`user_vehicles`	Patch UsersData.only.get => user; DELETE invalid	400	status 400	PASS
test_vehicle_detail_invalid_method	`vehicle_detail`	POST invalid	400 or 405	status in (400,405)	PASS

Backend pytest tests — Tables (Part 3 / Final)

backend/lets_go/test/tests/test_views_ridebooking.py

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
test_get_ride_booking_details_invalid_method	`views_ridebooking.get_ride_booking_details`	POST request (invalid method expected)	405 Method Not Allowed	`status_code == 405`	PASS
test_get_confirmed_passengers_invalid_method	`views_ridebooking.get_confirmed_passengers`	POST request (invalid method expected)	405 Method Not Allowed	`status_code == 405`	PASS

backend/lets_go/test/tests/test_views_support_chat.py

Test case	Function/unit under test	Input / setup
TestViewsSupportChatHelpers.test_to_int_and_parse_json_body	`_to_int`, `_parse_json_body`	`_to_int('12')`; POST JSON `{'a':1}`
TestViewsSupportChatHelpers.test_bot_reply_text	`_bot_reply_text`	Input text: `"what is fare"`
TestViewsSupportChatHelpers.test_serialize_support_message	`_serialize_support_message`	Message namespace with `id=1`, thread inf created_at.isoformat
TestViewsSupportChatEndpoints.test_support_guest_invalid_method	`support_guest`	GET invalid
TestViewsSupportChatEndpoints.test_view_bot_invalid_method	`view_bot`	PUT invalid
TestViewsSupportChatEndpoints.test_view_adminchat_invalid_method	`view_adminchat`	PUT invalid
TestViewsSupportChatEndpoints.test_ensure_thread_smoke	`_ensure_thread`	Patch `SupportThread.objects.get_or_cre (thread(id=1), True)`
TestViewsSupportChatEndpoints.test_resolve_owner_from_query_user_not_found	`_resolve_owner_from_query`	Patch `UsersData.objects.filter().first` None; request `?user_id=5`
TestViewsSupportChatEndpoints.test_resolve_owner_from_body_guest_not_found	`_resolve_owner_from_body`	Patch `GuestUser.objects.filter().first` None; body `{'guest_user_id':5}`

Test case	Function/unit under test	Input / setup
TestViewsSupportChatEndpoints.test_sync_guest_fcm_updates	`_sync_guest_fcm`	guest namespace; patch `GuestUser.objects.filter`; patch `register_fcm_token_with_supabase`

backend/lets_go/test/tests/test_views_user_notifications.py

Test case	Function/unit under test	Input / setup	Expected output	Actual outp (asserted in
test_list_notifications_requires_user_or_guest	`list_notifications`	GET with no `user_id`/`guest_user_id`	400	`status_co`
test_list_notifications_user_success	`list_notifications`	Patch `NotificationInbox.objects.filter` side effects: first returns list qs with one notification; second returns count=3; request `?user_id=12&limit=50&offset=0`	200 + payload: success true, unread_count=3, 1 notification	asserts `success==` `unread_co` `len==1`, firs
test_list_notifications_guest_success	`list_notifications`	Patch filters: list empty; count 0; request `?guest_user_id=7`	200 + unread_count 0	asserts
test_unread_count_user_and_guest	`notification_unread_count`	Patch count=5 for user request, then count=2 for guest request	200 with correct unread_count	asserts unre values
test_mark_all_read_user_and_guest	`mark_all_notifications_read`	POST JSON `{user_id:1}` then `{guest_user_id:2}`; patch `NotificationInbox.objects`	200 and update performed via filter	asserts statu and `filter.ca` both times
test_mark_read_and_dismiss_not_found	`mark_notification_read`, `dismiss_notification`	Patch `NotificationInbox.objects.get` raises DoesNotExist	404 for both	asserts 404
test_mark_read_and_dismiss_success	`mark_notification_read`, `dismiss_notification`	Patch get returns notification namespaces with `save` mocked	200 and `save()` called	asserts 200 a `save.call`

backend/lets_go/test/tests/test_views_negotiation.py (confirming full coverage)

Test case	Function/unit under test	Input / setup
TestViewsNegotiationHelpers.test_to_int_pkr	`_to_int_pkr`	`'22.7'`
TestViewsNegotiationHelpers.test_serialize_booking_detail	`_serialize_booking_detail`	Booking namespace with ids + nest trip/passenger/stops
TestViewsNegotiationEndpoints.test_handle_ride_booking_request_invalid_method	`handle_ride_booking_request`	GET invalid
test_list_pending_requests_invalid_method	`list_pending_requests`	POST invalid
test_list_pending_requests_not_found	`list_pending_requests`	Patch `Trip.objects.filter().valu` => None
test_booking_request_details_invalid_method	`booking_request_details`	POST invalid
test_respond_booking_request_invalid_method	`respond_booking_request`	GET invalid
test_unblock_passenger_for_trip_invalid_method	`unblock_passenger_for_trip`	GET invalid
test_passenger_respond_booking_invalid_method	`passenger_respond_booking`	GET invalid
test_get_booking_negotiation_history_invalid_method	`get_booking_negotiation_history`	POST invalid
test_request_ride_booking_invalid_method	`request_ride_booking`	GET invalid

Section B: Flutter generated contract tests (`lets_go/test/generated/**`)

Tables (Part 1)

These tests don't validate runtime behavior; they validate **code contract presence**:

- file is non-empty
- class declarations exist
- expected function names (symbols) exist via regex

lets_go/test/generated/utils/map_util_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/map_util.dart contract → source file is non-empty	Contract for `lib/utils/map_util.dart`	Read source file to string	`source.trim().isNotEmpty == true`	asserted true	PASS
utils/map_util.dart contract → declares expected classes	Contract for `MapUtil` class	Source string contains `class MapUtil`	`true`	asserted true	PASS
utils/map_util.dart contract → contains expected callable symbols	Contract for functions	Regex matches for `boundsFromPoints`, `calculateDistanceMeters`, `centerFromPoints`, `generateInterpolatedRoute`, `roadPolylineOrFallback`	each regex match true	asserted true	PASS

lets_go/test/generated/utils/test_frontend_calculator_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/test_frontend_calculator.dart contract → source file is non-empty	Contract for `lib/utils/test_frontend_calculator.dart`	Read source	non-empty	asserted true	PASS
utils/test_frontend_calculator.dart contract → contains expected callable symbols	Contract for main()	Regex match main(	true	asserted true	PASS

lets_go/test/generated/utils/battery_optimization_helper_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	S
utils/battery_optimization_helper.dart contract → source file is non-empty	Contract for `lib/utils/battery_optimization_helper.dart`	Read source	non-empty	asserted true	P
utils/battery_optimization_helper.dart contract → declares expected classes	`BatteryOptimizationHelper` existence	`source.contains('class BatteryOptimizationHelper')`	true	asserted true	P
utils/battery_optimization_helper.dart contract → contains expected callable symbols	`requestIgnoreOptimizations()` existence	regex matches	true	asserted true	P

lets_go/test/generated/utils/auth_session_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/auth_session.dart contract → source file is non-empty	Contract for `lib/utils/auth_session.dart`	Read source	non-empty	asserted true	PASS
utils/auth_session.dart contract → declares expected classes	`AuthSession` existence	contains `class AuthSession`	true	asserted true	PASS
utils/auth_session.dart contract → contains expected callable symbols	`clear()`, `load()`, `save()` existence	regex matches	true	asserted true	PASS

Tables (Part 2: remaining `generated/utils`)

> All these tests follow the same contract pattern:

- read `lib/...` source file as string
- assert **non-empty**
- assert **class exists** (sometimes)
- assert **expected symbols exist** via regex (sometimes)

lets_go/test/generated/utils/road_polyline_service_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Stat
utils/road_polyline_service.dart contract → source file is non-empty	Contract for `lib/utils/road_polyline_service.dart`	Read source file	`source.trim().isNotEmpty == true`	asserted true	PAS
utils/road_polyline_service.dart contract → declares expected classes	Contract ensures `RoadPolylineService` exists	Source contains `class RoadPolylineService`	true	asserted true	PAS

lets_go/test/generated/utils/test_hybrid_search_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/test_hybrid_search.dart contract → source file is non-empty	Contract for `lib/utils/test_hybrid_search.dart`	Read source	non-empty	asserted true	PASS
utils/test_hybrid_search.dart contract → declares expected classes	`HybridSearchTest` exists	contains `class HybridSearchTest`	true	asserted true	PASS
utils/test_hybrid_search.dart contract → contains expected callable symbols	`testPlacesService()` exists	regex match `testPlacesService(`	true	asserted true	PASS

lets_go/test/generated/utils/fare_calculator_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/fare_calculator.dart contract → source file is non-empty	Contract for `lib/utils/fare_calculator.dart`	Read source	non-empty	asserted true	PASS
utils/fare_calculator.dart contract → declares expected classes	`FareCalculator` exists	contains `class FareCalculator`	true	asserted true	PASS
utils/fare_calculator.dart contract → contains expected callable symbols	Fare calculator API surface exists	regex matches for `formatFare`, `getFareBreakdownText`, `getFareSummary`, `getFuelEfficiency`, `getFuelPrices`, `updateFuelPrices`	all true	PASS	

lets_go/test/generated/utils/debug_fare_calculator_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/debug_fare_calculator.dart contract → source file is non-empty	Contract for `lib/utils/debug_fare_calculator.dart`	Read source	non-empty	asserted true	PASS
utils/debug_fare_calculator.dart contract → declares expected classes	`DebugFareCalculator` exists	contains `class DebugFareCalculator`	true	asserted true	PASS

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/debug_fare_calculator.dart contract → contains expected callable symbols	Debug/test helper API exists	regex matches for `compareWithBackend`, `testCalculationComponents`, `testFareConsistency`, `testFrontendCalculator`, `testHybridFareCalculation`, `testUserReportedIssue`	all true	PASS	

`generated/utils/*_contract_test.dart` **(remaining batch)**

lets_go/test/generated/utils/image_utils_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/image_utils.dart contract → source file is non-empty	Contract for `lib/utils/image_utils.dart`	Read source file as string	`source.trim().isNotEmpty == true`	asserted true	PASS
utils/image_utils.dart contract → declares expected classes	`ImageUtils` class presence	`source.contains('class ImageUtils')`	true	asserted true	PASS
utils/image_utils.dart contract → contains expected callable symbols	Image util API surface exists	Regex matches for `ensureValidImageUrl(`, `getFallbackImageUrl(`, `isValidImageUrl(`	all true	PASS	

lets_go/test/generated/utils/recreate_trip_mapper_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/recreate_trip_mapper.dart contract → source file is non-empty	Contract for `lib/utils/recreate_trip_mapper.dart`	Read source	non-empty	asserted true	PASS
utils/recreate_trip_mapper.dart contract → declares expected classes	`RecreateTripMapper` presence	contains `class RecreateTripMapper`	true	asserted true	PASS
utils/recreate_trip_mapper.dart contract → contains expected callable symbols	Mapper API exists	Regex matches `normalizeRideBookingDetail(` and `parsePolylinePoints(`	both true	PASS	

lets_go/test/generated/utils/test_route_creation_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/test_route_creation.dart contract → source file is non-empty	Contract for `lib/utils/test_route_creation.dart`	Read source	non-empty	asserted true	PASS
utils/test_route_creation.dart contract → declares expected classes	`RouteCreationUtils` presence	contains `class RouteCreationUtils`	true	asserted true	PASS
utils/test_route_creation.dart contract → contains expected callable symbols	Distance function exposed	Regex matches `calculateDistance(`	true	PASS	

lets_go/test/generated/utils/actual_path_rules_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/actual_path_rules.dart contract → source file is non-empty	Contract for `lib/utils/actual_path_rules.dart`	Read source	non-empty	asserted true	PASS
utils/actual_path_rules.dart contract → declares expected classes	`ActualPathRules` presence	contains `class ActualPathRules`	true	PASS	
utils/actual_path_rules.dart contract → contains expected callable symbols	Utility symbols exist	Regex matches `sameLatLng(` and `startsWithStops(`	both true	PASS	

lets_go/test/generated/utils/road_polyline_service_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/road_polyline_service.dart contract → source file is non-empty	Contract for `lib/utils/road_polyline_service.dart`	Read source	non-empty	asserted true	PASS
utils/road_polyline_service.dart contract → declares expected classes	`RoadPolylineService` presence	contains class name	true	PASS	

lets_go/test/generated/utils/test_hybrid_search_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/test_hybrid_search.dart contract → source file is non-empty	Contract for `lib/utils/test_hybrid_search.dart`	Read source	non-empty	PASS	
utils/test_hybrid_search.dart contract → declares expected classes	`HybridSearchTest` presence	contains class name	true	PASS	
utils/test_hybrid_search.dart contract → contains expected callable symbols	`testPlacesService` exists	Regex matches	true	PASS	

lets_go/test/generated/utils/fare_calculator_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/fare_calculator.dart contract → source file is non-empty	Contract for `lib/utils/fare_calculator.dart`	Read source	non-empty	PASS	
utils/fare_calculator.dart contract → declares expected classes	`FareCalculator` exists	contains class name	true	PASS	
utils/fare_calculator.dart contract → contains expected callable symbols	Fare methods exist	Regex matches: `formatFare`, `getFareBreakdownText`, `getFareSummary`, `getFuelEfficiency`, `getFuelPrices`, `updateFuelPrices`	all true	PASS	

lets_go/test/generated/utils/debug_fare_calculator_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/debug_fare_calculator.dart contract → source file is non-empty	Contract for `lib/utils/debug_fare_calculator.dart`	Read source	non-empty	PASS	
utils/debug_fare_calculator.dart contract → declares expected classes	`DebugFareCalculator` exists	contains class name	true	PASS	

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
utils/debug_fare_calculator.dart contract → contains expected callable symbols	Debug methods exist	Regex matches: `compareWithBackend`, `testCalculationComponents`, `testFareConsistency`, `testFrontendCalculator`, `testHybridFareCalculation`, `testUserReportedIssue`	all true	PASS	

B2) Start `generated/controllers/**` (batch 1)

lets_go/test/generated/controllers/signup_login_controllers/login_controller_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output
controllers/.../login_controller.dart contract → source file is non-empty	Contract for `lib/controllers/signup_login_controllers/login_controller.dart`	Read source	non-empty
controllers/.../login_controller.dart contract → declares expected classes	`LoginController` exists	`source.contains('class LoginController')`	true

lets_go/test/generated/controllers/signup_login_controllers/otp_verification_controller_contract_test.dart

Test case	Function/unit under test	Input / setup
controllers/.../otp_verification_controller.dart contract → source file is non-empty	Contract for `lib/controllers/signup_login_controllers/otp_verification_controller.dart`	Read source
controllers/.../otp_verification_controller.dart contract → declares expected classes	`OTPVerificationController` exists	contains class nan
controllers/.../otp_verification_controller.dart contract → contains expected callable symbols	Controller API exists	Regex matches: `cleanupSignup` `dispose`, `initExpiryFro` `loadSignupDat` `resendOtp`, `startEmailTim` `startPhoneTim` `submitFinalRe`

lets_go/test/generated/controllers/ride_posting_controllers/create_route_controller_contract_test.dart

Test case	Function/unit under test	Input / setup
controllers/.../create_route_controller.dart contract → source file is non-empty	Contract for `lib/controllers/ride_posting_controllers/create_route_controller.dart`	Read source
controllers/.../create_route_controller.dart contract → declares expected classes	`CreateRouteController` exists	contains class name

Test case	Function/unit under test	Input / setup
controllers/.../create_route_controller.dart contract → contains expected callable symbols	Route controller surface exists	Regex matches: `Timer(`, `addPointToRoute`, `buildFullLabel`, `calculateDistance`, `calculateDistanceFr` `calculateRouteMetri` `clearRoute`, `clearSear` `createRoute`, `deleteSt` `dispose`, `editStopName` `fetchRoute`, `findNearbyPlaceName`, `getCurrentLocation`, `getPlaceNameFromCoo` `getRouteData`, `handleM` `loadExistingRouteDa` `loadPlacesData`, `poiPriorityScore`, `removeDuplicatesAnd` `searchPlaces`, `selectSearchResult`, `updateRoute`, `updateSt`

lets_go/test/generated/controllers/post_bookings_controller/live_tracking_controller_contract_test.dart

Test case	Function/unit under test	Input / setup
controllers/.../live_tracking_controller.dart contract → source file is non-empty	Contract for `lib/controllers/post_bookings_controller/live_tracking_controller.dart`	Read source
controllers/.../live_tracking_controller.dart contract → declares expected classes	`LiveTrackingController` exists	contains class name
controllers/.../live_tracking_controller.dart contract → contains expected callable symbols	Tracking API exists	Regex matches: `detachUi`, `dispose`, `generatePickupCode`, `init`, `pointForStopOrder`, `refreshTripLayout`, `setSelectedBooking` `startRide`, `stopSendingLocatio` `verifyPickupCode`

Controllers contract tests (`lets_go/test/generated/controllers/**`) — Remaining controllers (profile + ride_booking + ride_posting + post_bookings)

lets_go/test/generated/controllers/profile/profile_main_controller_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output
controllers/profile/profile_main_controller.dart contract → source file is non-empty	Contract for `lib/controllers/profile/profile_main_controller.dart`	Read source	non-empty
controllers/profile/profile_main_controller.dart contract → declares expected classes	`ProfileMainController` exists	contains class name	true
controllers/profile/profile_main_controller.dart contract → contains expected callable symbols	Required symbol exists	Regex matches `ensureLicenseIfMissing(`	true

lets_go/test/generated/controllers/profile/profile_general_info_controller_contract_test.dart

Test case	Function/unit under test	Input / setup	Ex ou
controllers/profile/profile_general_info_controller.dart contract → source file is non-empty	Contract for `lib/controllers/profile/profile_general_info_controller.dart`	Read source	no em
controllers/profile/profile_general_info_controller.dart contract → declares expected classes	`ProfileGeneralInfoController` exists	contains class name	tru
controllers/profile/profile_general_info_controller.dart contract → contains expected callable symbols	Required methods exist	Regex matches: `getCnicImages`, `hydrateProfile`, `imageUrl`, `resolveCnic`, `resolvePhone`, `resolveString`, `saveChanges`, `setEditing`, `toggleEdit`	all

lets_go/test/generated/controllers/profile/profile_vehicle_info_controller_contract_test.dart

Test case	Function/unit under test	Input / setup
controllers/profile/profile_vehicle_info_controller.dart contract → source file is non-empty	Contract for `lib/controllers/profile/profile_vehicle_info_controller.dart`	Read source
controllers/profile/profile_vehicle_info_controller.dart contract → declares expected classes	`ProfileVehicleInfoController` exists	contains class name
controllers/profile/profile_vehicle_info_controller.dart contract → contains expected callable symbols	Required methods exist	Regex matches: `computeDriverByLicer` `ensureVehicleDetail` `getLicenseImages`, `hydrateUser`, `license` `loadVehicles`, `userImg`

lets_go/test/generated/controllers/profile/profile_contact_change_controller_contract_test.dart

Test case	Function/unit under test	Input / setup	Ex ou
controllers/profile/profile_contact_change_controller.dart contract → source file is non-empty	Contract for `lib/controllers/profile/profile_contact_change_controller.dart`	Read source	no em
controllers/profile/profile_contact_change_controller.dart contract → declares expected classes	`ProfileContactChangeController` exists	contains class name	tru
controllers/profile/profile_contact_change_controller.dart contract → contains expected callable symbols	Required methods exist	Regex matches: `sendOtp(`, `verifyOtp(`	bo

lets_go/test/generated/controllers/profile/vehicle_form_controller_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserte in test)
controllers/profile/vehicle_form_controller.dart contract → source file is non-empty	Contract for `lib/controllers/profile/vehicle_form_controller.dart`	Read source	non-empty	PASS
controllers/profile/vehicle_form_controller.dart contract → declares expected classes	`VehicleFormController` exists	contains class name	true	PASS

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserte in test)
controllers/profile/vehicle_form_controller.dart contract → contains expected callable symbols	Required methods exist	Regex matches: `deleteVehicle(`, `submit(`	both true	PASS

Ride Booking controllers

lets_go/test/generated/controllers/ride_booking_controllers/ride_details_view_controller_contract_test.dart

Test case	Function/unit under test
controllers/ride_booking_controllers/ride_details_view_controller.dart contract → source file is non-empty	Contract for `lib/controllers/ride_booking_controllers/ride_details_view_controller.`
controllers/ride_booking_controllers/ride_details_view_controller.dart contract → declares expected classes	`RideDetailsViewController` exists
controllers/ride_booking_controllers/ride_details_view_controller.dart contract → contains expected callable symbols	Required methods exist

lets_go/test/generated/controllers/ride_booking_controllers/ride_request_controller_contract_test.dart

Test case	Function/unit under test	Inp
controllers/ride_booking_controllers/ride_request_controller.dart contract → source file is non-empty	Contract for `lib/controllers/ride_booking_controllers/ride_request_controller.dart`	Re
controllers/ride_booking_controllers/ride_request_controller.dart contract → declares expected classes	`RideRequestController` exists	co
controllers/ride_booking_controllers/ride_request_controller.dart contract → contains expected callable symbols	Booking request API exists	Re list far ge `in` `re` `se` me `up` `up` `up`

lets_go/test/generated/controllers/ride_booking_controllers/ride_booking_details_controller_contract_test.dart

Test case	Function/unit under test
controllers/ride_booking_controllers/ride_booking_details_controller.dart contract → source file is non-empty	Contract for `lib/controllers/ride_booking_controllers/ride_booking_details_contr`

Test case	Function/unit under test
controllers/ride_booking_controllers/ride_booking_details_controller.dart contract → declares expected classes	`RideBookingDetailsController` exists
controllers/ride_booking_controllers/ride_booking_details_controller.dart contract → contains expected callable symbols	Booking details API exists

Ride Posting controllers

lets_go/test/generated/controllers/ride_posting_controllers/create_ride_controller_contract_test.dart

Test case	Function/unit under test	Input
controllers/ride_posting_controllers/create_ride_controller.dart contract → source file is non-empty	Contract for `lib/controllers/ride_posting_controllers/create_ride_controller.dart`	Read s
controllers/ride_posting_controllers/create_ride_controller.dart contract → declares expected classes	`CreateRideController` exists	conta
controllers/ride_posting_controllers/create_ride_controller.dart contract → contains expected callable symbols	Required methods exist	Regex `navig`

lets_go/test/generated/controllers/ride_posting_controllers/create_ride_details_controller_contract_test.dart

Test case	Function/unit under test
controllers/ride_posting_controllers/create_ride_details_controller.dart contract → source file is non-empty	Contract for `lib/controllers/ride_posting_controllers/create_ride_details_controll`
controllers/ride_posting_controllers/create_ride_details_controller.dart contract → declares expected classes	`RideDetailsController` exists

Test case	Function/unit under test
controllers/ride_posting_controllers/create_ride_details_controller.dart contract → contains expected callable symbols	Ride creation details API exists

lets_go/test/generated/controllers/ride_posting_controllers/my_rides_controller_contract_test.dart

Test case	Function/unit under test	Input / setu
controllers/ride_posting_controllers/my_rides_controller.dart contract → source file is non-empty	Contract for `lib/controllers/ride_posting_controllers/my_rides_controller.dart`	Read source
controllers/ride_posting_controllers/my_rides_controller.dart contract → declares expected classes	`MyRidesController` exists	contains clas name
controllers/ride_posting_controllers/my_rides_controller.dart contract → contains expected callable symbols	My rides API exists	Regex matcl `cancelBoo` `cancelRid` `deleteRid` `dispose`, `loadUserR`

lets_go/test/generated/controllers/ride_posting_controllers/ride_edit_controller_contract_test.dart

Test case	Function/unit under test	Input / set
controllers/ride_posting_controllers/ride_edit_controller.dart contract → source file is non-empty	Contract for `lib/controllers/ride_posting_controllers/ride_edit_controller.dart`	Read sourc
controllers/ride_posting_controllers/ride_edit_controller.dart contract → declares expected classes	`RideEditController` exists	contains cl

Test case	Function/unit under test	Input / set
controllers/ride_posting_controllers/ride_edit_controller.dart contract → contains expected callable symbols	Ride edit API exists	Regex mat `applyUpd` `calculat` `cancelRi` `fetchRou` `getCurre` `initiali` `loadUser` `togglePr` `updateRi` `updateSt` `updateTo`

lets_go/test/generated/controllers/ride_posting_controllers/ride_request_controller_contract_test.dart

Test case	Function/unit under test	Inp
controllers/ride_posting_controllers/ride_request_controller.dart contract → source file is non-empty	Contract for `lib/controllers/ride_posting_controllers/ride_request_controller.dart`	Rea
controllers/ride_posting_controllers/ride_request_controller.dart contract → declares expected classes	`RideRequestController` exists	con
controllers/ride_posting_controllers/ride_request_controller.dart contract → contains expected callable symbols	Request/negotiation API exists	Reg sym for `ini` `rec` `set` me

lets_go/test/generated/controllers/ride_posting_controllers/ride_view_controller_contract_test.dart

Test case	Function/unit under test	Input / sel
controllers/ride_posting_controllers/ride_view_controller.dart contract → source file is non-empty	Contract for `lib/controllers/ride_posting_controllers/ride_view_controller.dart`	Read sour
controllers/ride_posting_controllers/ride_view_controller.dart contract → declares expected classes	`RideViewController` exists	contains cl
controllers/ride_posting_controllers/ride_view_controller.dart contract → contains expected callable symbols	View ride API exists	Regex mat `cancelRi` `fetchRou` `getCurre` `initiali`

lets_go/test/generated/controllers/ride_posting_controllers/ride_view_edit_controller_contract_test.dart

Test case	Function/unit under test
controllers/ride_posting_controllers/ride_view_edit_controller.dart contract → source file is non-empty	Contract for `lib/controllers/ride_posting_controllers/ride_view_edit_controller.dart`
controllers/ride_posting_controllers/ride_view_edit_controller.dart contract → declares expected classes	`RideViewEditController` + `scope` symbol exist

Post-bookings controllers (remaining ones)

lets_go/test/generated/controllers/post_bookings_controller/driver_live_tracking_controller_contract_test.dart

Test case	Function/unit under test
controllers/post_bookings_controller/driver_live_tracking_controller.dart contract → source file is non-empty	Contract for `lib/controllers/post_bookings_controller/driver_live_tracking_contro`
controllers/post_bookings_controller/driver_live_tracking_controller.dart contract → declares expected classes	`DriverLiveTrackingController` exists

lets_go/test/generated/controllers/post_bookings_controller/passenger_live_tracking_controller_contract_test.dart

Test case	Function/unit under test
controllers/post_bookings_controller/passenger_live_tracking_controller.dart contract → source file is non-empty	Contract for `lib/controllers/post_bookings_controller/passenger_live_tracking_`
controllers/post_bookings_controller/passenger_live_tracking_controller.dart contract → declares expected classes	`PassengerLiveTrackingController` exists

Screens contract tests (`lets_go/test/generated/screens/**`) — Batch 1

lets_go/test/generated/screens/home_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
screens/home_screen.dart contract → source file is non-empty	Contract for `lib/screens/home_screen.dart`	Read source file	`source.trim().isNotEmpty == true`	asserted true	PASS
screens/home_screen.dart contract → declares expected classes	UI classes exist	Source contains `class HomeScreen` and `class _HomeScreenState`	both true	PASS	
screens/home_screen.dart contract → contains expected callable symbols	Widget lifecycle/helpers exist	Regex matches: `build(`, `dispose(`, `initOnce(`, `initState(`, `setModalState(`, `setState(`, `suggest(`, `toDouble(`, `vehicleThumbUrl(`	all true	PASS	

lets_go/test/generated/screens/notifications_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	S
screens/notifications_screen.dart contract → source file is non-empty	Contract for `lib/screens/notifications_screen.dart`	Read source	non-empty	PASS	
screens/notifications_screen.dart contract → declares expected classes	Screen + State exist	Contains `NotificationsScreen` and `_NotificationsScreenState`	both true	PASS	
screens/notifications_screen.dart contract → contains expected callable symbols	Private handlers exist	Regex matches: `_load(`, `_markAllRead(`, `_dismiss(`, `_handleTap(`	all true	PASS	

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	S
screens/notifications_screen.dart contract → uses notifications ApiService methods	Contract for API usage	Source contains `ApiService.listNotifications`, `ApiService.dismissNotification`, `ApiService.markAllNotificationsRead`, `ApiService.markNotificationRead`	all true	PASS	

Post-booking screens

lets_go/test/generated/screens/post_booking_screens/live_tracking_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
screens/post_booking_screens/live_tracking_screen.dart contract → source file is non-empty	Contract for `lib/screens/post_booking_screens/live_tracking_screen.dart`	Read source
... → declares expected classes	Screen and internal UI classes exist	Contains `LiveTrackingScreen`, `_LegendRow`, `_LiveTrackingScreenS`
... → contains expected callable symbols	Widget lifecycle/helpers exist	Regex matches: `build(`, `closeTo(`, `dispose(`, `initState(`, `setState(`

lets_go/test/generated/screens/post_booking_screens/driver_live_tracking_screen_contract_test.dart

Test case	Function/unit under test	Input / set
screens/post_booking_screens/driver_live_tracking_screen.dart contract → source file is non-empty	Contract for `lib/screens/post_booking_screens/driver_live_tracking_screen.dart`	Read sour
... → declares expected classes	Screen/state + legend exist	Contains `DriverLi` `_DriverL` `_LegendR`
... → contains expected callable symbols	Widget lifecycle exists	Regex mat `initStat`

lets_go/test/generated/screens/post_booking_screens/passenger_live_tracking_screen_contract_test.dart

Test case	Function/unit under test	In
screens/post_booking_screens/passenger_live_tracking_screen.dart contract → source file is non-empty	Contract for `lib/screens/post_booking_screens/passenger_live_tracking_screen.dart`	Re
... → declares expected classes	Screen + State exist	Co `Pa` `_P`
... → contains expected callable symbols	Widget lifecycle exists	Re `in`

lets_go/test/generated/screens/post_booking_screens/passenger_payment_screen_contract_test.dart

Test case	Function/unit under test	Input / setup

Test case	Function/unit under test	Input / setup
screens/post_booking_screens/passenger_payment_screen.dart contract → source file is non-empty	Contract for `lib/screens/post_booking_screens/passenger_payment_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `PassengerPa` `_PassengerI`
... → contains expected callable symbols	Widget lifecycle exists	Regex matche `initState(`,

lets_go/test/generated/screens/post_booking_screens/driver_payment_confirmation_screen_contract_test.dart

Test case	Function/unit under test
screens/post_booking_screens/driver_payment_confirmation_screen.dart contract → source file is non-empty	Contract for `lib/screens/post_booking_screens/driver_payment_confirmation_screen.`
... → declares expected classes	Screen + State exist
... → contains expected callable symbols	Widget lifecycle exists

Chat screens

lets_go/test/generated/screens/chat_screens/passenger_chat_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expe outpu
screens/chat_screens/passenger_chat_screen.dart contract → source file is non-empty	Contract for `lib/screens/chat_screens/passenger_chat_screen.dart`	Read source	non-empt
... → declares expected classes	Screen + State exist	Contains `PassengerChatScreen`, `_PassengerChatScreenState`	both
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `dispose(`, `initState(`, `setState(`	all tru

Screens contract tests (`lets_go/test/generated/screens/**`) — Batch 2

lets_go/test/generated/screens/chat_screens/driver_chat_members_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
screens/chat_screens/driver_chat_members_screen.dart contract → source file is non-empty	Contract for `lib/screens/chat_screens/driver_chat_members_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `DriverChatMembersScree` `_DriverChatMembersScre`
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `initState(`, `setState(`

lets_go/test/generated/screens/chat_screens/driver_individual_chat_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
screens/chat_screens/driver_individual_chat_screen.dart contract → source file is non-empty	Contract for `lib/screens/chat_screens/driver_individual_chat_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `DriverIndividualCha` `_DriverIndividualCh`
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `initState(`, `setState`

Profile screens (`generated/screens/profile_screens/*_contract_test.dart`) — Batch 1

lets_go/test/generated/screens/profile_screens/profile_main_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expecte output
screens/profile_screens/profile_main_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_main_screen.dart`	Read source	non-empty
... → declares expected classes	Screen + State exist	Contains `ProfileMainScreen`, `_ProfileMainScreenState`	both tru
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `dispose(`, `initState(`, `setState(`	all true

lets_go/test/generated/screens/profile_screens/profile_edit_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expecte output
screens/profile_screens/profile_edit_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_edit_screen.dart`	Read source	non-empty
... → declares expected classes	Screen + State exist	Contains `ProfileEditScreen`, `_ProfileEditScreenState`	both true
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `dispose(`, `initState(`, `setState(`	all true

lets_go/test/generated/screens/profile_screens/profile_general_info_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
screens/profile_screens/profile_general_info_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_general_info_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `ProfileGeneralInf` `_ProfileGeneralIn`
... → contains expected callable symbols	Widget lifecycle/helper exists	Regex matches: `build` `docImage(`, `initStat`

lets_go/test/generated/screens/profile_screens/profile_contact_change_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
screens/profile_screens/profile_contact_change_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_contact_change_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `ProfileContac` `_ProfileConta`
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `b` `initState(`, `se`

lets_go/test/generated/screens/profile_screens/profile_blocked_users_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
screens/profile_screens/profile_blocked_users_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_blocked_users_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `ProfileBlockedU` `_ProfileBlocked`
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `bui` `initState(`, `setSt`

lets_go/test/generated/screens/profile_screens/profile_cnic_edit_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
screens/profile_screens/profile_cnic_edit_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_cnic_edit_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `ProfileCnicEditScreen`, `_ProfileCnicEditScreenS`
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `dispose(`, `initState(`, `setState(`

Profile screens (`generated/screens/profile_screens/*_contract_test.dart`) — Batch 2

lets_go/test/generated/screens/profile_screens/profile_driving_license_edit_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
...profile_driving_license_edit_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_driving_license_edit_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `ProfileDrivingLicense` `_ProfileDrivingLicens`
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `di` `initState(`, `setState(`

lets_go/test/generated/screens/profile_screens/profile_emergency_contact_edit_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
...profile_emergency_contact_edit_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_emergency_contact_edit_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `ProfileEmergency` `_ProfileEmergen`
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `bui` `setState(`

lets_go/test/generated/screens/profile_screens/profile_photos_edit_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expec outpu
...profile_photos_edit_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_photos_edit_screen.dart`	Read source	non-empty
... → declares expected classes	Screen + State exist	Contains `ProfilePhotosEditScreen`, `_ProfilePhotosEditScreenState`	both t
... → contains expected callable symbols	Widget rendering/state exists	Regex matches: `build(`, `setState(`	both t

lets_go/test/generated/screens/profile_screens/profile_change_password_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
...profile_change_password_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_change_password_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `ProfileChangePasswordScreen`, `_ProfileChangePasswordScreen`
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `dispose(`, `setState(`

lets_go/test/generated/screens/profile_screens/profile_bank_info_edit_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
...profile_bank_info_edit_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_bank_info_edit_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `ProfileBankInfoEditScreen`, `_ProfileBankInfoEditScreenState`
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `dispose(`, `initState(`, `setState(`

lets_go/test/generated/screens/profile_screens/profile_ride_history_detail_screen_contract_test.dart

Test case	Function/unit under test	Input / setup

Test case	Function/unit under test	Input / setup
...profile_ride_history_detail_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_ride_history_detail_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `ProfileRideHistoryDetai` `_ProfileRideHistoryDeta`

lets_go/test/generated/screens/profile_screens/booked_ride_history_detail_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
...booked_ride_history_detail_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/booked_ride_history_detail_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `BookedRideHistoryDetail` `_BookedRideHistoryDetai`
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `init` `setState(`

lets_go/test/generated/screens/profile_screens/created_ride_history_detail_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
...created_ride_history_detail_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/created_ride_history_detail_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `CreatedRideHistoryDeta` `_CreatedRideHistoryDet`
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `ini` `setState(`

Profile screens (`generated/screens/profile_screens/*_contract_test.dart`) — Remaining files

From the folder listing, the **remaining not-yet-tabulated** profile screen contract tests are:

- profile_ride_history_screen_contract_test.dart
- profile_screen_contract_test.dart
- profile_vehicle_info_screen_contract_test.dart
- vehicle_detail_screen_contract_test.dart
- vehicle_form_screen_contract_test.dart

(Everything else in that `profile_screens` folder was already tabulated in earlier batches.)

lets_go/test/generated/screens/profile_screens/profile_ride_history_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Exp out
...profile_ride_history_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_ride_history_screen.dart`	Read source	nor em
... → declares expected classes	Screen + State exist	Contains `ProfileRideHistoryScreen`, `_ProfileRideHistoryScreenState`	bot

Test case	Function/unit under test	Input / setup	Exp out
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `dispose(`, `initState(`, `setState(`	all t

lets_go/test/generated/screens/profile_screens/profile_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Status
...profile_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_screen.dart`	Read source	non-empty	PASS	
... → declares expected classes	`ProfileScreen` exists	Contains `class ProfileScreen`	true	PASS	
... → contains expected callable symbols	Widget build exists	Regex matches: `build(`	true	PASS	

lets_go/test/generated/screens/profile_screens/profile_vehicle_info_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Exp out
...profile_vehicle_info_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/profile_vehicle_info_screen.dart`	Read source	nor em
... → declares expected classes	Screen + State exist	Contains `ProfileVehicleInfoScreen`, `_ProfileVehicleInfoScreenState`	bot
... → contains expected callable symbols	Widget lifecycle/helper exists	Regex matches: `build(`, `dispose(`, `docImage(`, `initState(`, `setState(`	all t

lets_go/test/generated/screens/profile_screens/vehicle_form_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)	Stat
...vehicle_form_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/vehicle_form_screen.dart`	Read source	non-empty	PASS	
... → declares expected classes	Screen + State exist	Contains `VehicleFormScreen`, `_VehicleFormScreenState`	both true	PASS	
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `dispose(`, `initState(`, `setState(`	all true	PASS	

lets_go/test/generated/screens/profile_screens/vehicle_detail_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)
...vehicle_detail_screen.dart contract → source file is non-empty	Contract for `lib/screens/profile_screens/vehicle_detail_screen.dart`	Read source	non-empty	PASS

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)
... → declares expected classes	Screen + State exist	Contains `VehicleDetailScreen`, `_VehicleDetailScreenState`	both true	PASS
...vehicle_detail_screen.dart contract → contains expected callable symbols	UI helper methods exist	Regex matches: `build(`, `hasMeaningfulData(`, `infoRow(`, `initState(`, `setState(`, `statusColor(`	all true	PASS

lets_go/test/generated/screens/ride_booking_screens/ride_request_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted in test)
...ride_request_screen.dart contract → source file is non-empty	Contract for `lib/screens/ride_booking_screens/ride_request_screen.dart`	Read source	non-empty	PASS
... → declares expected classes	Screen + State exist	Contains `RideRequestScreen`, `_RideRequestScreenState`	both true	PASS
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `dispose(`, `initState(`, `setState(`	all true	PASS

lets_go/test/generated/screens/ride_booking_screens/driver_requests_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output
...driver_requests_screen.dart contract → source file is non-empty	Contract for `lib/screens/ride_booking_screens/driver_requests_screen.dart`	Read source	non-empty
... → declares expected classes	Screen + State exist	Contains `DriverRequestsScreen`, `_DriverRequestsScreenState`	both true
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `initState(`, `setState(`	all true

lets_go/test/generated/screens/ride_booking_screens/ride_details_view_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expect output
...ride_details_view_screen.dart contract → source file is non-empty	Contract for `lib/screens/ride_booking_screens/ride_details_view_screen.dart`	Read source	non-empty
... → declares expected classes	Screen + State exist	Contains `RideDetailsViewScreen`, `_RideDetailsViewScreenState`	both tr
... → contains expected callable symbols	Widget lifecycle exists	Regex matches: `build(`, `dispose(`, `initState(`, `setState(`	all true

lets_go/test/generated/screens/ride_booking_screens/ride_booking_details_screen_contract_test.dart

Test case	Function/unit under test	Input / setup
...ride_booking_details_screen.dart contract → source file is non-empty	Contract for `lib/screens/ride_booking_screens/ride_booking_details_screen.dart`	Read source
... → declares expected classes	Screen + State exist	Contains `RideBookingDetailsScreen`, `_RideBookingDetailsScreenStat`
... → contains expected callable symbols	Widget/build helpers exist	Regex matches: `Builder(`, `build(`, `dispose(`, `initState(`, `setState(`

lets_go/test/generated/screens/ride_booking_screens/negotiation_details_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output
...negotiation_details_screen.dart contract → source file is non-empty	Contract for `lib/screens/ride_booking_screens/negotiation_details_screen.dart`	Read `source`	non-empty
... → declares expected classes	`NegotiationDetailsScreen`, `_NegotiationDetailsScreenState`	`source.contains(...)`	true
... → contains expected callable symbols	lifecycle	regex matches `build(`, `dispose(`, `initState(`, `setState(`	all true

lets_go/test/generated/screens/ride_booking_screens/passenger_response_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)
...passenger_response_screen.dart contract → source file is non-empty	`lib/screens/ride_booking_screens/passenger_response_screen.dart`	Read source	non-empty	asserted true
... → declares expected classes	`PassengerResponseScreen`, `_PassengerResponseScreenState`	contains	true	asserted true
... → contains expected callable symbols	lifecycle	`build(`, `dispose(`, `initState(`, `setState(`	all true	PASS

lets_go/test/generated/screens/ride_booking_screens/request_response_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Sta
...request_response_screen.dart contract → source file is non-empty	`lib/screens/ride_booking_screens/request_response_screen.dart`	Read source	non-empty	asserted true	PA
... → declares expected classes	`RequestResponseScreen`, `_RequestResponseScreenState`	contains	true	asserted true	PA
... → contains expected callable symbols	lifecycle	`build(`, `dispose(`, `initState(`, `setState(`	all true	PASS	

lets_go/test/generated/screens/ride_posting_screens/create_route_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status
...create_route_screen.dart contract → source file is non-empty	`lib/screens/ride_posting_screens/create_route_screen.dart`	Read source	non-empty	asserted true	PASS
... → declares expected classes	`CreateRouteScreen`, `_CreateRouteScreenState`	contains	true	asserted true	PASS
... → contains expected callable symbols	lifecycle + helper	`build(`, `dispose(`, `initState(`, `setState(`, `toInt(`	all true	PASS	

lets_go/test/generated/screens/ride_posting_screens/create_ride_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status
...create_ride_screen.dart contract → source file is non-empty	`lib/screens/ride_posting_screens/create_ride_screen.dart`	Read source	non-empty	asserted true	PASS
... → declares expected classes	`CreateRideScreen`, `_CreateRideScreenState`	contains	true	asserted true	PASS
... → contains expected callable symbols	lifecycle	`build(`, `dispose(`, `initState(`, `setState(`	all true	PASS	

lets_go/test/generated/screens/ride_posting_screens/create_ride_details_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)
...create_ride_details_screen.dart contract → source file is non-empty	`lib/screens/ride_posting_screens/create_ride_details_screen.dart`	Read source	non-empty	asserted true
... → declares expected classes	`RideDetailsScreen`, `_RideDetailsScreenState`	contains	true	asserted true
... → contains expected callable symbols	lifecycle + helper	`build(`, `dispose(`, `initState(`, `setState(`, `toInt(`	all true	PASS

lets_go/test/generated/screens/ride_posting_screens/my_rides_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status
...my_rides_screen.dart contract → source file is non-empty	`lib/screens/ride_posting_screens/my_rides_screen.dart`	Read source	non-empty	asserted true	PASS
... → declares expected classes	`MyRidesScreen`, `_MyRidesScreenState`	contains	true	asserted true	PASS
... → contains expected callable symbols	lifecycle + numeric helper	`asInt(`, `build(`, `dispose(`, `initState(`, `setState(`	all true	PASS	

lets_go/test/generated/screens/ride_posting_screens/ride_edit_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status
...ride_edit_screen.dart contract → source file is non-empty	`lib/screens/ride_posting_screens/ride_edit_screen.dart`	Read source	non-empty	asserted true	PASS
... → declares expected classes	`RideEditScreen`, `_RideEditScreenState`	contains	true	asserted true	PASS
... → contains expected callable symbols	lifecycle	`build(`, `initState(`, `setState(`	all true	PASS	

lets_go/test/generated/screens/ride_posting_screens/ride_view_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status
...ride_view_screen.dart contract → source file is non-empty	`lib/screens/ride_posting_screens/ride_view_screen.dart`	Read source	non-empty	asserted true	PASS
... → declares expected classes	`RideViewScreen` exists	contains `class RideViewScreen`	true	PASS	
... → contains expected callable symbols	numeric + builder helpers	`asNum(`, `asNumLocal(`, `build(`, `mk(`, `sumNum(`	all true	PASS	

lets_go/test/generated/screens/ride_posting_screens/booking_detail_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Ac ou (as
...booking_detail_screen.dart contract → source file is non-empty	`lib/screens/ride_posting_screens/booking_detail_screen.dart`	Read source	non-empty	ass tru
... → declares expected classes	`BookingDetailScreen` exists	contains `class BookingDetailScreen`	true	PA
... → contains expected callable symbols	booking helper functions exist	`asInt(`, `asNum(`, `build(`, `canCancelBooking(`, `cancelBooking(`, `isWithinPassengerSegment(`, `mk(`, `normalizePaymentStatus(`, `toInt(`	all true	PA

lets_go/test/generated/screens/signup_login_screens/login_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status
...login_screen.dart contract → source file is non-empty	`lib/screens/signup_login_screens/login_screen.dart`	Read source	non-empty	asserted true	PASS
... → declares expected classes	`LoginScreen`, `LoginScreenState`	contains	true	PASS	
... → contains expected callable symbols	lifecycle	`build(`, `dispose(`, `initState(`, `setState(`	all true	PASS	

lets_go/test/generated/screens/signup_login_screens/forgot_password_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Statu
...forgot_password_screen.dart contract → source file is non-empty	`lib/screens/signup_login_screens/forgot_password_screen.dart`	Read source	non-empty	PASS	
... → declares expected classes	`ForgotPasswordScreen`, `_ForgotPasswordScreenState`	contains	true	PASS	
... → contains expected callable symbols	lifecycle	`build(`, `dispose(`, `initState(`, `setState(`	all true	PASS	

lets_go/test/generated/screens/signup_login_screens/otp_verification_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Act out (as
...otp_verification_screen.dart contract → source file is non-empty	`lib/screens/signup_login_screens/otp_verification_screen.dart`	Read source	non-empty	PA
... → declares expected classes	`OTPVerificationScreen`, `_OTPVerificationScreenState`	contains	true	PA
... → contains expected callable symbols	lifecycle + dep hook	`build(`, `didChangeDependencies(`, `dispose(`, `initState(`	all true	PA

lets_go/test/generated/screens/signup_login_screens/otp_verification_reset_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actu outp (asse
...otp_verification_reset_screen.dart contract → source file is non-empty	`lib/screens/signup_login_screens/otp_verification_reset_screen.dart`	Read source	non-empty	PASS
... → declares expected classes	`OTPVerificationResetScreen`, `_OTPVerificationResetScreenState`	contains	true	PASS
... → contains expected callable symbols	lifecycle	`build(`, `dispose(`, `initState(`, `setState(`	all true	PASS

lets_go/test/generated/screens/signup_login_screens/register_pending_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	A o (a
...register_pending_screen.dart contract → source file is non-empty	`lib/screens/signup_login_screens/register_pending_screen.dart`	Read source	non-empty	P
... → declares expected classes	`RegisterPendingScreen`, `_RegisterPendingScreenState`	contains	true	P
... → contains expected callable symbols	lifecycle + data push methods	`build(`, `didChangeDependencies(`, `putEmergency(`, `putPersonal(`, `setState(`	all true	P

lets_go/test/generated/screens/signup_login_screens/reset_password_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status
...reset_password_screen.dart contract → source file is non-empty	`lib/screens/signup_login_screens/reset_password_screen.dart`	Read source	non-empty	PASS	

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status
... → declares expected classes	`ResetPasswordScreen`, `_ResetPasswordScreenState`	contains	true	PASS	
... → contains expected callable symbols	lifecycle	`build(`, `dispose(`, `initState(`	all true	PASS	

lets_go/test/generated/screens/signup_login_screens/signup_cnic_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status
...signup_cnic_screen.dart contract → source file is non-empty	`lib/screens/signup_login_screens/signup_cnic_screen.dart`	Read source	non-empty	PASS	
... → declares expected classes	`SignupCnicScreen`, `_SignupCnicScreenState`	contains	true	PASS	
... → contains expected callable symbols	lifecycle	`build(`, `initState(`, `setState(`	all true	PASS	

lets_go/test/generated/screens/signup_login_screens/signup_emergency_contact_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output
...signup_emergency_contact_screen.dart contract → source file is non-empty	`lib/screens/signup_login_screens/signup_emergency_contact_screen.dart`	Read source	non-empty
... → declares expected classes	`SignupEmergencyContactScreen`, `_SignupEmergencyContactScreenState`	contains	true
... → contains expected callable symbols	lifecycle	`build(`, `dispose(`, `initState(`, `setState(`	all true

lets_go/test/generated/screens/signup_login_screens/signup_personal_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Statu
...signup_personal_screen.dart contract → source file is non-empty	`lib/screens/signup_login_screens/signup_personal_screen.dart`	Read source	non-empty	PASS	
... → declares expected classes	`SignupPersonalScreen`, `_SignupPersonalScreenState`, `_UsernameLtrFormatter`	contains	true	PASS	
... → contains expected callable symbols	lifecycle	`build(`, `dispose(`, `initState(`, `setState(`	all true	PASS	

lets_go/test/generated/screens/signup_login_screens/signup_vehicle_screen_contract_test.dart

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status
...signup_vehicle_screen.dart contract → source file is non-empty	`lib/screens/signup_login_screens/signup_vehicle_screen.dart`	Read source	non-empty	PASS	
... → declares expected classes	`SignupVehicleScreen`, `_SignupVehicleScreenState`	contains	true	PASS	

Test case	Function/unit under test	Input / setup	Expected output	Actual output (asserted)	Status
... → contains expected callable symbols	lifecycle	`build(`, `initState(`, `setState(`	all true	PASS	