

LẬP TRÌNH C CƠ BẢN

Danh sách tuyến tính

Nội dung

- Cài đặt danh sách liên kết đơn
- Cài đặt danh sách liên kết đôi



Bài tập quản lý hồ sơ sinh viên

- Hồ sơ sinh viên bao gồm:
 - name: tên của sinh viên
 - email: địa chỉ email của sinh viên
- Viết chương trình trong chế độ tương tác dòng lệnh thực hiện các nghiệp vụ cơ bản trong quản lý hồ sơ sinh viên
 - Đọc dữ liệu từ file văn bản vào danh sách
 - In danh sách sinh viên
 - Thêm 1 hồ sơ vào cuối danh sách
 - Xóa 1 hồ sơ
 - Tìm kiếm hồ sơ
 - Lưu hồ sơ vào file văn bản



Khai báo dữ liệu

```
#include <stdio.h>
#define MAX L 256
typedef struct Profile{
    char name[MAX_L];
    char email[MAX L];
    struct Profile* next;
}Profile;
Profile* first, *last;
```



```
Profile* makeProfile(char* name, char* email){
    Profile* node = (Profile*)malloc(sizeof(Profile));
    strcpy(node->name,name);
    strcpy(node->email,email);
    node->next = NULL;
    return node;
}
void initList(){
    first = NULL; last = NULL;
int listEmpty(){
    return first == NULL && last == NULL;
}
```



```
void insertLast(char* name, char* email){
    Profile* profile = makeProfile(name,email);
    if(listEmpty()){
            first = profile; last = profile;
    }else{
        last->next = profile; last = profile;
}
void printList(){
    for(Profile* p = first; p != NULL; p = p->next)
        printf("%s, %s\n",p->name, p->email);
}
```



```
Profile* removeProfile(Profile* f, char* name){
    if(listEmpty()) return NULL;
    if(strcmp(f->name,name) == 0){
        Profile* tmp = f->next;
        free(f);
        if(tmp == NULL) last = NULL;
        return tmp;
    }else{
        f->next = removeProfile(f->next,name);
        return f;
}
```



```
void load(char* filename){
    FILE* f = fopen(filename, "r");
    if(f == NULL) printf("Load data -> file not found\n");
    while(!feof(f)){
        char name[256], email[256];
        fscanf(f, "%s%s", name, email);
        insertLast(name,email);
    fclose(f);
}
```



```
void processFind(){
    char name[256];
    scanf("%s",name);
    Profile* profile = NULL;
    for(Profile* p = first; p != NULL; p = p->next){
        if(strcmp(p->name,name)==0){
            profile = p; break;
    }
    if(profile == NULL){
        printf("NOT FOUND profile %s\n",name);
    }else{
        printf("FOUND profile %s, %s\n",profile->name,profile->email);
```



```
void processLoad(){
  char filename[256];
  scanf("%s",filename);
  load(filename);
}
void processStore(){
  char filename[256];
  scanf("%s",filename);
  FILE* f = fopen(filename, "w");
  for(Profile* p = first; p != NULL; p = p->next){
        fprintf(f, "%s %s",p->name,p->email);
        if(p->next != NULL) fprintf(f,"\n");
  fclose(f);
```



```
void processInsert(){
    char name[256], email[256];
    scanf("%s%s",name,email);
    insertLast(name,email);
}

void processRemove(){
    char name[256];
    scanf("%s",name);
    first = removeProfile(first,name);
}
```



```
int main(){
    initList();
    while(1){
        printf("Enter command: ");
        char cmd[256];
        scanf("%s",cmd);
        if(strcmp(cmd, "Quit") == 0) break;
        else if(strcmp(cmd, "Load") == 0) processLoad();
        else if(strcmp(cmd, "Print") == 0) printList();
        else if(strcmp(cmd, "Find") == 0) processFind();
        else if(strcmp(cmd, "Insert") == 0) processInsert();
        else if(strcmp(cmd, "Remove") == 0) processRemove();
        else if(strcmp(cmd, "Store") == 0) processStore();
```



• Định nghĩa cấu trúc dữ liệu

```
#include <stdio.h>
#define MAX L 256
typedef struct Profile{
    char name[MAX L];
    char email[MAX_L];
    struct Profile* next;// pointer to the next element
    struct Profile* prev;// pointer to the predecessor
}Profile;
Profile* first, *last;
```



```
Profile* makeProfile(char* name, char* email){
    Profile* node = (Profile*)malloc(sizeof(Profile));
    strcpy(node->name,name);
    strcpy(node->email,email);
    node->next = NULL;
    node->prev = NULL;
    return node;
```



```
void initList(){
    first = NULL; last = NULL;
int listEmpty(){
    return first == NULL && last == NULL;
}
void printListLeft2Right(){
    for(Profile* p = first; p != NULL; p = p->next)
        printf("%s, %s\n",p->name, p->email);
}
void printListRight2Left(){
    for(Profile* p = last; p != NULL; p = p->prev)
        printf("%s, %s\n",p->name, p->email);
}
```



```
void insertLast(char* name, char* email){
    Profile* profile = makeProfile(name,email);
    if(listEmpty()){
        first = profile; last = profile;
    }else{
        last->next = profile; profile->prev = last;
        last = profile;
    }
}
```



```
Profile* find(char*name){
    for(Profile* p = first; p != NULL; p = p->next){
        if(strcmp(p->name,name)==0){
            return p;
        }
    }
    return NULL;
}
```



```
void removeProfile(char* name){
    if(listEmpty()) return NULL;
    Profile* profile = find(name);
    if(profile == NULL){
        printf("NOT FOUND %s\n",name);
    }else{
        Profile* left = profile->prev;
        Profile* right = profile->next;
        if(left != NULL) left->next = right;
        if(right != NULL) right->prev = left;
        if(left == NULL) first = right;
        if(right == NULL) last = left;
        free(profile);
```

```
void load(char* filename){
    FILE* f = fopen(filename, "r");
    if(f == NULL) printf("Load data -> file not found\n");
    initList();
    while(!feof(f)){
        char name[256], email[256];
        fscanf(f, "%s%s", name, email);
        insertLast(name,email);
        printf("insert %s, %s\n",name,email);
    fclose(f);
```



```
void processFind(){
    char name[256];
    scanf("%s",name);
    Profile* profile = find(name);
    if(profile == NULL){
        printf("NOT FOUND profile %s\n",name);
    }else{
        printf("FOUND profile %s, %s\n",profile->name,profile->email);
    }
}
```



```
void processLoad(){
  char filename[256];
  scanf("%s",filename);
  load(filename);
void processStore(){
  char filename[256];
  scanf("%s",filename);
  FILE* f = fopen(filename, "w");
  for(Profile* p = first; p != NULL; p = p->next){
        fprintf(f,"%s %s",p->name,p->email);
        if(p->next != NULL) fprintf(f,"\n");
  }
  fclose(f);
```

```
void processInsert(){
    char name[256], email[256];
    scanf("%s%s",name,email);
    insertLast(name,email);
}

void processRemove(){
    char name[256];
    scanf("%s",name);
    removeProfile(name);
}
```



```
void processPrintList(){
    printf("Danh sach tu trai qua phai\n");
    printListLeft2Right();
    printf("Danh sach tu phai qua trai\n");
    printListRight2Left();
}
void finalize(){
    Profile* p = first;
    while(p != NULL){
        Profile* np = p->next;
        free(p);
        p = np;
```



```
int main(){
    initList();
    while(1){
        printf("Enter command: ");
        char cmd[256];
        scanf("%s",cmd);
        if(strcmp(cmd,"Quit")==0) break;
        else if(strcmp(cmd, "Load") == 0) processLoad();
        else if(strcmp(cmd, "Print") == 0) processPrintList();
        else if(strcmp(cmd, "Find") == 0) processFind();
        else if(strcmp(cmd, "Insert") == 0) processInsert();
        else if(strcmp(cmd, "Remove") == 0) processRemove();
        else if(strcmp(cmd, "Store")==0) processStore();
    }
    finalize();
}
```