

# Assessing Covid-19 Situation in Vietnam Using a Data-Driven Epidemiological Compartmental Model

Vo Le Tung

Assessor: Assoc. Prof. Huynh Trung Hieu

Co-Assessor: Assoc. Prof. Nguyen Tuan Duc

Vietnamese - German University  
Frankfurt University of Applied Sciences

January 26, 2022

# Outline

- 1 Introduction
- 2 Literature review
- 3 Methodologies
- 4 Results
- 5 Discussion
- 6 Conclusion

# Outline for Introduction

## 1 Introduction

# The Covid-19 disease

- Health impacts
  - 230 million global infections
  - 4.7 million global deaths

# The Covid-19 disease

- Health impacts
  - 230 million global infections
  - 4.7 million global deaths
- Economic impacts
  - Delayed shipments
  - Increased transaction cost

# Why do we need a Covid-19 model?

- Lack of research on the impacts of Non-Pharmaceutical Intervention (NPI) in Vietnam

# Why do we need a Covid-19 model?

- Lack of research on the impacts of Non-Pharmaceutical Intervention (NPI) in Vietnam
- Need of a simple tool for assessing the disease current and future progression

# Goals

- A model that works with the data availability in Vietnam



# Goals

- A model that works with the data availability in Vietnam
- An explainable model that can be used by experts

# Goals

- A model that works with the data availability in Vietnam
- An explainable model that can be used by experts
- Assess the effectiveness of mobility data in predicting future cases

# Outline for Literature review

- 2 Literature review
  - Related works
  - Artificial neural networks

# Mathematical models: Compartmental

## Susceptible-Exposed-Infective-Removed (SEIR) model [1]

$$S' = -\beta(N)SI$$

$$E' = \beta(N)SI - \kappa E$$

$$I' = \kappa E - \alpha I$$

$$R' = f\alpha I$$

$$N' = -(1 - f)\alpha I$$






Figure: States graph for the SEIR model

# Mathematical models: Agent-based



(a) Transmission networks



(b) States graph

Figure: Covasim model [2]

# Mathematical models: Pros & cons

## Pros

- Explainable
- Based on many years of research
- Easy to understand and implement

# Mathematical models: Pros & cons

## Pros

- Explainable
- Based on many years of research
- Easy to understand and implement

## Cons

- Low representational capabilities
- The represented dynamics are stationary
- Unrealistic assumptions about real-world scenarios

# Data-driven models

- Autoregressive Integrated Moving Average (ARIMA) models [3]–[5]



# Data-driven models

- Autoregressive Integrated Moving Average (ARIMA) models [3]–[5]
- Explainable Artificial Neural Network (ANN) encoder [6]

# Data-driven models

- Autoregressive Integrated Moving Average (ARIMA) models [3]–[5]
- Explainable Artificial Neural Network (ANN) encoder [6]
- Recurrent Neural Network (RNN) [7], [8]
  - Long Short Term Memory (LSTM)
  - Bidirectional Long Short Term Memory (Bi-LSTM)
  - Gated Recurrent Unit (GRU)

# Data-driven models: Pros & cons

## Pros

- High prediction accuracy
- Allow for modeling without needing domain knowledge

# Data-driven models: Pros & cons

## Pros

- High prediction accuracy
- Allow for modeling without needing domain knowledge

## Cons

- Unexplainable
- Relied on large amount of data
- Inability to capture the true disease dynamics

## Novel compartmental models: Using mobility data






Figure: SEIR model informed with mobility data [9]

# Novel compartmental models: Using neural networks



(a) QSIR [10]



(b) Time-dependent SIR [11]

**Figure:** Predict the parameters of compartmental models with Artificial Neural Networks (ANNs)

# Multi-layer perceptron: Graph representation




Figure: A Multi-Layer Perceptron (MLP) with four layers

# Multi-layer perceptron: Mathematical representation

## Definition

$$g(X) = \phi_n(W_n \phi_{n-1}(\cdots (W_2 \phi_1(W_1 X + b_1) + b_2) + \cdots) + b_n)$$



# Multi-layer perceptron: Mathematical representation

## Definition

$$g(X) = \phi_n(W_n \phi_{n-1}(\cdots (W_2 \phi_1(W_1 X + b_1) + b_2) + \cdots) + b_n)$$

## Theorem

*Given appropriate weights, ANNs can approximate any arbitrary function  $f : \mathbb{R}^M \rightarrow \mathbb{R}^N$  [12]–[14]*

# Training neural networks: Back-propagation

## Mean Squared Error (MSE)

$$\mathcal{L} = \frac{1}{N} \sum_{i=1}^N (g(X_i) - Y_i)^2$$





Figure: Graph representation of the back-propagation algorithm

# Physics-informed neural networks



**Figure:** The schematic of Physics-Informed Neural Networks (PINNs) for solving Partial Differential Equations (PDEs) [15].

# Neural ordinary differential equations: Idea




Figure: Skip connection

# Neural ordinary differential equations: Idea




Figure: Skip connection

## Observation

$$h_{t+1} = h_t + f(h_t, \theta_t)$$
$$\Leftrightarrow \frac{dh(t)}{dt} = f(h(t), t, \theta)$$

# Neural ordinary differential equations: Formulation

Neural Ordinary Differential Equation (NeuralODE) output

$$z(t_1) = z(t_0) + \int_{t_0}^{t_1} f(z(t), t, \theta) dt$$

# Neural ordinary differential equations: Formulation

## Neural Ordinary Differential Equation (NeuralODE) output

$$z(t_1) = z(t_0) + \int_{t_0}^{t_1} f(z(t), t, \theta) dt$$

- Memory efficiency

# Neural ordinary differential equations: Formulation

## Neural Ordinary Differential Equation (NeuralODE) output

$$z(t_1) = z(t_0) + \int_{t_0}^{t_1} f(z(t), t, \theta) dt$$

- Memory efficiency
- Adaptive computation



# Neural ordinary differential equations: Formulation

## Neural Ordinary Differential Equation (NeuralODE) output

$$z(t_1) = z(t_0) + \int_{t_0}^{t_1} f(z(t), t, \theta) dt$$

- Memory efficiency
- Adaptive computation
- Scalable and invertible normalizing flows


# Neural ordinary differential equations: Formulation

## Neural Ordinary Differential Equation (NeuralODE) output


$$z(t_1) = z(t_0) + \int_{t_0}^{t_1} f(z(t), t, \theta) dt$$

- Memory efficiency
- Adaptive computation
- Scalable and invertible normalizing flows
- Continuous time series models

# Neural ordinary differential equations: Outputs




(a) ResNet



(b) NeuralODE

**Figure:** Comparison between ResNet's discrete state transformations and Neural Ordinary Differential Equation (NeuralODE) continuous state transformations

# Neural ordinary differential equations: Gradients



**Figure:** Reverse-mode differentiation of an Ordinary Differential Equation (ODE) solution. [16]

# Outline for Methodologies

- 3 Methodologies
  - Model definition
  - Datasets
  - Parameters estimation
  - Experiments

# Universal differential equation

Universal Differential Equation (UDE) [17] is a neural network architecture based on NeuralODE

## Definition

$$u' = f(u, t, U_{\theta}(u, t))$$

# System of ODEs

## Definition

$$S' = -\frac{\beta(t)SI}{N}$$

$$E' = \frac{\beta(t)SI}{N} - \gamma E$$

$$I' = \gamma E - \lambda I$$

$$R' = (1 - \alpha(t)) * \lambda * I$$

$$D' = \alpha(t) * \lambda * I$$

$$N' = -\alpha * \lambda * I$$

$$C' = -C + \gamma * E$$

$$T' = \gamma * E$$

# System parameters

## Box constraints for time-independent parameters

$$\gamma = \gamma_L + (\gamma_U - \gamma_L) * \sigma(\gamma')$$

$$\lambda = \lambda_L + (\lambda_U - \lambda_L) * \sigma(\lambda')$$



# System parameters

## Box constraints for time-independent parameters

$$\gamma = \gamma_L + (\gamma_U - \gamma_L) * \sigma(\gamma')$$

$$\lambda = \lambda_L + (\lambda_U - \lambda_L) * \sigma(\lambda')$$

## Neural networks for time-dependent parameters

$$\beta(t) = \mathcal{NN}_{\theta_1}(\mathcal{F})$$

$$\alpha(t) = \mathcal{NN}_{\theta_2}\left(\frac{t}{t_{\max}}, \frac{I(t-1)}{N(t-1)}, \frac{R(t-1)}{N(t-1)}, \frac{D(t-1)}{N(t-1)}\right)$$

- Hidden layers activation: mish [18]
- Output layer activation  $\nu_i = \nu_{i,L} + (\nu_{i,U} - \nu_{i,L}) * \sigma(z_i)$

# Neural network input features

1st. set of input features

$$\mathcal{F}_1(t) = \left\{ \frac{t}{t_{\max}}, \frac{S(t-1)}{N(t-1)}, \frac{E(t-1)}{N(t-1)}, \frac{I(t-1)}{N(t-1)} \right\}$$

# Neural network input features

## 1st. set of input features

$$\mathcal{F}_1(t) = \left\{ \frac{t}{t_{\max}}, \frac{S(t-1)}{N(t-1)}, \frac{E(t-1)}{N(t-1)}, \frac{I(t-1)}{N(t-1)} \right\}$$

## 2nd. set of input features

$$\mathcal{F}_2(t) = \mathcal{F}_1(t) \cup \{\text{MovementRange}(t)\}$$

# Neural network input features

## 1st. set of input features

$$\mathcal{F}_1(t) = \left\{ \frac{t}{t_{\max}}, \frac{S(t-1)}{N(t-1)}, \frac{E(t-1)}{N(t-1)}, \frac{I(t-1)}{N(t-1)} \right\}$$

## 2nd. set of input features

$$\mathcal{F}_2(t) = \mathcal{F}_1(t) \cup \{\text{MovementRange}(t)\}$$

## 3rd. set of input features

$$\mathcal{F}_3(t) = \mathcal{F}_2(t) \cup \{\text{SocialProximityToCases}(t)\}$$

# Covid-19 cases time series

date	infective	confirmed	recoveries	deaths
1/22/20	0	0	0	0
1/23/20	2	2	0	0
1/24/20	2	2	0	0
...	...	...	...	...

**Table:** Structure of the processed Covid-19 time series datasets

- John Hopkins University (JHU) Covid-19 public datasets
- *VNExpress* Covid-19 public dashboard
- *VnCDC* Covid-19 public dashboard

# Facebook's movement range maps dataset

ds	country	polygon	rel. change	stay put ratio
...	...	...	...	...
2021-01-01	VNM	VNM.1.10_1	0.125	0.270
2021-01-02	VNM	VNM.1.10_1	0.052	0.259
2021-01-03	VNM	VNM.1.10_1	0.185	0.269
...	...	...	...	...

**Table:** Structure of Facebook's Movement Range Maps (MRMs) dataset.

# Facebook's social connectedness index

## Social Connectedness Index (SCI)

$$SCI_{i,j} = \frac{\text{FB connections}_{i,j}}{\text{FB users}_i * \text{FB users}_j},$$

# Facebook's social connectedness index

## Social Connectedness Index (SCI)

$$SCI_{i,j} = \frac{\text{FB connections}_{i,j}}{\text{FB users}_i * \text{FB users}_j},$$

## Social Proximity to Cases (SPC) index [19]

$$SPC_{i,t} = \sum_j^C \text{Cases per } 10k_{j,t} \frac{SCI_{i,j}}{\sum_h^C SCI_{i,h}},$$



# Population data

ID_1	NAME_1	AVGPOPULATION
3	Ha Noi	8.2466e6
62	Vinh Phuc	1.1712e6
...	...	...
1001.0	Autauga, Alabama, US	55869
1003.0	Baldwin, Alabama, US	223234
...	...	...

**Table:** Structure of the processed average population datasets

- Vietnam General Statistics Office (GSO)
- JHU Covid-19 datasets

# Loss function

## Regularized MSE with scaled outputs

$$\mathcal{L}(\hat{y}, y) = \frac{1}{T} \sum_{i=1}^N \sum_{t=0}^{T-1} \left[ e^{\zeta t} \left( \frac{\hat{y}_{i,t} - y_{i,t}}{\max(y_i) - \min(y_i)} \right)^2 \right] + \frac{\lambda}{2T} (\|\theta_1\|_2^2 + \|\theta_2\|_2^2)$$

# Training process




Figure: Model training procedure

# Data preprocessing

- Applied 7-day moving average to all datasets
- Applied min-max scaling on the Movement Range Map (MRM) dataset and Social Proximity to Cases (SPC) index

# Data preprocessing

- Applied 7-day moving average to all datasets
- Applied min-max scaling on the Movement Range Map (MRM) dataset and Social Proximity to Cases (SPC) index
- Training period: 48 days
  - Vietnam: First date when the total confirmed cases passed 500
  - United States: 1st July 2021

# Data preprocessing

- Applied 7-day moving average to all datasets
- Applied min-max scaling on the Movement Range Map (MRM) dataset and Social Proximity to Cases (SPC) index
- Training period: 48 days
  - Vietnam: First date when the total confirmed cases passed 500
  - United States: 1st July 2021
- Testing period: 28 days

# Differential equation solver configurations

- Tsit5 solver (Tsitouras Runge-Kutta 5/4 method [20])
- InterpolatingAdjoint technique for approximating gradients in NeuralODE [21]

# Optimizer configurations

- Initial time span of 4 days
- Time span increment of 4 days



# Optimizer configurations

- Initial time span of 4 days
- Time span increment of 4 days
- Time weighting parameter  $\zeta = -0.001$

# Optimizer configurations

- Initial time span of 4 days
- Time span increment of 4 days
- Time weighting parameter  $\zeta = -0.001$
- ADAM optimizer
  - Learning rate 0.05
    - decay rate 0.5
    - decay step 1000
    - decay limit 0.00001
  - 1000 iterations on each time span

# Optimizer configurations

- Initial time span of 4 days
- Time span increment of 4 days
- Time weighting parameter  $\zeta = -0.001$
- ADAM optimizer
  - Learning rate 0.05
    - decay rate 0.5
    - decay step 1000
    - decay limit 0.00001
  - 1000 iterations on each time span
- BFGS optimizer
  - *Initial stepnorm* 0.01
  - 1000 iterations on the full time span

# Initial conditions

Location	$S(0)$	$E(0)$	$I(0)$	$R(0)$
Vietnam	9.75e7	25	5	2817
Ho Chi Minh city	9.22e6	173.5	34.7	360.1
Binh Duong	2.58e6	206.4	41.2	314.7
Dong Nai	3.17e6	295	59	194.8
Long An	1.71e6	217.8	43.5	300.5
United States	2.99e8	71890	14378	3.31e7
Los Angeles, California	8.78e6	2500	500	1.22e6
Cook, Illinois	4.59e6	615	123	546508
Harris, Texas	4.30e6	930	186	396430
Maricopa, Arizona	3.92e6	1325	265	549899

**Table:** Initial conditions for the system of ODEs

# Initial parameters

Parameter	Value	Lower bound	Upper bound
$\beta$	<i>N/A</i>	0.05	1.67
$\gamma$	1/4	1/4	1/4
$\lambda$	1/14	1/14	1/14
$\alpha$	<i>N/A</i>	0.005	0.05
$\theta_1$	<i>glorot_normal</i>	<i>N/A</i>	<i>N/A</i>
$\theta_2$	<i>glorot_normal</i>	<i>N/A</i>	<i>N/A</i>

**Table:** Initial parameters for the system of ODEs

# Outline for Results

## 4 Results

- Model's outputs for Vietnam and the United States
- Model's outputs for counties in the United States
- Model's outputs for provinces in Vietnam

Model's outputs for Vietnam and the United States

# Forecasts: Country-level data








Figure: Forecasts made by different versions of the model

# $R_0$ and fatality rate: Country-level data



(a) Viet nam



(b) United States

Figure: Disease metrics learned by different versions of the model



# MAPE: Country-level data




Figure: MAPE for 28-day forecast horizon

Model's outputs for counties in the United States

# Forecasts: Counties in the United States





Figure: Forecasts made by different versions of the model


Model's outputs for counties in the United States

# $R_0$ and fatality rate: Counties in the United States



(a) Harris, TX

(b) Los Angeles, CA



(c) Maricopa, AZ

(d) Cook, IL

Figure: Disease metrics learned by different versions of the model

Model's outputs for counties in the United States

# MAPE: Counties in the United States




Figure: MAPE for 28-day forecast horizon

Model's outputs for provinces in Vietnam

# Forecasts: Provinces in Vietnam








Figure: Forecasts made by different versions of the model

Model's outputs for provinces in Vietnam



# $R_0$ and fatality rate: Provinces in Vietnam





(a) Dong Nai



(b) Long An



(c) Binh Duong



(d) Ho Chi Minh city

Figure: Disease metrics learned by different versions of the model

Model's outputs for provinces in Vietnam

# MAPE: Provinces in Vietnam




Figure: MAPE for 28-day forecast horizon

# Outline for Discussion

## 5 Discussion

- Model's convergence and generalizability
- Model's limitations



# About the results

- Could capture the disease trends with high accuracy

# About the results

- Could capture the disease trends with high accuracy
- Accuracy get lower as we extrapolated further into the future

# About the results

- Could capture the disease trends with high accuracy
- Accuracy get lower as we extrapolated further into the future
- Bad fit and low forecast accuracy when applied to data with high fluctuation

# About the results

- Could capture the disease trends with high accuracy
- Accuracy get lower as we extrapolated further into the future
- Bad fit and low forecast accuracy when applied to data with high fluctuation
- No improvement in the forecast accuracy when mobility data was incorporated

# Model's convergence and generalizability

- The model could get stuck in bad local minima, due to
  - ODEs *stiffness*
  - High frequency changes

# Model's convergence and generalizability

- The model could get stuck in bad local minima, due to
  - ODEs *stiffness*
  - High frequency changes
- The model was separately trained at each location and only capable of making forecast for the location that it was trained with

# Model's convergence and generalizability

- The model could get stuck in bad local minima, due to
  - ODEs *stiffness*
  - High frequency changes
- The model was separately trained at each location and only capable of making forecast for the location that it was trained with
- Forecast can only be made for a short period after the training period

# Model's limitations

- Issues with ground truth data



# Model's limitations

- Issues with ground truth data
- Inability to capture rapid trend changes

# Model's limitations

- Issues with ground truth data
- Inability to capture rapid trend changes
- Bad local minima

# Model's limitations

- Issues with ground truth data
- Inability to capture rapid trend changes
- Bad local minima
- Compartmental model bias

# Model's limitations

- Issues with ground truth data
- Inability to capture rapid trend changes
- Bad local minima
- Compartmental model bias
- Covariates bias

# Model's limitations

- Issues with ground truth data
- Inability to capture rapid trend changes
- Bad local minima
- Compartmental model bias
- Covariates bias
- Inability to capture real dynamics of the disease

# Model's limitations

- Issues with ground truth data
- Inability to capture rapid trend changes
- Bad local minima
- Compartmental model bias
- Covariates bias
- Inability to capture real dynamics of the disease
- Neural network interpretability

# Outline for Conclusion

## 6 Conclusion

# What has been done?

**Goals:** An explainable Covid-19 model that can work with the low data availability in Vietnam



# What has been done?

**Goals:** An explainable Covid-19 model that can work with the low data availability in Vietnam

- Collect and process Covid-19 related data for various locations

# What has been done?

**Goals:** An explainable Covid-19 model that can work with the low data availability in Vietnam

- Collect and process Covid-19 related data for various locations
- Implement a model an explainable Covid-19 model using UDE
  - Progression of all compartments can be given by the model
  - Metric about the disease, e.g.  $\mathcal{R}_0$ , can be derived

# What has been done?

**Goals:** An explainable Covid-19 model that can work with the low data availability in Vietnam

- Collect and process Covid-19 related data for various locations
- Implement a model an explainable Covid-19 model using UDE
  - Progression of all compartments can be given by the model
  - Metric about the disease, e.g.  $\mathcal{R}_0$ , can be derived
- Add mobility data to the model and show that ineffectiveness of the approach

# Future improvements

- Increase the model complexity with additional compartments and parameters

# Future improvements

- Increase the model complexity with additional compartments and parameters
- Include additional time-varying covariates

# Future improvements

- Increase the model complexity with additional compartments and parameters
- Include additional time-varying covariates
- Implement better methods and algorithms for training UDE

# Future improvements

- Increase the model complexity with additional compartments and parameters
- Include additional time-varying covariates
- Implement better methods and algorithms for training UDE
- Use methods such as SINDy to find a governing equation and improve the model interpretability

# References I

- [1] F. Brauer, “Compartmental Models in Epidemiology,” in *Mathematical Epidemiology*, ser. Lecture Notes in Mathematics, F. Brauer, P. van den Driessche, and J. Wu, Eds., red. by J. .-. Morel, F. Takens, and B. Teissier, vol. 1945, Berlin, Heidelberg: Springer Berlin Heidelberg, 2008, pp. 19–79.
- [2] C. C. Kerr, R. M. Stuart, D. Mistry, *et al.*, “Covasim: An agent-based model of COVID-19 dynamics and interventions,” *PLOS Computational Biology*, vol. 17, no. 7, e1009149, Jul. 26, 2021.
- [3] Z. Ceylan, “Estimation of COVID-19 prevalence in Italy, Spain, and France,” *Science of The Total Environment*, vol. 729, p. 138 817, Aug. 10, 2020.



## References II

- [4] R. K. Singh, M. Rani, A. S. Bhagavathula, *et al.*, “Prediction of the COVID-19 Pandemic for the Top 15 Affected Countries: Advanced Autoregressive Integrated Moving Average (ARIMA) Model,” *JMIR Public Health and Surveillance*, vol. 6, no. 2, e19115, May 13, 2020.
- [5] M. H. D. M. Ribeiro, R. G. da Silva, V. C. Mariani, and L. d. S. Coelho, “Short-term forecasting COVID-19 cumulative confirmed cases: Perspectives for Brazil,” *Chaos, Solitons & Fractals*, vol. 135, p. 109 853, Jun. 1, 2020.
- [6] A. Ramchandani, C. Fan, and A. Mostafavi, “DeepCOVIDNet: An Interpretable Deep Learning Model for Predictive Surveillance of COVID-19 Using Heterogeneous Features and Their Interactions,” *IEEE Access*, vol. 8, pp. 159 915–159 930, 2020.

## References III

- [7] V. K. R. Chimmula and L. Zhang, "Time series forecasting of COVID-19 transmission in Canada using LSTM networks," *Chaos, Solitons, and Fractals*, vol. 135, p. 109 864, Jun. 2020.
- [8] F. Shahid, A. Zameer, and M. Muneeb, "Predictions for COVID-19 with deep learning models of LSTM, GRU and Bi-LSTM," *Chaos, Solitons, and Fractals*, vol. 140, p. 110 212, Nov. 2020.
- [9] S. Chang, E. Pierson, P. W. Koh, *et al.*, "Mobility network models of COVID-19 explain inequities and inform reopening," *Nature*, vol. 589, no. 7840, pp. 82–87, 7840 Jan. 2021.

## References IV

- [10] R. Dandekar, C. Rackauckas, and G. Barbastathis, “A Machine Learning-Aided Global Diagnostic and Comparative Tool to Assess Effect of Quarantine Control in COVID-19 Spread,” *Patterns*, vol. 1, no. 9, p. 100145, Dec. 11, 2020.
- [11] S. Y. Jung, H. Jo, H. Son, and H. J. Hwang, “Real-World Implications of a Rapidly Responsive COVID-19 Spread Model with Time-Dependent Parameters via Deep Learning: Model Development and Validation,” *Journal of Medical Internet Research*, vol. 22, no. 9, e19907, Sep. 9, 2020.
- [12] G. Cybenkot, “Approximation by superpositions of a sigmoidal function,” , p. 12,
- [13] K. Hornik, “Approximation capabilities of multilayer feedforward networks,” *Neural Networks*, vol. 4, no. 2, pp. 251–257, 1991.

# References V

- [14] K. Hornik, M. Stinchcombe, and H. White, "Multilayer feedforward networks are universal approximators," *Neural Networks*, vol. 2, no. 5, pp. 359–366, Jan. 1989.
- [15] Y. Guo, X. Cao, L. Bainian, and M. Gao, "Solving Partial Differential Equations Using Deep Learning and Physical Constraints," *Applied Sciences*, vol. 10, p. 5917, Aug. 26, 2020.
- [16] R. T. Q. Chen, Y. Rubanova, J. Bettencourt, and D. Duvenaud, "Neural Ordinary Differential Equations," (Dec. 13, 2019), [Online]. Available: <http://arxiv.org/abs/1806.07366> (visited on 09/26/2021).

# References VI

- [17] C. Rackauckas, Y. Ma, J. Martensen, *et al.*, “Universal Differential Equations for Scientific Machine Learning,” (Aug. 6, 2020), [Online]. Available: <http://arxiv.org/abs/2001.04385> (visited on 09/11/2021).
- [18] D. Misra, “Mish: A Self Regularized Non-Monotonic Activation Function,” (Aug. 13, 2020), [Online]. Available: <http://arxiv.org/abs/1908.08681> (visited on 12/06/2021).
- [19] T. Kuchler, D. Russel, and J. Stroebe, “The Geographic Spread of COVID-19 Correlates with the Structure of Social Networks as Measured by Facebook,” [National Bureau of Economic Research, Working Paper 26990](#), Apr. 2020.

## References VII

- [20] C. Tsitouras, “RungeKutta pairs of order 5(4) satisfying only the first column simplifying assumption,” *Computers & Mathematics with Applications*, vol. 62, no. 2, pp. 770–775, Jul. 2011.
- [21] T. Daulbaev, A. Katrutsa, L. Markeeva, J. Gusak, A. Cichocki, and I. Oseledets, “Interpolation Technique to Speed Up Gradients Propagation in Neural ODEs,” (Oct. 30, 2020), [Online]. Available: <http://arxiv.org/abs/2003.05271> (visited on 01/26/2022).