Tutorials Exercises W3Schools app iOS & Android NEW Sign In
CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

C# For Loop

‹ Previous Next ›

C# For Loop

SHARE

When you know exactly how many times you want to loop through a block of code, use the `for` loop instead of a `while` loop:

Syntax

Get your own C# Server

```
for (statement 1; statement 2; statement 3)
{
  // code block to be executed
}
```

Statement 1 is executed (one time) before the execution of the code block.

Statement 2 defines the condition for executing the code block.

Statement 3 is executed (every time) after the code block has been executed.

The example below will print the numbers 0 to 4:

Example

```
for (int i = 0; i < 5; i++)
```

Tutorials Exercises W3Schools app iOS & Android NEW Sign In
CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

Try it Yourself »

Example explained

Statement 1 sets a variable before the loop starts (`int i = 0`).

Statement 2 defines the condition for the loop to run (`i` must be less than `5`). If the condition is `true` , the loop will start over again, if it is `false` , the loop will end.

Statement 3 increases a value (`i++`) each time the code block in the loop has been executed.

Another Example

This example will only print even values between 0 and 10:

Example

```
for (int i = 0; i <= 10; i = i + 2)
{
  Console.WriteLine(i);
}
```

Try it Yourself »

Tutorials Exercises W3Schools app iOS & Android NEW Sign In
CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

It is also possible to place a loop inside another loop. This is called a **nested loop**.

The "inner loop" will be executed one time for each iteration of the "outer loop":

Example

```
// Outer loop
for (int i = 1; i <= 2; ++i)
{
  Console.WriteLine("Outer: " + i);  // Executes 2 times

  // Inner loop
  for (int j = 1; j <= 3; j++)
  {
    Console.WriteLine(" Inner: " + j); // Executes 6 times (2 * 3)
  }
}
```

Try it Yourself »

Exercise ?

Drag and drop the correct keyword and condition to ensure the loop runs while `i` is less than 5.

```
            (int i = 0;           ; i++)
{
  Console.WriteLine(i);
}
```

Submit Answer »

‹ Previous Sign in to track progress Next ›

schools

Get Certified in C#

Boost your career with an official certification

$95

Get certified

FREE ACCOUNT

Track your progress

XP earned	0
Day streak	0

NEW

Learn in Adventure Mode

Coding fundamentals as bite-sized lessons and challenges.

Download on the App Store GET IT ON Google Play

Tutorials Exercises
NEW W3Schools app iOS & Android
Sign In
. CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS
Sign in to track progress
schools
PLUS
SPACES
GET CERTIFIED
FOR TEACHERS
PRACTICE
CONTACT US

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
Java Tutorial
C++ Tutorial
jQuery Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
Java Reference
AngularJS Reference
jQuery Reference

Tutorials Exercises W3Schools app iOS & Android NEW Sign In

CSS JAVASCRIPT SQL PYTHON JAVA PHP C C++ C# AWS

How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
Java Examples
XML Examples
jQuery Examples

Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate
jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate

FORUM ABOUT CAMPUS

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.
Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness
of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookies and privacy policy.

Copyright 1999-2026 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.