

Robotics

Exercise 8

Lecturer: Jim Mainprice
TAs: Philipp Kratzer, Janik Hager, Yoojin Oh
Machine Learning & Robotics lab, U Stuttgart
Universitätsstraße 38, 70569 Stuttgart, Germany

July 1, 2021

1 Probability Basics (5 Points)

Probability theory is very useful in Robotics. Probabilities allow us to express **stochasticity** and to model **uncertainty** (e.g. uncertainty about the robot state given sensor information). Make yourself familiar with probability theory: take a look at lecture slides **09-probabilities**.

a) Box 1 contains 8 apples and 4 oranges. Box 2 contains 10 apples and 2 oranges. Boxes are chosen with equal probability. What is the probability of choosing an apple? If an apple is chosen, what is the probability that it came from box 1? (1P)

$$P(\text{Apple}) = 0.5 \times \frac{8}{12} + 0.5 \times \frac{10}{12} = \frac{9}{12} = \frac{3}{4}$$

A : from box 1 B : apple

$$P(A|B) = P(B|A) \cdot \frac{P(A)}{P(B)} = \frac{8}{12} \times \frac{0.5}{0.75} = \frac{8}{9}$$

b) The blue M&M was introduced in 1995. Before then, the color mix in a bag of plain M&Ms was: 30% Brown, 20% Yellow, 20% Red, 10% Green, 10% Orange, 10% Tan. Afterward it was: 24% Blue, 20% Green, 16% Orange, 14% Yellow, 13% Red, 13% Brown.

1994: yellow: 20%, green: 10% 1996: yellow: 14%, green: 20%

A friend of mine has two bags of M&Ms, and he tells me that one is from 1994 and one from 1996. He won't tell me which is which, but he gives me one M&M from each bag. One is yellow and one is green. What is the probability that the yellow M&M came from the 1994 bag? (1P)

$$P(Y, G) = 0.2 \times 0.2 + 0.14 \times 0.2 = 0.04 + 0.028 = 0.068$$

$$P(1994Y, 1996G | Y, G) = \frac{P(1994Y, 1996G) \cdot P(Y, G)}{P(Y, G)} = \frac{0.2 \times 0.2}{0.068} \approx 74.1\%$$

c) The Monty Hall Problem: I have three boxes. In one I put a prize, and two are empty. I then mix up the boxes. You want to pick the box with the prize in it. You choose one box. I then randomly select another one of the two remaining boxes and show that it is empty (this is not supposed to be another random experiment; just assume that an empty box is picked). I then give you the chance to change your choice of boxes—should you do so? (1P)

let $A = \{\text{pick} == \text{Prize}\}$ $B = \{\text{Rest} == \text{Prize}\}$ $P(A) = \frac{1}{3}$ $P(B) = 1 - P(A) = \frac{2}{3}$ (since one box is shown empty) \therefore should change

d) Given a joint probability $P(X, Y)$ over 2 binary random variables as the table

	Y=0	Y=1
X=0	.06	.24
X=1	.14	.56

for $\forall x, y, P(x, y) = P(x) \cdot P(y)$

What are $P(X)$ and $P(Y)$? Are X and Y independent? (1P)

$$P(X=1, Y=1) = 0.56 = P(X=1) \cdot P(Y=1) = 0.56 \therefore \text{independent}$$

e) What is the equation of a n-dim Gaussian distribution with mean μ and covariance matrix Σ ? What does the mean and the covariance matrix tell us? (1P)

$$P(x) = \frac{1}{(2\pi)^{\frac{n}{2}} |\Sigma|^{\frac{1}{2}}} \exp\left(-\frac{1}{2}(x-\mu)^T \Sigma^{-1}(x-\mu)\right)$$

μ is the bias, the mean of distribution, n is the dimensions.
 Σ is the covariance-matrix, the uncertainty of distribution.

2 Particle Filtering the location of a car (7 points)

You are going to implement a particle filter. Access the code as usual:

- For python run: `jupyter-notebook course1-Lectures/07-particle_filter/particle_filter.ipynb`
- For C++ run: `cd course1-Lectures/07-particle_filter, 'make', './x.exe'`

$$\Sigma^{-1} \approx H_{\log(P)}^T, \quad \mathbb{E}\left(H_{\log(P)}\right) = I$$

\uparrow
Fisher information matrix


The motion of the car is described by the following:

$$\text{State } q = \begin{pmatrix} x \\ y \\ \theta \end{pmatrix}$$

$$\text{Controls } u = \begin{pmatrix} v \\ \varphi \end{pmatrix}$$

$$\text{System equation} \quad \begin{pmatrix} \dot{x} \\ \dot{y} \\ \dot{\theta} \end{pmatrix} = \begin{pmatrix} v \cos \theta \\ v \sin \theta \\ (v/L) \tan \varphi \end{pmatrix}$$

$$|\varphi| < \Phi$$



Rotation matrix
SO2.

$$\begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix}$$

The `CarSimulator` simulates the described car (using Euler integration with step size 1sec). At each time step a control signal $u = (v, \phi)$ moves the car a bit and Gaussian noise with standard deviation $\sigma_{\text{dynamics}} = .03$ is added to x , y and θ . Then, in each step, the car measures the relative positions of m landmark points (green cylinders), resulting in an observation $y_t \in \mathbb{R}^{m \times 2}$; these observations are Gaussian-noisy with standard deviation $\sigma_{\text{observation}} = .5$. In the current implementation the control signal $u_t = (.1, .2)$ is fixed (roughly driving circles).

a) Odometry (dead reckoning): First write a particle filter (with $N = 100$ particles) that ignores the observations. For this you need to use the cars system dynamics (described above) to propagate each particle, and add some noise σ_{dynamics} to each particle (step 3 on slide 10:22). Draw the particles (their x, y component) into the display. Expected is that the particle cloud becomes larger and larger. (3 P)

b) Next implement the likelihood weights $w_i \propto P(y_t | x_t^i) = \mathcal{N}(y_t | y(x_t^i), \sigma) \propto e^{-\frac{1}{2}(y_t - y(x_t^i))^2 / \sigma^2}$ where $y(x_t^i)$ is the (ideal) observation the car would have if it were in the particle position x_t^i . Since $\sum_i w_i = 1$, normalize the weights after this computation. (2 P)

c) Test the full particle filter including the likelihood weights and resampling. Test using a larger ($10\sigma_{\text{observation}}$) and smaller ($\sigma_{\text{observation}}/10$) variance in the computation of the likelihood. (2 P)

please see the code implementation.

derivation of Bayes Filter

$$P(A|B, C) = \frac{P(B|A, C) \cdot P(A|C)}{P(B|C)}$$

states : x_t
observations : y_t
control : u_t

$$P_t(x_t) = P(x_t | y_{0:t}, u_{0:t-1}) \quad \text{likelihood.}$$

$$= P(y_t | x_t, y_{0:t-1}, u_{0:t-1}) \cdot P(x_t | y_{0:t-1}, u_{0:t-1}) \quad \leftarrow \text{prior}$$

$$= C_t \cdot P(y_t | x_t) \cdot P(x_t | y_{0:t-1}, u_{0:t-1}) \quad \leftarrow \text{evidence as constant } C_t.$$

$$= C_t \cdot P(y_t | x_t) \cdot \int P(x_t, x_{t+1} | y_{0:t-1}, u_{0:t-1}) dx_{t+1} \quad \leftarrow \text{marginal probability.}$$

$$= C_t \cdot P(y_t | x_t) \cdot \int P(x_t | x_{t+1}, y_{0:t-1}, u_{0:t-1}) \cdot P(x_{t+1} | y_{0:t-1}, u_{0:t-1}) dx_{t+1} \quad \leftarrow \text{Bayes rule - recursive form.}$$

$$= C_t \cdot P(y_t | x_t) \cdot \int P(x_t | x_{t+1}, u_{t+1}) \cdot P(x_{t+1} | y_{0:t-1}, u_{0:t-1}) dx_{t+1}$$

$$= C_t \cdot P(y_t | x_t) \cdot \int P(x_t | x_{t+1}, u_{t+1}) \cdot P_{t+1}(x_{t+1}) dx_{t+1}$$

observation model
new info.

transition model.
predictive estimation.

old estimation

observation model:
 $P(y_t | x_t)$

transition model:
 $P(x_{t+1} | x_t, u_t)$

First-order Markov.