

TeenWorks: Post a Service handoff

Context to continue this work in a new Claude session · repo `levv123/teenworks-app` · branch `claude/affectionate-mendel-qs8rpf` · 2026-09-25

How to use this document. Start the new session on repo `levv123/teenworks-app`, branch `claude/affectionate-mendel-qs8rpf`. Give it this PDF and say what you want next. Everything below is already committed and pushed. The PDF also lives in the repo at `docs/post-a-service-handoff.pdf`.

1. Where things stand

Commit	What it did
<code>26b043d</code>	Backend compatibility: migration 017 (pricing_type, duration_minutes, location, availability_days; Yard Work / Tech Help / Errands categories), web-safe photo upload, the <code>serviceDraft.ts</code> adapter.
<code>4b7f367</code>	The new three-step Post a Service flow (Category -> Details -> Preview & Post), plus migration 018 ("Other" category) and fixes for the image picker / file-system conflicts.
<code>6b8b3df</code>	Fixes for everything the review and browser tests confirmed (listed in section 6).

The base before this work is `ca90adc` (merge of PR #1). No pull request has been opened for this branch yet.

2. Ground rules the user set (keep following these)

- **Scope lock:** change only Earn side -> Post a Service. Leave Home, Analytics, Profile, My Services, Hire side, discovery, detail screens, bottom nav, navigation, theme, tokens, shared UI components, Expo config, dependencies and package versions alone.
- Use the existing TeenWorks visual system (`src/design/tokens.ts`, `src/ui/*`, `docs/DESIGN.md`). Don't add a new design system.
- Backend: reuse what exists. Change it only for a real conflict, and make the smallest change. Don't redesign, replace tables or touch unrelated tables.
- No authenticated Supabase user -> no fake accounts or database records; fall back gracefully to the existing app behavior.
- Back/Edit must keep all entered data. Photos are optional; every other field is required before preview.

3. Architecture you need to know

- Expo SDK 51, React Native 0.74, react-native-web, React Navigation 6. Deployed as a web app/PWA on Vercel (`npm run build:web`).

- The **mounted app** (App.tsx -> `src/navigation/MainNavigator.tsx`) runs on a **local store**, `src/store/AppStore.tsx`, seeded from `src/data/mock.ts` and persisted to localStorage key `teenworks.v1`. Types for it are in `src/data/types.ts`.
- The **Supabase layer** (`src/api/*`, `src/types/index.ts`, `supabase/schema.sql` + `migrations/`) came from an older version of the app. Its screens (`src/screens/shared|client|provider|auth`) and `AuthContext` are **not mounted**, so there is no sign-in screen in the current app.
- Services table: `public.provider_services`. RLS: public read; the owner (`provider_id = auth.uid()`) can insert, update and delete. `provider_id` has a foreign key to `provider_profiles.user_id` (migration 008).
- Photos go to the storage bucket `portfolio` under `service-images/<userId>/`. No file in the repo creates this bucket.
- `metro.config.js` swaps `expo-image-picker`, `expo-location` and `expo-notifications` for empty modules on web.

4. The flow as built

- **Route:** `PostService` (URL `/post-service`). Same route and export as before; opened from the Home CTA and from My Services (+ button, and Edit with `?serviceId=`).
- **Step 1, Category:** a 4×2 grid (Yard Work, Pets, Moving, Cleaning, Tech Help, Tutoring, Errands, More). "More" = category id `'other'` ("Other" in the listing and in the database).
- **Step 2, Details:** photos first (up to 5, the first is the cover), title, description (20–400 characters), price in whole dollars (max \$500), Hourly/Fixed, duration, location (prefilled from the app location), day toggles.
- **Step 3, Preview:** the listing as a customer sees it (built like Gig Detail), with **Edit** and **Post Service** (**Save Changes** when editing).
- A 1—2—3 step indicator; finished steps can be tapped. All steps share one form object, so header back, Edit, the step dots, Android back and browser back all keep the data.
- Duration choices are stored as `duration_minutes`: Under 1 hour = 45, 1–2 hours = 90, 2–4 hours = 180, 4+ hours = 240. Stored values map back to a choice by range.
- **Signed in to Supabase:** photos are uploaded (`uploadServiceImage`), then `postServiceDraft` / `updateServiceDraft` run, and the service is mirrored into the local store with `remoteId`. **Signed out:** it saves to the local store only, device-only photos are dropped, and the preview says so. Either way the user lands on My Services with a toast.
- While a post is in flight, back is locked and a double tap can't post twice. A failed post keeps the form and any photos already uploaded, so a retry doesn't upload them again.

5. Files

File	Role
<code>src/screens/earn/PostServiceScreen.tsx</code>	The flow container: steps, validation display, back handling (<code>beforeRemove</code> , including web RESET), posting, edit mode, re-seeding after the store loads.

<code>src/features/postService/</code>	<code>CategoryGrid</code> , <code>StepIndicator</code> , <code>PhotoStrip</code> , <code>ServiceDetailsForm</code> , <code>ServicePreview</code> , <code>constants.ts</code> (limits, durations, days), <code>form.ts</code> (form type, validation, conversions), <code>publish.ts</code> (session check, uploads, save), <code>index.ts</code> .
<code>src/api/serviceDraft.ts</code>	Maps form fields to provider_services columns: category slug -> category_id (by name), rate -> starting_price, rateType -> pricing_type, durationMinutes -> duration_minutes, place -> location, availability -> availability_days, images, is_active. Creates the provider profile if it's missing.
<code>src/api/services.ts</code>	Web photo picking through a hidden file input. The native picker and <code>expo-file-system/legacy</code> are required lazily. The web upload reads blobs with fetch.
<code>src/data/types.ts</code> , <code>src/data/mock.ts</code>	Adds the 'other' category ID (it appears in <code>CATEGORY_BY_ID</code> only, not <code>CATEGORIES</code>) and optional <code>images</code> , <code>durationMinutes</code> and <code>remoteId</code> fields on services.
<code>supabase/migrations/017_*.sql</code> , <code>018_*.sql</code>	The new columns and categories. Both are safe to run twice.
<code>docs/DESIGN.md</code>	The Post a Service row now describes the flow.

6. Verification done

- `npx tsc -p tsconfig.check.json` passes. The full-project typecheck shows only errors that were already there (legacy files). `npm run build:web` succeeds.
- Pixel regression: 27 screens/states compared against the pre-feature build, 0 pixels different.
- Signed-in path, tested in Chromium against a network-level fake of Supabase: every column in the insert payload was checked, uploads happen before the insert, editing sends a PATCH to the same row, and failure/retry and double tap were covered. 131 of 132 assertions pass; the one failure was the test checking for the old step 2 header text in edit mode.
- Fixes confirmed by tests: back locked while posting; browser back steps back through the flow; signed-out photos dropped; grid aligned at 320–1280 wide; price paste handling; aria-checked on web; the "saved on this device" note matches what actually happens; reloading on an edit link re-seeds the form.
- **Not tested:** a real Supabase project, a real phone, native builds.

7. Blockers and open items

Native photos are broken. The installed `expo-image-picker` 56 (and `expo-file-system` 56, `expo-document-picker` 56) are built for a newer Expo than SDK 51. The picker crashes when it loads. On native, "Add photos" shows a "Couldn't open your photos" toast instead of crashing the app. The fix is to install the SDK 51 versions (e.g. `expo-image-picker ~15.0`); that's a dependency change and needs the user's approval.

No sign-in in the current app. Every post takes the signed-out path (saved on the device, without photos). Saving to Supabase for real needs an auth screen or `AuthContext` mounted, which was outside this task's scope.

- Before real use: apply migrations 017 and 018, and make sure a **public** storage bucket `portfolio` exists with insert allowed for signed-in users.
- Open decision: "More" was built as "save under Other." If the user meant "open a list of more categories," it needs changing.
- Minor, not fixed: an update the database silently refuses (0 rows, RLS mismatch) is still reported as success. If the migrations are missing, one post attempt uploads photos before failing on the category. The Supabase client now loads at startup (about +72 KB gzipped). Other legacy API files (`requests.ts`, `portfolio.ts`, `proof.ts`, `deliverables.ts`) still import the incompatible picker/file-system at the top of the file.
- My Services still shows only the local store. Loading services from Supabase there was out of scope.

8. How to test again

1. `npm ci`, then `npx tsc -p tsconfig.check.json` and `npm run build:web`.
2. For the signed-in path: build with `EXPO_PUBLIC_SUPABASE_URL=https://fakeproj.supabase.co` `EXPO_PUBLIC_SUPABASE_ANON_KEY=fake-anon-key` `npx expo export --platform web`, serve the output, seed a supabase-js session in `localStorage` under `sb-fakeproj-auth-token`, and answer `https://fakeproj.supabase.co/**` with Playwright `page.route`.
3. Playwright in this environment: use the global `playwright` package with `executablePath: '/opt/pw-browsers/chromium-1194/chrome-linux/chrome'`. RN-web screens stay mounted underneath, so scope locators with `.filter({ visible: true })`. Button names: `'Continue →'` and `'Preview →'` (use exact matching; the step dots are named "Step N of 3, ...").