

Mitzi - Exercise 3

Christoph Hofer
0955139

Stefan Lew
0856722

January 22, 2014

Contents

1	Our Final Code	3
1.1	ChessGame.java	3
1.2	Piece.java	4
1.3	Side.java	5
1.4	PieceHelper.java	6
1.5	SquareHelper.java	7
1.6	IBrain.java	13
1.7	IMove.java	14
1.8	IPosition.java	15
1.9	IPositionAnalyzer.java	22
1.10	RandyBrain.java	23
1.11	HumanBrain.java	24
1.12	Move.java	25
1.13	Direction.java	29
1.14	Position.java	30
1.15	AnalysisResult.java	74
1.16	BasicMoveComparator.java	79
1.17	CaptureComparator.java	81
1.18	BasicBoardAnalyzer.java	86
1.19	BoardAnalyzer.java	87
1.20	Flag.java	106
1.21	GameState.java	106
1.22	IrreversibleMoveStack.java	109
1.23	KillerMoves.java	111
1.24	MateScores.java	113
1.25	MitziBrain.java	113
1.26	ResultCache.java	125
1.27	UCIReporter.java	127
1.28	MitziGUI.java	130

1 Our Final Code

1.1 ChessGame.java

```
package mitzi;

import mitzi.IMove;
import mitzi.RandyBrain;

/**
 * The environment for playing chess
 *
 */
public class ChessGame {

    private static GameState game_state;

    public static void main(String[] args) {

        System.out.println("Lets play chess!");

        IMove move;

        game_state = new GameState();

        RandyBrain randy = new RandyBrain();
        HumanBrain human = new HumanBrain();
        //MitziBrain mitzi = new MitziBrain();

        while (true) {
            //Humans turn
            human.set(game_state);
            move = human.search(0, 0, 0, false, null);
            game_state.doMove(move);
            if (game_state.getPosition().isMatePosition()) {
                System.out.println("You won!");
                break;
            }
            if (game_state.getPosition().isStaleMatePosition()) {
                System.out.println("Draw!");
                break;
            }
            System.out.println(game_state.getPosition());

            //Randys turn
```

```
    randy.set(game_state);
    move = randy.search(0, 0, 0, false, null);
    System.out.println("Randy plays:" + move);
    game_state.doMove(move);
    if (game_state.getPosition().isMatePosition()) {
        System.out.println("You lost!");
        break;
    }
    if (game_state.getPosition().isStaleMatePosition()) {
        System.out.println("Draw!");
        break;
    }
    System.out.println(game_state.getPosition());

    /*
    //Mitzi's turn
    mitzi.set(game_state);
    move = mitzi.search(100000, 100000, 6, false, null);
    System.out.println("Mitzi plays:" + move);
    game_state.doMove(move);
    if (game_state.getPosition().isMatePosition()) {
        System.out.println("You lost!");
        break;
    }
    if (game_state.getPosition().isStaleMatePosition()) {
        System.out.println("Draw!");
        break;
    }
    System.out.println(game_state.getPosition());
    */
}

}

}
```

1.2 Piece.java

```
package mitzi;

/**
 * An enum containing the different Pieces
 */
public enum Piece {
```

```
    PAWN, ROOK, BISHOP, KNIGHT, QUEEN, KING;
}
```

1.3 Side.java

```
package mitzi;

/**
 * An enum containing the two different sides.
 *
 */
public enum Side {
    BLACK, WHITE;

    /**
     * returns the opposite side of the given side
     * @param side the given side
     * @return the opposite side
     */
    public static Side getOppositeSide(Side side) {
        switch (side) {
            case BLACK:
                return WHITE;
            default:
                return BLACK;
        }
    }

    /**
     * returns the side sign of the given side
     * @param side the given side
     * @return -1 if side == black, 1 otherwise.
     */
    public static int getSideSign(Side side) {
        switch (side) {
            case BLACK:
                return -1;
            default:
                return +1;
        }
    }
}
```

1.4 PieceHelper.java

```
package mitzi;

import java.util.Locale;

public final class PieceHelper {

    /**
     * A String for the algebraic names of the pieces. P... Pawn, R... Rook,
     * etc.
     */
    public static final String[] ALGEBRAIC_NAMES = { "P", "R", "N", "B", "Q",
        "K" };

    private PieceHelper() {
    };

    /**
     * Converts a Piece of a given Side into string. Capital letters are white,
     * lower case letters are black.
     *
     * @param side
     *         the gives side
     * @param piece
     *         the given piece
     * @return the string representation of the piece.
     */
    public static String toString(final Side side, final Piece piece) {
        return toString(side, piece, false);
    }

    /**
     * Converts a Piece of a given Side into string. Capital letters are white,
     * lower case letters are black. Additionally, you have the choice to omit
     * writing a P for pawn.
     *
     * @param side
     *         the gives side
     * @param piece
     *         the given piece
     * @param omitPawnLetter
     *         if the pawnletter should be omitted or not.
     * @return the string representation of the piece.
     */
    public static String toString(final Side side, final Piece piece,
```

```
        final boolean omitPawnLetter) {

    if (omitPawnLetter && piece == Piece.PAWN) {
        return "";
    } else if (side == Side.BLACK) {
        return pieceToString(piece).toLowerCase(Locale.ENGLISH);
    } else {
        return pieceToString(piece);
    }
}

/**
 * converts a given piece into a string, no distinction which side.
 *
 * @param piece
 *         the given piece
 * @return the string representation.
 */
private static String pieceToString(final Piece piece) {
    switch (piece) {
        case PAWN:
            return "P";
        case ROOK:
            return "R";
        case KNIGHT:
            return "N";
        case BISHOP:
            return "B";
        case QUEEN:
            return "Q";
        default:
            return "K";
    }
}
}
```

1.5 SquareHelper.java

```
package mitzi;

import java.util.ArrayList;
import java.util.HashSet;
```

```
import java.util.LinkedList;
import java.util.List;
import java.util.Set;

/**
 * In brief, each square of the chessboard has a two-digit designation. The
 * first digit is the number of the column, from left to right from White's
 * point of view. The second digit is the row from the edge near White to the
 * other edge.
 *
 * @see <a href="https://en.wikipedia.org/wiki/ICCF_numeric_notation">ICCF
 *      numeric notation</a>
 */
public final class SquareHelper {

    /**
     * the letters of the columns of the chessboard
     */
    private static final String[] letters = { "a", "b", "c", "d", "e", "f",
        "g", "h" };

    /**
     * stores all squares in a certain direction for a certain source square
     */
    private static ArrayList<ArrayList<List<Integer>>> squares_direction = new
        ArrayList<ArrayList<List<Integer>>>();

    /**
     * stores all squares reachable for the knight from a certain source square
     */
    private static ArrayList<List<Integer>> squares_direction_knight = new
        ArrayList<List<Integer>>();

    public static LinkedList<Integer> all_squares = new LinkedList<Integer>();

    private SquareHelper() {
    };

    static {
        //initialize with null
        for (int i = 0; i < 89; i++) {
            squares_direction.add(null);
            squares_direction_knight.add(null);
        }

        for (int i = 1; i < 9; i++)
```



```
for (int j = 1; j < 9; j++) {
    int source_square = getSquare(i, j);
    all_squares.add(source_square);
    ArrayList<List<Integer>> dir_list = new ArrayList<List<Integer>>();
    for (int k = 0; k < 9; k++)
        dir_list.add(null);
    ArrayList<Integer> dir_list_knight = new ArrayList<Integer>();

    // compute squares for pieces except the knight
    for (Direction dir : Direction.values()) {
        ArrayList<Integer> square_list = new ArrayList<Integer>();

        int square = source_square + dir.offset;
        while (isValidSquare(square)) {
            square_list.add(square);
            square += dir.offset;
        }
        dir_list.set(dir.ordinal(), square_list);
    }

    // squares for Knight
    for (Direction dir : Direction.values()) {

        int square = source_square + dir.knight_offset;
        if (isValidSquare(square)) {
            dir_list_knight.add(square);
        }
    }
    squares_direction.set(source_square, dir_list);
    squares_direction_knight.set(source_square, dir_list_knight);
}

}

/**
 * Returns the integer value of the square's column. Starting with 1 at
 * column a and ending with 8 at column h.
 *
 * @return the integer value of the square's column.
 */
public static int getColumn(int square) {
    return square / 10;
}

/**
 * Returns the integer value of the square's row. Where row 1 is row 1 and
```

```
* so forth, obviously.
*
* @return the integer value of the square's row.
*/
public static int getRow(int square) {
    return square % 10;
}

/**
 * Returns the square-number for a given row and column. Row 1 and column 2
 * results in 12.
 *
 * @return the integer value of the square
 */
public static int getSquare(int row, int column) {
    return 10 * column + row;
}

/**
 * Check if the square is white on a traditional chess board.
 *
 * @param square
 *         the integer code of the square
 *
 * @return true if the square is white and false otherwise
 */
public static boolean isWhite(int square) {
    return (square / 10 + square % 10) % 2 != 0;
}

/**
 * Check if the square is black on a traditional chess board.
 *
 * @param square
 *         the integer code of the square
 *
 * @return true if the square is black and false otherwise
 */
public static boolean isBlack(int square) {
    return !isWhite(square);
}

/**
 * returns all squares in all possible directions for a given source square
 *
 * @param square
```

```
*           the source square
* @return an ArrayList, indexed by the ordinal of the direction, containing
*           a List of squares in the desired direction
*/
public static ArrayList<List<Integer>> getSquaresAllDirections(int square) {
    return squares_direction.get(square);
}

public static List<Integer> getAllSquaresInDirection(
    ArrayList<List<Integer>> squares, Direction direction) {
    return squares.get(direction.ordinal());
}

/**
 * Gives an ordered List of squares going in a straight line from the source
 * square.
 *
 * @param source_square
 *           the square from where to start
 * @param direction
 *           one of the values SquareHelper.EAST, SquareHelper.NORTHEAST,
 *           SquareHelper.NORTH,
 * @return the list of squares ordered from the source_square to the boards
 *         edge
 */
public static List<Integer> getAllSquaresInDirection(int source_square,
    Direction direction) {

    return squares_direction.get(source_square).get(direction.ordinal());
}

/**
 * Gives a List of squares reached by a knight from the source square (in no
 * specific order).
 *
 * @param source_square
 *           the square from where to start
 * @return the list of squares a knight can reach
 */
public static List<Integer> getAllSquaresByKnightStep(int source_square) {

    return squares_direction_knight.get(source_square);
}

/**
 * Checks if the integer value of the square is inside the board's borders.
```

```
*
* @param square
*         the square to be checked
* @return true if the square is on the board
*/
public static boolean isValidSquare(int square) {
    int row = getRow(square);
    int column = getColumn(square);
    return (row >= 1 && row <= 8 && column >= 1 && column <= 8);
}

/**
 * Returns a string representation of the square in algebraic notation.
 *
 * Each square is traditionally identified by a unique coordinate pair
 * consisting of a letter and a number. The vertical columns from White's
 * left (the queenside) to his right (the kingside) are labeled a through h.
 * The horizontal rows are numbered 1 to 8 starting from White's side of the
 * board. Thus, each square has a unique identification of a letter followed
 * by a number. For example, the white king starts the game on square e1,
 * while the black knight on b8 can move to open squares a6 or c6.
 *
 * @return a string representation of the square in algebraic notation.
 */
public static String toString(int square) {
    return letters[getColumn(square) - 1]
        + Integer.toString(getRow(square));
}

/**
 * converts the string representation of a square into a the ICCF notation.
 *
 * @param notation
 *         the given square in string notation
 * @return the square in integer representation.
 */
public static int fromString(String notation) {
    int i = 0;
    while (letters[i].charAt(0) != notation.charAt(0)) {
        i++;
    }
    return (i + 1) * 10 + Character.getNumericValue(notation.charAt(1));
}

/**
 * returns the number for the i_th row seen from a given side. i.e. the last
```

```
* row for black is 1, the 3rd row for white is 3, the 3rd row for black is
* 6;
*
* @param side
*         the given side
* @param i_th
*         the i_th row, where the (global) row number is wanted.
* @return the (global) row number.
*/
public static int getRowForSide(Side side, int i_th) {
    if (side == Side.BLACK)
        return 9 - i_th;
    else
        return i_th;
}
}
```

1.6 IBrain.java

```
package mitzi;

import java.util.List;

public interface IBrain {

    /**
     * Before the engine is asked to search on a game state, there will always
     * be
     * this command to tell the engine about the current game state.
     *
     * @param game_state
     *         the current game state
     */
    public void set(GameState game_state);

    /**
     * Start calculating on the current position.
     *
     * @param movetime
     *         search for exactly this time in milliseconds
     * @param maxMoveTime
     *         search for at most this time in milliseconds
     * @param searchDepth
     */
}
```

```

    *           the maximum search depth in plys
    * @param infinite
    *           If set to true, search until the "stop" command. Do not exit
    *           the search without being told so in this mode!
    * @param searchMoves
    *           Restrict search to this moves only. If null, the engine may
    *           search any moves.
    * @return the hopefully best move
    */
public IMove search(int movetime, int maxMoveTime, int searchDepth,
    boolean infinite, List<IMove> searchMoves);

/**
 * Stop calculating immediately and return the best move.
 *
 * @return the currently best move
 */
public IMove stop();
}

```

1.7 IMove.java

```

package mitzi;

public interface IMove {

    /**
     *
     * @return the source of the move
     */
    public int getFromSquare();

    /**
     *
     * @return the destination of the move
     */
    public int getToSquare();

    /**
     *
     * @return the promotion of the pawn. EMPTY if no promotion.
     */
    public Piece getPromotion();
}

```

```
/**
 *
 * @return the string representation of the move
 */
public String toString();
}
```

1.8 IPosition.java

```
package mitzi;

import java.util.List;
import java.util.Set;

/**
 * This class provides an interface for a generic chess for the positions on a
 * chess board.
 *
 */
public interface IPosition {

    /**
     * Sets the board to the initial position at the start of a game.
     */
    public void setToInitial();

    /**
     * Sets the board to a position given in Forsyth-Edwards Notation (FEN).
     *
     * @see <a
     *      href="https://en.wikipedia.org/wiki/Forsyth-Edwards_Notation">Wikipedia
     *      - Forsyth-Edwards Notation</a>
     */
    public void setToFEN(String fen);

    /**
     * Return an independent copy of the IPosition.
     *
     * @return the copy
     */
    public IPosition returnCopy();
}
```

```
/**
 * Performs the given move and returns a new position. There is no check,
 * that the performed move is legal!
 *
 * @param move
 *         the move, which should be performed. Please note, that the
 *         move must be valid, no checking is done.
 * @return the new board and a boolean, if the half_move_clock should be
 *         reseted.
 */
public IPosition doMove_copy(IMove move);

/**
 * Performs the given move on the actual board. There is no check, that the
 * performed move is legal!
 *
 * @param move
 *         the move, which should be performed. Please note, that the
 *         move must be valid, no checking is done.
 */
public void doMove(IMove move);

/**
 * Reverts the given move. In addition a stack is used to recover the whole
 * information. There is no check, that the performed move is legal!
 *
 * @param move
 *         the move, which should be performed. Please note, that the
 *         move must be valid, no checking is done.
 */
public void undoMove(IMove move);

/**
 * Returns, which side has to move.
 *
 * @return the active Side of the actual position
 */
public Side getActiveColor();

/**
 * En passant target square. If there's no en passant target square, this is
 * -1. If a pawn has just made a two-square move, this is the position
 * "behind" the pawn. This is recorded regardless of whether there is a pawn
 * in position to make an en passant capture.
 */
```



```
* @return the square "behind" the pawn which can be take en passant
*/
public int getEnPassant();

/**
 * Check if the king can use castling to get to a specified square.
 *
 * @param king_to
 *         the square to be checked
 *
 * @return true if the king is allowed to move to the square by castling
 *
 * @see <a href="http://www.fide.com/fide/handbook?id=124&view=article">FIDE
 *      Rule 3.8</a>
 */
public boolean canCastle(int king_to);

/**
 * The position stores also an eventual analysis result from board
 * evaluation.
 *
 * @return the analysis result of the board.
 */
public AnalysisResult getAnalysisResult();

/**
 * Sets/update the actual analysis result.
 *
 * @param new_result
 *         the new analysis result.
 */
public void updateAnalysisResult(AnalysisResult new_result);

/**
 * Checks if a given side, can still castle.
 *
 * @param color
 *         the given side
 * @return true, if the given side can castle, false else.
 */
public Boolean colorCanCastle(Side color);

/**
 * Returns all squares, occupied by a given side.
 *
 * @param color
```

```
*           the given side
* @return a set of integers, containing all squares, where a piece of this
*           side is placed.
*/
public Set<Integer> getOccupiedSquaresByColor(Side color);

/**
 * Returns all squares, occupied by a given piece.
 *
 * @param type
 *           the given piece
 * @return a set of integers, containing all squares, where this piece is
 *         placed.
 */
public Set<Integer> getOccupiedSquaresByType(Piece type);

/**
 * Returns all squares, occupied by a given piece and side.
 *
 * @param color
 *           the given side
 * @param type
 *           the given piece
 * @return a set of integers, containing all squares, where the piece of
 *         this side is placed.
 */
public Set<Integer> getOccupiedSquaresByColorAndType(Side color, Piece
    type);

/**
 * returns the square, where the king for a side is positioned.
 *
 * @param side
 *           the given side
 * @return the square where the king is
 */
public int getKingPos(Side side);

/**
 * Returns the number of occupied squares by a given side.
 *
 * @param color
 *           the given side
 * @return the number of squares, where a piece of the given side is placed.
 */
public int getNumberOfPiecesByColor(Side color);
```

```
/**
 * Returns the number of occupied squares by a given piece.
 *
 * @param type
 *         the given piece
 * @return the number of squares, where the piece is placed.
 */
public int getNumberOfPiecesByType(Piece type);

/**
 * Returns the number of occupied squares by a given piece and side.
 *
 * @param color
 *         the given side
 * @param type
 *         the given piece
 * @return the number of squares, where the piece of this side is placed.
 */
public int getNumberOfPiecesByColorAndType(Side color, Piece type);

/**
 * Computes all possible moves for the active side. Moves, where the active
 * color is check, are invalid and got deleted.
 *
 * @return a set of all valid and possible moves.
 */
public List<IMove> getPossibleMoves();

/**
 * Computes all possible moves for the active side from a specific square.
 * Moves, where the active color is check, are invalid and got deleted.
 *
 * @param square
 *         the given square
 * @return a set of all valid and possible moves from the given square.
 */
public List<IMove> getPossibleMovesFrom(int square, boolean pseudolegal);

/**
 * Computes all possible moves for the active side to a specific square.
 * Moves, where the active color is check, are invalid and got deleted.
 * Please note, that this functions calls getPossibleMoves() and extracts
 * the desired ones.
 *
 * @param square
```

```

    *           the given square
    * @return a set of all valid and possible moves to the given square.
    */
public List<IMove> getPossibleMovesTo(int square);

/**
 * returns the side of the piece on a given square
 *
 * @param square
 *           the given square
 * @return the side, if this square is occupied by a side and null if it is
 *         empty.
 */
public Side getSideFromBoard(int square);

/**
 * returns the piece on a given square
 *
 * @param square
 *           the given square
 * @return the piece, if this square is occupied and null if it is empty.
 */
public Piece getPieceFromBoard(int square);

/**
 * checks if the actual position is a check position.
 *
 * @return true if the position is a check position
 */
public boolean isCheckPosition();

/**
 * checks if the actual position is a mate position.
 *
 * @return true if the position is a mate position
 */
public boolean isMatePosition();

/**
 * checks if the actual position is a stalemate position.
 *
 * @return true if the position is a stalemate position
 */
public boolean isStaleMatePosition();

/**
```

```
* checks if a given move is a valid move. Note, that this function calls
* first getPossibleMoves() and then searches the given move in all possible
* moves
*
* @param move
*         the move to be checked
* @return true, if the move is possible
*/
public boolean isPossibleMove(IMove move);

/**
 * converts the given position in fen notation
 *
 * @return a string of the actual position in fen notation
 */
public String toFEN();

/**
 * searches all moves, which are a capture and promotions
 *
 * @return the desired set of moves of all captures and promotions.
 */
public List<IMove> generateCaptures();

/**
 * Since AnalysisResults are stored in the Transposition Tables
 * (ResultCache), it is important to ensure that the AnalysisResult
 * corresponding to the actual position should be used, if there are
 * collisions with hashvalues. Therefore a second one (this one) is created
 * to identify the position and these problems unlikely.
 *
 * @return a different hashvalue
 */
public long hashCode2();

/**
 * computes all information and stores them, which is needed for fast board
 * evaluation.
 */
public void cacheOccupiedSquares();

public void setHalfMoveClock(int parseInt);

public int getHalfMoveClock();

boolean isCheckAfterMove(IMove move);
```

```
void getPotentialAttackersTo(int square, Piece attacking_dir,
    List<IMove> result);

List<IMove> getPotentialAttackersTo(int square, Piece attacking_dir);

List<IMove> getPotentialAttackersTo(int square);

List<IMove> getPossibleMoves(boolean pseudolegal);
}
```

1.9 IPositionAnalyzer.java

```
package mitzi;

public interface IPositionAnalyzer {

    /**
     * Evaluates the given board and returns a value in centipawns, this
     * function should not include further increase of search depth.
     *
     * @param board
     *         the board to be analyzed
     * @return a analysisResult, containing the value in centipawns
     */
    public AnalysisResult eval0(IPosition board);

    /**
     * Evaluates the given board and returns a value in centipawns, this
     * function should/can include further increase of search depth.
     *
     * @param board
     *         the board to be analyzed
     * @param alpha
     *         the alpha value of the alpha-beta algorithm
     * @param beta
     *         the beta value of the alpha-beta algorithm
     * @return a analysisResult, containing the value in centipawns and the
     *         selective depth
     * @throws InterruptedException
     */
    public AnalysisResult evalBoard(IPosition board, int alpha, int beta)
        throws InterruptedException;
}
```

```
/**
 * stores the castling rights
 * @param position the actual position
 */
public void setCastling(IPosition position);
}
```

1.10 RandyBrain.java

```
package mitzi;

import java.util.List;
import java.util.Random;

/**
 * This class implements the most basic search engine, the random move
 * selection. All possible moves of the actual game state are computed and one
 * of them is randomly selected.
 */
public class RandyBrain implements IBrain {

    /**
     * The current game state
     */
    private GameState game_state;

    @Override
    public void set(GameState game_state) {
        this.game_state = game_state;
    }

    @Override
    public IMove search(int movetime, int maxMoveTime, int searchDepth,
        boolean infinite, List<IMove> searchMoves) {

        List<IMove> moves = game_state.getPosition().getPossibleMoves();

        int randy = new Random().nextInt(moves.size());
        int i = 0;
        for (IMove move : moves) {
            if (i == randy)
                return move;
        }
    }
}
```

```
        i = i + 1;
    }

    return null; // cannot not happen anyway
}

@Override
public IMove stop() {
    // no need to implement the stop function, since RandyBrain is fast
    // enough.
    return null;
}
}
```

1.11 HumanBrain.java

```
package mitzi;

import java.io.BufferedReader;
import java.io.IOException;
import java.io.InputStreamReader;
import java.util.List;

import mitzi.GameState;

public class HumanBrain implements IBrain {

    /**
     * The current game state
     */
    private GameState game_state;

    @Override
    public void set(GameState game_state) {
        this.game_state = game_state;
    }

    @Override
    public IMove search(int movetime, int maxMoveTime, int searchDepth,
        boolean infinite, List<IMove> searchMoves) {

        //Read in the move as string
    }
```



```
BufferedReader reader = new BufferedReader(new
    InputStreamReader(System.in));
String string_move = null;
try {
    string_move = reader.readLine();
} catch (IOException e) {
    // TODO Auto-generated catch block
    e.printStackTrace();
}

//convert it to an object move.
IMove move = new Move(string_move);
//if the move was illegal, the player has to choose another one.
while(!game_state.getPosition().isPossibleMove(move)){
    System.out.println("Illegal move, choose another one!");
    try {
        string_move = reader.readLine();
    } catch (IOException e) {
        // TODO Auto-generated catch block
        e.printStackTrace();
    }
    move = new Move(string_move);
}
//return the choosen move.
return move;
}

@Override
public IMove stop() {
    return null;
}
}
```

1.12 Move.java

```
package mitzi;

import java.util.Locale;
import java.util.Set;

public final class Move implements IMove {

    /**
```

```
    * the source square of the move
    */
private final short src;

/**
 * the destination square of the move
 */
private final short dest;

/**
 * the piece, resulting from promotion. null if no promotion
 */
private final Piece promotion;

/**
 * Move constructor
 *
 * @param src
 *         Source
 * @param dest
 *         Destination
 * @param promotion
 *         Promotion (if no, then omit)
 */
public Move(int src, int dest, Piece promotion) {
    this.src = (short) src;
    this.dest = (short) dest;
    this.promotion = promotion;
}

/**
 * Move constructor (no promotion)
 *
 * @param src
 *         Source square
 * @param dest
 *         Destination square
 */
public Move(int src, int dest) {
    this(src, dest, null);
}

/**
 * Move constructor from string notation
 *
 * @param notation
```

```
*           the string representation of the move
*/
public Move(String notation) {
    String[] squares = new String[2];

    squares[0] = notation.substring(0, 2);
    squares[1] = notation.substring(2, 4);

    src = (short) SquareHelper.fromString(squares[0]);
    dest = (short) SquareHelper.fromString(squares[1]);

    if (notation.length() > 4) {
        String promo_string = notation.substring(4, 5).toLowerCase(
            Locale.ENGLISH);
        if (promo_string.equals("q")) {
            promotion = Piece.QUEEN;
        } else if (promo_string.equals("r")) {
            promotion = Piece.ROOK;
        } else if (promo_string.equals("n")) {
            promotion = Piece.KNIGHT;
        } else if (promo_string.equals("b")) {
            promotion = Piece.BISHOP;
        } else {
            promotion = null;
        }
    } else {
        promotion = null;
    }
}

/**
 *
 * Checks if a move is in a given List of moves
 *
 * @param moves
 *         List of moves
 * @param move
 *         the move to be searched
 * @return true if move is in moves, else false
 */
public static boolean MovesListIncludesMove(Set<Move> moves, Move move) {
    return moves.contains(move);
}

@Override
```

```
public int getFromSquare() {
    return src;
}

@Override
public int getToSquare() {
    return dest;
}

@Override
public Piece getPromotion() {
    return promotion;
}

@Override
public String toString() {
    String promote_to;
    if (getPromotion() != null) {
        promote_to = PieceHelper.toString(Side.WHITE, getPromotion());
    } else {
        promote_to = "";
    }
    return SquareHelper.toString(getFromSquare())
        + SquareHelper.toString(getToSquare()) + promote_to;
}

@Override
public int hashCode() {
    final int prime = 31;
    int result = 1;
    result = prime * result + dest;
    result = prime * result
        + ((promotion == null) ? 0 : promotion.hashCode());
    result = prime * result + src;
    return result;
}

@Override
public boolean equals(Object obj) {
    if (this == obj) {
        return true;
    }
    if (obj == null) {
        return false;
    }
    if (getClass() != obj.getClass()) {
```

```
        return false;
    }
    Move other = (Move) obj;
    if (dest != other.dest || promotion != other.promotion
        || src != other.src) {
        return false;
    }
    return true;
}
}
```

1.13 Direction.java

```
package mitzi;

import java.util.EnumSet;

/**
 * This class represents stores the information about the offset for moving a
 * piece from a square in a specific direction. The offset for a knight is
 * different for the other figures.
 */
public enum Direction {
    EAST(10, 21), NORTHEAST(11, 12), NORTH(1, -8), NORTHWEST(-9, -19), WEST(
        -10, -21), SOUTHWEST(-11, -12), SOUTH(-1, 8), SOUTHEAST(9, 19);

    /**
     * Add to a square value to go one step in the specified direction.
     *
     * White is South, Black is North.
     */
    public final int offset;

    /**
     * Add to a square value to go one knight-step in the specified direction.
     *
     * One up and two right is East. Two up one right is Northeast. Basically,
     * the orientation is shifted a bit counterclockwise.
     */
    public final int knight_offset;

    Direction(int offset, int knight_offset) {
        this.offset = offset;
        this.knight_offset = knight_offset;
    }
}
```

```
}

/**
 * Returns the direction in which a pawn of the specified color can move
 * (without capturing).
 *
 * @param color
 *         the color of the piece
 * @return NORTH for white and SOUTH for black
 */
public static Direction pawnDirection(Side color) {
    if (color == Side.WHITE) {
        return NORTH;
    } else {
        return SOUTH;
    }
}

/**
 * Returns a set of directions in which a pawn of the specified color can
 * capture other pieces.
 *
 * @param color
 *         the color of the piece
 * @return the set of directions allowed
 */
public static EnumSet<Direction> pawnCapturingDirections(Side color) {
    if (color == Side.WHITE) {
        return EnumSet.of(NORTHEAST, NORTHWEST);
    } else {
        return EnumSet.of(SOUTHEAST, SOUTHWEST);
    }
}
}
```

1.14 Position.java

```
package mitzi;

import java.util.ArrayList;
import java.util.Arrays;
import java.util.EnumSet;
import java.util.HashMap;
```

```
import java.util.HashSet;
import java.util.Iterator;
import java.util.List;
import java.util.Map;
import java.util.Set;

import mitzi.IrreversibleMoveStack.MoveInfo;

/**
 * The class implements the position of the figures on a chess board. The
 *   board
 * * is represented as two 8*8 +1 arrays - one for the sides, one for the
 *   pieces.
 * * All accesses to a square outside the chessboard are mapped to the 65th
 *   entry
 * * of the board, which is always null. This map from square to array index is
 * * performed by the function <code>squareToArrayIndex(square)</code>, which
 * * looks up in the <code>square_to_array_index array</code>. For informations
 * * about the <code>int</code> value of a square, see
 * * <code>SqaureHelper.java</code>.
 * */
public class Position implements IPosition {

    /**
     * the initial position of the sides
     */
    protected static Side[] initial_side_board = { Side.BLACK, Side.BLACK,
        Side.BLACK, Side.BLACK, Side.BLACK, Side.BLACK, Side.BLACK,
        Side.BLACK, Side.BLACK, Side.BLACK, Side.BLACK, Side.BLACK,
        Side.BLACK, Side.BLACK, Side.BLACK, Side.BLACK, null, null, null,
        null, null, null, null, null, null, null, null, null, null,
        null, null, null, null, null, null, null, null, null, null,
        null, null, null, null, null, null, null, Side.WHITE, Side.WHITE,
        Side.WHITE, Side.WHITE, Side.WHITE, Side.WHITE, Side.WHITE,
        Side.WHITE, Side.WHITE, Side.WHITE, Side.WHITE, Side.WHITE,
        Side.WHITE, Side.WHITE, Side.WHITE, Side.WHITE, null };

    /**
     * the initial position of the pieces
     */
    protected static Piece[] initial_piece_board = { Piece.ROOK, Piece.KNIGHT,
        Piece.BISHOP, Piece.QUEEN, Piece.KING, Piece.BISHOP, Piece.KNIGHT,
        Piece.ROOK, Piece.PAWN, Piece.PAWN, Piece.PAWN, Piece.PAWN,
        Piece.PAWN, Piece.PAWN, Piece.PAWN, Piece.PAWN, null, null, null,
        null, null, null, null, null, null, null, null, null, null,
        null,
```

```
    null, null, null, null, null, null, null, null, null, null, null,
    null, null, null, null, null, null, null, Piece.PAWN, Piece.PAWN,
    Piece.PAWN, Piece.PAWN, Piece.PAWN, Piece.PAWN, Piece.PAWN,
    Piece.PAWN, Piece.ROOK, Piece.KNIGHT, Piece.BISHOP, Piece.QUEEN,
    Piece.KING, Piece.BISHOP, Piece.KNIGHT, Piece.ROOK, null };

/**
 * this array maps the integer value of an square to the array index of
 * array representation of the board in this class
 */
protected static int[] square_to_array_index = { 64, 64, 64, 64, 64, 64,
    64, 64, 64, 64, 64, 56, 48, 40, 32, 24, 16, 8, 0, 64, 64, 57, 49,
    41, 33, 25, 17, 9, 1, 64, 64, 58, 50, 42, 34, 26, 18, 10, 2, 64,
    64, 59, 51, 43, 35, 27, 19, 11, 3, 64, 64, 60, 52, 44, 36, 28, 20,
    12, 4, 64, 64, 61, 53, 45, 37, 29, 21, 13, 5, 64, 64, 62, 54, 46,
    38, 30, 22, 14, 6, 64, 64, 63, 55, 47, 39, 31, 23, 15, 7, 64, 64,
    64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64,
    64, 64, 64 };

/**
 * the array of Sides, containing the information about the position of the
 * sides of the pieces
 */
private Side[] side_board = new Side[65];

/**
 * the array of Pieces, containing the information about the position of the
 * pieces
 */
private Piece[] piece_board = new Piece[65];

/**
 * squares c1, g1, c8 and g8 in ICCF numeric notation. do not change the
 * squares' order or bad things will happen! set to -1 if castling not
 * allowed.
 */
private int[] castling = { -1, -1, -1, -1 };

/**
 * the square of the en_passant_target, -1 if none.
 */
private int en_passant_target = -1;

/**
 * the side, which has to move
 */
```



```
private Side active_color;

/**
 * contains the information about the value of the position.
 */
private AnalysisResult analysis_result = null;

/**
 * This is the number of halfmoves since the last pawn advance or capture.
 * This is used to determine if a draw can be claimed under the fifty-move
 * rule.
 */
public int half_move_clock;

// The following class members are used to prevent multiple computations
/**
 * caching of the possible moves
 */
private List<IMove> possible_moves = new ArrayList<IMove>(50);

/**
 * true if, the possible moves were not computed for this position.
 */
private boolean possible_moves_is_null = true;

/**
 * caching if the current position is check.
 */
private Boolean is_check;

/**
 * caching if the current position is mate.
 */
private Boolean is_mate;

/**
 * caching if the current position is stalemate.
 */
private Boolean is_stale_mate;

// the following maps takes and Integer, representing the color, type or
// PieceValue and returns the set of squares or the number of squares!
/**
 * this map maps the PieceValue, i.e. 10*side.ordinal + piece.ordinal, to
 * the set of squares where the pieces of the side are positioned.
 */
```

```
private Map<Integer, Set<Integer>> occupied_squares_by_color_and_type = new
    HashMap<Integer, Set<Integer>>();

/**
 * this map maps the side, i.e. side.ordinal, to the set of squares where
 * the side has pieces.
 */
private Map<Side, Set<Integer>> occupied_squares_by_color = new
    HashMap<Side, Set<Integer>>();

/**
 * this map maps the piece, i.e. piece.ordinal, to the set of squares where
 * the pieces are positioned.
 */
private Map<Piece, Set<Integer>> occupied_squares_by_type = new
    HashMap<Piece, Set<Integer>>();

/**
 * caching the number of occupied squares for each side of a piece in an
 * small array.
 */
private int[] num_occupied_squares_by_color_and_type = new int[16];

/**
 * caching the positions of the kings. (indexed by the ordinal of the side)
 */
private int[] king_pos = new int[2];

/**
 * saves the side, which got captured by the last tinyDoMove
 */
private Side side_capture;

/**
 * saves the piece, which got captured by the last tinyDoMove
 */
private Piece piece_capture;

/**
 * saves if the old position after tinyDoMove was check or not
 */
Boolean old_check;

private Boolean pseudolegal_moves;
```

```
//
-----

/**
 * Resets and clears the stored class members.
 */
private void resetCache() {
    possible_moves.clear();
    possible_moves_is_null = true;
    pseudolegal_moves = null;
    is_check = null;
    is_mate = null;
    is_stale_mate = null;
    analysis_result = null;
    occupied_squares_by_color_and_type.clear();
    occupied_squares_by_type.clear();
    occupied_squares_by_color.clear();
}

/**
 * computes the index for the internal array representation of an square
 *
 * @param square
 *         the given square
 * @return the index
 */
private int squareToArrayIndex(int square) {
    if (square < 0)
        return 64;
    return square_to_array_index[square];
}

/**
 * computes a copy of the actual board, only the necessary informations are
 * copied, plus <code>num_occupied_squares_by_color_and_type</code>
 *
 * @return a incomplete copy of the board.
 */
@Override
public Position returnCopy() {
    Position newBoard = new Position();

    newBoard.active_color = active_color;
    newBoard.en_passant_target = en_passant_target;
    System.arraycopy(castling, 0, newBoard.castling, 0, 4);
}
```

```
System.arraycopy(side_board, 0, newBoard.side_board, 0, 65);
System.arraycopy(piece_board, 0, newBoard.piece_board, 0, 65);

System.arraycopy(num_occupied_squares_by_color_and_type, 0,
    newBoard.num_occupied_squares_by_color_and_type, 0, 16);

System.arraycopy(king_pos, 0, newBoard.king_pos, 0, 2);
return newBoard;
}

/**
 * returns the Side, which occupies a given square
 *
 * @return the side of the piece which is on the square
 */
public Side getSideFromBoard(int square) {
    int i = squareToArrayIndex(square);
    return side_board[i];
}

/**
 * returns the piece, which occupies a given square
 *
 * @return the piece which is on the square
 */
public Piece getPieceFromBoard(int square) {
    int i = squareToArrayIndex(square);
    return piece_board[i];
}

/**
 * sets a piece on the board.
 *
 * @param square
 *         the square, where the piece should be set
 * @param side
 *         the given side
 * @param piece
 *         the given piece
 */
private void setOnBoard(int square, Side side, Piece piece) {
    int i = squareToArrayIndex(square);
    side_board[i] = side;
    piece_board[i] = piece;
}
```

```
/**
 * returns the opponents side of the actual board
 *
 * @return the side of the opponent
 */
public Side getOpponentsColor() {
    if (active_color == Side.BLACK)
        return Side.WHITE;
    else
        return Side.BLACK;
}

/**
 * returns the eventual result of the position evaluation
 */
public AnalysisResult getAnalysisResult() {
    return analysis_result;
}

/**
 * updates the result of the board. (only if it more valuable, i.e.
 * comparison of the depth)
 *
 * @param analysis_result
 *        the new analysis result
 */
public void updateAnalysisResult(AnalysisResult analysis_result) {
    if (analysis_result == null)
        throw new NullPointerException();

    if (this.analysis_result == null
        || this.analysis_result.compareQualityTo(analysis_result) <= 0) {
        this.analysis_result = analysis_result;
    }
}

/**
 * checks is a move is a hit. there is no check, that the move is legal!.
 *
 * @param move
 *        the move to be checked
 * @return true, if it is a hit, false otherwise
 */
public boolean isHit(IMove move) {
    int dest = move.getToSquare();
    int src = move.getFromSquare();
}
```

```
// a hit happens iff the dest is an enemy or its en passant
if (getSideFromBoard(dest) == Side.getOppositeSide(active_color)
    || (getPieceFromBoard(src) == Piece.PAWN && dest == this
        .getEnPassant()))
    return true;
return false;
}

@Override
public void setToInitial() {
    System.arraycopy(initial_side_board, 0, side_board, 0, 65);
    System.arraycopy(initial_piece_board, 0, piece_board, 0, 65);

    castling[0] = 31;
    castling[1] = 71;
    castling[2] = 38;
    castling[3] = 78;

    half_move_clock = 0;
    en_passant_target = -1;
    active_color = Side.WHITE;

    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal() * 10
        + Piece.KING.ordinal()] = 1;
    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal() * 10
        + Piece.QUEEN.ordinal()] = 1;
    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal() * 10
        + Piece.ROOK.ordinal()] = 2;
    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal() * 10
        + Piece.BISHOP.ordinal()] = 2;
    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal() * 10
        + Piece.KNIGHT.ordinal()] = 2;
    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal() * 10
        + Piece.PAWN.ordinal()] = 8;
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal() * 10
        + Piece.KING.ordinal()] = 1;
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal() * 10
        + Piece.QUEEN.ordinal()] = 1;
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal() * 10
        + Piece.ROOK.ordinal()] = 2;
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal() * 10
        + Piece.BISHOP.ordinal()] = 2;
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal() * 10
        + Piece.KNIGHT.ordinal()] = 2;
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal() * 10
```

```
        + Piece.PAWN.ordinal()] = 8;

king_pos[Side.WHITE.ordinal()] = 51;
king_pos[Side.BLACK.ordinal()] = 58;
resetCache();
}

@Override
public void setToFEN(String fen) {
    side_board = new Side[65];
    piece_board = new Piece[65];

    castling[0] = -1;
    castling[1] = -1;
    castling[2] = -1;
    castling[3] = -1;
    en_passant_target = -1;

    resetCache();

    String[] fen_parts = fen.split(" ");

    // populate the squares
    String[] fen_rows = fen_parts[0].split("/");
    char[] pieces;
    for (int row = 1; row <= 8; row++) {
        int offset = 0;
        for (int column = 1; column + offset <= 8; column++) {
            pieces = fen_rows[8 - row].toCharArray();
            int square = (column + offset) * 10 + row;
            switch (pieces[column - 1]) {
                case 'P':
                    setOnBoard(square, Side.WHITE, Piece.PAWN);
                    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal()
                        * 10 + Piece.PAWN.ordinal()]++;
                    break;
                case 'R':
                    setOnBoard(square, Side.WHITE, Piece.ROOK);
                    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal()
                        * 10 + Piece.ROOK.ordinal()]++;
                    break;
                case 'N':
                    setOnBoard(square, Side.WHITE, Piece.KNIGHT);
                    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal()
                        * 10 + Piece.KNIGHT.ordinal()]++;
                    break;
            }
        }
    }
}
```

```
case 'B':
    setOnBoard(square, Side.WHITE, Piece.BISHOP);
    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal()
        * 10 + Piece.BISHOP.ordinal()]++;
    break;
case 'Q':
    setOnBoard(square, Side.WHITE, Piece.QUEEN);
    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal()
        * 10 + Piece.QUEEN.ordinal()]++;
    break;
case 'K':
    setOnBoard(square, Side.WHITE, Piece.KING);
    king_pos[Side.WHITE.ordinal()] = (byte) square;
    num_occupied_squares_by_color_and_type[Side.WHITE.ordinal()
        * 10 + Piece.KING.ordinal()]++;
    break;
case 'p':
    setOnBoard(square, Side.BLACK, Piece.PAWN);
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal()
        * 10 + Piece.PAWN.ordinal()]++;
    break;
case 'r':
    setOnBoard(square, Side.BLACK, Piece.ROOK);
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal()
        * 10 + Piece.ROOK.ordinal()]++;
    break;
case 'n':
    setOnBoard(square, Side.BLACK, Piece.KNIGHT);
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal()
        * 10 + Piece.KNIGHT.ordinal()]++;
    break;
case 'b':
    setOnBoard(square, Side.BLACK, Piece.BISHOP);
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal()
        * 10 + Piece.BISHOP.ordinal()]++;
    break;
case 'q':
    setOnBoard(square, Side.BLACK, Piece.QUEEN);
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal()
        * 10 + Piece.QUEEN.ordinal()]++;
    break;
case 'k':
    setOnBoard(square, Side.BLACK, Piece.KING);
    king_pos[Side.BLACK.ordinal()] = (byte) square;
    num_occupied_squares_by_color_and_type[Side.BLACK.ordinal()
        * 10 + Piece.KING.ordinal()]++;
```



```
        break;
    default:
        offset += Character.getNumericValue(pieces[column - 1]) - 1;
        break;
    }
}
}

// set active color
switch (fen_parts[1]) {
case "b":
    active_color = Side.BLACK;
    break;
case "w":
    active_color = Side.WHITE;
    break;
}

// set possible castling moves
if (!fen_parts[2].equals("-")) {
    char[] castlings = fen_parts[2].toCharArray();
    for (int i = 0; i < castlings.length; i++) {
        switch (castlings[i]) {
            case 'K':
                castling[1] = 71;
                break;
            case 'Q':
                castling[0] = 31;
                break;
            case 'k':
                castling[3] = 78;
                break;
            case 'q':
                castling[2] = 38;
                break;
        }
    }
}

// set en passant square
if (!fen_parts[3].equals("-")) {
    en_passant_target = SquareHelper.fromString(fen_parts[3]);
}
}

@Override
```

```
public IPosition doMove_copy(IMove move) {
    Position newBoard = this.returnCopy();

    int src = move.getFromSquare();
    int dest = move.getToSquare();

    Piece piece = getPieceFromBoard(src);
    Piece capture = getPieceFromBoard(dest);
    boolean resets_half_move_clock = false;
    // if promotion
    if (move.getPromotion() != null) {
        newBoard.setOnBoard(src, null, null);
        newBoard.setOnBoard(dest, active_color, move.getPromotion());
        resets_half_move_clock = true;
        newBoard.num_occupied_squares_by_color_and_type[active_color
            .ordinal() * 10 + Piece.PAWN.ordinal()]--;
        newBoard.num_occupied_squares_by_color_and_type[active_color
            .ordinal() * 10 + move.getPromotion().ordinal()]++;
    }
    // If castling
    else if (piece == Piece.KING && Math.abs((src - dest)) == 20) {
        newBoard.setOnBoard(dest, active_color, Piece.KING);
        newBoard.setOnBoard(src, null, null);
        newBoard.setOnBoard((src + dest) / 2, active_color, Piece.ROOK);
        if (SquareHelper.getColumn(dest) == 3)
            newBoard.setOnBoard(src - 40, null, null);
        else
            newBoard.setOnBoard(src + 30, null, null);
    }
    // If en passant
    else if (piece == Piece.PAWN && dest == this.getEnPassant()) {
        newBoard.setOnBoard(dest, active_color, Piece.PAWN);
        newBoard.setOnBoard(src, null, null);
        if (active_color == Side.WHITE) {
            capture = getPieceFromBoard(dest - 1);
            newBoard.setOnBoard(dest - 1, null, null);
        } else {
            capture = getPieceFromBoard(dest + 1);
            newBoard.setOnBoard(dest + 1, null, null);
        }
        resets_half_move_clock = true;
    }
    // Usual move
    else {
        Side side = getSideFromBoard(src);
```

```
newBoard.setOnBoard(dest, side, piece);
newBoard.setOnBoard(src, null, null);
if (this.getSideFromBoard(dest) != null || piece == Piece.PAWN)
    resets_half_move_clock = true;
}

if (resets_half_move_clock)
    newBoard.half_move_clock = 0;

// update counters
if (capture != null) {
    newBoard.num_occupied_squares_by_color_and_type[Side
        .getOppositeSide(active_color).ordinal()
        * 10
        + capture.ordinal()]--;
}

// Change active_color after move
newBoard.active_color = Side.getOppositeSide(active_color);

// Update en_passant
if (piece == Piece.PAWN && Math.abs(dest - src) == 2)
    newBoard.en_passant_target = (dest + src) / 2;
else
    newBoard.en_passant_target = -1;

// Update castling
if (piece == Piece.KING) {
    newBoard.king_pos[active_color.ordinal()] = (byte) dest;
    if (active_color == Side.WHITE && src == 51) {
        newBoard.castling[0] = -1;
        newBoard.castling[1] = -1;
    } else if (active_color == Side.BLACK && src == 58) {
        newBoard.castling[2] = -1;
        newBoard.castling[3] = -1;
    }
} else if (piece == Piece.ROOK) {
    if (active_color == Side.WHITE) {
        if (src == 81)
            newBoard.castling[1] = -1;
        else if (src == 11)
            newBoard.castling[0] = -1;
    } else {
        if (src == 88)
            newBoard.castling[3] = -1;
        else if (src == 18)
```

```
        newBoard.castling[2] = -1;
    }
}
if (capture == Piece.ROOK) {
    if (active_color == Side.BLACK) {
        if (dest == 81)
            newBoard.castling[1] = -1;
        else if (dest == 11)
            newBoard.castling[0] = -1;
    } else {
        if (dest == 88)
            newBoard.castling[3] = -1;
        else if (dest == 18)
            newBoard.castling[2] = -1;
    }
}

return newBoard;
}

@Override
public int getEnPassant() {
    return en_passant_target;
}

@Override
public boolean canCastle(int king_to) {
    if ((king_to == 31 && castling[0] != -1)
        || (king_to == 71 && castling[1] != -1)
        || (king_to == 38 && castling[2] != -1)
        || (king_to == 78 && castling[3] != -1)) {
        return true;
    } else {
        return false;
    }
}

@Override
public Boolean colorCanCastle(Side color) {

    // Set the right color
    if (active_color != color)
        active_color = getOpponentsColor();

    // check for castling
    if (!isCheckedPosition()) {
```

```
int off = 0;
int square = 51;

if (color == Side.BLACK) {
    off = 2;
    square = 58;
}

for (int i = 0; i < 2; i++) {
    int castle_flag = 0;
    Integer new_square = castling[i + off];
    // castling must still be possible to this side
    if (new_square != -1) {

        Direction dir;
        if (i == 0)
            dir = Direction.WEST;
        else
            dir = Direction.EAST;

        List<Integer> line = SquareHelper.getAllSquaresInDirection(
            square, dir);

        // Check each square if it is empty
        for (Integer squ : line) {
            if (getSideFromBoard(squ) != null) {
                castle_flag = 1;
                break;
            }
            if (squ == new_square)
                break;
        }
        if (castle_flag == 1)
            continue;

        // Check each square if the king on it would be check
        for (Integer squ : line) {
            setOnBoard(squ, active_color, Piece.KING);
            setOnBoard(square, null, null);

            if (isCheckPosition()) {
                setOnBoard(square, active_color, Piece.KING);
                setOnBoard(squ, null, null);
                break;
            }
            setOnBoard(square, active_color, Piece.KING);
        }
    }
}
```

```
        setOnBoard(squ, null, null);
        if (squ == new_square) {
            // If the end is reached, then stop checking.

            // undoing change of color
            if (active_color == color)
                active_color = getOpponentsColor();

            return true;
        }
    }
}

// undoing change of color
if (active_color == color)
    active_color = getOpponentsColor();

return false;
}

@Override
public Set<Integer> getOccupiedSquaresByColor(Side color) {

    if (occupied_squares_by_color.containsKey(color) == false) {
        Set<Integer> set = new HashSet<Integer>();

        for (int square : SquareHelper.all_squares)
            if (getSideFromBoard(square) == color)
                set.add(square);

        occupied_squares_by_color.put(color, set);
        return set;
    }
    return occupied_squares_by_color.get(color);
}

@Override
public Set<Integer> getOccupiedSquaresByType(Piece type) {

    if (occupied_squares_by_type.containsKey(type) == false) {
        Set<Integer> set = new HashSet<Integer>();

        for (int square : SquareHelper.all_squares)
            if (getPieceFromBoard(square) == type)
```

```
        set.add(square);

        occupied_squares_by_type.put(type, set);
        return set;
    }
    return occupied_squares_by_type.get(type);
}

@Override
public Set<Integer> getOccupiedSquaresByColorAndType(Side color, Piece
    type) {

    int value = color.ordinal() * 10 + type.ordinal();

    if (occupied_squares_by_color_and_type.containsKey(value) == false) {
        Set<Integer> set = new HashSet<Integer>();
        if (type == Piece.KING)
            set.add((int) king_pos[color.ordinal()]);
        else {
            for (int square : SquareHelper.all_squares)
                if (type == getPieceFromBoard(square)
                    && color == getSideFromBoard(square))
                    set.add(square);
        }
        occupied_squares_by_color_and_type.put(value, set);
        return set;
    }
    return occupied_squares_by_color_and_type.get(value);
}

@Override
public int getNumberOfPiecesByColor(Side side) {
    int result = 0;
    for (Piece piece : Piece.values()) {
        result += num_occupied_squares_by_color_and_type[side.ordinal()
            * 10 + piece.ordinal()];
    }
    return result;
}

@Override
public int getNumberOfPiecesByType(Piece piece) {
    int result = 0;
    for (Side side : Side.values()) {
        result += num_occupied_squares_by_color_and_type[side.ordinal()
            * 10 + piece.ordinal()];
    }
}
```

```
        * 10 + piece.ordinal()];
    }
    return result;
}

@Override
public int getNumberOfPiecesByColorAndType(Side color, Piece type) {
    int value = color.ordinal() * 10 + type.ordinal();
    return num_occupied_squares_by_color_and_type[value];
}

@Override
public List<IMove> getPossibleMoves() {
    return getPossibleMoves(false);
}

@Override
public List<IMove> getPossibleMoves(boolean pseudolegal) {

    if (possible_moves_is_null == true ) {

        // loop over all squares
        for (int square : SquareHelper.all_squares) {
            if (getSideFromBoard(square) == active_color)
                possible_moves.addAll(getPossibleMovesFrom(square,
                    pseudolegal));
        }
        pseudolegal_moves = pseudolegal;
        possible_moves_is_null = false;
    }
    else if (!pseudolegal && pseudolegal_moves)
    {
        Iterator<IMove> iter = possible_moves.iterator();
        while(iter.hasNext())
        {
            IMove m = iter.next();
            if(isCheckAfterMove(m))
                iter.remove();
        }
        pseudolegal_moves = false;
    }

    return possible_moves;
}
```



```
@Override
public List<IMove> getPossibleMovesFrom(int square, boolean pseudolegal) {
    // The case, that the destination is the opponents king cannot happen.

    Piece type = getPieceFromBoard(square);
    Side opp_color = getOpponentsColor();

    ArrayList<List<Integer>> all_squares = SquareHelper
        .getSquaresAllDirections(square);
    List<Integer> squares;
    List<IMove> moves = new ArrayList<IMove>(35);
    Move move;

    // Types BISHOP, QUEEN, ROOK
    if (type == Piece.BISHOP || type == Piece.QUEEN || type == Piece.ROOK) {

        // Loop over all directions and skip not appropriate ones
        for (Direction direction : Direction.values()) {

            // Skip N,W,E,W with BISHOP and skip NE,NW,SE,SW with ROOK
            if (((direction == Direction.NORTH
                || direction == Direction.EAST
                || direction == Direction.SOUTH || direction == Direction.WEST) &&
                type == Piece.BISHOP)
                || ((direction == Direction.NORTHWEST
                || direction == Direction.NORTHEAST
                || direction == Direction.SOUTHEAST || direction ==
                Direction.SOUTHWEST) && type == Piece.ROOK)) {

                continue;
            } else {
                // do stuff
                squares = SquareHelper.getAllSquaresInDirection(
                    all_squares, direction);

                for (Integer new_square : squares) {
                    Piece piece = getPieceFromBoard(new_square);
                    Side color = getSideFromBoard(new_square);
                    if (piece == null || color == opp_color) {

                        move = new Move(square, new_square);
                        moves.add(move);
                        if (piece != null && color == opp_color)
                            // not possible to go further
                            break;
                    } else
                }
            }
        }
    }
}
```

```
        break;
    }
}

}

}

if (type == Piece.PAWN) {
    // If Pawn has not moved yet (steps possible)
    if ((SquareHelper.getRow(square) == 2 && active_color == Side.WHITE)
        || (SquareHelper.getRow(square) == 7 && active_color ==
            Side.BLACK)) {

        if (getSideFromBoard(square
            + Direction.pawnDirection(active_color).offset) == null) {
            move = new Move(square, square
                + Direction.pawnDirection(active_color).offset);
            moves.add(move);
            if (getSideFromBoard(square + 2
                * Direction.pawnDirection(active_color).offset) == null) {
                move = new Move(square, square + 2
                    * Direction.pawnDirection(active_color).offset);
                moves.add(move);
            }
        }

        Set<Direction> pawn_capturing_directions = Direction
            .pawnCapturingDirections(active_color);
        for (Direction direction : pawn_capturing_directions) {
            if (getSideFromBoard(square + direction.offset) ==
                getOpponentsColor()) {
                move = new Move(square, square + direction.offset);
                moves.add(move);
            }
        }

    }

    // if Promotion will happen
    else if ((SquareHelper.getRow(square) == 7 && active_color ==
        Side.WHITE)
        || (SquareHelper.getRow(square) == 2 && active_color ==
            Side.BLACK)) {
        if (getSideFromBoard(square
            + Direction.pawnDirection(active_color).offset) == null) {
            move = new Move(square, square
```

```
        + Direction.pawnDirection(active_color).offset,
        Piece.QUEEN);
moves.add(move);
move = new Move(square, square
    + Direction.pawnDirection(active_color).offset,
    Piece.KNIGHT);
moves.add(move);

move = new Move(square, square
    + Direction.pawnDirection(active_color).offset,
    Piece.ROOK);
moves.add(move);
move = new Move(square, square
    + Direction.pawnDirection(active_color).offset,
    Piece.BISHOP);
moves.add(move);

}
Set<Direction> pawn_capturing_directions = Direction
    .pawnCapturingDirections(active_color);
for (Direction direction : pawn_capturing_directions) {
    if (getSideFromBoard(square + direction.offset) ==
        getOpponentsColor()) {
        move = new Move(square, square + direction.offset,
            Piece.QUEEN);
        moves.add(move);
        move = new Move(square, square + direction.offset,
            Piece.KNIGHT);
        moves.add(move);

        move = new Move(square, square + direction.offset,
            Piece.ROOK);
        moves.add(move);
        move = new Move(square, square + direction.offset,
            Piece.BISHOP);
        moves.add(move);
    }
}

}
// Usual turn and en passant is possible, no promotion
else {
    if (getSideFromBoard(square
        + Direction.pawnDirection(active_color).offset) == null) {
        move = new Move(square, square
            + Direction.pawnDirection(active_color).offset);
```

```
        moves.add(move);
    }
    Set<Direction> pawn_capturing_directions = Direction
        .pawnCapturingDirections(active_color);
    for (Direction direction : pawn_capturing_directions) {
        if ((getSideFromBoard(square + direction.offset) ==
            getOpponentsColor())
            || square + direction.offset == getEnPassant()) {
            move = new Move(square, square + direction.offset);
            moves.add(move);
        }
    }
}

if (type == Piece.KING) {
    for (Direction direction : Direction.values()) {
        Integer new_square = square + direction.offset;

        if (SquareHelper.isValidSquare(new_square)) {
            move = new Move(square, new_square);
            Side side = getSideFromBoard(new_square);
            // if the new square is empty or occupied by the opponent
            if (side != active_color)
                moves.add(move);
        }
    }
}

// Castle Moves
// If the King is not check now, try castle moves
if (!isCheckedPosition()) {
    int off = 0;
    if (active_color == Side.BLACK)
        off = 2;

    for (int i = 0; i < 2; i++) {
        int castle_flag = 0;
        Integer new_square = castling[i + off];
        // castling must still be possible to this side
        if (new_square != -1) {

            Direction dir;
            if (i == 0)
                dir = Direction.WEST;
            else
                dir = Direction.EAST;
```

```
List<Integer> line = SquareHelper
    .getAllSquaresInDirection(square, dir);

// Check each square if it is empty
int last_squ = line.get(line.size() - 1);
for (Integer squ : line) {
    if (squ == last_squ)
        break;
    if (getSideFromBoard(squ) != null) {
        castle_flag = 1;
        break;
    }
}

if (castle_flag == 1)
    continue;

// Check each square if the king on it would be check
for (Integer squ : line) {

    setOnBoard(squ, active_color, Piece.KING);
    setOnBoard(square, null, null);
    is_check = null;
    king_pos[active_color.ordinal()] = squ;
    if (isCheckPosition()) {
        setOnBoard(square, active_color, Piece.KING);
        setOnBoard(squ, null, null);
        is_check = false; // king is not check in the
                        // original position
        king_pos[active_color.ordinal()] = square;
        break;
    }
    setOnBoard(square, active_color, Piece.KING);
    setOnBoard(squ, null, null);
    is_check = false;
    king_pos[active_color.ordinal()] = squ;
    if (squ == new_square) {
        // if everything is right, then add the move
        move = new Move(square, squ);
        moves.add(move);
        break;
    }
}
}
```

```
    }
  }
}
if (type == Piece.KNIGHT) {
    squares = SquareHelper.getAllSquaresByKnightStep(square);
    for (Integer new_square : squares) {
        Side side = getSideFromBoard(new_square);
        if (side != active_color) {
            move = new Move(square, new_square);
            moves.add(move);
        }
    }
}

if (!pseudolegal) {
    // remove invalid positions
    Iterator<IMove> iter = moves.iterator();
    IMove mv;
    while (iter.hasNext()) {
        mv = iter.next();
        if (isCheckAfterMove(mv))
            iter.remove();
    }
}
return moves;
}

@Override
public List<IMove> getPotentialAttackersTo(int square) {
    List<IMove> result = new ArrayList<IMove>();

    for (Piece p : Piece.values())
        getPotentialAttackersTo(square, p, result);

    // TODO: en passant

    return result;
}

@Override
public List<IMove> getPossibleMovesTo(int square) {

    List<IMove> result = new ArrayList<IMove>();
    Side s = getSideFromBoard(square);
    if (s == active_color)
        return result;
}
```

```
Side side = active_color;
Side opp_side = Side.getOppositeSide(side);

IMove move;

EnumSet<Piece> dirs = EnumSet.of(Piece.BISHOP, Piece.ROOK,
    Piece.KNIGHT, Piece.KING);
if (s == opp_side)
    getPotentialAttackersTo(square, Piece.PAWN, result);

for (Piece p : dirs)
    getPotentialAttackersTo(square, p, result);

// en passant
if (s == null
    && (square + Direction.pawnDirection(opp_side).offset ==
        en_passant_target)) {
    for (Direction dir : Direction.pawnCapturingDirections(opp_side)) {
        int squ = square + dir.offset;
        if (getPieceFromBoard(squ) == Piece.PAWN
            && getSideFromBoard(squ) == active_color) {
            move = new Move(squ, square);
            if (!isCheckedAfterMove(move))
                result.add(move);
        }
    }
}

// Castling moves
if (canCastle(square)) {
    if (!isCheckedPosition()) {

        int old_king_pos = king_pos[active_color.ordinal()];
        int castle_flag = 0;

        Direction dir;
        if (square < king_pos[active_color.ordinal()])
            dir = Direction.WEST;
        else
            dir = Direction.EAST;

        List<Integer> line = SquareHelper.getAllSquaresInDirection(
            old_king_pos, dir);

        // Check each square if it is empty
```

```
int last_squ = line.get(line.size() - 1);
for (Integer squ : line) {
    if (squ == last_squ)
        break;
    if (getSideFromBoard(squ) != null) {
        castle_flag = 1;
        break;
    }
}

if (castle_flag != 1) {

    // Check each square if the king on it would be check
    for (Integer squ : line) {

        setOnBoard(squ, active_color, Piece.KING);
        setOnBoard(old_king_pos, null, null);
        is_check = null;
        king_pos[active_color.ordinal()] = squ;
        if (isCheckPosition()) {
            setOnBoard(old_king_pos, active_color, Piece.KING);
            setOnBoard(squ, null, null);
            is_check = false; // king is not check in the
                            // original position
            king_pos[active_color.ordinal()] = old_king_pos;
            break;
        }
        setOnBoard(old_king_pos, active_color, Piece.KING);
        setOnBoard(squ, null, null);
        is_check = false;
        king_pos[active_color.ordinal()] = old_king_pos;
        if (squ == square) {
            // if everything is right, then add the move
            move = new Move(old_king_pos, squ);
            result.add(move);
            break;
        }
    }
}

}

// usual pawn move (1 square)
int new_square = square + Direction.pawnDirection(opp_side).offset;
if (s == null && getPieceFromBoard(new_square) == Piece.PAWN
```



```
        && getSideFromBoard(new_square) == active_color) {
    if (SquareHelper.getRow(square) == SquareHelper.getRowForSide(
        active_color, 8)) {
        // promotion
        move = new Move(new_square, square);
        if (!isCheckAfterMove(move)) {
            move = new Move(new_square, square, Piece.QUEEN);
            result.add(move);
            move = new Move(new_square, square, Piece.KNIGHT);
            result.add(move);
            move = new Move(new_square, square, Piece.BISHOP);
            result.add(move);
            move = new Move(new_square, square, Piece.ROOK);
            result.add(move);
        }
    } else {
        // usual move
        move = new Move(new_square, square);
        if (!isCheckAfterMove(move))
            result.add(move);
    }
}

// usual pawn move (2 squares)
new_square += Direction.pawnDirection(opp_side).offset;
if (SquareHelper.getRow(square) == SquareHelper.getRowForSide(side, 4)
    && s == null && getPieceFromBoard(new_square) == Piece.PAWN
    && getSideFromBoard(new_square) == active_color) {
    move = new Move(new_square, square);
    if (!isCheckAfterMove(move))
        result.add(move);
}

return result;
}

@Override
public List<IMove> getPotentialAttackersTo(int square, Piece attacking_dir)
{
    List<IMove> result = new ArrayList<IMove>();
    getPotentialAttackersTo(square, attacking_dir, result);
    return result;
}

@Override
public void getPotentialAttackersTo(int square, Piece attacking_dir,
```

```
List<IMove> result) {

Side side = active_color;
Side opp_side = Side.getOppositeSide(active_color);
List<Integer> squares;
IMove move;

if (attacking_dir == Piece.PAWN) {
    for (Direction dir : Direction.pawnCapturingDirections(opp_side)) {
        int new_square = square + dir.offset;
        if (getPieceFromBoard(new_square) == Piece.PAWN
            && getSideFromBoard(new_square) == side) {

            move = new Move(new_square, square);
            if (SquareHelper.getRow(square) == SquareHelper
                .getRowForSide(side, 8)) {
                // promotion
                if (!isCheckAfterMove(move)) {
                    move = new Move(new_square, square, Piece.QUEEN);
                    result.add(move);
                    move = new Move(new_square, square, Piece.KNIGHT);
                    result.add(move);
                    move = new Move(new_square, square, Piece.BISHOP);
                    result.add(move);
                    move = new Move(new_square, square, Piece.ROOK);
                    result.add(move);
                }
            } else if (!isCheckAfterMove(move))
                result.add(move);
        }
    }
} else if (attacking_dir == Piece.KNIGHT) {
    squares = SquareHelper.getAllSquaresByKnightStep(square);
    for (int squ : squares) {
        if (getPieceFromBoard(squ) == Piece.KNIGHT
            && getSideFromBoard(squ) == side) {
            move = new Move(squ, square);
            if (!isCheckAfterMove(move))
                result.add(move);
        }
    }
} else if (attacking_dir == Piece.KING) {
    for (Direction dir : Direction.values()) {
        if (getPieceFromBoard(square + dir.offset) == Piece.KING
            && getSideFromBoard(square + dir.offset) == side) {
            move = new Move(square + dir.offset, square);
```

```
        if (!isCheckAfterMove(move)) {
            result.add(move);
            break;
        }
    }
}

EnumSet<Direction> dirs = null;
if (attacking_dir == Piece.ROOK)
    dirs = EnumSet.of(Direction.NORTH, Direction.SOUTH, Direction.WEST,
        Direction.EAST);
else if (attacking_dir == Piece.BISHOP)
    dirs = EnumSet.of(Direction.NORTHEAST, Direction.SOUTHEAST,
        Direction.NORTHWEST, Direction.SOUTHWEST);

if (attacking_dir == Piece.ROOK || attacking_dir == Piece.BISHOP) {
    ArrayList<List<Integer>> all_squares = SquareHelper
        .getSquaresAllDirections(square);
    for (Direction dir : dirs) {
        squares = all_squares.get(dir.ordinal());
        for (int squ : squares)
            if (getSideFromBoard(squ) == opp_side)
                break;
            else if (getSideFromBoard(squ) == side) {

                Piece p = getPieceFromBoard(squ);
                if (p == Piece.QUEEN || p == attacking_dir) {

                    move = new Move(squ, square);
                    if (!isCheckAfterMove(move))
                        result.add(move);
                }
                break;
            }
    }
}

@Override
public boolean isCheckAfterMove(IMove move) {

    boolean is_check = false;

    tinyDoMove(move);
    active_color = Side.getOppositeSide(active_color);
```

```
    if (isCheckPosition())
        is_check = true;
    active_color = Side.getOppositeSide(active_color);
    tinyUndoMove(move);

    return is_check;
}

@Override
public boolean isCheckPosition() {
    if (is_check == null) {
        is_check = true;
        int king_pos = getKingPos(active_color);
        ArrayList<List<Integer>> all_squares = SquareHelper
            .getSquaresAllDirections(king_pos);
        // go in each direction
        for (Direction direction : Direction.values()) {
            List<Integer> line = SquareHelper.getAllSquaresInDirection(
                all_squares, direction);
            // go until
            int iter = 0;
            for (int square : line) {
                iter++;
                // some piece is found
                Piece piece = getPieceFromBoard(square);
                if (piece != null) {
                    Side side = getSideFromBoard(square);
                    if (side == active_color) {
                        break;
                    } else {
                        if (piece == Piece.PAWN && iter == 1) {
                            if (((direction == Direction.NORTHEAST || direction ==
                                Direction.NORTHWEST) && active_color == Side.WHITE)
                                || ((direction == Direction.SOUTHEAST || direction ==
                                    Direction.SOUTHWEST) && active_color == Side.BLACK)) {
                                return true;
                            }
                        }
                        } else if (piece == Piece.ROOK) {
                            if (direction == Direction.EAST
                                || direction == Direction.WEST
                                || direction == Direction.NORTH
                                || direction == Direction.SOUTH) {
                                return true;
                            }
                        } else if (piece == Piece.BISHOP) {
```

```
        if (direction == Direction.NORTHEAST
            || direction == Direction.NORTHWEST
            || direction == Direction.SOUTHEAST
            || direction == Direction.SOUTHWEST) {
            return true;
        }
    } else if (piece == Piece.QUEEN) {
        return true;
    } else if (piece == Piece.KING && iter == 1) {
        return true;
    }
    break;
}
}
}
}

// check for knight attacks
List<Integer> knight_squares = SquareHelper
    .getAllSquaresByKnightStep(king_pos);
for (int square : knight_squares) {
    Piece piece = getPieceFromBoard(square);
    if (piece == Piece.KNIGHT) {
        Side side = getSideFromBoard(square);
        if (side != active_color) {
            return true;
        }
    }
}
is_check = false;
}
return is_check.booleanValue();

}

@Override
public boolean isMatePosition() {
    if (is_mate == null) {
        is_mate = true;
        List<IMove> moves = getPossibleMoves();
        if (moves.isEmpty() && isCheckPosition())
            return true;
        is_mate = false;
    }
    return is_mate.booleanValue();
}
```

```
@Override
public boolean isStaleMatePosition() {
    if (is_stale_mate == null) {
        is_stale_mate = true;
        List<IMove> moves = getPossibleMoves();
        if (moves.isEmpty())
            return true;
        is_stale_mate = false;
    }
    return is_stale_mate.booleanValue();
}

@Override
public boolean isPossibleMove(IMove move) {

    List<IMove> possible_moves = getPossibleMoves();

    return possible_moves.contains(move);
}

public String toString() {
    return toFEN();
}

@Override
public String toFEN() {
    StringBuilder fen = new StringBuilder();

    // piece placement
    for (int row = 0; row < 8; row++) {

        int counter = 0;

        for (int column = 0; column < 8; column++) {

            if (side_board[row * 8 + column] == null) {
                counter++;
            } else {
                if (counter != 0) {
                    fen.append(counter);
                    counter = 0;
                }
                fen.append(PieceHelper.toString(
                    side_board[row * 8 + column], piece_board[row * 8
                        + column]));
            }
        }
    }
}
```

```
    }
    if (column == 7 && counter != 0) {
        fen.append(counter);
    }
}

if (row != 7) {
    fen.append("/");
}
fen.append(" ");

// active color
if (active_color == Side.WHITE) {
    fen.append("w");
} else {
    fen.append("b");
}
fen.append(" ");

// castling availability
boolean castle_flag = false;
if (castling[1] != -1) {
    fen.append("K");
    castle_flag = true;
}
if (castling[0] != -1) {
    fen.append("Q");
    castle_flag = true;
}
if (castling[3] != -1) {
    fen.append("k");
    castle_flag = true;
}
if (castling[2] != -1) {
    fen.append("q");
    castle_flag = true;
}
if (!castle_flag) {
    fen.append("-");
}
fen.append(" ");

// en passant target square
if (en_passant_target == -1) {
    fen.append("-");
}
```

```
    } else {
        fen.append(SquareHelper.toString(en_passant_target));
    }

    return fen.toString();
}

@Override
public Side getActiveColor() {
    return active_color;
}

@Override
public int hashCode() {
    final int prime = 31;
    int result = 1;

    for (Side element : side_board)
        result = prime * result
            + (element == null ? 0 : element.ordinal() + 1);

    for (Piece element : piece_board)
        result = prime * result
            + (element == null ? 0 : element.ordinal() + 1);

    for (int element : castling)
        result = prime * result + element;

    result = prime * result + active_color.ordinal();

    result = prime * result + en_passant_target;

    return result;
}

@Override
public boolean equals(Object obj) {
    if (this == obj) {
        return true;
    }
    if (obj == null) {
        return false;
    }
    if (getClass() != obj.getClass()) {
        return false;
    }
}
```



```
Position other = (Position) obj;
if (!Arrays.equals(side_board, other.side_board)
    || !Arrays.equals(piece_board, other.piece_board)
    || !Arrays.equals(castling, other.castling)
    || en_passant_target != other.en_passant_target
    || active_color != other.active_color) {
    return false;
}
return true;
}

@Override
public List<IMove> generateCaptures() {
    List<IMove> poss_moves = getPossibleMoves();
    List<IMove> result = new ArrayList<IMove>(poss_moves.size());

    for (IMove move : poss_moves)
        if (isHit(move) || move.getPromotion() != null)
            result.add(move);
    return result;
}

@Override
public long hashCode2() {
    final int prime = 23;
    long result = 1;

    for (Side element : side_board)
        result = prime * result
            + (element == null ? 0 : element.ordinal() + 1);

    for (Piece element : piece_board)
        result = prime * result
            + (element == null ? 0 : element.ordinal() + 1);

    for (int element : castling)
        result = prime * result + element;

    result = prime * result + active_color.ordinal();

    result = prime * result + en_passant_target;

    return result;
}

@Override
```

```
public int getKingPos(Side side) {
    return king_pos[side.ordinal()];
}

@Override
public void cacheOccupiedSquares() {

    Side s;
    Piece p;
    Set<Integer> w_pawn = new HashSet<Integer>();
    Set<Integer> w_rook = new HashSet<Integer>();
    Set<Integer> w_bishop = new HashSet<Integer>();
    Set<Integer> w_knight = new HashSet<Integer>();
    Set<Integer> w_queen = new HashSet<Integer>();

    Set<Integer> b_pawn = new HashSet<Integer>();
    Set<Integer> b_rook = new HashSet<Integer>();
    Set<Integer> b_bishop = new HashSet<Integer>();
    Set<Integer> b_knight = new HashSet<Integer>();
    Set<Integer> b_queen = new HashSet<Integer>();

    for (int square : SquareHelper.all_squares) {

        s = getSideFromBoard(square);
        if (s == null)
            continue;
        p = getPieceFromBoard(square);
        switch (s) {
            case WHITE:
                switch (p) {
                    case PAWN:
                        w_pawn.add(square);
                        break;
                    case ROOK:
                        w_rook.add(square);
                        break;
                    case BISHOP:
                        w_bishop.add(square);
                        break;
                    case KNIGHT:
                        w_knight.add(square);
                        break;
                    case QUEEN:
                        w_queen.add(square);
                        break;
                    default:

```

```
        break;
    }
    break;
case BLACK:
    switch (p) {
    case PAWN:
        b_pawn.add(square);
        break;
    case ROOK:
        b_rook.add(square);
        break;
    case BISHOP:
        b_bishop.add(square);
        break;
    case KNIGHT:
        b_knight.add(square);
        break;
    case QUEEN:
        b_queen.add(square);
        break;
    default:
        break;
    }
    break;
}

}

occupied_squares_by_color_and_type.put(Side.WHITE.ordinal() * 10
    + Piece.PAWN.ordinal(), w_pawn);
occupied_squares_by_color_and_type.put(Side.WHITE.ordinal() * 10
    + Piece.ROOK.ordinal(), w_rook);
occupied_squares_by_color_and_type.put(Side.WHITE.ordinal() * 10
    + Piece.BISHOP.ordinal(), w_bishop);
occupied_squares_by_color_and_type.put(Side.WHITE.ordinal() * 10
    + Piece.KNIGHT.ordinal(), w_knight);
occupied_squares_by_color_and_type.put(Side.WHITE.ordinal() * 10
    + Piece.QUEEN.ordinal(), w_queen);

occupied_squares_by_color_and_type.put(Side.BLACK.ordinal() * 10
    + Piece.PAWN.ordinal(), b_pawn);
occupied_squares_by_color_and_type.put(Side.BLACK.ordinal() * 10
    + Piece.ROOK.ordinal(), b_rook);
occupied_squares_by_color_and_type.put(Side.BLACK.ordinal() * 10
    + Piece.BISHOP.ordinal(), b_bishop);
occupied_squares_by_color_and_type.put(Side.BLACK.ordinal() * 10
```

```
        + Piece.KNIGHT.ordinal(), b_knight);
occupied_squares_by_color_and_type.put(Side.BLACK.ordinal() * 10
        + Piece.QUEEN.ordinal(), b_queen);

}

@Override
public void doMove(IMove move) {

    int src = move.getFromSquare();
    int dest = move.getToSquare();

    Piece piece = getPieceFromBoard(src);
    Piece capture = getPieceFromBoard(dest);

    setOnBoard(dest, active_color, piece);
    setOnBoard(src, null, null);

    boolean resets_half_move_clock = false;

    // if promotion
    if (move.getPromotion() != null) {
        setOnBoard(dest, active_color, move.getPromotion());
        resets_half_move_clock = true;
        num_occupied_squares_by_color_and_type[active_color.ordinal() * 10
            + Piece.PAWN.ordinal()]--;
        num_occupied_squares_by_color_and_type[active_color.ordinal() * 10
            + move.getPromotion().ordinal()]++;
    }
    // If castling
    else if (piece == Piece.KING && Math.abs((src - dest)) == 20) {
        setOnBoard((src + dest) / 2, active_color, Piece.ROOK);
        if (SquareHelper.getColumn(dest) == 3)
            setOnBoard(src - 40, null, null);
        else
            setOnBoard(src + 30, null, null);
    }
    // If en passant
    else if (piece == Piece.PAWN && dest == en_passant_target) {
        if (active_color == Side.WHITE) {
            setOnBoard(dest - 1, null, null);
        } else {
            setOnBoard(dest + 1, null, null);
        }
        num_occupied_squares_by_color_and_type[Side.getOppositeSide(
            active_color).ordinal()]
    }
```

```
        * 10 + Piece.PAWN.ordinal()]--;
    resets_half_move_clock = true;
}
// Usual move
else {
    if (capture != null || piece == Piece.PAWN)
        resets_half_move_clock = true;
}

// update counters
if (capture != null) {
    num_occupied_squares_by_color_and_type[Side.getOppositeSide(
        active_color).ordinal()
        * 10 + capture.ordinal()]--;
}

IrreversibleMoveStack.addInfo(half_move_clock, castling,
    en_passant_target, capture, is_check);

// reset half move clock
if (resets_half_move_clock)
    half_move_clock = 0;

// Update en_passant
if (piece == Piece.PAWN && Math.abs(dest - src) == 2)
    en_passant_target = (dest + src) / 2;
else
    en_passant_target = -1;

// Update castling
if (piece == Piece.KING) {
    king_pos[active_color.ordinal()] = (byte) dest;
    if (active_color == Side.WHITE && src == 51) {
        castling[0] = -1;
        castling[1] = -1;
    } else if (active_color == Side.BLACK && src == 58) {
        castling[2] = -1;
        castling[3] = -1;
    }
} else if (piece == Piece.ROOK) {
    if (active_color == Side.WHITE) {
        if (src == 81)
            castling[1] = -1;
        else if (src == 11)
            castling[0] = -1;
    } else {
```

```
        if (src == 88)
            castling[3] = -1;
        else if (src == 18)
            castling[2] = -1;
    }
}
if (capture == Piece.ROOK) {
    if (active_color == Side.BLACK) {
        if (dest == 81)
            castling[1] = -1;
        else if (dest == 11)
            castling[0] = -1;
    } else {
        if (dest == 88)
            castling[3] = -1;
        else if (dest == 18)
            castling[2] = -1;
    }
}

// Change active_color after move
active_color = Side.getOppositeSide(active_color);

resetCache();

}

@Override
public void undoMove(IMove move) {

    resetCache();

    int src = move.getFromSquare();
    int dest = move.getToSquare();

    Piece piece = getPieceFromBoard(dest);

    // Change active_color after move
    active_color = Side.getOppositeSide(active_color);

    // get the missing information
    MoveInfo inf = IrreversibleMoveStack.irr_move_info.removeLast();

    en_passant_target = inf.en_passant_square;
    Piece capture = inf.capture;
    half_move_clock = inf.half_move_clock;
```

```
System.arraycopy(inf.castling, 0, castling, 0, 4);
is_check = inf.is_check;

setOnBoard(src, active_color, piece);
if (capture != null)
    setOnBoard(dest, Side.getOppositeSide(active_color), capture);
else
    setOnBoard(dest, null, null);

// if promotion
if (move.getPromotion() != null) {
    setOnBoard(src, active_color, Piece.PAWN);
    num_occupied_squares_by_color_and_type[active_color.ordinal() * 10
        + Piece.PAWN.ordinal()]++;
    num_occupied_squares_by_color_and_type[active_color.ordinal() * 10
        + move.getPromotion().ordinal()]--;
}
// If castling
else if (piece == Piece.KING && Math.abs((src - dest)) == 20) {
    setOnBoard((src + dest) / 2, null, null);
    if (SquareHelper.getColumn(dest) == 3)
        setOnBoard(src - 40, active_color, Piece.ROOK);
    else
        setOnBoard(src + 30, active_color, Piece.ROOK);
}
// If en passant
else if (piece == Piece.PAWN && dest == en_passant_target) {
    if (active_color == Side.WHITE) {
        setOnBoard(dest - 1, Side.getOppositeSide(active_color),
            Piece.PAWN);
    } else {
        setOnBoard(dest + 1, Side.getOppositeSide(active_color),
            Piece.PAWN);
    }
    num_occupied_squares_by_color_and_type[Side.getOppositeSide(
        active_color).ordinal()
        * 10 + Piece.PAWN.ordinal()]++;
}

// update counters
if (capture != null) {
    num_occupied_squares_by_color_and_type[Side.getOppositeSide(
        active_color).ordinal()
        * 10 + capture.ordinal()]++;
}
```

```
if (piece == Piece.KING) {
    king_pos[active_color.ordinal()] = (byte) src;
}

is_mate = false;
is_stale_mate = false;

}

/**
 * Performs a incomplete version of doMove. This function only sets the new
 * figure, deletes the captures ones (are saved in side_capture and
 * piece_capture) and changes the active color. Note that it is not possible
 * to perform tinyDoMove twice, because the captured figure of the first
 * application will be lost.
 *
 * @param move
 *         the move to be performed, must be a legal move
 */
private void tinyDoMove(IMove move) {

    int src = move.getFromSquare();
    int dest = move.getToSquare();

    Piece piece = getPieceFromBoard(src);
    Side s_piece = getSideFromBoard(src);
    piece_capture = getPieceFromBoard(dest);
    side_capture = getSideFromBoard(dest);

    setOnBoard(dest, s_piece, piece);
    setOnBoard(src, null, null);

    // if promotion
    if (move.getPromotion() != null) {
        setOnBoard(dest, s_piece, move.getPromotion());
    }
    // If castling
    else if (piece == Piece.KING && Math.abs((src - dest)) == 20) {
        setOnBoard((src + dest) / 2, s_piece, Piece.ROOK);
        if (SquareHelper.getColumn(dest) == 3)
            setOnBoard(src - 40, null, null);
        else
            setOnBoard(src + 30, null, null);
    }
}
```



```
// If en passant
else if (piece == Piece.PAWN && dest == en_passant_target) {
    if (active_color == Side.WHITE)
        setOnBoard(dest - 1, null, null);
    else
        setOnBoard(dest + 1, null, null);
}

// Update castling
if (piece == Piece.KING)
    king_pos[s_piece.ordinal()] = dest;

// Change active_color after move
active_color = Side.getOppositeSide(active_color);

old_check = is_check;

is_check = null;
is_mate = null;
is_stale_mate = null;
}

/**
 * inverts the function tinyDoMove(), note that only one application can be
 * inverted!
 *
 * @param move
 *         the move to be inverted.
 */
private void tinyUndoMove(IMove move) {

    int src = move.getFromSquare();
    int dest = move.getToSquare();

    Piece piece = getPieceFromBoard(dest);
    Side s_piece = getSideFromBoard(dest);

    // Change active_color after move
    active_color = Side.getOppositeSide(active_color);

    setOnBoard(dest, side_capture, piece_capture);
    setOnBoard(src, s_piece, piece);
    // if promotion
    if (move.getPromotion() != null) {
        setOnBoard(src, s_piece, Piece.PAWN);
    }
}
```

```
    }
    // If castling
    else if (piece == Piece.KING && Math.abs((src - dest)) == 20) {
        setOnBoard((src + dest) / 2, null, null);
        if (SquareHelper.getColumn(dest) == 3)
            setOnBoard(src - 40, s_piece, Piece.ROOK);
        else
            setOnBoard(src + 30, s_piece, Piece.ROOK);
    }
    // If en passant
    else if (piece == Piece.PAWN && dest == en_passant_target) {
        if (s_piece == Side.WHITE)
            setOnBoard(dest - 1, Side.getOppositeSide(s_piece), Piece.PAWN);
        else
            setOnBoard(dest + 1, Side.getOppositeSide(s_piece), Piece.PAWN);
    }

    // Update king position
    if (piece == Piece.KING)
        king_pos[s_piece.ordinal()] = src;

    is_check = old_check;
    is_mate = false;
    is_stale_mate = false;
}

@Override
public void setHalfMoveClock(int paramInt) {
    half_move_clock = paramInt;
}

@Override
public int getHalfMoveClock() {
    return half_move_clock;
}
}
```

1.15 AnalysisResult.java

```
package mitzi;
```

```
import java.util.LinkedList;

/*
 * Size of the class:
 * Header:      8 bytes
 * short :      2 bytes
 * Boolean:     16 bytes (8 header + 1 boolean + 7 round up to multiple of 8)
 * boolean:     1 byte
 * 2*byte:      2 bytes
 * Flag:        4 bytes (like int? )
 * IMove:       16 bytes ( 8 header + 2 short+ 2 short + 4 Piece (like int) + 0
 *               round up to multiple of 8)
 * long:        8 bytes
 * linkedList:  24 + (8 + 24 + 16)k = 24 + 48k bytes
 *               (list: 8 header + 8 reference to first elem + 4 size + 8k reference
 *               to each node + 4 round up 24+ 8k)
 *               (node: 8 header + 8 reference to next node + 8 reference to class =
 *               24)
 *               (class: 16 byte)
 *
 * round up:    7 byte
 * total size:  88 + 48k bytes.
 *
 * k = 3 : 232 bytes
 * k = 5 : 328 bytes
 * k =10 : 568 bytes
 *
 * lets assume that a single analysis needs about 500 bytes.
 * Then a 500 MB TranspositionTable can hold about 1 Mio entries.
 *
 * http://www.javamex.com/tutorials/memory/object\_memory\_usage.shtml
 * http://www.sandeshshrestha.com/blog/memory-used-by-java-data-types/
 */

public final class AnalysisResult {

    /**
     * The boards score in centipawns.
     */
    public short score;

    /**
     * If true, the board is a stalemate position. I. e. no moves are possible
     * but there is no check. If null, then it has not been analyzed.
     */
}
```

```
public Boolean is_stalemate;

/**
 * If the evaluation method considers this board to be in an unstable state
 * and recommends a deeper evaluation or is simply not sure, this is set to
 * true.
 */
public boolean needs_deeper;
/**
 * The distance to (complete) search depth at which this result was
 * obtained.
 */
public byte plys_to_eval0 = 0;

/**
 * The distance to selective search depth at which this result was obtained.
 */
public byte plys_to_seldepth = 0;

/**
 * The state of the result in alpha-beta search: exact, fail-high or
 * fail-low
 */
public Flag flag;

/**
 * The best move from current board.
 */
public IMove best_move;

/**
 * Since AnalysisResults are stored in the Transposition Tables
 * (ResultCache), it is important to ensure that the AnalysisResult
 * corresponding to the actual position should be used, if there are
 * collisions with hashvalues. Therefore a second one (this one) is created
 * to identify the position and these problems unlikely.
 */
public long hashvalue;

/**
 * A sorted list of the better moves in reverse order, i.e. the last moves
 * are better, then the first ones.
 */
public LinkedList<IMove> best_moves = new LinkedList<IMove>();

AnalysisResult(int score, Boolean is_stalemate, boolean needs_deeper,
```

```
    int plys_to_eval0, int plys_to_seldepth, Flag flag) {
this.score = (short) score;
this.is_stalemate = is_stalemate;
this.needs_deeper = needs_deeper;
this.plys_to_eval0 = (byte) plys_to_eval0;
this.plys_to_seldepth = (byte) plys_to_seldepth;
this.flag = flag;
}

AnalysisResult(int score, Boolean is_stalemate, boolean needs_deeper,
    int plys_to_eval0, int plys_to_seldepth, Flag flag,
    IMove best_move, long hashvalue) {
this.score = (short) score;
this.is_stalemate = is_stalemate;
this.needs_deeper = needs_deeper;
this.plys_to_eval0 = (byte) plys_to_eval0;
this.plys_to_seldepth = (byte) plys_to_seldepth;
this.flag = flag;
this.best_move = best_move;
this.hashvalue = hashvalue;
}

/**
 * computes a copy of the analysis result without the list of good moves and
 * the hashvalue.
 *
 * @return a copy without some elements.
 */
public AnalysisResult tinyCopy() {
    return new AnalysisResult(score, is_stalemate, needs_deeper,
        plys_to_eval0, plys_to_seldepth, null, best_move, 0);
}

/**
 * sets all values of analysis result except the list of good moves and the
 * hashvalue.
 *
 * @param score
 *         the new score
 * @param is_stalemate
 *         the new status of is_stalemate
 * @param needs_deeper
 *         the new status of needs_deeper
 * @param plys_to_eval0
 *         the new number of plys to base case.
 * @param plys_to_seldepth
```

```
*           the new number of plys to base case of selective depth.
* @param flag
*           the new flag
* @param best_move
*           the new best move.
*/
public void tinySet(int score, boolean is_stalemate, boolean needs_deeper,
    int plys_to_eval0, int plys_to_seldepth, Flag flag, IMove best_move) {
    this.score = (short) score;
    this.is_stalemate = is_stalemate;
    this.needs_deeper = needs_deeper;
    this.plys_to_eval0 = (byte) plys_to_eval0;
    this.plys_to_seldepth = (byte) plys_to_seldepth;
    this.flag = flag;
    this.best_move = best_move;
}

/**
 * sets all values of analysis result except the list of good moves and the
 * hashvalue.
 *
 * @param ar
 *           the new analysis result
 */
public void tinySet(AnalysisResult ar) {
    tinySet(ar.score, ar.is_stalemate, ar.needs_deeper, ar.plys_to_eval0,
        ar.plys_to_seldepth, ar.flag, ar.best_move);
}

/**
 * enables a comparison of two results.
 *
 * @param o
 *           the other result.
 * @return 0 if there are the same or have the same value, 1 if the actual
 *         one is more valuable then the other one, -1 else.
 */
public int compareQualityTo(AnalysisResult o) {
    if (o == null)
        throw new NullPointerException();

    if (this == o)
        return 0;

    // (deeper results)
    if (this.plys_to_eval0 > o.plys_to_eval0)
```

```
        return 1;

    if (this.plys_to_eval0 == o.plys_to_eval0
        && this.plys_to_seldepth == o.plys_to_seldepth)
        return 0;

    return -1;
}

/**
 * returns the Principal Variation, i.e. a sequence of best moves moves. It
 * may be cut off, if entries in the ResultCache are overridden.
 *
 * @param pos
 *         the position, where the PV starts
 * @return a linked list with the PV
 */
public LinkedList<IMove> getPV(IPosition pos, int counter) {
    LinkedList<IMove> pv = new LinkedList<IMove>();
    IPosition best_child;
    AnalysisResult ar;
    if (best_move != null && counter >= 0) {
        pv.add(best_move);
        best_child = pos.doMove_copy(best_move);
        ar = ResultCache.getResult(best_child);
        counter--;
        if (ar != null)
            pv.addAll(ar.getPV(best_child, counter));
    }
    return pv;
}

@Override
public String toString() {
    return "cp: " + score + " depth: " + plys_to_eval0
        + (flag != null ? " flag: " + flag : "");
}
}
```

1.16 BasicMoveComparator.java

```
package mitzi;

import java.util.Comparator;
```

```
import java.util.HashMap;
import java.util.Map;

public class BasicMoveComparator implements Comparator<IMove> {

    /**
     * saves the actual board, where the moves should be compared
     */
    private IPosition board;

    /**
     * map, which maps a move to its value. Initial size set to 35 to prevent
     */
    private Map<IMove, Integer> move_values = new HashMap<IMove, Integer>(35,
        1);

    /**
     * contains values for move comparison
     */
    private static final int[] piece_values = { 100, 500, 325, 325, 975, 000 };

    /**
     * value of a square where a piece moves to or from.
     */
    private static final int[] center_values = { -1, -1, -1, -1, -1, -1, -1,
        -1, -1, -1, -1, 0, 2, 4, 7, 7, 4, 3, 0, -1, -1, 1, 5, 8, 12, 12, 8,
        5, 1, -1, -1, 3, 8, 12, 17, 17, 12, 8, 3, -1, -1, 6, 10, 15, 20,
        20, 15, 10, 6, -1, -1, 6, 10, 15, 20, 20, 15, 10, 6, -1, -1, 3, 8,
        12, 17, 17, 12, 8, 3, -1, -1, 1, 5, 8, 12, 12, 8, 5, 1, -1, -1, 0,
        2, 4, 7, 7, 4, 2, 0, -1, -1, -1, -1, -1, -1, -1, -1, -1, -1, -1,
        -1, -1, -1, -1, -1, -1, -1, -1, -1, -1, -1 };

    public BasicMoveComparator(IPosition board) {
        this.board = board;
    }

    /**
     * Grades an IMove by some heuristics.
     *
     * Ignoring special situations like en passant and castling.
     *
     * @param move the current move
     */
    private void computeValue(IMove move) {
        int value = 0;
```



```
// moved figure
Piece src_piece = board.getPieceFromBoard(move.getFromSquare());

// captured figure
Piece dest_piece = board.getPieceFromBoard(move.getToSquare());

if (dest_piece != null) {
    // try to get advantage in exchange
    value += (piece_values[dest_piece.ordinal()]
        - piece_values[src_piece.ordinal()] + 1) * 16;
}
// move with more powerful pieces
value += piece_values[src_piece.ordinal()];

// move to the center (but away with the king)
value += (center_values[move.getToSquare()] - center_values[move
    .getFromSquare()]) * (src_piece == Piece.KING ? -1 : 1);

move_values.put(move, value);
}

/**
 * compares two moves by there value.
 */
@Override
public int compare(IMove m1, IMove m2) {
    if (!move_values.containsKey(m1))
        computeValue(m1);
    if (!move_values.containsKey(m2))
        computeValue(m2);

    return Integer.compare(move_values.get(m1), move_values.get(m2));
}
}
```

1.17 CaptureComparator.java

```
package mitzi;

import java.util.ArrayList;
import java.util.Comparator;
import java.util.EnumSet;
```

```
import java.util.HashMap;
import java.util.Iterator;
import java.util.List;
import java.util.Map;

public class CaptureComparator implements Comparator<IMove> {

    /**
     * saves the actual board, where the moves should be compared
     */
    private IPosition board;

    /**
     * map, which maps a move to its value. Initial size set to 35 to prevent
     */
    private Map<IMove, Integer> move_values = new HashMap<IMove, Integer>(35,
        1);

    private static final int[] piece_values = { 100, 500, 325, 325, 975, 000 };

    private ArrayList<List<IMove>> attackers = new ArrayList<List<IMove>>(2);

    public CaptureComparator(IPosition board) {
        this.board = board.returnCopy();
    }

    private int seeCapture(IMove m) {
        int value = 0;
        int square = m.getToSquare();
        Side side = board.getActiveColor();

        Piece piece = board.getPieceFromBoard(square);
        if (piece == null
            && SquareHelper.getRow(square) != SquareHelper.getRowForSide(
                board.getActiveColor(), 8))
            piece = Piece.PAWN; // en_passant
        else if (piece == null)
            piece = Piece.KING; // promotion, no capture - value of King is 0

        if (attackers.size() < 2) {
            attackers.add(null);
            attackers.add(null);
        }

        List<IMove> captures = board.getPotentialAttackersTo(square);
        captures.remove(m);
    }
}
```

```
attackers.set(side.ordinal(), captures);

board.doMove(m);

value = (piece_values[piece.ordinal()] - see(square, m));

board.undoMove(m);

attackers.clear();
move_values.put(m, value);
return value;
}

private int see(int square, IMove m) {

    int value = 0;
    Side side = board.getActiveColor();
    update_attackers(square, m);
    IMove move = get_smallest_attacker(side);
    /* skip if the square isn't attacked anymore by this side */
    if (move != null) {
        Piece piece = board.getPieceFromBoard(move.getToSquare());
        board.doMove(move);

        // Do not consider captures if they lose material, therefore max
        // zero
        value = Math.max(0,
            piece_values[piece.ordinal()] - see(square, move));

        board.undoMove(move);
    }
    return value;
}

@Override
public int compare(IMove m1, IMove m2) {
    if (!move_values.containsKey(m1))
        seeCapture(m1);
    if (!move_values.containsKey(m2))
        seeCapture(m2);

    return Integer.compare(move_values.get(m1), move_values.get(m2));
}

public IMove get_smallest_attacker(Side side) {
```

```
Piece p;
int val = 1001;
IMove best_move = null;
List<IMove> captures = attackers.get(side.ordinal());

if(captures.isEmpty())
    return null;

piece_values[Piece.KING.ordinal()] = 1000;
for (IMove move : captures) {
    p = board.getPieceFromBoard(move.getFromSquare());
    if (piece_values[p.ordinal()] < val) {
        best_move = move;
        val = piece_values[p.ordinal()];

        if (val == 100) {
            captures.remove(move);
            return best_move;
        }
    }
}

piece_values[Piece.KING.ordinal()] = 0;
captures.remove(best_move);

return best_move;
}

private void update_attackers(int square, IMove last_move) {

    Side just_computed_side = null;
    if(attackers.get(board.getActiveColor().ordinal())==null){
        List<IMove> captures2 = board.getPotentialAttackersTo(square);
        attackers.set(board.getActiveColor().ordinal(), captures2);
        if(captures2.isEmpty())
            return;
        just_computed_side = board.getActiveColor();
    }

    if(last_move.getPromotion() != null){
        Iterator<IMove> it =
            attackers.get(Side.getOppositeSide(board.getActiveColor()).ordinal()).iterator();
        while(it.hasNext())
            if(it.next().getPromotion()!=null)
                it.remove();
    }
}
```

```
Piece p = board.getPieceFromBoard(square);

// find attacking direction
if (p == Piece.KNIGHT)
    return;
if (p == Piece.KING)
    return; // should be changed maybe...

int squ_from = last_move.getFromSquare();

int diff = squ_from - square;

Direction direction = null;
EnumSet<Direction> dir_pos = EnumSet.of(Direction.NORTHEAST,
    Direction.EAST, Direction.SOUTHEAST);
EnumSet<Direction> dir_neg = EnumSet.of(Direction.SOUTHWEST,
    Direction.WEST, Direction.NORTHWEST);

if (diff > 0) {
    for (Direction dir : dir_pos) {
        if (diff % dir.offset == 0) {
            direction = dir;
        }
    }
    if (diff < 8)
        direction = Direction.NORTH;
} else {
    for (Direction dir : dir_neg) {
        if (diff % dir.offset == 0) {
            direction = dir;
        }
    }
    if (diff > -8)
        direction = Direction.SOUTH;
}

int new_square = squ_from + direction.offset;
IMove move;
EnumSet<Direction> dir_lines = EnumSet.of(Direction.EAST,
    Direction.SOUTH, Direction.NORTH, Direction.WEST);
EnumSet<Direction> dir_diag = EnumSet.of(Direction.SOUTHEAST,
    Direction.SOUTHWEST, Direction.NORTHEAST, Direction.NORTHWEST);
while (SquareHelper.isValidSquare(new_square)) {
    Side s = board.getSideFromBoard(new_square);
    if (s != null) {
```

```
        if(s==just_computed_side)
            return;
        p = board.getPieceFromBoard(new_square);
        if (p == Piece.QUEEN) {
            move = new Move(new_square, square);
            if (!board.isCheckAfterMove(move))
                attackers.get(s.ordinal()).add(move);
        } else if (p == Piece.BISHOP) {
            if (dir_diag.contains(direction)) {
                move = new Move(new_square, square);
                if (!board.isCheckAfterMove(move))
                    attackers.get(s.ordinal()).add(move);
            }
        } else if (p == Piece.ROOK) {
            if (dir_lines.contains(direction)) {
                move = new Move(new_square, square);
                if (!board.isCheckAfterMove(move))
                    attackers.get(s.ordinal()).add(move);
            }
        }
        return;
    }
    new_square += direction.offset;
}
}
```

1.18 BasicBoardAnalyzer.java

```
package mitzi;

public class BasicBoardAnalyzer implements IPositionAnalyzer {

    private int[] start_castling;

    private int[] piece_values = { 100, 500, 325, 325, 975, 000 };

    @Override
    public AnalysisResult eval0(IPosition board) {

        int score = 0;
        int bishop_pair_value = 50;
```

```
// basic evaluation
for (Side side : Side.values()) {
    int side_sign = Side.getSideSign(side);

    // piece values
    for (Piece piece : Piece.values()) {
        score += board.getNumberOfPiecesByColorAndType(side, piece)
            * piece_values[piece.ordinal()] * side_sign;
    }

    // bishop pair gives bonus
    if (board.getNumberOfPiecesByColorAndType(side, Piece.BISHOP) == 2) {
        score += bishop_pair_value * side_sign;
    }
}
AnalysisResult result = new AnalysisResult(score, null, true, 0, 0, null);
return result;
}

@Override
public AnalysisResult evalBoard(IPosition board, int alpha, int beta){

    return eval0(board);
}

@Override
public void setCastling(IPosition position){
    start_castling[0] = position.canCastle(31) ? 31 : -1;
    start_castling[1] = position.canCastle(71) ? 71 : -1;
    start_castling[2] = position.canCastle(38) ? 38 : -1;
    start_castling[3] = position.canCastle(78) ? 78 : -1;
}
}
```

1.19 BoardAnalyzer.java

```
package mitzi;

import static mitzi.MateScores.NEG_INF;

import java.util.ArrayList;
import java.util.Collections;
import java.util.List;
import java.util.Set;
```

```
/**
 *
 * This class computes the value of a board in a proper way, see
 * http://philemon.cycovery.com/site/part2.html for more details.
 *
 */
public class BoardAnalyzer implements IPositionAnalyzer {

    /**
     * the square to array index from Position.java
     */
    protected static int[] square_to_array_index = { 64, 64, 64, 64, 64, 64,
        64, 64, 64, 64, 64, 56, 48, 40, 32, 24, 16, 8, 0, 64, 64, 57, 49,
        41, 33, 25, 17, 9, 1, 64, 64, 58, 50, 42, 34, 26, 18, 10, 2, 64,
        64, 59, 51, 43, 35, 27, 19, 11, 3, 64, 64, 60, 52, 44, 36, 28, 20,
        12, 4, 64, 64, 61, 53, 45, 37, 29, 21, 13, 5, 64, 64, 62, 54, 46,
        38, 30, 22, 14, 6, 64, 64, 63, 55, 47, 39, 31, 23, 15, 7, 64, 64,
        64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64, 64,
        64, 64, 64 };

    /**
     * the material value of a piece.
     */
    static private int[] piece_values = { 100, 500, 325, 325, 975, 000 };

    // The following arrays contains the value of a piece on a specific square,
    // always in favor of white. Since the arrays are symmetric w.r.t. the
    // columns, BLACK uses 63-i entry with opposite sign.
    /**
     * value of squares for bishop and knight, in favor of white
     */
    static private int[] piece_activity_b_k = { -16, -16, -8, -8, -8, -8, -16,
        -16, -16, -16, -4, -4, -4, -4, -16, -16, -8, 2, 6, 6, 6, 6, 2, -8,
        -8, 2, 6, 6, 6, 6, 2, -8, -8, 2, 4, 4, 4, 4, 2, -8, -8, 2, 2, 2, 2,
        2, 2, -8, -8, -8, 0, 0, 0, 0, -8, -8, -16, -8, -8, -8, -8, -8, -8,
        -16 };

    /**
     * value of squares for rook, in favor of white
     */
    static private int[] piece_activity_r = { 0, 0, 4, 6, 6, 4, 0, 0, 0, 0, 4,
        6, 6, 4, 0, 0, 0, 0, 4, 6, 6, 4, 0, 0, 0, 0, 4, 6, 6, 4, 0, 0, 0,
        0, 4, 6, 6, 4, 0, 0, 0, 0, 4, 6, 6, 4, 0, 0, 0, 0, 4, 6, 6, 4, 0,
        0, 0, 0, 4, 6, 6, 4, 0, 0, };

    /**
```



```
* value of squares for queen, in favor of white
*/
static private int[] piece_activity_q = { 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 4,
    5, 5, 4, 0, 0, 0, 2, 4, 10, 10, 4, 2, 0, 0, 2, 10, 12, 12, 10, 2,
    0, -10, 2, 10, 12, 12, 10, 2, -10, -10, -10, 4, 10, 10, 4, -10,
    -10, -10, 2, 8, 8, 8, 8, 2, -10, -10, -8, 0, 0, 0, 0, -8, -10, };

/**
 * value of squares, which are weak/strong squares for bishop and knight
 */
static private int[] weak_positions = { 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
    0, 0, 0, 0, 0, 8, 12, 12, 8, 0, 0, 0, 2, 12, 16, 16, 12, 2, 0,
    0, 2, 12, 20, 20, 12, 2, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
    0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, };

/**
 * value of squares for white pawns. (not symmetric)
 */
static private int[] pawn_positions_w = { 0, 0, 0, 0, 0, 0, 0, 0, 28, 28,
    35, 42, 45, 35, 28, 28, -9, -3, 7, 12, 15, 7, -3, -9, -10, -10, 6,
    9, 10, 6, -11, -10, -11, -11, 4, 5, 6, 2, -11, -11, -11, -11, 0, 0,
    1, 0, -11, -11, -6, -6, 4, 5, 5, 4, -6, -6, 0, 0, 0, 0, 0, 0, 0, 0 };

/**
 * value of squares for black pawns. (not symmetric)
 */
static private int[] pawn_positions_b = { 0, 0, 0, 0, 0, 0, 0, 0, -6, -6,
    4, 5, 5, 4, -6, -6, -11, -11, 0, 0, 1, 0, -11, -11, -11, -11, 4, 5,
    6, 2, -11, -11, -10, -10, 6, 9, 10, 6, -11, -10, -9, -3, 7, 12, 15,
    7, -3, -9, 28, 28, 35, 42, 45, 35, 28, 28, 0, 0, 0, 0, 0, 0, 0, 0 };

/**
 * value of squares for white king, not valid in endgame. (not symmetric)
 */
static private int[] king_positions_w = { 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
    0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
    0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, -10, -15,
    -10, 0, 0, 5, 10, 18, -8, -3, -8, 23, 10 };

/**
 * value of squares for black king, not valid in endgame. (not symmetric)
 */
static private int[] king_positions_b = { 5, 10, 18, -8, -3, -8, 23, 10, 0,
    0, 0, -10, -15, -10, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
    0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
    0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0 };
```

```
/**
 * value for twin pawns for different rows.
 */
static private int[] twin_pawns = { 0, 0, 1, 2, 3, 4, 7, 0 };

/**
 * value for covered pawns for different rows.
 */
static private int[] covered_pawns = { 0, 0, 4, 6, 8, 12, 16, 0 };

/**
 * value for passed pawns for different rows.
 */
static private int[] passed_pawn = { 0, 2, 10, 20, 40, 60, 70, 0 };

/**
 * value for passed pawns, where in front of the pawn is a king for
 * different rows.
 */
static private int[] passed_pawn_with_king = { 0, 0, 0, 0, 10, 50, 80, 0 };

/**
 * value for blocked passed pawns
 */
static private int[] blocked_passed_pawn = { 0, 0, -8, -16, -32, -45, -58,
    0 };

/**
 * if not all Bishop and Knight has moved, moving the queen results in
 * negative score
 */
static private int PREMATURE_QUEEN = -17;

/**
 * bonus, if the rook is on an open line (no other pawns)
 */
static private int ROOK_OPEN_LINE = 20;

/**
 * bonus if the rook is on an halfopen line (only opponents pawns)
 */
static private int ROOK_HALFOPEN_LINE = 5;

/**
 * bonus if the rook is in the 7th row and opponents king is in the 8th or
```

```
* pawn in the 7th
*/
static private int ROOK_7TH_2ND = 25;

/**
 * bonus if the previous bonus holds and the 7th row is empty.
 */
static private int ROOK_7TH_2ND_ABSOLUTE = 15;

/**
 * bonus if a rook covers the other rook, this replaces the ROOK_7TH_2ND and
 * counts for each rook (both on the 7th row)
 */
static private int REINFORCED_ROOK_7TH_2ND = 40;

/**
 * bonus if a rook is behind a passed pawn
 */
static private int PASSED_ROOK_SUPPORT = 10;

/**
 * gives a bonus if both bishops are still available in the endgame
 */
static private int ENDGAME_BISHOP_BONUS = 10; // not yet implemented

/**
 * bonus/malus if the bishop is caged on he baseline (the pawn in front of
 * the bishop has moved and the two pawns left and right of the bisop have
 * not moved )
 */
static private int BISHOP_BASELINE_CAGED = -12;

/**
 * bonus if a queen is covered on the 7th row by a rook
 */
static private int REINFORCING_QUEEN_7TH_2ND = 20;

/**
 * The player receives a bonus if the 2 bishops are alive.
 */
static private int bishop_pair_value = 25;

/**
 * multiple pawns in a columns get a malus.
 */
static private int MULTI_PAWN = -10;
```

```
/**
 * a isolated pawns (no pawn on the neighboring columns) get a malus
 */
static private int ISOLATED_PAWN = -20;

/**
 * bonus for covered passed pawns on the 7th row
 */
static private int COVERED_PASSED_7TH_PAWN = 90;

/**
 * malus if castling is loss (needs to be fixed and optimized)
 */
static private int CASTLING_LOSS = -40;

/**
 * the number of pieces when the endgame starts (a first draft, needs to be
 * optimized)
 */
static public int ENDGAME_THRESHOLD = 12;

/**
 * counts the number of board evaluations in quiesce().
 */
static public long eval_counter_seldepth = 0;

/**
 * counts the number of found positions in Transposition Table
 */
static public long table_counter = 0;

private int[] start_castling = new int[4];

@Override
public AnalysisResult eval0(IPosition board) {
    int score = 0;
    // compute all the information needed by the evaluation function once.
    board.cacheOccupiedSquares();

    // Evaluate the pieces
    score += evalPieces(board);

    // Evaluate Pawn Structure
    score += evalPawns(board);
}
```

```
// Evaluate Diagonals and lines
score += evalLinesAndDiagonals(board);

// Evaluate position - activity
score += evalPieceActivity(board);

// Evaluate weak/strong position
score += evalWeakPosition(board);

// Evaluate the King's position (not in endgame)
score += evalKingPos(board);

AnalysisResult result = new AnalysisResult(score, false, false, 0, 0,
    Flag.EXACT);
return result;
}

@Override
public AnalysisResult evalBoard(IPosition position, int alpha, int beta)
    throws InterruptedException {
    AnalysisResult result = quiesce(position, alpha, beta);

    // The analysis result should always contain the pure value (not
    // perturbed via side_sign)
    return result;
}

/**
 * Implements Quiescence search to avoid the horizon effect. The function
 * increase the search depth until no capture is possible, where only
 * captures are analyzed. The optimal value is found using the negamax
 * algorithm.
 *
 * @see <a
 *
 *      href="http://chessprogramming.wikispaces.com/Quiescence+Search">http://chessprogramm
 *
 * @param position
 *      the position to be analyzed
 * @param alpha
 *      the alpha value of alpha-beta search
 * @param beta
 *      the beta value of alpha-beta search
 * @return the value of the board ( in favor of white)
 *
 * @throws InterruptedException
```

```
*/
private AnalysisResult quiesce(IPosition position, int alpha, int beta)
    throws InterruptedException {

    if (Thread.interrupted()) {
        throw new InterruptedException();
    }

    int side_sign = Side.getSideSign(position.getActiveColor());

    // Cache lookup
    AnalysisResult entry = ResultCache.getResult(position);
    if (entry != null) {
        table_counter++;
        if (entry.flag == Flag.EXACT) {
            AnalysisResult new_entry = entry.tinyCopy();
            return new_entry;
        } else if (entry.flag == Flag.LOWERBOUND)
            alpha = Math.max(alpha, entry.score * side_sign);
        else if (entry.flag == Flag.UPPERBOUND)
            beta = Math.min(beta, entry.score * side_sign);

        if (alpha >= beta) {
            AnalysisResult new_entry = entry.tinyCopy();
            return new_entry;
        }
    }

    // generate moves
    List<IMove> moves = position.getPossibleMoves();

    // check for mate and stalemate
    if (moves.isEmpty()) {
        eval_counter_seldepth++;
        if (position.isCheckPosition()) {
            return new AnalysisResult(NEG_INF * side_sign, false, false, 0,
                0, Flag.EXACT);
        } else {
            return new AnalysisResult(0, true, false, 0, 0, Flag.EXACT);
        }
    }

    // evaluation of the current board.
    AnalysisResult standing_pat = eval0(position);
    eval_counter_seldepth++;
}
```

```
int negaval = standing_pat.score * side_sign;

// alpha beta cutoff
if (negaval >= beta)
    return standing_pat;
alpha = Math.max(alpha, negaval);

// Generate possible Captures
List<IMove> captures = position.generateCaptures();
if (captures.size()>1) {
    // Generate MoveComparator
    BasicMoveComparator move_comparator = new BasicMoveComparator(position);

    //CaptureComparator move_comparator = new CaptureComparator(position);
    Collections.sort(captures,
        Collections.reverseOrder(move_comparator));
}

AnalysisResult result = null;
int best_value = NEG_INF;

for (IMove move : captures) {

    position.doMove(move);
    AnalysisResult result_temp = quiesce(position, -beta, -alpha);
    position.undoMove(move);

    negaval = result_temp.score * side_sign;

    // find the best result
    if (negaval > best_value) {
        best_value = negaval;
        result = result_temp;
    }

    // cut-off
    if (negaval >= beta) {
        result.plys_to_seldepth++;
        return result;
    }
    alpha = Math.max(alpha, negaval);
}

// the standing_pat was computed in this depth
if (result == null)
    return standing_pat;
```

```
// the result comes from a depth below
result.plys_to_seldepth++;
return result;

}

/**
 * Evaluates only the material value of the board.
 *
 * @param board
 *         the actual board
 * @return the material value ( in favor of white)
 */
private int evalPieces(IPosition board) {
    int score = 0;

    // basic evaluation
    for (Side side : Side.values()) {
        int side_sign = Side.getSideSign(side);

        // piece values
        for (Piece piece : Piece.values()) {
            score += board.getNumberOfPiecesByColorAndType(side, piece)
                * piece_values[piece.ordinal()] * side_sign;
        }

        // bishop pair gives bonus
        if (board.getNumberOfPiecesByColorAndType(side, Piece.BISHOP) == 2) {
            score += bishop_pair_value * side_sign;
        }
    }

    return score;
}

/**
 * Computes the value of the possible activity of the pieces, e.g.
 * centralization,...
 *
 * @param board
 *         the board to be analyzed
 * @return the score for the activity of Rook, Bishop, Knight, Queen ( in
 *         favor of white)
 */
private int evalPieceActivity(IPosition board) {
```



```
int score = 0;
Set<Integer> squares;
boolean queen_moved_last, queen_startpos;

for (Side side : Side.values()) {
    int side_sign = Side.getSideSign(side);
    queen_moved_last = true;
    queen_startpos = false;

    // Queen
    squares = board.getOccupiedSquaresByColorAndType(side, Piece.QUEEN);
    if (side == Side.WHITE)
        for (int squ : squares)
            score += piece_activity_q[square_to_array_index[squ]];
    else
        for (int squ : squares)
            score -= piece_activity_q[63 - square_to_array_index[squ]];

    if ((squares.contains(SquareHelper.getSquare(
        SquareHelper.getRowForSide(side, 1), 4))))
        queen_startpos = true;

    // Bishop
    squares = board
        .getOccupiedSquaresByColorAndType(side, Piece.BISHOP);
    if (side == Side.WHITE)
        for (int squ : squares)
            score += piece_activity_b_k[square_to_array_index[squ]];
    else
        for (int squ : squares)
            score -= piece_activity_b_k[63 - square_to_array_index[squ]];

    if (!queen_startpos
        && (squares.contains(SquareHelper.getSquare(
            SquareHelper.getRowForSide(side, 1), 3)) || squares
            .contains(SquareHelper.getSquare(
                SquareHelper.getRowForSide(side, 1), 3))))
        queen_moved_last = false;

    // Knight
    squares = board
        .getOccupiedSquaresByColorAndType(side, Piece.KNIGHT);
    if (side == Side.WHITE)
        for (int squ : squares)
            score += piece_activity_b_k[square_to_array_index[squ]];
    else
```

```
        for (int squ : squares)
            score -= piece_activity_b_k[63 - square_to_array_index[squ]];

    if (!queen_startpos
        && (squares.contains(SquareHelper.getSquare(
            SquareHelper.getRowForSide(side, 1), 2)) || squares
            .contains(SquareHelper.getSquare(
                SquareHelper.getRowForSide(side, 1), 2))))
        queen_moved_last = false;

    // Rook
    squares = board.getOccupiedSquaresByColorAndType(side, Piece.ROOK);
    if (side == Side.WHITE)
        for (int squ : squares)
            score += piece_activity_r[square_to_array_index[squ]];
    else
        for (int squ : squares)
            score -= piece_activity_r[63 - square_to_array_index[squ]];

    if (!queen_startpos && !queen_moved_last)
        score += side_sign * PREMATURE_QUEEN;

}
return score;
}

/**
 * this function evaluates the weak position of an outpost, however only for
 * bishop and knight. If a knight is covered by pawn, the value increases.
 *
 * @param board
 *         the board to be analyzed
 * @return the score w.r.t. weak/ strong positions ( in favor of white)
 */
private int evalWeakPosition(IPosition board) {

    int score = 0;
    Set<Integer> squares;

    for (Side side : Side.values()) {

        // Bishop
        squares = board
            .getOccupiedSquaresByColorAndType(side, Piece.BISHOP);
        if (side == Side.WHITE)
            for (int squ : squares)
```

```
        score += weak_positions[square_to_array_index[squ]];
    else
        for (int squ : squares)
            score -= weak_positions[63 - square_to_array_index[squ]];

    // Knight (value get multiplied times the number of pawn covering
    // the knight, if no cover no bonus is added)
    squares = board
        .getOccupiedSquaresByColorAndType(side, Piece.BISHOP);
    int count = 0;
    if (side == Side.WHITE) {
        for (int squ : squares) {
            for (Direction dir : Direction
                .pawnCapturingDirections(Side.BLACK))
                if (board.getPieceFromBoard(squ + dir.offset) == Piece.PAWN)
                    count++;
            score += count * weak_positions[square_to_array_index[squ]];
        }
    } else {
        for (int squ : squares) {
            for (Direction dir : Direction
                .pawnCapturingDirections(Side.WHITE))
                if (board.getPieceFromBoard(squ + dir.offset) == Piece.PAWN)
                    count++;
            score -= count
                * weak_positions[63 - square_to_array_index[squ]];
        }
    }

    return score;
}

/**
 * Evaluates if rooks occupies open/halfopen lines, if they occupies the
 * 7-th row or are covered there and if the bishop is caged on the baseline
 * (the pawn in front of him has moved the the neighboring ones are here)
 *
 * @param board
 *         the board to be evaluated
 * @return the score ( in favor of white)
 */
private int evalLinesAndDiagonals(IPosition board) {
    int score = 0;
```

```
Set<Integer> squares_rook, squares_bishop;
Piece p;
Side s;

for (Side side : Side.values()) {
    int side_sign = Side.getSideSign(side);
    Side opp_side = Side.getOppositeSide(side);

    squares_rook = board.getOccupiedSquaresByColorAndType(side,
        Piece.ROOK);

    // Open line and halfopen line bonus
    for (int square : squares_rook) {

        boolean half_open = true;
        boolean open = true;
        List<Integer> squares = new ArrayList<Integer>(
            SquareHelper.getAllSquaresInDirection(square,
                Direction.NORTH));
        squares.addAll(SquareHelper.getAllSquaresInDirection(square,
            Direction.SOUTH));

        for (int squ : squares) {
            if (board.getPieceFromBoard(squ) == Piece.PAWN) {
                if (board.getSideFromBoard(squ) == board
                    .getActiveColor()) {
                    half_open = false;
                    open = false;
                    break;
                } else
                    open = false;
            }
        }
        if (half_open && open)
            score += side_sign * ROOK_OPEN_LINE;
        else if (half_open)
            score += side_sign * ROOK_HALFOPEN_LINE;

        // 7th || 2nd line bonus
        if (SquareHelper.getRow(square) == SquareHelper.getRowForSide(
            side, 7)) {

            boolean rook_7 = true;
            boolean rook_7_abs = true;
            boolean rook_7_cover_r = false;
            boolean rook_7_cover_q = false;
```

```
boolean emty_direction = true;

// Check all squares at the west side of the rook
for (int squ : SquareHelper.getAllSquaresInDirection(
    square, Direction.WEST)) {
    p = board.getPieceFromBoard(squ);
    s = board.getSideFromBoard(squ);
    if (p == Piece.PAWN && s == opp_side) {
        rook_7 = false;
        rook_7_abs = false;
        break;
    } else if (emty_direction && p != null) {
        emty_direction = false;
        rook_7_abs = false;
        if (p == Piece.ROOK && s == side)
            rook_7_cover_r = true;
        else if (p == Piece.QUEEN && s == side)
            rook_7_cover_q = true;
    }
}

// Check all squares at the east side of the rook
emty_direction = true;
for (int squ : SquareHelper.getAllSquaresInDirection(
    square, Direction.EAST)) {
    p = board.getPieceFromBoard(squ);
    s = board.getSideFromBoard(squ);
    if (rook_7 && p == Piece.PAWN && s == opp_side) {
        rook_7 = false;
        rook_7_abs = false;
        break;
    } else if (emty_direction && p != null) {
        rook_7_abs = false;
        emty_direction = false;
        if (p == Piece.ROOK && s == side)
            rook_7_cover_r = true;
        else if (p == Piece.QUEEN && s == side)
            rook_7_cover_q = true;
    }
}

int king_pos = board.getKingPos(opp_side);
if (SquareHelper.getRow(king_pos) == SquareHelper
    .getRowForSide(side, 8))
```

```
        rook_7 = true;

    if (rook_7)
        score += side_sign * ROOK_7TH_2ND;
    if (rook_7_abs)
        score += side_sign * ROOK_7TH_2ND_ABSOLUTE;
    if (rook_7_cover_r)
        score += side_sign * REINFORCED_ROOK_7TH_2ND;
    if (rook_7_cover_q)
        score += side_sign * REINFORCING_QUEEN_7TH_2ND;
    }

}

squares_bishop = board.getOccupiedSquaresByColorAndType(side,
    Piece.BISHOP);
int row_s = SquareHelper.getRowForSide(side, 1);
boolean bishop_caged = false;
for (int square : squares_bishop)
    if ((square == SquareHelper.getSquare(row_s, 3) || square ==
        SquareHelper
            .getSquare(row_s, 6))
        && (board.getPieceFromBoard(square
            + Direction.pawnDirection(side).offset) == Piece.PAWN && board
            .getSideFromBoard(square
                + Direction.pawnDirection(side).offset) == side)) {
        bishop_caged = true;
        for (Direction dir : Direction
            .pawnCapturingDirections(side)) {
            if (board.getPieceFromBoard(square + dir.offset) != Piece.PAWN
                || board.getSideFromBoard(square + dir.offset) != side)
                bishop_caged = false;
        }
    }
}
if (bishop_caged == true)
    score += side_sign * BISHOP_BASELINE_CAGED;
}
return score;
}

/**
 * evaluates the pawn structure. Checks for covered pawns, passed pawns,
 * isolated pawns, twin pawns... value dependent of the row
 *
 * @param position
 *         the current position
 * @return the value of the pawn structure in favor of white
```

```
*/
private int evalPawns(IPosition position) {

    int score = 0;
    int row, col, col_2, row_side;
    boolean isolated, covered, passed;
    for (Side side : Side.values()) {
        int side_sign = Side.getSideSign(side);
        Side opp_side = Side.getOppositeSide(side);
        Set<Integer> squares_pawn = position
            .getOccupiedSquaresByColorAndType(side, Piece.PAWN);
        Set<Integer> squares_pawn_opp = position
            .getOccupiedSquaresByColorAndType(opp_side, Piece.PAWN);

        if (side == Side.WHITE)
            for (int squ : squares_pawn)
                score += pawn_positions_w[square_to_array_index[squ]];
        else
            for (int squ : squares_pawn)
                score -= pawn_positions_b[square_to_array_index[squ]];

        for (int squ_1 : squares_pawn) {
            row = SquareHelper.getRow(squ_1);
            col = SquareHelper.getColumn(squ_1);

            row_side = SquareHelper.getRowForSide(side, row);

            isolated = true;
            covered = false;

            for (int squ_2 : squares_pawn) {
                // dont check the pawn with himself
                if (squ_2 == squ_1)
                    continue;

                col_2 = SquareHelper.getColumn(squ_2);
                if (col == col_2)
                    // add malus for multiple pawns in the same line.
                    // TODO: maybe dont increase malus for triple,... pawns
                    score += side_sign * MULTI_PAWN;
                else if (col == col_2 + 1 || col == col_2 - 1) {
                    isolated = false;

                    if (row == SquareHelper.getRow(squ_2))
                        // add bonus for twinpawns
                        score += side_sign * twin_pawns[row_side];
                }
            }
        }
    }
}
```

```
        else if (row == SquareHelper.getRow(squ_2
            - Direction.pawnDirection(side).offset)) {
            // add bonus for covered pawns
            // TODO: maybe dont increase bonus for pawns covered
            // by 2 pawns
            covered = true;
            score += side_sign * covered_pawns[row_side];
        }
    }

}

if (isolated == true)
    score += side_sign * ISOLATED_PAWN;

// check if a pawn is passed
passed = true;
for (int squ_2 : squares_pawn_opp) {
    col_2 = SquareHelper.getColumn(squ_2);
    if (col == col_2 || col == col_2 + 1 || col == col_2 - 1) {
        passed = false;
        break;
    }
}

}

if (passed == true) {
    // check if a passed pawn is blocked
    for (int squ_2 : squares_pawn_opp) {
        if (squ_1 + Direction.pawnDirection(side).offset == squ_2) {
            score += side_sign * blocked_passed_pawn[row_side];
            break;
        }
    }
}

// check if a passed pawn is covered by a king (the king
// should be in front of the pawn)
for (Direction dir : Direction
    .pawnCapturingDirections(side))
    if (squ_1 + dir.offset == position.getKingPos(side))
        score += side_sign
            * passed_pawn_with_king[row_side];

// add the bonus for a passed pawn
score += side_sign * passed_pawn[row_side];

// additional bonus for covered passed pawn
```



```
        if (covered == true
            && row == SquareHelper.getRowForSide(side, 7))
            score += side_sign * COVERED_PASSED_7TH_PAWN;

        // if a rook is behind a passed pawn
        // TODO: check if it better do add the bonus is a rook is on
        // the same line (behind the pawn)
        if (position.getPieceFromBoard(squ_1
            - Direction.pawnDirection(side).offset) == Piece.ROOK
            && position.getSideFromBoard(squ_1
            - Direction.pawnDirection(side).offset) == side)
            score += side_sign * PASSED_ROOK_SUPPORT;
    }

}

}

return score;
}

/**
 * draft of king's position evaluation function.
 *
 * @param position
 *         the current position
 * @return the score
 */
private int evalKingPos(IPosition position) {
    int score = 0;
    int count_fig = position.getNumberOfPiecesByColor(Side.WHITE)
        + position.getNumberOfPiecesByColor(Side.BLACK);
    if (count_fig > ENDGAME_THRESHOLD)
        for (Side side : Side.values()) {
            int side_sign = Side.getSideSign(side);
            if (side == Side.WHITE)
                score += side_sign
                    * king_positions_w[square_to_array_index[position
                        .getKingPos(side)]];
            else
                score += side_sign
                    * king_positions_b[square_to_array_index[position
                        .getKingPos(side)]];
        }

    return score;
}
```

```
public void setCastling(IPosition position){
    start_castling[0] = position.canCastle(31) ? 31 : -1;
    start_castling[1] = position.canCastle(71) ? 71 : -1;
    start_castling[2] = position.canCastle(38) ? 38 : -1;
    start_castling[3] = position.canCastle(78) ? 78 : -1;
}
}
```

1.20 Flag.java

```
package mitzi;

/**
 * The flags for the entries in the Transposition Table (PositionCache).
 *
 */
public enum Flag {
    EXACT, LOWERBOUND, UPPERBOUND
}
```

1.21 GameState.java

```
package mitzi;

import java.util.ArrayList;

public class GameState {

    /**
     * the actual position of the current game state
     */
    private IPosition position;

    /**
     * the history of played moves
     */
    private ArrayList<IMove> history = new ArrayList<IMove>();

    /**
     * The number of the full move. It starts at 1, and is incremented after
```

```
    * Black's move.
    */
private int full_move_clock;

private class GameClock {
    // TODO study UCI time management
}

/**
 * creates a new Game with initial position.
 */
public GameState() {
    position = new Position();
    setToInitial();
}

/**
 * sets the current game to the initial state.
 */
public void setToInitial() {
    position.setToInitial();
    full_move_clock = 1;
}

/**
 * sets the current game to the position of the given fen string
 *
 * @param fen
 *         the position in fen notation
 */
public void setToFEN(String fen) {
    position = new Position();
    position.setToFEN(fen);

    String[] fen_parts = fen.split(" ");
    // set half move clock
    position.setHalfMoveClock(Integer.parseInt(fen_parts[4]));
    // set full move clock
    full_move_clock = Integer.parseInt(fen_parts[5]);
}

/**
 * Do the given move and update half_move_clock, full_move_clock and
 * history. It is checked, if the move is valid or not.
 *
 * @param move
```

```

    *           the given move
    */
public void doMove(IMove move) {
    if (position.isPossibleMove(move)) {
        position = position.doMove_copy(move);
        /*if (move.resets_half_move_clock) {
            half_move_clock = 0;
        }*/
        if (position.getActiveColor() == Side.BLACK) {
            full_move_clock++;
        }
        history.add(move);

    } else {
        throw new IllegalArgumentException("INVALID MOVE");
    }
}

/**
 * @return the actual position of the game
 */
public IPosition getPosition() {
    return position;
}

/**
 * creates the fen string of the actual board.
 */
@Override
public String toString() {
    StringBuilder fen = new StringBuilder();

    fen.append(position.toString());
    fen.append(" ");

    // halfmove clock
    fen.append(position.getHalfMoveClock());
    fen.append(" ");

    // fullmove clock
    fen.append(full_move_clock);

    return fen.toString();
}

/**
```

```
    * This is the number of halfmoves since the last pawn advance or capture.
    * This is used to determine if a draw can be claimed under the fifty-move
    * rule.
    *
    * @return number of halfmoves since the last pawn advance or capture
    */
public int getHalfMoveClock() {
    return position.getHalfMoveClock();
}

/**
 * The number of the full move. It starts at 1, and is incremented after
 * Black's move.
 *
 * @return number of the full move
 */
public int getFullMoveClock() {
    return full_move_clock;
}

/**
 * return all previous played moves.
 *
 * @return returns a list of all played moves.
 */
public ArrayList<IMove> getHistory() {
    return history;
}
}
```

1.22 IrreversibleMoveStack.java

```
package mitzi;

import java.util.LinkedList;

/**
 * This class represents a stack, storing the information, which cannot be
 * reverted only with a given move. It is implemented as a LinkedList
 * containing
 * a class which stores the half move clock, the castling, the en passant
 * target
 * and the captured piece. (en passant captures does not count as capture).
 * The

```

```
* elements should be accessed via irr_move_info.removeLast();
*/
public class IrreversibleMoveStack {

    static public class MoveInfo {

        int half_move_clock;
        int[] castling = new int[4];
        int en_passant_square;
        Piece capture;
        Boolean is_check;

    }

    /**
     * the stack containing the information
     */
    static public LinkedList<MoveInfo> irr_move_info = new
        LinkedList<MoveInfo>();

    private IrreversibleMoveStack() {

    }

    /**
     * add a new entry.
     *
     * @param half_move_clock
     *         the old half move clock
     * @param castling
     *         the castling array
     * @param en_passant_square
     *         the en passant target square
     * @param capture
     *         the piece, which got captured (null if no capture)
     */
    static public void addInfo(int half_move_clock, int[] castling,
        int en_passant_square, Piece capture, Boolean is_check) {

        MoveInfo inf = new MoveInfo();
        System.arraycopy(castling, 0, inf.castling, 0, 4);
        inf.en_passant_square = en_passant_square;
        inf.half_move_clock = half_move_clock;
        inf.capture = capture;
        inf.is_check = is_check;

        irr_move_info.addLast(inf);
    }
}
```

```
}  
  
}
```

1.23 KillerMoves.java

```
package mitzi;  
  
import java.util.HashMap;  
import java.util.LinkedList;  
import java.util.List;  
import java.util.Map;  
  
/**  
 * this class saves for each ply a certain number (e.g. 2) of moves  
 * (killermoves), which causes an alpha-beta cutoff. If more moves are saved,  
 * that allowed, then they get deleted in the order they are saved (like  
 * FIFO). This should improve the move ordering.  
 */  
public class KillerMoves {  
  
    /**  
     * a map from a ply to the killermoves.  
     */  
    private static Map<Integer, LinkedList<IMove>> killer_moves = new  
        HashMap<Integer, LinkedList<IMove>>(  
            35);  
  
    /**  
     * number of killermoves saved  
     */  
    private static int MAX_SIZE = 2;  
  
    KillerMoves() {  
    };  
  
    /**  
     * returns for a given ply the killer moves, note that it should be checked  
     * if the move is legal.  
     *  
     * @param ply  
     *         the plys from root node  
     * @return a list of killer moves.
```

```
    */
static LinkedList<IMove> getKillerMoves(int ply) {
    LinkedList<IMove> k_m = killer_moves.get(ply);
    if (k_m == null)
        k_m = new LinkedList<IMove>();
    return k_m;
}

/**
 * add a new killermove, if more moves are saved than MAX_SIZE, the first
 * killermove got removed.
 *
 * @param ply
 *         depth in the search tree
 * @param move
 *         the move to be added
 */
static void addKillerMove(int ply, IMove move) {
    LinkedList<IMove> k_m = killer_moves.get(ply);
    if (k_m == null)
        k_m = new LinkedList<IMove>();
    if (k_m.size() == MAX_SIZE)
        k_m.iterator().remove();

    k_m.add(move);
}

/**
 * add a new killermove, if more moves are saved than MAX_SIZE, the first
 * killermove got removed.
 *
 * @param ply
 *         depth in the search tree
 * @param move
 *         the move to be added
 * @param entry
 *         if available the old entry can be used for faster update. This
 *         should be a reference to the old element.
 */
static void addKillerMove(int ply, IMove move, List<IMove> entry) {
    if (entry.size() == MAX_SIZE)
        entry.iterator().remove();
    entry.add(move);
}

/**
```



```
    * updates the killermoves after the best move was found, i.e. all moves are
    * shifted from depth -> depth -2
    */
    static void updateKillerMove() {
        for (int i = 2; killer_moves.containsKey(i); i++)
            killer_moves.put(i - 2, killer_moves.get(i));
    }
}
```

1.24 MateScores.java

```
package mitzi;

/**
 * contains the scores for mate positions
 */
public final class MateScores {

    private MateScores() {
    }

    public static final int POS_INF = +30767;
    public static final int NEG_INF = -30767;
}
```

1.25 MitziBrain.java

```
package mitzi;

import java.util.ArrayList;
import java.util.Collections;
import java.util.List;
import java.util.Random;
import java.util.Timer;
import java.util.TimerTask;
import java.util.concurrent.ExecutorService;
import java.util.concurrent.Executors;
import java.util.concurrent.TimeUnit;

import static mitzi.MateScores.*;
```

```
import mitzi.UCIReporter.InfoType;

/**
 * This class implements the AI of Mitzi. The best move is found using the
 * negamax algorithms with Transposition tables. The class regularly sends
 * information about the current search, including nodes per second ("nps"),
 * the
 * filling of the Transposition Table ("hashfull") and the current searched
 * move
 * on top-level. The board evaluation is moved to a separate class
 * BoardAnalyzer.
 *
 */
public class MitziBrain implements IBrain {

    /**
     * maximal number of threads
     */
    private static final int THREAD_POOL_SIZE = 1;

    /**
     * unit for time management
     */
    private static final TimeUnit THREAD_TIMEOUT_UNIT = TimeUnit.MILLISECONDS;

    /**
     * timeout for thread shutdown
     */
    private static final int THREAD_TIMEOUT = 1000;

    /**
     * upper limit for evaluation time
     */
    private int maxEvalTime;

    /**
     * the currently best result
     */
    private AnalysisResult result;

    /**
     * the executor for the tasks
     */
    private ExecutorService exe;

    /**
```

```
* the current game state
*/
private GameState game_state;

private class PositionEvaluator implements Runnable {

    private final IPosition position;
    private final int searchDepth;

    public PositionEvaluator(final IPosition position, final int depth) {
        this.position = position;
        this.searchDepth = depth;
    }

    @Override
    public void run() {

        try {
            // Parameters for aspiration windows
            int alpha = NEG_INF; // initial value
            int beta = POS_INF; // initial value
            int asp_window = 25; // often 50 or 25 is used
            int factor = 2; // factor for increasing if out of bounds

            // iterative deepening
            for (int current_depth = 1; current_depth <= searchDepth;
                current_depth++) {
                table_counter = 0;
                BoardAnalyzer.table_counter = 0;

                result = negaMax(position, current_depth, current_depth,
                    alpha, beta);
                position.updateAnalysisResult(result);

                if (result.score == POS_INF || result.score == NEG_INF) {
                    break;
                }

                // If Value is out of bounds, redo search with larger
                // bounds, but with the same variation tree
                if (result.score <= alpha) {
                    alpha -= factor * asp_window;
                    current_depth--;
                    UCIReporter
                        .sendInfoString("Boards found: "
                            + (table_counter + BoardAnalyzer.table_counter));
                }
            }
        }
    }
}
```

```
        continue;
    } else if (result.score >= beta) {
        beta += factor * asp_window;
        current_depth--;
        UCIRReporter
            .sendInfoString("Boards found: "
                + (table_counter + BoardAnalyzer.table_counter));
        continue;
    }

    alpha = result.score - asp_window;
    beta = result.score + asp_window;

    UCIRReporter.sendInfoString("Boards found: "
        + (table_counter + BoardAnalyzer.table_counter));
}
} catch (InterruptedException e) {
}
}

@Override
public String toString() {
    return position.toString();
}
}

/**
 * counts the number of evaluated board
 */
private long eval_counter;

/**
 * counts the number of found boards in the transposition table.
 */
private long table_counter;

/**
 * the board analyzer for board evaluation
 */
private IPositionAnalyzer board_analyzer = new BoardAnalyzer();

/**
 * the current time.
 */
```

```
private long start_mtime = System.currentTimeMillis();

private Timer timer;

@Override
public void set(GameState game_state) {
    this.game_state = game_state;
    this.eval_counter = 0;
    this.table_counter = 0;
}

/**
 * @return the time, which passes since start_mtime
 */
private long runTime() {
    return System.currentTimeMillis() - start_mtime;
}

/**
 * Sends updates about evaluation status to UCI GUI, namely the number of
 * searched board per second and the size of the Transposition Table in
 * permill of the maximal size.
 */
class UCIOUpdater extends TimerTask {
    private long old_mtime;
    private long old_eval_counter;
    private long old_eval_counter_seldepth;

    @Override
    public void run() {
        long mtime = System.currentTimeMillis();

        long eval_span_0 = eval_counter - old_eval_counter;
        long eval_span_sel = BoardAnalyzer.eval_counter_seldepth
            - old_eval_counter_seldepth;
        long eval_span = eval_span_0 + eval_span_sel;

        if (old_mtime != 0) {
            long time_span = mtime - old_mtime;
            UCIReporter.sendInfoNum(InfoType.NPS, eval_span * 1000
                / time_span);

            UCIReporter.sendInfoNum(InfoType.HASHFULL,
                ResultCache.getHashfull());
        }
    }
}
```

```
        old_mtime = mtime;
        old_eval_counter += eval_span_0;
        old_eval_counter_seldepth += eval_span_sel;
    }
}

/**
 * NegaMax with Alpha Beta Pruning and Transposition Tables
 *
 * @see <a
 *      href="http://en.wikipedia.org/wiki/Negamax#NegaMax_with_Alpha_Beta_Pruning_and_Transp
 *      with Alpha Beta Pruning and Transposition Tables</a>
 * @param position
 *      the position to evaluate
 * @param total_depth
 *      the total depth to search
 * @param depth
 *      the remaining depth to search
 * @param alpha
 *      the alpha value
 * @param beta
 *      the beta value
 * @return returns the result of the evaluation, stored in the class
 *      AnalysisResult
 *
 * @throws InterruptedException
 */
private AnalysisResult negaMax(IPosition position, int total_depth,
    int depth, int alpha, int beta) throws InterruptedException {

    if (Thread.interrupted()) {
        throw new InterruptedException();
    }
    //
    // -----
    // whose move is it?
    Side side = position.getActiveColor();
    int side_sign = Side.getSideSign(side);

    //
    // -----
    int alpha_old = alpha;
```

```
// Cache lookup (Transposition Table)
AnalysisResult entry = ResultCache.getResult(position);
if (entry != null && entry.plys_to_eval0 >= depth) {
    table_counter++;
    if (entry.flag == Flag.EXACT)
        return entry.tinyCopy();
    else if (entry.flag == Flag.LOWERBOUND)
        alpha = Math.max(alpha, entry.score * side_sign);
    else if (entry.flag == Flag.UPPERBOUND)
        beta = Math.min(beta, entry.score * side_sign);

    if (alpha >= beta)
        return entry.tinyCopy();
}

// -----
// base of complete tree search
if (depth == 0) {
    // position is a leaf node
    return board_analyzer.evalBoard(position, alpha, beta);
}

// -----
// generate moves
List<IMove> moves = position.getPossibleMoves(true);

// -----
// Sort the moves:
ArrayList<IMove> ordered_moves = new ArrayList<IMove>(40);
ArrayList<IMove> remaining_moves = new ArrayList<IMove>(40);
BasicMoveComparator move_comparator = new BasicMoveComparator(position);

// Get Killer Moves:
List<IMove> killer_moves = KillerMoves.getKillerMoves(total_depth
    - depth);

// if possible use the moves from Position cache as the moves with
// highest priority
int number_legal_movs_TT = 0;
if (entry != null) {
    ordered_moves.addAll(entry.best_moves);
    number_legal_movs_TT = ordered_moves.size();
}
```

```
for (IMove k_move : killer_moves)
    if (moves.contains(k_move)
        && !ordered_moves.contains(k_move))
        ordered_moves.add(k_move);

} else {
    // Killer_moves have highest priority
    for (IMove k_move : killer_moves)
        if (moves.contains(k_move))
            ordered_moves.add(k_move);
}
// add the remaining moves and sort them using a basic heuristic
for (IMove move : moves)
    if (!ordered_moves.contains(move))
        remaining_moves.add(move);

Collections.sort(remaining_moves,
    Collections.reverseOrder(move_comparator));
ordered_moves.addAll(remaining_moves);
//
-----

if (entry != null && entry.plys_to_eval0 < depth)
    entry.best_moves.clear();

// create new AnalysisResult and parent
AnalysisResult new_entry = null, parent = null;
if (entry == null)
    new_entry = new AnalysisResult(0, null, false, 0, 0, null);

int best_value = NEG_INF; // this starts always at negative!

int i = 0;
int illegal_move_counter = 0;
// alpha beta search
for (IMove move : ordered_moves) {

    if(i>=number_legal_movs_TT && position.isCheckAfterMove(move)){
        illegal_move_counter++;
        continue;
    }

    // output currently searched move to UCI
    if (depth == total_depth && total_depth >= 6)
        UCIReporter.sendInfoCurrMove(move, i + 1);
```



```
position.doMove(move);
AnalysisResult result = negaMax(position, total_depth, depth - 1,
    -beta, -alpha);
position.undoMove(move);

int negaval = result.score * side_sign;

// better variation found
if (negaval > best_value || parent == null) {

    best_value = negaval;

    // update cache entry
    if (entry != null && entry.plys_to_eval0 < depth)
        entry.best_moves.add(move);
    if (entry == null)
        new_entry.best_moves.add(move);

    // update AnalysisResult
    byte old_seldepth = (parent == null ? 0
        : parent.plys_to_seldepth);
    parent = result; // change reference
    parent.best_move = move;
    parent.plys_to_eval0 = (byte) depth;
    if (best_value != POS_INF) {
        parent.plys_to_seldepth = (byte) Math.max(old_seldepth,
            parent.plys_to_seldepth);
    }

    // output to UCI
    if (depth == total_depth) {
        position.updateAnalysisResult(parent);
        game_state.getPosition().updateAnalysisResult(parent);
        UCIReporter.sendInfoPV(game_state.getPosition(), runTime());
    }
}

// alpha beta cutoff
alpha = Math.max(alpha, negaval);
if (alpha >= beta) {
    // set also KillerMove:
    if (!killer_moves.contains(move))
        KillerMoves.addKillerMove(total_depth - depth, move,
            killer_moves);
    break;
}
```

```
        i++;
    }
    // check for mate and stalemate
    if (illegal_move_counter == ordered_moves.size()) {
        eval_counter++;
        if (position.isCheckPosition()) {
            return new AnalysisResult(NEG_INF * side_sign, false, false, 0,
                                      0, Flag.EXACT);
        } else {
            return new AnalysisResult(0, true, false, 0, 0, Flag.EXACT);
        }
    }

    // -----
    // Transposition Table Store;
    if (best_value <= alpha_old)
        parent.flag = Flag.UPPERBOUND;
    else if (best_value >= beta)
        parent.flag = Flag.LOWERBOUND;
    else
        parent.flag = Flag.EXACT;

    if (entry != null && entry.plys_to_eval0 < depth) {
        entry.tinySet(parent);
        Collections.reverse(entry.best_moves);
    }

    if (entry == null) {
        new_entry.tinySet(parent);
        Collections.reverse(new_entry.best_moves);
        ResultCache.setResult(position, new_entry);
    }

    return parent;
}

@Override
public IMove search(int movetime, int maxMoveTime, int searchDepth,
                   boolean infinite, List<IMove> searchMoves) {

    // note, the variable searchMoves is currently unused, this feature is
    // not yet implemented!
}
```

```
// set up threading
timer = new Timer();
exe = Executors.newFixedThreadPool(THREAD_POOL_SIZE);

// make a copy of the actual position
IPosition position = game_state.getPosition().returnCopy();

board_analyzer.setCastling(position);

int max_depth;

// set parameters for searchtime and searchdepth
if (movetime == 0 && maxMoveTime == 0) {
    maxEvalTime = 60 * 60 * 1000; // 1h
    max_depth = searchDepth;
} else if (movetime == 0 && infinite == false) {
    maxEvalTime = maxMoveTime;
    max_depth = searchDepth;
} else if (movetime == 0 && infinite == true) {
    maxEvalTime = maxMoveTime;
    max_depth = 200;
} else if (maxMoveTime == 0) {
    maxEvalTime = movetime;
    max_depth = 200; // this can never be reached :)
} else if (infinite == true) {
    maxEvalTime = maxMoveTime;
    max_depth = 200; // this can never be reached :)
} else {
    maxEvalTime = Math.min(movetime, maxMoveTime);
    max_depth = searchDepth;
}

timer.scheduleAtFixedRate(new UCIUpdater(), 1000, 5000);
start_mtime = System.currentTimeMillis();

// reset the result
result = null;

// create a new task
PositionEvaluator evaluator = new PositionEvaluator(position, max_depth);

// execute the task
exe.execute(evaluator);

return wait_until();
}
```

```
/**
 * stops all active threads if mitzi is running out of time
 *
 * @return the best move
 */
public IMove wait_until() {

    exe.shutdown();

    // wait for termination of execution
    try {
        if (exe.awaitTermination(maxEvalTime, THREAD_TIMEOUT_UNIT)) {
            UCIReporter.sendInfoString("task completed");
        } else {
            UCIReporter.sendInfoString("forcing task shutdown");
            exe.shutdownNow();
            exe.awaitTermination(THREAD_TIMEOUT, TimeUnit.SECONDS);
        }
    } catch (InterruptedException e) {
        // TODO Auto-generated catch block
        e.printStackTrace();
    }

    // shut down timers and update killer moves
    timer.cancel();
    UCIReporter.sendInfoPV(game_state.getPosition(), runTime());
    KillerMoves.updateKillerMove();

    // if no best_move has been found yet, choose any
    if (result == null) {
        List<IMove> possibleMoves = game_state.getPosition()
            .getPossibleMoves();
        int randy = new Random().nextInt(possibleMoves.size());
        return possibleMoves.get(randy);
    }

    // return the best move of the last completely searched tree
    return result.best_move;
}

@Override
public IMove stop() {
    // shut down immediately
    exe.shutdownNow();
}
```

```
// shut down timers and update killer moves
timer.cancel();
UCIReporter.sendInfoPV(game_state.getPosition(), runTime());
KillerMoves.updateKillerMove();

// return the best move of the last completely searched tree
if (result == null)
    return null; // this should never happen

return result.best_move;
}
}
```

1.26 ResultCache.java

```
package mitzi;

import java.util.LinkedHashMap;
import java.util.Map;

/**
 * After creating a new <code>AnalysisResult</code> instance, use this class
 * to
 * cache it for later lookup of moves, score, etc. The AnalysisResults are
 * indexed by the HashCode of the corresponding position, therefore it can
 * happen, that different AnalysisResults have the same HashCode. In such a
 * case, the old values get overridden. The AnalysisResults store a different
 * hashvalue to reduce the probability of using a wrong AnalysisResult, if two
 * positions have the same HashCode.
 *
 */
public class ResultCache {

    private static final int MAX_ENTRIES = 600000;

    /**
     * A map from the Position's <code>hashCode</code> to the AnalysisResult.
     * The size of the table is limited with <code>MAX_ENTRIES</code>
     */
    private static LinkedHashMap<Integer, AnalysisResult> position_cache = new
        LinkedHashMap<Integer, AnalysisResult>(
            MAX_ENTRIES + 1, 1) {

        private static final long serialVersionUID = 4582735742585308092L;
    }
}
```

```
protected boolean removeEldestEntry(
    Map.Entry<Integer, AnalysisResult> eldest) {
    return size() > MAX_ENTRIES;
}

};

/**
 * Cannot be instantiated. For access to the static cache use
 * <code>ResultCache.getPosition(p)</code>.
 */
private ResultCache() {
}

/**
 * Looks up a <code>Position</code> in the cache and returns the saved value
 * if found and with coinciding second hashvalue. otherwise null.
 *
 * @param lookup
 *         the <code>Position</code> to look up in the cache
 * @return a previously cached <code>AnalysisResult</code> if available,
 *         null otherwise.
 */
public static AnalysisResult getResult(IPosition lookup) {
    int hash = lookup.hashCode();
    AnalysisResult ce = position_cache.get(hash);
    if (ce == null || lookup.hashCode2() != ce.hashvalue)
        return null;
    else
        return ce;
}

/**
 * stores a AnalysisResult corresponding to a Position. The second
 * hashvalue is automatically set here.
 * @param pos the position corresponding to the AnalysisResult
 * @param ce the AnalysisResult
 */
public static void setResult(IPosition pos, AnalysisResult ce) {
    ce.hashvalue = pos.hashCode2();
    int hash = pos.hashCode();
    position_cache.put(hash, ce);
}

/**
```

```
    *
    * @return the number of stored results in this cache
    */
    public static int size() {
        return position_cache.size();
    }

    /**
    * @return the hash is x permill full
    */
    public static int getHashfull() {
        return (int) ((double) position_cache.size() / MAX_ENTRIES * 1000);
    }
}
```

1.27 UCIReporter.java

```
package mitzi;

import static mitzi.MateScores.*;

public final class UCIReporter {

    /**
    * the engine should send these infos regularly
    *
    * DEPTH: search depth in plies
    *
    * NODES: number of nodes searched
    *
    * NPS: number of nodes per second searched
    *
    * HASHFULL: the hash is x permill full
    */
    public static enum InfoType {
        DEPTH("depth"), NODES("nodes"), NPS("nps"), HASHFULL("hashfull");

        public String string;

        InfoType(String string) {
            this.string = string;
        }
    }
}
```

```
private static String last_pv = "";

private UCIRReporter() {
};

/**
 * Send debugging messages to the GUI.
 *
 * @param string
 *         the message to be displayed
 */
public static void sendInfoString(String string) {
    System.out.println("info string " + string);
}

/**
 * Send information about search depth, number of nodes searched and number
 * of nodes searched per second to the GUI.
 *
 * @param type
 *         one of UCIRReporter.InfoType
 * @param eval_counter
 *         the integer value to be sent
 */
public static void sendInfoNum(InfoType type, long eval_counter) {
    System.out.println("info " + type.string + " " + eval_counter);
}

/**
 * Send information about the currently searched move to the GUI.
 *
 * @param move
 *         currently searching this IMove
 * @param move_number
 *         currently searching move number n, for the first move n should
 *         be 1 not 0.
 */
public static void sendInfoCurrMove(IMove move, int move_number) {
    System.out.println("info currmove " + move + " currmovenumber "
        + move_number);
}

/**
 * The Principal variation (PV) is a sequence of moves that programs
```



```
* consider best and therefore expect to be played. Also all infos belonging
* to the PV should be sent together.
*
* @param position
*       a Position with an AnalysisResult
* @param time
*       the time searched in ms
*/
public static void sendInfoPV(IPosition position, long time) {
    AnalysisResult result = position.getAnalysisResult();
    if (result == null)
        return;

    StringBuilder pv = new StringBuilder();

    if (result.score == NEG_INF && position.getActiveColor() == Side.WHITE
        || result.score == POS_INF
        && position.getActiveColor() == Side.BLACK) {
        pv.append("info score mate -"
            + ((result.plys_to_eval0 + result.plys_to_seldepth + 1) / 2)
            + " depth " + result.plys_to_eval0 + " seldepth "
            + (result.plys_to_seldepth + result.plys_to_eval0) + " pv");
    } else if (result.score == NEG_INF
        && position.getActiveColor() == Side.BLACK
        || result.score == POS_INF
        && position.getActiveColor() == Side.WHITE) {
        pv.append("info score mate "
            + ((result.plys_to_eval0 + result.plys_to_seldepth + 1) / 2)
            + " depth " + result.plys_to_eval0 + " seldepth "
            + (result.plys_to_seldepth + result.plys_to_eval0) + " pv");
    } else {
        pv.append("info score cp " + result.score + " depth "
            + result.plys_to_eval0 + " seldepth "
            + (result.plys_to_seldepth + result.plys_to_eval0) + " pv");
    }

    for (IMove move : result.getPV(position, result.plys_to_eval0)) {
        pv.append(" " + move);
    }

    String new_pv = pv.toString();
    if (!last_pv.equals(new_pv)) {
        System.out.print(new_pv);
        System.out.println(" time " + time);
        last_pv = new_pv;
    }
}
```

```
}  
}
```

1.28 MitziGUI.java

```
package mitzi;  
  
import javax.swing.JFrame;  
  
import java.awt.*;  
import java.awt.event.*;  
  
import javax.swing.*;  
  
public class MitziGUI extends JFrame implements MouseListener,  
    MouseMotionListener {  
  
    private static final long serialVersionUID = -418000626395118246L;  
  
    JLayeredPane layeredPane;  
    JPanel chessBoard;  
    JLabel chessPiece;  
    int xAdjustment;  
    int yAdjustment;  
  
    int start_square;  
    int end_square;  
  
    private static GameState state = new GameState();  
  
    private static boolean mitzis_turn;  
  
    private static Side mitzis_side = null;  
  
    Dimension boardSize = new Dimension(800, 800);  
  
    public Object[] options = { "ok" };  
  
    public MitziGUI() {  
        redraw();  
    }  
  
    private void redraw() {
```

```
// Use a Layered Pane for this this application
layeredPane = new JLayeredPane();

layeredPane.setPreferredSize(boardSize);
layeredPane.addMouseListener(this);
layeredPane.addMouseMotionListener(this);

// Add a chess board to the Layered Pane
chessBoard = new JPanel();
layeredPane.add(chessBoard, JLayeredPane.DEFAULT_LAYER);
chessBoard.setLayout(new GridLayout(8, 8));
chessBoard.setPreferredSize(boardSize);
chessBoard.setBounds(0, 0, boardSize.width, boardSize.height);

// Color it b/w
Color black = Color.getHSBColor((float) 0.10, (float) 0.40,
    (float) 0.80);
Color white = Color.getHSBColor((float) 0.15, (float) 0.13,
    (float) 0.98);
for (int i = 0; i < 64; i++) {
    JPanel square = new JPanel(new BorderLayout());
    chessBoard.add(square);
    square.setBackground((i + i / 8) % 2 == 0 ? white : black);
}

getContentPane().removeAll();
getContentPane().add(layeredPane);
}

private int getSquare(int x, int y) {
    x = x / 100 + 1;
    y = (800 - y) / 100 + 1;
    return x * 10 + y;
}

private Component squareToComponent(int squ) {

    int row = 8 - squ % 10;
    int col = ((int) squ / 10) - 1;

    Component c = chessBoard.getComponent(row * 8 + col);
    return c;
}

public void setToFEN(String fen) {
```

```
redraw();

JPanel panel;

String[] fen_parts = fen.split(" ");

// populate the squares
String[] fen_rows = fen_parts[0].split("/");
char[] pieces;
for (int row = 0; row < 8; row++) {
    int offset = 0;
    for (int column = 0; column + offset < 8; column++) {
        pieces = fen_rows[row].toCharArray();
        int square = row * 8 + column + offset;
        JLabel piece;
        switch (pieces[column]) {
            case 'P':
                piece = new JLabel("");
                break;
            case 'R':
                piece = new JLabel("");
                break;
            case 'N':
                piece = new JLabel("");
                break;
            case 'B':
                piece = new JLabel("");
                break;
            case 'Q':
                piece = new JLabel("");
                break;
            case 'K':
                piece = new JLabel("");
                break;
            case 'p':
                piece = new JLabel("");
                break;
            case 'r':
                piece = new JLabel("");
                break;
            case 'n':
                piece = new JLabel("");
                break;
            case 'b':
                piece = new JLabel("");
                break;
        }
    }
}
```

```
        break;
    case 'q':
        piece = new JLabel("");
        break;
    case 'k':
        piece = new JLabel("");
        break;
    default:
        piece = new JLabel("");
        offset += Character.getNumericValue(pieces[column]) - 1;
        break;
    }
    panel = (JPanel) chessBoard.getComponent(square);
    piece.setFont(new Font("Serif", Font.PLAIN, 100));
    panel.add(piece);
}
}
chessBoard.updateUI();
}

public void mousePressed(MouseEvent e) {
    chessPiece = null;
    Component c = chessBoard.findComponentAt(e.getX(), e.getY());

    if (c instanceof JPanel)
        return;
    Point parentLocation = c.getParent().getLocation();
    xAdjustment = parentLocation.x - e.getX();
    yAdjustment = parentLocation.y - e.getY();
    start_square = getSquare(e.getX(), e.getY());
    chessPiece = (JLabel) c;
    chessPiece.setLocation(e.getX() + xAdjustment, e.getY() + yAdjustment);
    chessPiece.setSize(chessPiece.getWidth(), chessPiece.getHeight());
    layeredPane.add(chessPiece, JLayeredPane.DRAG_LAYER);
}

// Move the chess piece around
public void mouseDragged(MouseEvent me) {
    if (chessPiece == null)
        return;
    chessPiece
        .setLocation(me.getX() + xAdjustment, me.getY() + yAdjustment);
}

// Drop the chess piece back onto the chess board
public void mouseReleased(MouseEvent e) {
```

```
if (chessPiece == null)
    return;
chessPiece.setVisible(false);
end_square = getSquare(e.getX(), e.getY());

// check for promotion
IMove move;
if (state.getPosition().getPieceFromBoard(start_square) == Piece.PAWN
    && (SquareHelper.getRow(end_square) == 8 || SquareHelper
        .getRow(end_square) == 1)) {
    move = new Move(start_square, end_square, askPromotion());
} else {
    move = new Move(start_square, end_square);
}

//if its not your turn, you are not allowed to do anything.
if(mitzis_side == state.getPosition().getActiveColor())
{
    Container parent = (Container) squareToComponent(start_square);
    parent.add(chessPiece);
    chessPiece.setVisible(true);
    return;
}

//try to do move
try {
    state.doMove(move);
} catch (IllegalArgumentException ex) {
    Container parent = (Container) squareToComponent(start_square);
    parent.add(chessPiece);
    chessPiece.setVisible(true);
    return;
}

IPosition position = state.getPosition();
setToFEN(position.toFEN());
if (state.getPosition().isMatePosition()) {
    JOptionPane.showOptionDialog(this,
        "You Won!", "Information",
        JOptionPane.DEFAULT_OPTION, JOptionPane.QUESTION_MESSAGE, null,
        options, options[0]);
    return;
}
if (state.getPosition().isStaleMatePosition()) {
    JOptionPane.showOptionDialog(this,
```

```
        "Draw","Information",
        JOptionPane.DEFAULT_OPTION, JOptionPane.QUESTION_MESSAGE, null,
        options, options[0]);
    return;
}

mitzis_turn = true;
}

public void mouseClicked(MouseEvent e) {
}

public void mouseMoved(MouseEvent e) {
}

public void mouseEntered(MouseEvent e) {
}

public void mouseExited(MouseEvent e) {
}

private Piece askPromotion() {
    Object[] options = { "Queen", "Rook", "Bishop", "Knight" };
    int n = JOptionPane.showOptionDialog(this,
        "Which piece do you want to promote to?", "Pawn Promotion",
        JOptionPane.DEFAULT_OPTION, JOptionPane.QUESTION_MESSAGE, null,
        options, options[0]);
    if (n == 0) {
        return Piece.QUEEN;
    } else if (n == 1) {
        return Piece.ROOK;
    } else if (n == 2) {
        return Piece.BISHOP;
    } else {
        return Piece.KNIGHT;
    }
}

public static void main(String[] args) {
    JFrame frame = new MitziGUI();
    frame.setDefaultCloseOperation(DISPOSE_ON_CLOSE);
    frame.pack();
    frame.setResizable(false);
    frame.setLocationRelativeTo(null);
    frame.setVisible(true);
    frame.setTitle("Mitzi GUI");
}
```

```
MitziGUI gui = (MitziGUI) frame;
Object[] choice = { "You", "Mitzi" };

String initialFEN = "rnbqkbnr/pppppppp/8/8/8/8/PPPPPPPP/RNBQKBNR w KQkq -
0 1";
state.setToFEN(initialFEN);
gui.setToFEN(initialFEN);
int n = JOptionPane.showOptionDialog(frame,
    "Who should start","Question",
    JOptionPane.DEFAULT_OPTION, JOptionPane.QUESTION_MESSAGE, null,
    choice, choice[0]);

if(n==0)
{
    mitzis_turn = false;
    mitzis_side = Side.BLACK;
}
else
{
    mitzis_turn = true;
    mitzis_side = Side.WHITE;
}
IBrain mitzi = new MitziBrain();
IMove move;
while (true) {
    System.out.print("");
    if(mitzis_turn) {
        // Mitzis turn

        mitzi.set(state);
        move = mitzi.search(5000, 5000, 6, true, null);
        state.doMove(move);

        gui.setToFEN(state.getPosition().toFEN());
        if (state.getPosition().isMatePosition()) {
            JOptionPane.showOptionDialog(frame,
                "Mitzi Won!","Information",
                JOptionPane.DEFAULT_OPTION, JOptionPane.QUESTION_MESSAGE, null,
                gui.options, gui.options[0]);
            return;
        }
        if (state.getPosition().isStaleMatePosition()) {
            JOptionPane.showOptionDialog(frame,
                "Draw!","Information",
                JOptionPane.DEFAULT_OPTION, JOptionPane.QUESTION_MESSAGE, null,
```



```
        gui.options, gui.options[0]));  
    return;  
}  
    mitzis_turn=false;  
}  
}  
}  
}
```
