Rails Routing

(Rails)

Rails flow


1
2
3
4
Router
config/routes.rb
Controller
app/controllers
Model
app/models
View
app/views

HTTP request?

some link



HTTP basics

A protocol to transfer **resources**

Based on a system of **request / response**

Between 2 machines, **a client and a server**



HTTP request is MORE THAN a **URL**

HTTP request is MORE THAN a **URL**

HTTP request is **4 things**

1 - HTTP verb (GET / POST / PATCH / DELETE)

2 - URL

3 - headers

4 - body (not always)

Rails routing

GET /home



```
get “home” => “pages#home”
get “team” => “pages#team”
get “products” => “products#index”
post “products” => “products#create”
```

```
PagesController
  def home
    …
  end
```

Rails routing

GET /team



```
get “home” => “pages#home”

get “team” => “pages#team”

get “products” => “products#index”

post “products” => “products#create”
```

```
PagesController

  def home
    …
  end
  def team
    …
  end
```

Rails routing

GET /products



```
get “home” => “pages#home”

get “team” => “pages#team”

get “products” => “products#index”

post “products” => “products#create”
```

PagesController

```
ProductsController

def index
  …
end
```

Rails routing

POST /products



```
get “home” => “pages#home”

get “team” => “pages#team”

get “products” => “products#index”

post “products” => “products#create”
```

```
PagesController
```

```
ProductsController

  def index
    …
  end
  def create
    …
  end
```

Action/View convention

```
PagesController                  views/pages
  def home                       home.html.erb
    ...
  end
  def team                       team.html.erb
    ...
  end
```

ERB

Embedded **R**u**b**y



+

=

file.html

file.html**.erb**



Instance variables

PagesController

```
def home
  @time = Time.now
end
```

pages/home.html.**erb**

```
<h1>...</h1>
<%= @time %>
```

Congratz!

That was the hardest part :)