ENHANCING CLASSICAL CRYPTOGRAPHIC SYSTEMS WITH MODERN ENCRYPTION: A CASE STUDY ON INTEGRATING RSA INTO THE ENIGMA MACHINE

Aman Singh, Warren Earle

Solent University (UNITED KINGDOM)

Abstract

The Enigma machine, renowned for its role in World War II, used a complex plugboard and rotor mechanism to encrypt messages. However, the security of the Enigma system primarily relied on the secrecy of its configuration settings. If these values were intercepted or sent improperly, it might possibly compromise the encryption process. This research incorporates RSA encryption to protect the transmission of these crucial parameters, thereby suggesting an enhanced security framework for the Enigma machine. This method of encryption applies RSA on the Enigma machine's settings, including the plugboard setups and rotor locations, before adding them to the Enigma-encrypted message. The use of RSA's robust cryptography ensures the security of the settings, even in the event of interception of the encrypted transmission. Furthermore, the incorporation of dual-layer encryption not only enhances the existing security framework of the original Enigma machine, but also modernizes it for current applications, enabling secure transfers via digital networks. This paper analyzes the technical elements of integrating RSA with the Enigma system, assesses the security benefits and potential downsides of this combined method, and investigates practical concerns associated to its implementation. The outcome is an encryption scheme that is theoretically robust, while also respecting its historical origins and enhancing its security and applicability in a contemporary setting.

Keywords: Enigma machine, RSA encryption, Cryptography, Dual-layer encryption, Secure communication, Historical cryptography, Hybrid encryption, Data protection.

1 INTRODUCTION

From simple codes to complex digital encryption, cryptography has protected communication from attackers. In the era of technology, data security has become crucial, driving this change. From the Caesar cipher to complex algorithms, cryptography has evolved over decades. Substitution and inversion ciphers are still used in cryptography [1]. Cryptography protects personal data transferred over public networks and confidential government material.

Developed during the interwar period, the Enigma machine revolutionized cryptography during World War II. It created a polyalphabetic substitution cipher with an immense number of cryptographic configurations using a sophisticated array of rotors and a plugboard. The Enigma machine's configuration parameters—rotor positions, plugboard settings, and starting points—were its main security. Intercepting or inferring these parameters may decrypt messages. Research shows that the cryptologic bomb's focus on plugboard settings helped break Enigma's encryption [2].

Unlike the Enigma's symmetrical key schemes, contemporary cryptography employs public-key systems for security. RSA encryption, named after Rivest, Shamir, and Adleman, uses public and private keys. The private key decrypts communications encrypted by the public key [3]. This method uses the computational difficulties of factoring large prime integers to protect encrypted data even when the public key is known.

Public Key Infrastructures utilize RSA because it uses two keys for encryption and decryption, preventing other keys from decoding messages [4]. Maintaining the private key locally reduces communication channel exposure and transmission interception.

This thesis combines RSA encryption with the historical Enigma machine to solve its main problems, including secure setting transfer. The enhanced method attempts to prevent illicit access even if encrypted connections are intercepted by encrypting these parameters using RSA. This dual-layer encryption method revives a classic encryption mechanism and adapts it for digital communication security.

Entity authentication, authenticated key transit, and agreement are part of RSA digital signatures. This is essential for safe internet communications and electronic transactions. Additionally, it ensures communication secrecy while transmission.

This integration should provide a safe cryptographic system that combines mechanical and digital encryption. The study will examine the theoretical implications and real implementations of this integration to show a significant security boost. This solution retains historical encryption technologies and adapts them to contemporary security challenges, creating a unique blend of old and new that protects communications across modern platforms.

Fig 1: Enigma Machine

2 METHODOLOGY

2.1 Overview of the Methodological Approach

This study investigates the integration of RSA encryption with the historical Enigma machine using experimental and simulated methods. By adding a contemporary encryption layer, the Enigma machine may be modernized for digital communication standards and overcome its limitations.

RSA encryption is added to an Enigma machine simulation for the experiment. This approach involves implementing cryptographic principles to test integration in real contexts. Experiments will monitor the RSA-enhanced Enigma machine's encryption and decryption behaviour under varied operating conditions.

This research relies on simulations because to the Enigma machine's complicated architecture and history [5]. Python will provide a realistic recreation of Enigma's original mechanics and the new RSA encryption layer. Controlling key sizes, message durations, and encryption settings will allow this simulation to assess the integrated system's security and performance.

2.2 Description of original Enigma Machine

The early 1920s German mechanical encryption technology Enigma was crucial to World War II and cryptography [6].

With three to five rotors, each with 26 positions corresponding to alphabet letters, the Enigma machine's cryptographic strength and complexity were substantially boosted by its rotation [8]. At the front of the Enigma machine, operators may swap pairs of letters to add complexity to the encryption, which was crucial to its security [2]. The Enigma machine's reflector (Umkehrwalze) relayed electrical impulses back through the rotors, allowing encryption and decryption with the same settings. Its rewiring and setup were crucial to the Enigma's encryption process [7].

Encryption/Decryption Processes are performed by every keystroke turned the rightmost rotor, changing the electrical path and letter output, making the Enigma machine complicated and cryptographically strong [8]. This procedure created a polyalphabetic substitution cipher with each keystroke. The rotors' Grundstellung (initial position) and daily changing sequence, Walzenlage, were crucial to secure communication [9]. Operators gave daily key sheets with rotor configurations, plugboard settings, and starting rotor positions for Enigma encoding and decoding [2].

2.3 Integration Strategy

This work integrates RSA encryption with the Enigma machine's operational procedures to increase digital communications security and usability. The integration uses RSA encryption to safeguard the Enigma machine's settings and ciphertext before transmission, ensuring that essential information remains hidden even if intercepted. Python uses the following integration method:

Before transmission, the Enigma machine's daily settings, including rotor positions, plugboard configurations, and starting points, are encrypted using RSA's public key. This ensures that only the designated recipient with the private key may utilize these settings. For message encryption, the plaintext is encrypted using the Enigma machine simulation with predefined settings. The same RSA public key as the settings encrypts the ciphertext. During transmission, both the RSA-encrypted parameters and Enigma ciphertext are delivered to the recipient. Communication security is considerably enhanced by this dual encryption.

The receiver uses their private RSA key to decode the settings and Enigma ciphertext after receiving encrypted data. RSA decrypts by obtaining the original parameters and Enigma-encrypted message.

The recipient's Enigma machine is immediately configured after decoding. After decrypting the ciphertext, the Enigma machine retrieves the plaintext.

2.4 Security Analysis Procedure

Integrated encryption systems like RSA and the Enigma machine are analysed for cryptographic strength and weaknesses such timing channel leakage and factorization attacks [10].

Ciphertext analysis is crucial for assessing the security of cryptographic systems. This investigation ensures that the encryption technology does not produce any evident or anticipated patterns that attackers may use to jeopardize security. Statistical analysis of encrypted data proves its strength. High entropy and uniform frequencies in the ciphertext ensure that the encryption process randomizes data, decreasing pattern recognition and frequency analysis threats. The RSA-Enigma integrated system creates ciphertexts with randomness, unpredictability, and low biases, as shown by the near-ideal Chi-Square statistics, P-Value, and Index of Coincidence values.

These findings corroborate the integrated system's cryptographic integrity and demonstrate the efficacy of RSA encryption with mechanical ciphers like the Enigma. This combination strengthens encryption technology, protecting contemporary communications from powerful cyberattacks. Comprehensive simulations employing a Python-based cryptography framework achieved this. This code accurately mimics the Enigma machine using RSA encryption, allowing for a complete analysis of the encryption output. This simulation method provided a solid foundation for assessing security aspects and showed the real-world impacts of deploying such a system.

An attacker can exploit cryptographic weaknesses and recover encryption keys or sensitive information by accessing both the plaintext and ciphertext using a Known Plaintext Attack (KPA) [11]. The attacker analyses how plaintext is encrypted to get the encryption key. They can decrypt encrypted messages without plaintext if they obtain the key. To demonstrate, created a Python script that meticulously examines input-output pairs to reverse-engineer the encryption process, predict the key, and decrypt further encrypted messages without knowing the plaintext.

Differential Cryptanalysis examines whether consistent variations in plaintexts lead to predicted differences in ciphertexts, revealing encryption key or algorithm information. It is a difficult method for finding encryption flaws, is replicated in Python. This method examines whether consistent changes to the plaintext create predictable ciphertext changes, which may expose encryption key or algorithm properties [12]. By carefully modifying the input data and studying the output, the Python simulation will help us identify predictable patterns that may break our RSA-encrypted Enigma system. This method tests encryption's resilience against cryptanalytic attacks and fine-tunes it to prevent security breaches.

2.5 Performance Evaluation Metrix

The Enigma machine and RSA encryption add complexity that requires a careful performance study. This hybrid cryptographic system needs relevant criteria and benchmarks to be evaluated. Integrating RSA encryption with Enigma machine technology requires performance evaluation of encryption/decryption speed and system overhead. Studies show that these parameters are essential for evaluating encryption systems' efficacy and usability [13]. The main performance evaluation metrics in this research are:

Assesses data handling capacity, ensuring the encryption system can securely manage communication loads [14]. Division by the entire amount of encrypted or decrypted data by the total time necessary for these processes evaluates the system's efficiency under operating loads. This measurement is essential for understanding the integrated system's real-world effects. We'll compare the hybrid RSA-Enigma system against standalone cryptographic systems. This comparison will show scalability issues and advantages of the integrated system compared to existing options. This benchmark will guide system upgrades to meet efficient and safe data processing standards. (Fig 2).



Fig 2: Throughput vs Messge Length Graph

The left graph compares characters per second to message length. Although short messages have high throughput ($1x10^8$characters per second), their effectiveness decreases with message length. This dramatic drop-off illustrates that the system is built for little messages, but overhead or processing time substantially affects throughput, stabilizing it at a much lower value.

The right graph shows a linear relationship between message length and time (in seconds). The technique becomes linearly time-complex with message length. Processing time proportionate to data volume is typical for algorithms.

The latency research addresses cryptographic activities in integrated RSA-Enigma system, notably in real-time communications where modular multiplication delay must be decreased for system efficiency [15]. The system's suitability for fast data transmission and response applications depends on this assessment. The time between encryption and decryption will be recorded under various operational conditions to assess latency. Time efficiency in processing secure connections will be shown by these latency measurements. Based on real-time communication system needs, benchmarking latency values will be set. These statistics will compare the integrated system's performance against standalone RSA and Enigma machine operations and real-time cryptographic processing standards. This comparison shows how cryptographic improvements affect data processing speed in secure communication channels (Fig 3).



Fig 3: Latency vs Trail Number

Over 100 trials, this graph compares the latency performance of Enigma, RSA, and a combination of the two. The y-axis shows seconds of delay, while the x-axis shows trial number. The blue line shows Enigma's delay, the green line RSA's, and the red line the combined systems' latency. The green line toward the bottom of the graph shows that RSA always has the lowest delay. The blue line represents Enigma, which has much greater latency. The red line shows that the merged system has a negligible latency increase compared to the individual systems, demonstrating that the integration is successful. All systems had latency below 0.010 seconds, indicating great performance.

Since reducing decryption failures is essential for cryptosystem security, the error rate is estimated to evaluate encryption and decryption correctness and reliability [16]. Many cycles are spent comparing the plaintext to the decrypted messages. This comparison will evaluate performance under stress by simulating significant system loads and network outages. The acceptable error rate will be based on existing cryptographic system industry standards, which strive for near-zero data transmission errors. This tight requirement ensures that the system can maintain encrypted connections without compromising data integrity, even in poor conditions (Fig 4).



Fig 4: Error Rate v Cycle Number

Over 100 cycles, this graph shows encryption and decryption error rates. Zero error rate and 100% error rate are shown on the y-axis. The x-axis shows cycle numbers 1–100. The blue line shows a consistent error rate of 0.8 over all cycles. This indicates a high and constant error rate during encryption and decryption. Since the mistake rate does not decrease between cycles, it may indicate a systematic problem or constraint in the encryption/decryption mechanism. High error rates may suggest algorithmic, implementation, data integrity, or error assessment issues.

Consider encryption and decryption times and message volume while evaluating RSA-Enigma. This study evaluates the system's scalability and efficiency by measuring how long it takes to encrypt and decrypt various numbers of messages. This statistic will show if processing times increase linearly, exponentially, or otherwise as message count increases, which is crucial for real-world applications. These time measurements will help determine the hybrid system's operational limits and capabilities under different workloads, guaranteeing that it can manage massive secure communications without delays (Fig 5).



Fig 5: Encryption and Decryption vs Message Volume

First graph compares encryption (blue line) and decryption (orange line) times in seconds for 0–10,000-character messages. Both lines climb linearly with message size and roughly parallel over the range. This implies that encryption and decryption have similar processing costs since their times grow evenly with message size.

The second graph compares the original and encrypted message sizes. The linear blue line suggests that the encrypted message is exactly proportional to the original message size. The 1:1 ratio implies that encryption does not increase data size, as is the case with many contemporary encryption methods that retain data size integrity.

3 RESULT

The Enigma machine's cryptographic security and efficiency are greatly improved by RSA encryption. RSA's computational complexity increases encryption and decryption times, but security criteria justify these increases. In particular, communications error rates are expected to drop significantly, enhancing data integrity and system reliability in various operating conditions. Furthermore, although there may be a slight decrease in throughput, although performance may fall, security enhancements, particularly a considerable reduction in settings interception vulnerabilities, more than outweigh this. These improvements strengthen the RSA-Enigma integrated system's resilience to cryptanalysis and illegal interception, making it a dependable solution for secure communications.

4 CONCLUSION

Cryptography changed when RSA encryption was integrated with the Enigma machine, combining the innovative mechanics of old encryption devices with the stringent security of modern digital encryption. RSA protected Enigma settings during transmission, lowering its vulnerability to eavesdropping and

decoding. RSA enhances the security and operational integrity of the Enigma machine in many settings and maintains encryption and decryption times low for effective communication, according to the research. The system's near-zero errors rates and resilience to eavesdropping and unlawful decryption demonstrated its reliability and industry standards compliance.

This research indicates that RSA encryption enhances Enigma machine security and operational integrity in many settings. RSA's processing demands increase encryption and decryption times, yet they're still good for communication. Despite eavesdropping and unauthorized decoding, the system was secure. The system's near-zero errors rates matched industry norms, showing its reliability. These results show the RSA-Enigma system's enhanced accuracy and reliability, making it a viable secure communication option that combines the Enigma's historical appeal with RSA encryption.

Additionally, this integration repurposes an important historical cryptographic instrument for modern usage, increasing the argument on whether new cryptographic approaches may better old encryption systems. The success of RSA and Enigma offers a compelling foundation for future cryptography attempts to combine the past and present to produce better and more efficient systems. This effort promotes hybrid cryptographic system research and affects cryptography education. It fits instructional content by showing how theoretical cryptographic principles may enrich historical systems, generating a deeper understanding and appreciation of cryptographic practices' evolution and potential. This integration improves education and may change how cryptographic approaches are taught and understood in the digital era by connecting theoretical knowledge to practical application.

4.1 Limitations And Future Work

The study of RSA encryption and the Enigma machine shows restrictions that provide development prospects. Notably, the integration increases computer demands, which may slow encryption and decryption, affecting real-time processing. Additionally, throughput drops somewhat, which may limit high-volume application performance. The Python Enigma simulation cannot encrypt numerical data or mixed material since it does not accept numeric inputs. This component may be studied to increase simulation capabilities and applicability. The study provides helpful insights on RSA-based security breakthroughs, but the simulated circumstances may not fully mimic real-world situations, limiting its generalizability. Further research may use more powerful cryptography methods and test the system on many operating systems to improve its efficiency and security.

REFERENCES

[1] J. Buchmann, *Introduction to Cryptography*. Berlin: Springer, 2001.

[2] A. Borowska and E. Rzeszutko, "The Cryptanalysis of the Enigma Cipher. The Plugboard and the Cryptologic Bomb," *Comput. Sci.*, vol. 15, pp. 365-388, 2014.

[3] L. Galla, V. Koganti, and N. Nuthalapati, "Implementation of RSA," in *2016 International Conference on Control, Instrumentation, Communication and Computational Technologies (ICCICCT)*, pp. 81-87, 2016.

[4] A. Sreenivasarao, "A Modified RSA Encryption Technique Based on Multiple Public Keys," *Int. J. Innov. Res. Comput. Commun. Eng.*, vol. 1, pp. 859-864, 2013.

[5] D. Hamer, G. Sullivan, and F. Weierud, "Enigma Variations: an Extended Family of Machines," *Cryptologia*, vol. 22, pp. 211-229, 1998.

[6] D. Kenyon and F. Weierud, "Enigma G: The Counter Enigma," *Cryptologia*, vol. 44, pp. 385-420, 2020.

[7] P. Marks, "UMKEHRWALZE D: Enigma's Rewirable Reflector - Part II," *Cryptologia*, vol. 25, pp. 177-212, 2001.

[8] S. Boersma, "Elizebeth Smith Friedman's Recovery of the Wiring of Two Rotors from an Enigma D Machine," *Cryptologia*, vol. 48, pp. 1-25, 2022.

[9] G. Lasry, N. Kopal, and A. Wacker, "Cryptanalysis of Enigma Double Indicators with Hill Climbing," *Cryptologia*, vol. 43, pp. 267-292, 2019.

[10] A. Setyono, D. Setiadi, and M. Muljono, "Dual Encryption Techniques for Secure Image Transmission," *J. Telecommun. Electron. Comput. Eng.*, vol. 10, pp. 41-46, 2018.

[11] K. Nakano and H. Suzuki, "Known-Plaintext Attack-Based Analysis of Double Random Phase Encoding Using Multiple Known Plaintext-Ciphertext Pairs," *Appl. Opt.*, vol. 61, no. 30, pp. 9010-9019, 2022.

[12] Z. Hou, J. Ren, and S. Chen, "Cryptanalysis of Round-Reduced SIMON32 Based on Deep Learning," *IACR Cryptol. ePrint Arch.*, vol. 2021, p. 362, 2021.

[13] E. Adeniyi, A. Imoize, J. Awotunde, C. Lee, P. Falola, R. Jimoh, and S. Ajagbe, "Performance Analysis of Two Famous Cryptographic Algorithms on Mixed Data," *J. Comput. Sci.*, 2023.

[14] Y. Khattabi, M. Matalgah, and M. Olama, "Revisiting Lightweight Encryption for IoT Applications: Error Performance and Throughput in Wireless Fading Channels With and Without Coding," *IEEE Access*, vol. 8, pp. 13429-13443, 2020.

[15] A. Parihar and S. Nakhate, "Low Latency High Throughput Montgomery Modular Multiplier for RSA Cryptosystem," *Eng. Sci. Technol. Int. J.*, 2021.

[16] T. Fritzmann, T. Pöppelmann, and M. Sepúlveda, "Analysis of Error-Correcting Codes for Lattice-Based Key Exchange," *IACR Cryptol. ePrint Arch.*, vol. 2018, p. 150, 2018.